

FCC RADIO TEST REPORT

Applicant's company	Axesstel, Inc.
Applicant Address	6815 Flanders Drive Ste. 210 San Diego, CA 92121, U.S.A.
FCC ID	PH7SJE10
Manufacturer's company	Wistron NeWeb Corporation
Manufacturer Address	No.10-1, Li-hsin Road I, Hsinchu Science Park, Hsinchu 300, Taiwan, R.O.C.

Product Name	Smart Jacket
Brand Name	Axesstel
Model Name	SJE10
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Dec. 01, 2008
Final Test Date	Dec. 24, 2008
Submission Type	Original Equipment



Statement

Test result included is only for the 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies	4
3.5. Table for Test Modes	4
3.6. Table for Testing Locations.....	5
3.7. Table for Supporting Units	5
3.8. Table for Parameters of Test Software Setting	6
3.9. Test Configurations	7
4. TEST RESULT	10
4.1. AC Power Line Conducted Emissions Measurement.....	10
4.2. Maximum Conducted Output Power Measurement.....	14
4.3. Power Spectral Density Measurement	19
4.4. 6dB Spectrum Bandwidth Measurement	24
4.5. Radiated Emissions Measurement	29
4.6. Band Edge Emissions Measurement	47
4.7. Antenna Requirements	52
5. LIST OF MEASURING EQUIPMENTS	53
6. TEST LOCATION.....	54
7. TAF CERTIFICATE OF ACCREDITATION	55
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A18
APPENDIX B. TEST PHOTOS.....	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C3
APPENDIX D. CO-LOCATION REPORT.....	D1 ~ D3

History of This Test Report

Original Issue Date: Dec. 24, 2008

Report No.: FR8D0103

☒ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : Smart Jacket
Brand Name : Axesstel
Model Name : SJE10
Applicant : Axesstel, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 01, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink, appearing to read 'Wayne Hsu 2009.1.22', is written over a horizontal line.

Wayne Hsu

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.57 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	7.10 dB
4.3	15.247(e)	Power Spectral Density	Complies	12.45 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	1.31 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.45 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	$\pm 2.3\text{dB}$	Confidence levels of 95%
Maximum Conducted Output Power	$\pm 0.8\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 0.5\text{dB}$	Confidence levels of 95%
6dB Spectrum Bandwidth	$\pm 8.5 \times 10^{-8}$	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	$\pm 0.8\text{dB}$	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	$\pm 1.9\text{dB}$	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	$\pm 1.9\text{dB}$	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	$\pm 1.9\text{dB}$	Confidence levels of 95%
Temperature	$\pm 0.7^{\circ}\text{C}$	Confidence levels of 95%
Humidity	$\pm 3.2\%$	Confidence levels of 95%
DC / AC Power Source	$\pm 1.4\%$	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	Power Adapter / Battery
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 15.51 MHz ; 11g: 16.63 MHz
Conducted Output Power	11b: 17.54 dBm ; 11g: 22.90 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	DVE	DSA-20P-05 CH 050150	Input: 100-240VAC, 50/60Hz, 0.7A Output: 5VDC, 3A
Other			
Power	Brand	Model	Rating
Rechargeable Li-ion Battery Module	Axesstel	AXT_M4BT	3.7VDC, 4400mAh

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	WNC	XBAB-D1	PCB Antenna	I-PEX	2.79

3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	1
Maximum Peak Conducted Output Power	11b/BPSK	1 Mbps	1/6/11	NA
	11g/BPSK	6 Mbps	1/6/11	NA
Power Spectral Density 6dB Spectrum Bandwidth	11b/BPSK	1 Mbps	1/6/11	NA
	11g/BPSK	6 Mbps	1/6/11	NA
Radiated Emissions 9kHz~1GHz	Normal Link	Auto	-	1
Radiated Emissions 1GHz~10 th Harmonic	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11b/BPSK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1

The EUT could be applied with one express 3G card; therefore Maximum Permissible Exposure (please refer to Appendix C) and Co-location (please refer to Appendix D) tests are added for simultaneously transmit between wireless LAN and 3G card function.

Interface	Brand	Model	FCC ID
Express 3G card	Axesstel	EU230	PH7EU230

From above express 3G card, Model number: WU230 was selected for testing.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2KWM3945ABG
CMU200	ROHDE&SCHWARZ	108087	DoC
Express 3G card	Axesstel	EU230	PH7EU230

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g


Test Software Version	Atheros		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	18.5	18.5	19
IEEE 802.11g	18	22	16.5

The “ART” was executed the test program to control the EUT continuously receive and transmit RF signal.


3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


9kHz~1GHz




Above 1GHz (WiFi)



Above 1GHz (Co-location)



3.9.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	26°C	Humidity	58%
Test Engineer	Peter Wu	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16155	48.88	-16.51	65.38	48.61	0.07	0.20	QP
2	0.16155	35.52	-19.87	55.38	35.25	0.07	0.20	AVERAGE
3	0.26724	26.61	-24.59	51.20	26.37	0.04	0.20	AVERAGE
4	0.26724	42.08	-19.12	61.20	41.84	0.04	0.20	QP
5 @	0.33740	43.14	-16.13	59.27	42.90	0.04	0.20	QP
6	0.33740	28.36	-20.91	49.27	28.12	0.04	0.20	AVERAGE
7	0.41266	40.50	-17.09	57.59	40.27	0.03	0.20	QP
8	0.41266	29.77	-17.82	47.59	29.54	0.03	0.20	AVERAGE
9	0.50737	36.52	-19.48	56.00	36.29	0.03	0.20	QP
10	0.50737	22.45	-23.55	46.00	22.22	0.03	0.20	AVERAGE
11	0.72360	17.23	-28.77	46.00	17.00	0.03	0.20	AVERAGE
12	0.72360	31.56	-24.44	56.00	31.33	0.03	0.20	QP

Temperature	26°C	Humidity	58%
Test Engineer	Peter Wu	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16155	52.82	-12.57	65.38	52.52	0.10	0.20	QP
2	0.16155	23.32	-32.07	55.38	23.02	0.10	0.20	AVERAGE
3	0.21392	32.10	-20.95	53.05	31.82	0.08	0.20	AVERAGE
4	0.21392	46.36	-16.69	63.05	46.08	0.08	0.20	QP
5	0.28029	27.33	-23.48	50.81	27.05	0.08	0.20	AVERAGE
6	0.28029	41.76	-19.05	60.81	41.48	0.08	0.20	QP
7	0.33208	30.92	-18.48	49.40	30.65	0.07	0.20	AVERAGE
8	0.33208	43.41	-15.99	59.40	43.14	0.07	0.20	QP
9	0.56111	35.85	-20.15	56.00	35.58	0.07	0.20	QP
10	0.56111	19.26	-26.74	46.00	18.99	0.07	0.20	AVERAGE
11	0.73131	35.83	-20.17	56.00	35.56	0.07	0.20	QP
12	0.73131	22.89	-23.11	46.00	22.62	0.07	0.20	AVERAGE

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	RMS
Trace	Max Hold
Sweep Time	2.5ms

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	20°C	Humidity	60%
Test Engineer	Johnson Chang	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.29	30.00	Complies
6	2437 MHz	17.12	30.00	Complies
11	2462 MHz	17.54	30.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.39	30.00	Complies
6	2437 MHz	22.90	30.00	Complies
11	2462 MHz	17.28	30.00	Complies

Conducted Output Power Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 2.DEC.2008 15:31:05

Conducted Output Power Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 2.DEC.2008 15:32:31

Conducted Output Power Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 2.DEC.2008 15:33:56

Conducted Output Power Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 2.DEC.2008 15:36:01

Conducted Output Power Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 2.DEC.2008 15:35:19

Conducted Output Power Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 2.DEC.2008 15:34:38

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	20°C	Humidity	60%
Test Engineer	Johnson Chang	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-14.64	8.00	Complies
6	2437 MHz	-9.79	8.00	Complies
11	2462 MHz	-16.77	8.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-14.78	8.00	Complies
6	2437 MHz	-4.45	8.00	Complies
11	2462 MHz	-17.18	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 2.DEC.2008 16:01:40

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 2.DEC.2008 15:59:29

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 2.DEC.2008 15:57:16

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 2.DEC.2008 15:46:50

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 2.DEC.2008 15:49:10

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 2.DEC.2008 16:35:39

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

4.4.3. Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
- Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	20°C	Humidity	70%
Test Engineer	Johnson Chang	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.05	15.51	500	Complies
6	2437 MHz	12.05	15.51	500	Complies
11	2462 MHz	11.08	15.51	500	Complies

Configuration IEEE 802.11g


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.92	16.53	500	Complies
6	2437 MHz	16.02	16.69	500	Complies
11	2462 MHz	16.28	16.53	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 2.DEC.2008 16:00:12

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 2.DEC.2008 15:58:00

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 2.DEC.2008 15:55:49

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 2.DEC.2008 15:45:23

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 2.DEC.2008 15:47:41

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 2.DEC.2008 16:34:12

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Normal Link

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	133.790	23.91	-19.59	43.50	37.71	12.29	27.43	1.34	Peak	HORIZONTAL	0	100
2	400.540	29.01	-16.99	46.00	38.24	16.08	27.61	2.31	Peak	HORIZONTAL	0	100
3	501.420	39.59	-6.41	46.00	47.35	17.64	28.10	2.70	Peak	HORIZONTAL	0	100
4	599.390	30.05	-15.95	46.00	36.50	18.76	28.10	2.90	Peak	HORIZONTAL	0	100
5	800.180	39.68	-6.32	46.00	44.21	19.77	27.60	3.30	Peak	HORIZONTAL	0	100
6	867.110	30.98	-15.02	46.00	34.70	20.28	27.47	3.47	Peak	HORIZONTAL	0	100
7	1000.000	40.30	-13.70	54.00	42.31	21.29	27.00	3.70	Peak	HORIZONTAL	0	100

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	56.190	30.05	-9.95	40.00	49.55	7.47	27.78	0.80	Peak	VERTICAL	0	400
2	98.870	29.70	-13.80	43.50	45.33	10.79	27.61	1.18	Peak	VERTICAL	0	400
3	172.590	27.53	-15.97	43.50	40.22	12.97	27.23	1.56	Peak	VERTICAL	0	400
4	347.190	31.44	-14.56	46.00	41.84	14.64	27.23	2.19	Peak	VERTICAL	0	400
5	435.460	30.73	-15.27	46.00	39.37	16.62	27.78	2.51	Peak	VERTICAL	0	400
6	498.510	35.14	-10.86	46.00	42.93	17.60	28.09	2.70	Peak	VERTICAL	0	400
7	594.540	28.96	-17.04	46.00	35.46	18.70	28.10	2.89	Peak	VERTICAL	0	400
8	800.180	39.35	-6.65	46.00	43.88	19.77	27.60	3.30	Peak	VERTICAL	0	400
9	1000.000	35.15	-18.85	54.00	37.16	21.29	27.00	3.70	Peak	VERTICAL	0	400

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	26℃	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11b CH 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Preamp	Cable	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB			deg	cm
1	4824.010	48.56	-5.44	54.00	43.99	33.39	35.20	6.39 AVERAGE	HORIZONTAL	101	182
2	4824.140	52.69	-21.31	74.00	48.11	33.39	35.20	6.39 PEAK	HORIZONTAL	101	182


Vertical



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable			Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Remark	Pol/Phase	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	4823.950	52.11	-1.89	54.00	47.53	33.39	35.20	6.39	AVERAGE	VERTICAL	182	213
2	4824.080	54.42	-19.58	74.00	49.84	33.39	35.20	6.39	PEAK	VERTICAL	182	213


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11b CH 6

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	4873.950	46.50	-7.50	54.00	41.65	33.48	35.20	6.56	AVERAGE	HORIZONTAL	107	172
2	4874.030	50.84	-23.16	74.00	46.00	33.48	35.20	6.56	PEAK	HORIZONTAL	107	172


Vertical



	Freq	Level	Over	Limit	ReadAntenna	Preamp	Cable			Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm
1	4873.970	54.82	-19.18	74.00	49.98	33.48	35.20	6.56	PEAK	138	203
2 @	4874.010	52.59	-1.41	54.00	47.75	33.48	35.20	6.56	AVERAGE	138	203


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11b CH 11

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB			deg	cm
1	4924.030	47.69	-6.31	54.00	42.59	33.58	35.20	6.73 AVERAGE	HORIZONTAL	132	114
2	4924.140	53.06	-20.94	74.00	47.96	33.58	35.20	6.73 PEAK	HORIZONTAL	132	114


Vertical



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable		Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm
1 @	4924.010	52.69	-1.31	54.00	47.58	33.58	35.20	6.73	AVERAGE	336	235
2 @	4924.050	55.27	-18.73	74.00	50.16	33.58	35.20	6.73	PEAK	336	235


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11g CH 1

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable			Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Remark	Pol/Phase	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	4820.160	33.22	-20.78	54.00	28.64	33.39	35.20	6.39	AVERAGE	HORIZONTAL	0	100
2	4822.960	47.79	-26.21	74.00	43.21	33.39	35.20	6.39	PEAK	HORIZONTAL	0	100


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB			deg	cm
1	4822.270	54.93	-19.07	74.00	50.35	33.39	35.20	6.39 PEAK	VERTICAL	144	214
2	4825.800	38.32	-15.68	54.00	33.74	33.39	35.20	6.39 AVERAGE	VERTICAL	144	214


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11g CH 6

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☺	4871.780	42.65	-11.35	54.00	37.81	33.48	35.20	6.56	AVERAGE	HORIZONTAL	131	127
2 ☺	4875.390	58.74	-15.26	74.00	53.90	33.48	35.20	6.56	PEAK	HORIZONTAL	131	127


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☺	4871.740	49.16	-4.84	54.00	44.32	33.48	35.20	6.56	AVERAGE	VERTICAL	181	225
2 ☺	4872.260	65.60	-8.40	74.00	60.76	33.48	35.20	6.56	PEAK	VERTICAL	181	225


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11g CH 11

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	4921.500	33.31	-20.69	54.00	28.20	33.58	35.20	6.73	AVERAGE	HORIZONTAL	334	100
2	4925.860	46.97	-27.03	74.00	41.86	33.58	35.20	6.73	PEAK	HORIZONTAL	334	100

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	4922.860	49.70	-24.30	74.00	44.59	33.58	35.20	6.73	PEAK	VERTICAL	335	100
2	4923.790	35.12	-18.88	54.00	30.01	33.58	35.20	6.73	AVERAGE	VERTICAL	335	100

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1 MHz / 1 MHz for Peak

4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
- In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11b CH 1, 6, 11
Test Date	Dec. 01, 2008		

Channel 1

	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss			Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☺	2386.200	60.09	-13.91	74.00	29.18	28.05	0.00	2.86	PEAK	VERTICAL	96	100
2 ☺	2386.400	52.26	-1.74	54.00	21.34	28.05	0.00	2.86	AVERAGE	VERTICAL	96	100
3 ☺	2412.800	106.79			75.81	28.09	0.00	2.88	AVERAGE	VERTICAL	96	100
4 ☺	2413.000	110.55			79.58	28.09	0.00	2.88	PEAK	VERTICAL	96	100

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss			Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1	2388.800	54.97	-19.03	74.00	24.05	28.05	0.00	2.86	PEAK	VERTICAL	207	102
2 ☺	2390.000	42.82	-11.18	54.00	11.89	28.05	0.00	2.88	AVERAGE	VERTICAL	207	102
3 ☺	2438.600	110.89			79.82	28.18	0.00	2.90	PEAK	VERTICAL	207	102
4 ☺	2439.800	106.16			75.09	28.18	0.00	2.90	AVERAGE	VERTICAL	207	102
5 ☺	2483.500	55.15	-18.85	74.00	23.96	28.26	0.00	2.93	PEAK	VERTICAL	207	102
6 ☺	2483.500	43.57	-10.43	54.00	12.38	28.26	0.00	2.93	AVERAGE	VERTICAL	207	102

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss			Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☺	2463.400	110.31			79.18	28.22	0.00	2.91	PEAK	VERTICAL	145	100
2 ☺	2464.800	105.85			74.73	28.22	0.00	2.91	AVERAGE	VERTICAL	145	100
3 ☺	2487.800	52.63	-1.37	54.00	21.41	28.30	0.00	2.93	AVERAGE	VERTICAL	145	100
4 ☺	2488.000	60.89	-13.11	74.00	29.67	28.30	0.00	2.93	PEAK	VERTICAL	145	100

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	802.11g CH 1, 6, 11
Test Date	Dec. 01, 2008		

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☐	2390.000	53.25	-0.75	54.00	22.32	28.05	0.00	2.88	AVERAGE	VERTICAL	96	100
2 ☐	2390.000	67.41	-6.59	74.00	36.48	28.05	0.00	2.88	PEAK	VERTICAL	95	100
3 ☐	2407.400			74.00	79.94	28.09	0.00	2.88	PEAK	VERTICAL	95	100
4 ☐	2413.200			54.00	69.96	28.09	0.00	2.88	AVERAGE	VERTICAL	96	100

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☐	2390.000	44.73	-9.27	54.00	13.80	28.05	0.00	2.88	AVERAGE	VERTICAL	145	100
2 ☐	2390.000	57.94	-16.06	74.00	27.01	28.05	0.00	2.88	PEAK	VERTICAL	145	100
3 ☐	2439.000			74.00	84.33	28.18	0.00	2.90	PEAK	VERTICAL	145	100
4 ☐	2440.000			54.00	72.70	28.18	0.00	2.90	AVERAGE	VERTICAL	145	100
5 ☐	2483.500	61.05	-12.95	74.00	29.86	28.26	0.00	2.93	PEAK	VERTICAL	145	100
6 ☐	2483.500	48.14	-5.86	54.00	16.95	28.26	0.00	2.93	AVERAGE	VERTICAL	145	100

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 ☐	2463.600			74.00	80.03	28.22	0.00	2.91	PEAK	VERTICAL	144	100
2 ☐	2466.400			54.00	68.30	28.22	0.00	2.93	AVERAGE	VERTICAL	144	100
3 ☐	2483.500	53.55	-0.45	54.00	22.37	28.26	0.00	2.93	AVERAGE	VERTICAL	144	100
4 ☐	2483.500	68.61	-5.39	74.00	37.42	28.26	0.00	2.93	PEAK	VERTICAL	144	100

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 2.DEC.2008 16:01:48

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 2.DEC.2008 15:57:25

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 2.DEC.2008 15:46:59

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 2.DEC.2008 16:35:48

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2008	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2008	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN ST08	21653	9kHz – 30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2008	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2008	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9 kHz - 30 GHz	Jan. 10, 2008	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 12, 2008	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 04, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB020	30 MHz - 1 GHz	Dec. 17, 2008	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX106	03CH02-HY	1GHz~40GHz	Dec. 17, 2008	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 11, 2008	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 30, 2008*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Jul. 18, 2008	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2008	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Dec. 14, 2008	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)
Oscilloscope	Tektonix	TDS380	B016197	400MHz/ 2GS/s	Jun. 27, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: *Calibration Interval of instruments listed above is two year.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : LI190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.