4 FCC §101.1525 & §2.1091 – RF Exposure

4.1 Applicable Standard

According to FCC §1.1307 (b) (1) and §101.1525, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 MPE Results

72 GHz band:

Maximum peak output power at antenna input terminal (dBm):20.64Maximum peak output power at antenna input terminal (mW):115.8777Prediction distance (cm):1522Prediction frequency (MHz):72,375Maximum Antenna Gain, typical (dBi):54Maximum Antenna Gain (numeric):251188.6Power density of prediction frequency at 20 cm (mW/cm²):0.99991

Power density of prediction frequency at 20 cm (mW/cm²): 0.99991

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

^{* =} Plane-wave equivalent power density

82 GHz band:

Maximum peak output power at antenna input terminal (dBm): 20.46

Maximum peak output power at antenna input terminal (mW): 111.17

Prediction distance (cm): 1522
Prediction frequency (MHz): 82,375

Maximum Antenna Gain, typical (dBi): 54

Maximum Antenna Gain (numeric): 251188.6

Power density of prediction frequency at 20 cm (mW/cm²): 0.959314

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

74 GHz band:

Maximum peak output power at antenna input terminal (dBm):20.97Maximum peak output power at antenna input terminal (mW):125.026Prediction distance (cm):1581

Prediction frequency (MHz): 74,875

Maximum Antenna Gain, typical (dBi): 54

Maximum Antenna Gain (numeric): 251188.6
Power density of prediction frequency at 20 cm (mW/cm²): 0.99983

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

84 GHz band:

Maximum peak output power at antenna input terminal (dBm): 20.59

Maximum peak output power at antenna input terminal (mW): 114.551

Prediction distance (cm): 1581
Prediction frequency (MHz): 84,875

Maximum Antenna Gain, typical (dBi): 54

Maximum Antenna Gain, typical (dBi): 54

Maximum Antenna Gain (numeric): 251188.6

Power density of prediction frequency at 20 cm (mW/cm²): 0.916065

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

72/82 GHz Band:

The worst power density level at 1522 cm is 0.99991 mW/cm² antenna, which is below the uncontrolled exposure limit of 1.0 mW/cm².

74/84 GHz Band:

The worst power density level at 1581 cm is 0.99983 mW/cm² antenna, which is below the uncontrolled exposure limit of 1.0 mW/cm².

Note: The conducted output power was performed by the manufacturer.