



Technical Note

WipLL 1.9 GHz

Wireless IP-Based Local Loop System

Connecting the World with Wireless Access Solutions

Revision Record: WipLL 1.9		
Pub/ Rev	Date	Update Description
01	Aug-05	Airspan. Author: InterDoc
Publication No. 28080511-01		

© Copyright by **Airspan Networks LTD.**, 2003. All rights reserved worldwide.

The information contained in this document is proprietary and is subject to all relevant copyright, patent and other laws protecting intellectual property, as well as any specific agreement protecting **Airspan Networks LTD.** rights in the aforesaid information. Neither this document nor the information contained herein may be published, reproduced or disclosed to third parties, in whole or in part, without the express, prior, written permission of **Airspan Networks LTD.** In addition, any use of this document or the information contained herein for any purposes other than those for which it was disclosed is strictly forbidden.

Airspan Networks LTD. reserves the right, without prior notice or liability, to make changes in equipment design or specifications.

Information supplied by **Airspan Networks LTD.** is believed to be accurate and reliable. However, no responsibility is assumed by **Airspan Networks LTD.** for the use thereof nor for the rights of third parties which may be effected in any way by the use thereof.

Any representation(s) in this document concerning performance of **Airspan Networks LTD.** product(s) are for informational purposes only and are not warranties of future performance, either express or implied. **Airspan Networks LTD.** standard limited warranty, stated in its sales contract or order confirmation form, is the only warranty offered by **Airspan Networks LTD.** in relation thereto.

This document may contain flaws, omissions or typesetting errors; no warranty is granted nor liability assumed in relation thereto unless specifically undertaken in Airspan Networks LTD. sales contract or order confirmation. Information contained herein is periodically updated and changes will be incorporated into subsequent editions. If you have encountered an error, please notify Airspan Networks LTD. All specifications are subject to change without prior notice.

Contents

- 1. Scope4
- 2. SPR4
 - 2.1. EUT (SPR) test configuration**Error! Bookmark not defined.**
- 3. BSR5
 - 3.1. EUT (SPR) test configuration**Error! Bookmark not defined.**

1. Scope

This document provides a description of the WipLL 1.9 GHz product.

2. SPR

A subscriber premises radio, SPR 1.9 GHz FDD Ext., is part of a WipLL broadband fixed cellular wireless access system. The system provides a radio link between an end-user (a subscriber) and a network to give high-speed data access. The SPR's transceiver/receiver (FSK digital modulation, data rate up to 4 Mbps) uses TDM and operating in FDD duplexing mode (1,850 to 1,910 MHz Tx and 1,930 to 1,990 MHz Rx range), equipped with a 15 dBi gain external or 12 dBi internal antenna. The maximum RF output power (not including antenna gain) is 30 dBm and it can be reduced by software.

The SPR is installed outdoors and typically is mounted on a pole. The SPR transmits and receives traffic to and from the base station (i.e. BSR) respectively. The transceiver provides subscribers with "always-on" Internet, high speed data only, or data and voice (VoIP) services and is configured with a unique BSR reference number, preventing the SPR from relocating to another subscriber premises without authorization. The SPR has the same PCB components as the BSR, and differs only in the software and chassis dimensions.

The SPR is powered via a subscriber data adapter (SDA), which provides 48 VDC power.

3. BSR

A base station radio, BSR 1.9 GHz FDD Ext., is part of a WipLL broadband fixed cellular wireless access system. The system provides a radio link between an end-user (a subscriber) and a network to give high-speed data access. The BSR is a transceiver/receiver (FSK digital modulation, data rate up to 4 Mbps), using TDM and operating in FDD duplexing mode (1,850 to 1,910 MHz Rx and 1,930 to 1,990 MHz Tx range), equipped with a 16 dBi gain external or 11dBi internal antenna. The maximum RF output power (not including antenna gain) is 31dBm and it can be reduced by software.

The BSR is installed outdoors and typically is mounted on a pole. The BSR transmits and receives traffic to and from the end-user (i.e. SPR) respectively. The BSR provides subscribers with "always-on" Internet, high speed data only, or data and voice (VoIP) services.

The BSR is powered via a subscriber data adapter (SDA), which provides 48 VDC power.