



HERMON LABORATORIES



Hermon Laboratories Ltd.
P.O.Box 23
Binyamina 30500, Israel
Tel.+972 46288001
Fax.+972 46288277
e-mail: mail@hermonlabs.com

RADIO TEST REPORT

according to 47CFR Part 15, §15.247 and subpart B
for

Airspan Networks (Israel) Ltd.

EQUIPMENT UNDER TEST:

Base station radio unit

**Models: BSR 900MHz TDD Ext A, BSR 900MHz TDD V-pol A,
SPRL 900MHz TDD Ext A, SPRL 900MHz V-pol A**

This report is in conformity with ISO/IEC 17025. The A2LA logo endorsement applies only to the test methods and the standards that are listed in the scope of Hermon Laboratories accreditation.
The test results relate only to the items tested. **This test report must not be reproduced in any form except in full with the approval of Hermon Laboratories Ltd.**

Page 1 of 183



Contents

1	Project information.....	3
2	Summary of tests and signatures.....	4
3	EUT description	5
3.1	GENERAL DESCRIPTION	5
3.2	EUT TEST CONFIGURATION	5
4	Test results.....	6
4.1	PEAK POWER SPECTRAL DENSITY OF A HYBRID SYSTEM ACCORDING TO § 15.247(F),(D)	6
4.2	AVERAGE TIME OF HOPPING FREQUENCY OCCUPANCY ACCORDING TO § 15.247(F), (A)(1)	7
4.3	MAXIMUM PEAK OUTPUT POWER TEST ACCORDING TO §15.247(B)(3)	8
4.4	MINIMUM CHANNEL SEPARATION AND OCCUPIED BANDWIDTH ACCORDING TO § 15.247(A)(1), (2).....	9
4.5	OUT OF BAND CONDUCTED EMISSIONS TEST ACCORDING TO §15.247(C).....	10
4.6	RADIATED EMISSIONS WHICH FALL IN RESTRICTED BANDS TEST ACCORDING TO §15.247(C) AND § 15.205, §15.209(A)	11
4.7	CONDUCTED EMISSIONS TEST ACCORDING TO §15.107, 15.207	15
4.8	UNINTENTIONAL RADIATED EMISSIONS TEST ACCORDING TO §15.109.....	17
	Appendix A Plots	20
	Appendix B Test equipment used for tests.....	169
	Appendix C Test equipment correction factors.....	171
	Appendix D General information.....	183
	TEST FACILITY DESCRIPTION	183
	ABBREVIATIONS AND ACRONYMS	183
	SPECIFICATION REFERENCES	183



1 Project information

EUT attributes

Test item	Outdoor radio unit
Type (Model)	1) BSR 900MHz TDD Ext A, 2) BSR 900MHz TDD V-pol A, 3) SPRL 900MHz TDD Ext A, 4) SPRL 900MHz TDD V-pol A
Equipment FCC code	DSS

Applicant information

Applicant's responsible person	Mr. Zion Levi, compliance & testing engineer
Applicant/Manufacturer	Airspan Networks (Israel) Ltd.
Address	1, Harava street, "Unitronics" building
P.O.B.	199
City	Airport City
Postal code	70100
Country	Israel
Telephone number	+972 3977 7444
Telefax number	+972 3977 7400

Test details

Project number	15694
Location	Hermon Laboratories
Test performed	October 2, 14, 15, 2003; February 9, March 25, 2004
Purpose of test	Apparatus compliance verification in accordance with emission requirements
Test specifications	47CFR Part 15, §15.247 and subpart B



2 Summary of tests and signatures

The tests listed in the table below were performed.
The EUT was found complying with the limits of 47CFR Part 15, §15.247 and subpart B.

Test description	Specification reference	Tested by	Date tested	Test report paragraph	Verdict
Hybrid system					
Peak power spectral density at frequency hopping operation turned off	15.247(f)	Mr. Y. Neuman, test engineer	March 25, 2004	4.1	Pass
Average time of occupancy at frequency hopping operation turned on	15.247(f)	Mr. Y. Neuman, test engineer	October 15, 2003	4.2	Pass
Maximum peak output power at frequency hopping operation turned off	15.247(b)(3)	Mr. Y. Neuman, test engineer	March 25, 2004	4.3	Pass
Minimum channel separation	15.247(a)(1)	Manufacturer statement	NA	4.4	Pass
6 dB bandwidth	15.247(a)(2)	Mr. Y. Neuman, test engineer	October 2, 2003	4.4	Pass
Spurious emissions (conducted)	15.247(c)	Mr. Y. Neuman, test engineer	March 25, 2004	4.5	Pass
Spurious emissions (radiated) in restricted bands	15.209(a), 15.205(a, c)	Mr. Y. Neuman, test engineer	October 15, 2003; February 9, 2004	4.6	Pass
Unintentional radiation					
Conducted emissions	15.207, 15.107	Mr. Y. Neuman, test engineer	October 19, 2003	4.7	Pass
Radiated emissions	15.109	Mr. Y. Neuman, test engineer	February 9, 2004	4.8	Pass

Test report prepared by:

Mrs. M. Cherniavsky, MScEE, certification engineer

Test report approved by:

Mr. Michael Nikishin, MScEE, group leader



3 EUT description

3.1 General description

The EUTs, outdoor units (ODU), model names "BSR 900MHz TDD Ext A", "BSR 900MHz TDD V-pol A", "SPRL 900MHz TDD Ext A" and "SPRL 900MHz TDD V-pol A", are part of a WipLL broadband fixed cellular wireless access system. The system provides a radio link between an end-user (a subscriber) and a network itself to give high-speed data access. The EUT is a hybrid system transceiver operating in 903 MHz to 927 MHz range.

The "BSR/SPRL 900MHz TDD Ext A" models are equipped with an 11 dBi gain omnidirectional or 15.5 dBi gain (dual polarization or vertical polarization) external antenna, the "BSR/SPRL 900MHz TDD V-pol A" models - with a 8 dBi gain internal antenna. The BSR is installed outside the base station site and typically is mounted on a pole, the SPRL is installed at the subscriber's premises. The SPRL is a radio transceiver that transmits and receives traffic to and from the base station (i.e., BSR), respectively. The SPRL provides subscribers with "always-on" Internet, high-speed data-only, or data and voice (VoIP) services and is configured with a unique BSR reference number, preventing the SPRL from relocating to another subscriber premises without authorization.

The SPRL has identical to the BSR chassis, the same dimensions, contains the same PCB components and differs only in the software.

The EUT is powered via a subscriber data adapter (SDA), which provides 48 V DC power.

3.2 EUT test configuration

Throughout testing the radio communication was established. The EUT operating frequencies generated by clocks and oscillators: 350 MHz - first IF, 6 MHz – second IF, $[F_{\text{operating}} + 350 \text{ MHz}]$ – first LO, 356 MHz – second LO.



4 Test results

4.1 Peak power spectral density of a hybrid system according to § 15.247(f),(d)

METHOD OF MEASUREMENTS	FCC Docket No.96-8; FCC 97-114
DATE of TEST:	March 25, 2004
AMBIENT TEMPERATURE:	25°C
RELATIVE HUMIDITY:	45 %
AIR PRESSURE:	1017 hPa
RATED OUTPUT POWER:	23 dBm
OPERATING FREQUENCY RANGE:	903 - 927 MHz
MEASUREMENT UNCERTAINTY:	± 3.5 dB

Frequency hopping function was turned off.

Carrier frequency, MHz	Data transmission rate, Mbit/s	Peak power spectral density, dBm		Verdict	Reference to plots in Appendix A
		Measured	Limit		
903	4	7.50	8	Pass	A1
903	3	7.67		Pass	A2
915	4	7.33		Pass	A3
915	3	7.83		Pass	A4
927	4	7.50		Pass	A5
927	3	8.00		Pass	A6

LIMIT

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

TEST PROCEDURE

The EUT RF output was connected via attenuator to the spectrum analyzer; the settings are shown in the plots. Spectrum analyzer readings were corrected for external attenuation and cable loss. The measurements were performed in continuous transmission mode of operation for carrier (channel) frequency modulated with PRBS at low and high edges and at the middle of the range according to method #1 for peak power spectral density.

TEST EQUIPMENT USED:

HL 1424	HL 1650	HL 1651	HL 2254			
---------	---------	---------	---------	--	--	--



4.2 Average time of hopping frequency occupancy according to § 15.247(f), (a)(1)

METHOD OF MEASUREMENT: ANSI 63.4 §13.1.7
 DATE of TEST: October 15, 2003
 AMBIENT TEMPERATURE: 23°C
 RELATIVE HUMIDITY: 44 %
 AIR PRESSURE: 1012 hPa
 OPERATING FREQUENCY RANGE: 903 - 927 MHz
 MEASUREMENT UNCERTAINTY: ± 1%

Frequency hopping function was turned on.

Carrier frequency, MHz	Quantity of transmissions at one frequency	Tx ON of 1 transmission at one frequency, ms	Average time of occupancy during 10 s period, ms	Verdict	Reference to Plots in Appendix A
903	8	25.583	204.664	Pass	A7, A8

Average factor calculation according to §15.35(c):
 $20 \log (25.583/100) = -11.84 \text{ dB}$

LIMIT

Operating mode	Limit
Hybrid	With the hopping system operation turned on, an average time of occupancy on any frequency shall not exceed 0.4 s within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4: $25 \times 0.4 = 10 \text{ (sec)}$

TEST PROCEDURE

The EUT RF output was connected via attenuator to spectrum analyzer, which settings are shown in the plots. Spectrum analyzer readings were corrected for external attenuation and cable loss.

TEST EQUIPMENT USED:

HL 1097	HL 1424	HL 2399				
---------	---------	---------	--	--	--	--



4.3 Maximum peak output power test according to §15.247(b)(3)

METHOD OF MEASUREMENTS: ANSI 63.4 §13.1.4
DATE of TEST: March 25, 2004
AMBIENT TEMPERATURE: 25°C
RELATIVE HUMIDITY: 45 %
AIR PRESSURE: 1017 hPa
OPERATING FREQUENCY RANGE: 903 - 927 MHz
MEASUREMENT UNCERTAINTY: ± 3.5 dB

Carrier frequency, MHz	Data rate, Mbit/s	Peak output power, dBm	Limit, dBm	Margin, dB	Verdict	Reference to Plots in Appendix A
903	4	22.80	24.9	2.10	Pass	A9
903	3	17.33	24.9	7.57	Pass	A10
915	4	23.00	24.9	1.90	Pass	A11
915	3	17.17	24.9	7.73	Pass	A12
927	4	22.67	24.9	2.23	Pass	A13
927	3	17.33	24.9	7.57	Pass	A14

LIMIT

Operating frequency range, MHz	Number of hopping channels	Maximum peak output power*, W
Hybrid	any admissible	1

* Notes to table

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced below the stated values by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

External antenna gain is 15.5 dBi, it is used with BELDEN-9913 cable, which has 4.4 dB cable loss, peak output power limit is 24.9 dBm.

TEST PROCEDURE

The EUT RF output was connected via attenuator to spectrum analyzer, which settings are shown in the plots. Spectrum analyzer readings were corrected for external attenuation and cable loss.

TEST EQUIPMENT USED:

HL 1424	HL 1650	HL 1651	HL 2254			
---------	---------	---------	---------	--	--	--



4.4 Minimum channel separation and occupied bandwidth according to § 15.247(a)(1), (2)

METHOD OF MEASUREMENTS: ANSI 63.4 §13.1.7
DATE of TEST: October 2, 2003
AMBIENT TEMPERATURE: 23°C
RELATIVE HUMIDITY: 46 %
AIR PRESSURE: 1012 hPa
OPERATING FREQUENCY RANGE: 903 -927 MHz
MEASUREMENT UNCERTAINTY: ± 2.3 dB

According to applicant statement the minimum channel separation is 1 MHz.

Carrier frequency, MHz	Data rate, Mbit/s	6 dB bandwidth, kHz		Verdict	Reference to Plots in Appendix A
		Measured	Limit		
903	4	808	500	Pass	A15
903	3	525	500	Pass	A16
915	4	808	500	Pass	A17
915	3	515	500	Pass	A18
927	4	800	500	Pass	A19
927	3	515	500	Pass	A20

LIMIT

Operating frequency range, MHz	Allowed bandwidth	Channel carrier frequency separation (minimum)
Hybrid	any admissible	25 kHz or 20 dB bandwidth, which is greater

TEST PROCEDURE

The EUT RF output was connected to the spectrum analyzer, which settings are shown in the plots. Spectrum analyzer readings were corrected for external attenuation and cable loss.

TEST EQUIPMENT USED:

HL 1097	HL 1424	HL 2399				
---------	---------	---------	--	--	--	--



4.5 Out of band conducted emissions test according to §15.247(c)

METHOD OF MEASUREMENTS: ANSI 63.4 §13.1.5
DATE of TEST: March 25, 2004
AMBIENT TEMPERATURE: 25°C
RELATIVE HUMIDITY: 45 %
AIR PRESSURE: 1017 hPa
OPERATING FREQUENCY RANGE: 903 -927 MHz
RATED RF OUTPUT POWER: 23 dBm
MODULATION TECHNIQUE: hybrid
FREQUENCY RANGE: 9 kHz – 9.5 GHz
MEASUREMENT UNCERTAINTY: ± 4.3 dB

The frequency spectrum was investigated from 9 kHz up to 10th harmonic. The measurements were performed at maximum output power settings and 3 Mbit/s modulation rate that yield maximum power density. The effect of the data rate was observed and shown in plots A21&A29, A37&A45 (the 3 Mbit/s rate was used for measurements). All measured emissions were found below specified limit. Test results are shown in Plots A21 to A46.

Frequency, MHz	Carrier frequency, MHz	Data rate, Mbit/s	Resolution bandwidth, kHz	Spurious emission level, dBm	Spurious calculated limit, dBm	Margin, dB	Reference to plots in Appendix A
901.993	903	3	100	-17.17	2.0	19.17	A21, A25
901.723	903	4	100	-16.00	-0.5	15.50	A29, A30
928.003	927	3	100	-18.00	2.0	20.00	A37, A41
928.237	927	4	100	-15.50	-0.5	15.00	A45, A46

LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

TEST PROCEDURE

The EUT RF output was connected via attenuator to spectrum analyzer, which settings are shown in the plots. Spectrum analyzer readings were corrected for external attenuation and cable loss. Spurious emission measurements were performed at the lowest (903 MHz), the highest (927 MHz) and one of the middle channel (915 MHz) frequencies.

TEST EQUIPMENT USED:

HL 1424	HL 1650	HL 1651	HL 2254			
---------	---------	---------	---------	--	--	--



4.6 Radiated emissions which fall in restricted bands test according to §15.247(c) and § 15.205, §15.209(a)

METHOD OF MEASUREMENTS: ANSI 63.4 §13.1.4/ §13.1.5
TEST PERFORMED IN: Anechoic chamber, OATS
OPERATING FREQUENCY RANGE: 903 -927 MHz
RATED RF OUTPUT POWER: 23 dBm
TEST DISTANCE: 3 m
MEASUREMENT UNCERTAINTY: ± 4.3 dB

LIMIT

Radiated emissions, which fall in the restricted bands, must comply with §15.209(a) limits.

TEST PROCEDURE

The measurements were performed at maximum output power settings and 3 Mbit/s modulation rate that yield maximum power density.

The test was performed with transmitter operating at 3 carrier frequencies $F_{\min} = 903$ MHz, $F_{\text{middle}} = 915$ MHz, $F_{\max} = 927$ MHz. The measurements were performed at 3 m test distance from 150 kHz to 2.9 GHz in the anechoic chamber, up to the tenth harmonic of the highest fundamental frequency – at the OATS. The EUT was placed on a wooden 80 cm height turntable.

150 kHz – 30 MHz frequency range. The loop antenna was positioned with its plane vertical. The loop center was 1 meter above the ground plane. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated about its vertical axis.

30 MHz – 9.2 GHz frequency range. To find maximum radiation the turntable was rotated 360°, measuring antenna height was changed from 1 to 4 m, and the antennas polarization was changed from vertical to horizontal.

All emissions were found below the specified limit. For test results refer to Plots A47 – A94 for EUT with internal antenna and to Plots A95 – A139 – for EUT with external antenna.

EUT TYPE: BSR/SPRL 900MHz TDD V-pol A (with internal antenna)
DATE of TEST: February 9, 10, 2004
AMBIENT TEMPERATURE: 21°C
RELATIVE HUMIDITY: 55 %
AIR PRESSURE: 1020 hPa

Quasi-peak detector

Frequency, MHz	Antenna type	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Reference to Plots in Appendix A
38.17	Biconilog	18.42	40.00	21.58	A65, A79
280.01	Biconilog	41.89	46.00	4.11	A65, A79
334.08	Biconilog	31.07	46.00	14.93	A65, A79

The recorded test results were obtained through measurements with biconilog antenna at 1 m height in vertical polarization. Turntable position: 0° = EUT front panel faces the receiving antenna

**Peak value**

Frequency, MHz	Antenna polarization	Antenna height, m	Turntable position, °	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Reference to Plots in Appendix A
1146.8	Horizontal	1.1	210	42.30*	74	31.70	A53
1520.0	Horizontal	1.1	208	45.30*	74	28.7	A52
4272.0	Horizontal	1.0	0	50.33	74	23.67	A88
4628.0	Horizontal	1.0	0	47.17	74	26.83	A86
5012.0	Horizontal	1.0	0	52.17	74	21.83	A58
5060.0	Horizontal	1.0	0	50.17	74	23.83	A72
5108.0	Horizontal	1.0	0	50.00	74	24.00	A90
7518.0	Vertical	1.0	0	55.50	74	18.50	A61
7590.0	Vertical	1.0	0	55.67	74	18.33	A75
7662.0	Vertical	1.0	0	56.00	74	18.00	A93

* Below average limit

Average value

Frequency, MHz	Antenna polarization	Antenna height, m	Turntable position, °	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Reference to Plots in Appendix A
4272.0	Horizontal	1.0	0	47.33	54	6.67	A87
4628.0	Horizontal	1.0	0	42.00	54	12.00	A85
5012.0	Horizontal	1.0	0	38.49	54	15.51	A57
5060.0	Horizontal	1.0	0	34.49	54	19.51	A71
5108.0	Horizontal	1.0	0	34.49	54	19.51	A89
7518.0	Vertical	1.0	0	38.16	54	15.84	A60
7590.0	Vertical	1.0	0	37.33	54	16.67	A74
7662.0	Vertical	1.0	0	38.16	54	15.84	A92

The recorded test results were obtained through measurements with double ridged guide antenna.

Table abbreviations:

Margin = dB below (negative if above) specification limit.

Turntable position: 0° = EUT front panel faces the receiving antenna

TEST EQUIPMENT USED AT OATS:

HL 0038	HL 0091	HL 0287	HL 1424	HL 1942	HL 1984	HL 2254
HL 2259						

TEST EQUIPMENT USED IN ANECHOIC CHAMBER:

HL 0446	HL 0465	HL 0521	HL 0589	HL 0592	HL 0593	HL 0594
HL 0604	HL 1004	HL 1947	HL 2009	HL 2432		



EUT TYPE BSR/SPRL 900MHz TDD Ext A (with 15.5 dBi external antenna)
DATE of TEST: October 14, 15, 2003
AMBIENT TEMPERATURE: 24°C
RELATIVE HUMIDITY: 38 %
AIR PRESSURE: 1012 hPa

Quasi-peak detector

Frequency, MHz	Antenna type	Antenna height, m	Turntable position, °	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Reference to Plots in Appendix A
110.0	Biconilog	1.0	0	30.65	43.50	12.85	A96
240.0	Biconilog	1.02	51	38.03	46.00	7.97	A96
972.0	Biconilog	1.87	128	43.10	54.00	10.90	A97
985.0	Biconilog	1.84	118	40.91	54.00	13.09	A114

The recorded test results were obtained through measurements with antennas in vertical polarization.
Turntable position: 0° = EUT front panel faces the receiving antenna

Peak value

Frequency, MHz	Antenna polarization	Antenna height, m	Turntable position, °	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Reference to Plots in Appendix A
1000.8	Vertical	1.68	141	48.82	74	25.18	A132
1392.0	Vertical	1.50	7	46.59	74	27.41	A100
2710.0	Vertical	1.60	352	50.37	74	23.63	A101
2745.0	Vertical	1.60	344	49.40	74	24.60	A119
2848.0	Vertical	1.00	351	54.46	74	19.54	A103
5012.0	Horizontal	1.00	0	53.67	74	20.33	A106
5060.0	Horizontal	1.00	0	51.67	74	22.33	A123
7518.0	Vertical	1.00	0	53.67	74	20.33	A109
7590.0	Vertical	1.00	0	53.67	74	20.33	A126

The recorded test results were obtained through measurements with double ridged guide antenna.

**Average value**

Frequency, MHz	Antenna polarization	Antenna height, m	Turntable position, °	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Reference to Plots in Appendix A
1000.8	Vertical	1.68	141	35.57	54	18.43	A132
1392.0	Vertical	1.50	7	35.78	54	18.22	A100
2710.0	Vertical	1.60	352	26.31	54	27.69	A102
2745.0	Vertical	1.60	344	25.73	54	28.27	A120
2848.0	Vertical	1.00	351	49.26	54	4.74	A103
5012.0	Horizontal	1.00	0	39.83	54	14.17	A107
5060.0	Horizontal	1.00	0	36.33	54	17.67	A124
7518.0	Vertical	1.00	0	32.83	54	21.17	A110
7590.0	Vertical	1.00	0	33.83	54	20.17	A127

The recorded test results were obtained through measurements with double ridged guide antenna.

Table abbreviations:

Margin = dB below (negative if above) specification limit.

Turntable position: 0° = EUT front panel faces the receiving antenna

TEST EQUIPMENT USED AT OATS:

HL 0038	HL 0091	HL 0287	HL 1200	HL 1365	HL 1424	HL 1430
HL 1942	HL 1947	HL 1984	HL 2254	HL 2259		

TEST EQUIPMENT USED IN ANECHOIC CHAMBER:

HL 0446	HL 0465	HL 0521	HL 0589	HL 0592	HL 0593	HL 0594
HL 0604	HL 1004	HL 1947	HL 1984	HL 2009		



4.7 Conducted emissions test according to §15.107, 15.207

METHOD OF MEASUREMENTS: ANSI 63.4 §13.1.3
DATE of TEST: October 19, 2003
AMBIENT TEMPERATURE: 22°C
RELATIVE HUMIDITY: 44 %
AIR PRESSURE: 1008 hPa
FREQUENCY RANGE: 150 kHz – 30 MHz
OPERATION MODE: Transmit, receive
RESOLUTION BANDWIDTH: 9 kHz
MEASUREMENT UNCERTAINTY, dB
± 3.9 dB in 9 – 150 kHz
± 3.8 dB in 150 kHz – 30 MHz

Quasi-peak detector

Frequency, MHz	Line identification	Measured emissions, dB (µV)	Specification QP limit, dB (µV)	Margin, dB	Verdict	Reference to Plots in Appendix A
0.347355	Line 2	44.55	59.09	14.54	Pass	A147, A149
1.239205	Line 1	40.92	56.00	15.08	Pass	A146, A148
1.638965	Line 2	41.47	56.00	14.53	Pass	A147, A149
2.629685	Line 1	43.13	56.00	12.87	Pass	A146, A148
2.925295	Line 2	43.45	56.00	12.55	Pass	A147, A149
4.959983	Line 2	48.81	56.00	7.19	Pass	A146, A148

Average detector

Frequency, MHz	Line identification	Measured emissions, dB (µV)	Specification AVRG limit, dB (µV)	Margin, dB	Verdict	Reference to Plots in Appendix A
0.347355	Line 2	37.95	49.09	11.14	Pass	A147, A149
1.239205	Line 1	35.18	46.00	10.82	Pass	A146, A148
1.638965	Line 2	33.13	46.00	12.87	Pass	A147, A149
2.629685	Line 1	32.50	46.00	13.50	Pass	A146, A148
2.925295	Line 2	32.07	46.00	13.93	Pass	A147, A149
4.959983	Line 2	44.23	46.00	1.77	Pass	A146, A148



Limit

Frequency, MHz	Class B equipment, dB(μ V)	
	QP	AVRG
0.15 - 0.5	66 - 56*	56 - 46*
0.5 - 5	56	46
5 - 30	60	50

*The limit decreases linearly with the logarithm of frequency.

TEST PROCEDURE

The measurements were performed at mains terminals by means of LISN, connected to spectrum analyzer in the frequency range as referred to in the table above. The unused coaxial connector of the LISN was terminated with 50 Ω . The measurements were made with quasi-peak and average detectors as referred to in the tables. The position of the EUT cables was varied to determine maximum emission level.

TEST EQUIPMENT USED:

HL 0447	HL 0466	HL 0521	HL 0787	HL 1003	HL 1205	HL 1503
---------	---------	---------	---------	---------	---------	---------



4.8 Unintentional radiated emissions test according to §15.109

METHOD OF MEASUREMENT: ANSI 63.4 §11.6 / ANSI 63.4 §12.1.4
DISTANCE BETWEEN ANTENNA AND EUT: 3 m
THE EUT WAS TESTED AS: TABLE-TOP
FREQUENCY RANGE: 30 MHz – 5 GHz

The EUT highest used frequency (not including operating frequency), MHz	Upper frequency of measurement range, MHz
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency

LIMIT (§ 15.109)

Frequency, MHz	Class B equipment @ 3 m dB(μ V/m)
30 - 88	40
88 - 216	43.5
216 - 960	46
960 - 5000	54

TEST PROCEDURE

The EUT was placed on a wooden 80 cm height turntable. To find maximum radiation the turntable was rotated 360°, measuring antenna height was changed from 1 to 4 m, and the antenna polarization was changed from vertical to horizontal.



EUT TYPE	BSR/SPRL 900MHz TDD V-pol A (with internal antenna)
DATE of TEST:	February 9, 2004
TEST PERFORMED IN:	Anechoic chamber
FREQUENCY RANGE:	30 MHz – 5 GHz
AMBIENT TEMPERATURE:	21°C
RELATIVE HUMIDITY:	55 %
AIR PRESSURE:	1020 hPa

Frequency, MHz	Detector type	RBW, kHz	Antenna type	Ant. pol.	Ant. height, m	TT pos. (°)	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Verdict
66.48	Quasi-peak	120	Biconilog	H	4.0	227	34.99	40.00	5.01	Pass
80.00	Quasi-peak	120	Biconilog	V	1.0	285	33.77	40.00	6.23	Pass
360.00	Quasi-peak	120	Biconilog	H	1.0	158	45.01	46.00	0.99	Pass
465.34	Quasi-peak	120	Biconilog	V	1.0	167	44.73	46.00	1.27	Pass
731.24	Quasi-peak	120	Biconilog	V	1.1	122	39.49	46.00	6.51	Pass
797.72	Quasi-peak	120	Biconilog	H	1.0	154	45.18	46.00	0.82	Pass
930.67	Quasi-peak	120	Biconilog	H	1.0	164	45.17	46.00	0.83	Pass
4272.02	Average	1000	Double ridged guide	H	1.1	0	46.18	54.00	7.82	Pass

For full test results refer to Plots A140 – A142.

Table abbreviations:

RBW = resolution bandwidth
Ant. pol. = antenna polarization, V – vertical, H - horizontal
TT pos. = turntable position, 0° = EUT front panel faces the receiving antenna

TEST EQUIPMENT USED IN ANECHOIC CHAMBER:

HL 0465	HL 0521	HL 0589	HL 0592	HL 0593	HL 0594	HL 0604
HL 1004	HL 1947	HL 2009	HL 2432			



EUT TYPE BSR/SPRL 900MHz TDD Ext A (with 15.5 dBi external antenna)
DATE of TEST: October 14, 15, 2003
TEST PERFORMED IN: Anechoic chamber, OATS
FREQUENCY RANGE: 30 MHz – 6.5 GHz
AMBIENT TEMPERATURE: 24°C
RELATIVE HUMIDITY: 38 %
AIR PRESSURE: 1012 hPa

Frequency, MHz	Detector type	RBW, kHz	Antenna type	Ant. height, m	TT pos. (°)	Radiated emissions, dB (µV/m)	Limit, dB (µV/m)	Margin, dB	Verdict
110.0	Quai-peak	120	Biconilog	100	0	30.65	43.50	12.85	Pass
125.0	Quai-peak	120	Biconilog	100	4	29.02	43.50	14.48	Pass
240.0	Quai-peak	120	Biconilog	102	51	38.03	46.00	7.97	Pass
288.0	Quai-peak	120	Biconilog	100	194	31.50	46.00	14.50	Pass
528.0	Quai-peak	120	Biconilog	100	0	33.60	46.00	12.40	Pass
960.0	Quai-peak	120	Biconilog	143	3	32.97	46.00	13.03	Pass
1392.0	Average	1000	Double ridged guide	150	7	36.13	54.00	17.87	Pass
1824.3	Average	1000	Double ridged guide	170	13	39.39	54.00	14.61	Pass
2848.0	Average	1000	Double ridged guide	100	351	49.50	54.00	4.50	

The test results recorded in the table were obtained throughout measurements with antennas in vertical polarization.
For full test results refer to Plots A143– A145.

Table abbreviations:

RBW = resolution bandwidth
TT pos. = turntable position, 0° = EUT front panel faces the receiving antenna

TEST EQUIPMENT USED IN ANECHOIC CHAMBER:

HL 0465	HL 0521	HL 0589	HL 0592	HL 0593	HL 0594	HL 0604
HL 1004	HL 1947	HL 1984	HL 2009			

TEST EQUIPMENT USED AT OATS:

HL 0038	HL 0091	HL 0287	HL 1365	HL 1430	HL 1947	HL 1984
---------	---------	---------	---------	---------	---------	---------




Appendix A Plots

Plot A1

Power density measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 4 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A2

Power density measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A3

Power density measurements

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 4 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A6

Power density measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A7

Average time of occupancy

Mode: Hopping turned on




8 transmissions within 10 sec interval



Plot A8

Average time of occupancy

Mode: Hopping turned on



Average time of occupancy calculation:

25.583 ms x 8 times=204.664 ms

204.664 ms <400 ms


Verdict: PASS



Plot A9

Peak output power

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 4 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A10

Peak output power

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A11

Peak output power

Mode:	Hybrid
F _{MIDDLE} :	915 MHz
Bit rate:	4 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A12

Peak output power

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A13

Peak output power

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 4 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A14

Peak output power

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s




External attenuation (40 dB) and cable loss (0.3 dB) included in test result



Plot A15

6 dB bandwidth

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 4 Mbit/s






Plot A16

6 dB bandwidth

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s






Plot A17

6 dB bandwidth

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 4 Mbit/s






Plot A18

6 dB bandwidth

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s






Plot A19

6 dB bandwidth

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 4 Mbit/s






Plot A20

6 dB bandwidth

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s






Plot A21

Conducted emission measurements within the band

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s




In-band emissions level measured with RBW=100 kHz is 22 dBm
Limit for spurious emissions is 2 dBm



Plot A22

Conducted spurious emission measurements

Mode: Hybrid
Flow: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 9 kHz - 150 kHz






Plot A23

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 150 kHz – 30 MHz






Plot A24

Conducted spurious emission measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 30 MHz – 900 MHz






Plot A25

Conducted spurious emission measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 900 – 902 MHz






Plot A26

Conducted spurious emission measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 928 MHz - 1 GHz






Plot A27

Conducted spurious emission measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 1 GHz – 5 GHz






Plot A28

Conducted spurious emission measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 3 Mbit/s
Frequency range: 5 GHz – 9.5 GHz






Plot A29

Conducted emission measurements within the band

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 4 Mbit/s




Limit for spurious emissions is -0.5 dBm



Plot A30

Conducted spurious emission measurements

Mode: Hybrid
F_{Low}: 903 MHz
Bit rate: 4 Mbit/s
Frequency range: 900 MHz – 902 MHz






Plot A31

Conducted emission measurements within the band

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s




In-band emissions level measured with RBW=100 kHz is 22.3 dBm
Limit for spurious emissions = 22.3 dBm – 20 dB = 2.3 dBm



Plot A32

Conducted spurious emission measurements

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s
Frequency range: 9 kHz - 150 kHz






Plot A33

Conducted spurious emission measurements

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s
Frequency range: 150 kHz – 30 MHz






Plot A34

Conducted spurious emission measurements

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s
Frequency range: 30 MHz – 902 MHz






Plot A35

Conducted spurious emission measurements

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3 Mbit/s
Frequency range: 928 MHz - 5 GHz






Plot A36

Conducted spurious emission measurements

Mode: Hybrid
F_{MIDDLE}: 915 MHz
Bit rate: 3Mbit/s
Frequency range: 5 GHz – 9.5 GHz






Plot A37

Conducted emission measurements within the band

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s




In band emissions measured with RBW=100 kHz is 22 dBm
Limit for spurious emissions = 22 dBm -20 dB = 2 dBm



Plot A38

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s
Frequency range: 9 kHz - 150 kHz






Plot A39

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 4 Mbit/s
Frequency range: 150 kHz – 30 MHz






Plot A40

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s
Frequency range: 30 MHz – 902 MHz






Plot A41

Conducted spurious emission measurements at band edges

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s
Frequency range: 928 – 930 MHz






Plot A42

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s
Frequency range: 930 MHz - 1 GHz






Plot A43

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s
Frequency range: 1 GHz – 5 GHz






Plot A44

Conducted spurious emission measurements

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 3 Mbit/s
Frequency range: 5 GHz – 9.5 GHz






Plot A45

Conducted emission measurements within the band

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 4 Mbit/s






Plot A46

Conducted spurious emission measurements at band edges

Mode: Hybrid
F_{HIGH}: 927 MHz
Bit rate: 4 Mbit/s
Frequency range: 928 – 930 MHz






Plot A47

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

16:21:33 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 94.30 kHz
62.63 dB μ V/m

LOG REF 116 0 dB μ V/m



START 90.00 kHz STOP 110.00 kHz
R #1F BW 9.0 kHz AVG BW 30 kHz SWP 50.0 msec




Plot A48

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

16:18:26 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 440 kHz
48.46 dB μ V/m






Plot A49

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

16:05:17 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 200.3 MHz
40.01 dB μ V/m






Plot A50

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

16:00:32 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 960.20 MHz
36.78 dB μ V/m






Plot A51

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

13:29:19 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.5220 GHz
43.63 dB μ V/m






Plot A52

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

13:43:17 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.52020 GHz
34.69 dB μ V/m



E(peak)=45.3 dBuV/m; Horizontal polarization; H=1.1 m; 208°




Plot A53

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

13:49:20 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.14695 GHz
34.33 dB μ V/m



E(peak)=42.3 dBuV/m; Horizontal polarization; H=1.1 m; 210°




Plot A54

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, internal antenna

13:58:29 FEB 09, 2004


ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.9948 GHz
46.61 dB μ V/m





Plot A57

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, internal antenna




The 4th harmonic of the 1st LO (903+350=1253 MHz) x 4 = 5012 MHz
 Peak value.
 Average value = 50.33 dB(μV/m) + Average factor = 50.33 dB(μV/m) - 11.84 dB = 38.49 dB(μV/m)
 Horizontal polarization



Plot A58

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, internal antenna




Peak value.



Plot A59

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, internal antenna




No other spurious except the 6th harmonic of the 1st LO.



Plot A60

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, internal antenna




6th harmonic of the 1st LO: (903 MHz+350 MHz) x 6 = 7518 MHz
Average value = 50.0 dB(μV/m) + Average factor = 50.0 dB(μV/m) - 11.84 dB = 38.16 dB(μV/m)

Vertical polarization



Plot A61

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, internal antenna




Peak value.



Plot A62

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, internal antenna



(903 MHz+350 MHz) x 7= 8771 MHz - not restricted band




Plot A63

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, internal antenna

16:27:14 FEB 09. 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 93.45 kHz
62.80 dB μ V/m






Plot A64

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, internal antenna

16:29:53 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 440 kHz
48.21 dB μ V/m






Plot A65

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, internal antenna

15:34:53 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 292.3 MHz
40.33 dB μ V/m






Plot A66

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, internal antenna

15:54:30 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 960.20 MHz
37.37 dB μ V/m






Plot A67

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, internal antenna

14:09:09 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.1450 GHz
43.97 dB μ V/m






Plot A68

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, internal antenna

14:15:26 FEB 09. 2004


ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.8720 GHz
46.50 dB μ V/m





Plot A69


Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna





Plot A70


Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna





Plot A71

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna




4th harmonic of the 1st LO: (915 MHz+350 MHz) x 4=5060 MHz
Average value=46.33 dB(μV/m) + Average factor = 46.33 dB(μV/m) - 11.84 dB = 34.49 dB(μV/m)
Horizontal polarization



Plot A72

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna




Peak value.



Plot A73


Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna





Plot A74

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna




The 6th harmonic of the 1st LO: (915+350=1265 MHz) x 6=7590 MHz
Test result: measured value + average factor = 49.17 dB(μV/m) – 11.84 dB = 37.33 dB(μV/m)
Vertical polarization



Plot A75

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna




Peak value.



Plot A76

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, internal antenna



(915 MHz+350 MHz) (1st LO) x 7=8855 MHz - not restricted band




Plot A77

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, internal antenna

16:35:27 FEB 09. 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 90.50 kHz
62.83 dB μ V/m






Plot A78

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, internal antenna

16:32:50 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 410 kHz
47.96 dB μ V/m

LOG REF 96.0 dB μ V/m






Plot A79

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, internal antenna

15:43:03 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK QP AVC
MKR 280.3 MHz
40.78 dB μ V/m






Plot A80

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, internal antenna

15:47:14 FEB 09. 2004

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 960.10 MHz
36.92 dB μ V/m






Plot A81

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, internal antenna

14:34:20 FEB 09. 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.1450 GHz
43.56 dB μ V/m






Plot A82

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, internal antenna

14:29:13 FEB 09. 2004


ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.8598 GHz
46.35 dB μ V/m





Plot A85

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




13th harmonic of 2nd LO: 356 MHz x 13 = 4628 MHz
Average value
No average factor applicable.
Horizontal polarization



Plot A86

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




Peak value



Plot A87

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




12th harmonic of 2nd LO: 356 MHz x 12 = 4272 MHz
Average value
No average factor applicable
Horizontal polarization



Plot A88

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




Peak value



Plot A89

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




4th harmonic of the 1st LO: (927 MHz+350 MHz) x 4 = 5108 MHz
Average value = 46.33 dB(μV/m) + Average factor = 46.33 dB(μV/m) - 11.84 dB = 34.49 dB(μV/m)
Horizontal polarization



Plot A90

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




Peak value



Plot A91


Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna





Plot A92

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




6^{th} harmonic of the 1^{st} LO: $(927 \text{ MHz} + 350 \text{ MHz}) \times 6 = 7662 \text{ MHz}$
 Average value = $50.0 \text{ dB}(\mu\text{V}/\text{m}) + \text{Average factor} = 50.0 \text{ dB}(\mu\text{V}/\text{m}) - 11.84 \text{ dB} = 38.16 \text{ dB}(\mu\text{V}/\text{m})$
 Vertical polarization



Plot A93

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna




Peak value



Plot A94

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, internal antenna



7th harmonic of 1st LO (927 MHz+350 MHz) x 7 = 8939 MHz-not restricted band




Plot A95

Radiated spurious emission measurements in the anechoic chamber from 150 kHz to 30 MHz,
carrier frequency 903 MHz, 15.5 dBi external antenna

16:44:28 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 150 kHz
56.14 dB μ V/m



No spurious emissions were found




Plot A96

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

11:24:20 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 239.3 MHz
33.79 dB μ V/m






Plot A97

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

10:43:28 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 973.20 MHz
48.68 dB μ V/m





Plot A98

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

16:24:20 OCT 14, 2003


ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 1.3915 GHz
48.88 dB μ V/m

LOG REF 60.0 dB μ V/m

10
dB/
#ATN
0 dB

VA SB
SC FC
ACORR

START 1.0000 GHz STOP 1.7250 GHz
RL #IF BW 1.0 MHz AVG BW 3 MHz SWP 20.0 msec






Plot A99

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

16:27:18 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.8493 GHz
48.96 dB μ V/m






Plot A100

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

11:32:09 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 1.392013 GHz
35.78 dB μ V/m






Plot A101

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

12:12:12 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.709963 GHz
50 37 dB μ V/m






Plot A102

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

12:14:36 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.708300 GHz
38 15 dB μ V/m



Test result: measured value + average factor = 38.15 dB(μ V/m) – 11.84 dB = 26.31 dB(μ V/m)




Plot A103

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna

11:07:55 OCT 15, 2003


ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.848013 GHz
49.26 dB μ V/m





Plot A104

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna




No spurious emissions were found.



Plot A105

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna




No other spurious except the 4th harmonic of the LO.



Plot A106

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna




The 4th harmonic of the LO (903+350=1253 MHz)
Peak value.
Horizontal polarization



Plot A107

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna



The 4th harmonic of the LO (903+350=1253 MHz)

Average value.


Horizontal polarization

Test result: measured value + average factor = 51.67 dB(μV/m) – 11.84 dB = 26.31 dB(μV/m)



Plot A108

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna




No other spurious except the 6th harmonic of the LO.



Plot A109


Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna





Plot A111

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 903 MHz, 15.5 dBi external antenna



No spurious emissions were found.




Plot A112

Radiated spurious emission measurements in the anechoic chamber from 150 kHz to 30 MHz,
carrier frequency 915 MHz, 15.5 dBi external antenna

16:46:49 OCT 14, 2003

ACTU DET: PEAK
MEAS DET: PEAK QP AVG
MKR 150 kHz
56.26 dB μ V/m



No spurious emissions were found




Plot A113

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna

12:37:46 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 239.3 MHz
33.75 dB μ V/m






Plot A114

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna

12:48:42 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 985.00 MHz
47.38 dB μ V/m

LOG REF 60.0 dB μ V/m





Plot A115

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna


16:15:18 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 1.3915 GHz
48.90 dB μ V/m

LOG REF 60.0 dB μ V/m

10
dB/
#ATN
0 dB

VA SB
SC FC
ACORR



START 1.0000 GHz STOP 1.7250 GHz
RL #IF BW 1.0 MHz AVG BW 3 MHz SWP 20.0 msec



Plot A116

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna


16:09:56 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.8493 GHz
47.34 dB μ V/m

LOG REF 60.0 dB μ V/m

10
dB/
#ATN
0 dB

VA SB
SC FC
ACORR



START 2.2000 GHz STOP 2.9000 GHz
RL #IF BW 100 kHz AVO BW 300 kHz SWP 210 msec




Plot A117

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna

11:28:57 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.391963 GHz
35.64 dB μ V/m






Plot A118

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna

11:11:34 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.848013 GHz
49.05 dB μ V/m






Plot A119

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna

12:19:41 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.745700 GHz
49.40 dB μ V/m



The 3rd harmonic, peak value




Plot A120

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna

12:21:13 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.744313 GHz
37.57 dB μ V/m




The 3rd harmonic, average value

Test result: measured value + average factor = 37.57 dB(μ V/m) – 11.84 dB = 25.73dB(μ V/m)



Plot A121


Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna





Plot A122

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna




No other spurious except of the 4th harmonic of the LO.



Plot A123

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna




The 4th harmonic of the LO (915+350=1265 MHz)
Peak value.
Horizontal polarization



Plot A124

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna



The 4th harmonic of the LO (915+350=1265 MHz)

Average value.


Horizontal polarization

Test result: measured value + average factor = 48.17 dB(μV/m) – 11.84 dB = 36.33 dB(μV/m)



Plot A125

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna




No other spurious except the 6th harmonic of the LO.



Plot A127

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 915 MHz, 15.5 dBi external antenna



The 6th harmonic of the LO (915+350=1265 MHz)

Average value.

Vertical polarization

Test result: measured value + average factor = 45.67 dB(μV/m) – 11.84 dB = 33.83 dB(μV/m)




Plot A129

Radiated spurious emission measurements in the anechoic chamber from 150 kHz to 30 MHz,
carrier frequency 927 MHz, 15.5 dBi external antenna

16:50:13 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 150 kHz
55.67 dB μ V/m



No spurious emissions were found




Plot A130

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna

13:23:50 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 239.3 MHz
37.31 dB μ V/m





Plot A131

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna

13:07:01 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 995.50 MHz
46.59 dB μ V/m

LOG REF 60.0 dB μ V/m

10

dB/

ATN

10 dB

VA SB

SC FC

ACORR


START 960.00 MHz

RL IF BW 120 kHz

AVC BW 300 kHz

STOP 1.00000 GHz

SWP 37.5 msec






Plot A132

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna

15:51:25 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 1.0000 GHz
48.23 dB μ V/m





Plot A133

Radiated spurious emission measurements in the anechoic chamber in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna


16:05:15 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.8493 GHz
46.57 dB μ V/m

LOG REF 60.0 dB μ V/m

10
dB/
#ATN
0 dB

VA SB
SC FC
ACORR



START 2.2000 GHz STOP 2.9000 GHz
R #IF BW 100 kHz AVO BW 300 kHz SWP 210 msec




Plot A134

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna

11:25:07 OCT 15, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 1.391975 GHz
35.57 dB μ V/m






Plot A135

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna

11:19:05 OCT 15, 2003


ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.848013 GHz
49.12 dB μ V/m





Plot A136

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna




No spurious emissions were found.



Plot A138

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna




No spurious emissions were found.



Plot A139

Radiated spurious emission measurements at the OATS in restricted bands,
carrier frequency 927 MHz, 15.5 dBi external antenna



The 7th harmonic of the LO-not restricted band
LO: 927 + 350 = 1277 (MHz)
1277 x 7 = 8939 (MHz)




Plot A140

Radiated emission measurements in the anechoic chamber in receive mode, EUT with internal antenna

10:48:47 FEB 09. 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 360.2 MHz
43.99 dB μ V/m






Plot A141

Radiated emission measurements in the anechoic chamber in receive mode, EUT with internal antenna

12:04:34 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 2.881 GHz
47.35 dB μ V/m






Plot A142

Radiated emission measurements in the anechoic chamber in receive mode, EUT with internal antenna

12:18:31 FEB 09, 2004

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 4.200 GHz
48.69 dB μ V/m






Plot A143

Radiated emission measurements in the anechoic chamber in receive mode, EUT with external antenna

14:10:27 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 952.3 MHz
35.32 dB μ V/m






Plot A144

Radiated emission measurements in the anechoic chamber in receive mode, EUT with external antenna

15:11:57 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 2.848 GHz
49.43 dB μ V/m






Plot A145

Radiated emission measurements in the anechoic chamber in receive mode, EUT with external antenna

15:39:17 OCT 14, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 6.347 GHz
47.87 dB μ V/m






Plot A146

Conducted emission measurements at AC power line in receive mode

Line identification: Line 1
Limit: Quasi-peak, average

12:05:41 OCT 19, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 5.04 MHz
45.62 dB μ V/m






Plot A147

Conducted emission measurements at AC power line in receive mode

Line identification: Line 2
Limit: Quasi-peak, average

12:22:42 OCT 19, 2003

ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 4.88 MHz
49.67 dBμV






Plot A148

Conducted emission measurements at AC power line in transmit mode

Line identification: Line 1
Limit: Quasi-peak, average

12:45:12 OCT 19, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 4.88 MHz
49.57 dB μ V






Plot A149

Conducted emission measurements at AC power line in transmit mode

Line identification: Line 2
Limit: Quasi-peak, average

12:37:15 OCT 19, 2003

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 14.99 MHz
30.55 dBμV





Appendix B Test equipment used for tests

HL Serial No.	Description	Manufacturer information			Due calibration Month/ year
		Name	Model No.	Serial No.	
0038	Antenna Mast, 1-4 m	Hermon Labs	AM-1	028	2/05 check
0091	Position controller for antenna mast + turntable, OFTS	Hermon Labs	CRL-2	091	4/05 check
0287	Turntable, motorized diameter, 2 m	Hermon Labs	TMD-2	042	11/04 check
0446	Active loop antenna 10 kHz-30 MHz	Electro-Mechanics	6502	2857	10/04
0447	LISN, 16/2, 300 V RMS	Hermon Labs	LISN 16-1	447	11/04
0465	Anechoic chamber 9 (L) x 6.5 (W) x 5.5 (H) m	Hermon Labs	AC-1	023	10/04
0466	Shielded room 3 (L) x 3 (W) x 2.4 (H) m	Hermon Labs	SR-1	024	11/04 check
0521	Spectrum analyzer with RF filter section (EMI receiver 9 kHz - 6.5 GHz)	Hewlett Packard	8546A	0319	7/04
0589	Cable coaxial, GORE A2POL118.2, 3m	Hermon Labs	GORE-3	589	11/04
0592	Position controller	Hermon Labs	L2-SR3000	100	5/04 check
0593	Antenna Mast, 1-4 m/ 1-6 m Pneumatic	Hermon Labs	AM-F1	101	2/05 check
0594	Turntable for Anechoic Chamber, flush mounted, d=1.2 m, pneumatic	Hermon Labs	WDC1	102	1/05 check
0604	Antenna biconilog log-periodic/T bow- tie, 26 - 2000 MHz	EMCO	3141	9611-1011	1/05
0787	Transient limiter	Hewlett Packard	11947A-8ZE	3107A01877	11/04
1003	Cable coaxial, M17/164, 10 m	Hermon Labs	C17164-10	161	11/04
1004	Cable coaxial, ANDREW PSWJ4, 6 m	Hermon Labs	ANDREW-6	163	12/04
1097	Attenuator, 50 Ohm, 2 W, DC to 8 GHz, 20 dB	Midwest Microwave	0793-20-NN- 07	1097	1/05
1200	Quadruplexer	Electronica	UE 84	0240	4/05 check
1205	One phase voltage regulator, 2kVA, 0- 250V	Hermon Labs	TDGC-2	109	6/04 check
1365	Cable coaxial, RG-214, 5 m	Hermon Labs	C214-5	1365	4/05
1424	Spectrum analyzer, 30 Hz - 40 GHz	Agilent Technologies	8564EC	3946A00219	8/04



HL Serial No.	Description	Manufacturer information			Due calibration Month/ year
		Name	Model No.	Serial No.	
1430	EMI receiver system, 9 kHz - 2.9 GHz	Agilent Technologies	8542E	3807A00262	9/04
1503	Cable RF, 6 m	Belden	M17/167 MIL-C-17	1503	9/04 check
1650	Attenuators set (2, 3, 5, 20 dB), DC – 18 GHz	M/A –COM	2082	1650	3/05
1651	Attenuators set (2, 3, 5, 20 dB), DC – 18 GHz	M/A –COM	2082	1651	3/05
1942	Cable 18 GHz, 4 m, blue	Rhophase Microwave Ltd	SPS-1803A-4000-NPS	T4658	10/04
1947	Cable 18 GHz, 6.5 m, blue	Rhophase Microwave Ltd	NPS-1803A-6500-NPS	T4974	10/04
1984	Antenna, double ridged waveguide horn, 1-18 GHz, 300W, N-type	EMC Test Systems	3115	9911-5964	3/05
2009	Cable RF, 8 m	Alpha Wire	RG-214	2009	12/04
2254	Cable 40GHz, 0.8 m, blue	Rhophase Microwave Limited	KPS-1503A-800-KPS	W4907	11/04
2259	Amplifier low noise 2-20 GHz	Sophia Wireless	LNA0220-C	0223	11/04
2399	Cable 40 GHz, 1.5 m, blue	Rhophase Microwave Ltd.	KPS-1503A-1500-KPS	X2945	6/04
2432	Antenna, double-ridged waveguide horn, 1-18 GHz	EMC Test Systems	3115	000271777	7/04



Appendix C Test equipment correction factors

Correction factor
Line impedance stabilization network
Model LISN 16 - 1
Hermon Laboratories

Frequency, kHz	Correction factor, dB
10	4.9
15	2.86
20	1.83
25	1.25
30	0.91
35	0.69
40	0.53
50	0.35
60	0.25
70	0.18
80	0.14
90	0.11
100	0.09
125	0.06
150	0.04

The correction factor in dB is to be added to meter readings of an interference analyzer or a spectrum analyzer.

Antenna factor
Active Loop Antenna
Model 6502, S/N 2857

Frequency, MHz	Magnetic antenna factor, dB	Electric antenna factor, dB
0.009	-32.8	18.7
0.010	-33.8	17.7
0.020	-38.3	13.2
0.050	-41.1	10.4
0.075	-41.3	10.2
0.100	-41.6	9.9
0.150	-41.7	9.8
0.250	-41.6	9.9
0.500	-41.8	9.8
0.750	-41.9	9.7
1.000	-41.4	10.1
2.000	-41.5	10.0
3.000	-41.4	10.2
4.000	-41.4	10.1
5.000	-41.5	10.1
10.000	-41.9	9.6
15.000	-41.9	9.6
20.000	-42.2	9.3
25.000	-42.8	8.7
30.000	-44.0	7.5

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



**Antenna factor,
biconilog antenna EMCO, model 3141,
serial number 1011 (HL 0604)**

Frequency, MHz	Antenna factor, dB(1/m)	Frequency, MHz	Antenna factor, dB(1/m)
26	7.8	940	24.0
28	7.8	960	24.1
30	7.8	980	24.5
40	7.2	1000	24.9
60	7.1	1020	25.0
70	8.5	1040	25.2
80	9.4	1060	25.4
90	9.8	1080	25.6
100	9.7	1100	25.7
110	9.3	1120	26.0
120	8.8	1140	26.4
130	8.7	1160	27.0
140	9.2	1180	27.0
150	9.8	1200	26.7
160	10.2	1220	26.5
170	10.4	1240	26.5
180	10.4	1260	26.5
190	10.3	1280	26.6
200	10.6	1300	27.0
220	11.6	1320	27.8
240	12.4	1340	28.3
260	12.8	1360	28.2
280	13.7	1380	27.9
300	14.7	1400	27.9
320	15.2	1420	27.9
340	15.4	1440	27.8
360	16.1	1460	27.8
380	16.4	1480	28.0
400	16.6	1500	28.5
420	16.7	1520	28.9
440	17.0	1540	29.6
460	17.7	1560	29.8
480	18.1	1580	29.6
500	18.5	1600	29.5
520	19.1	1620	29.3
540	19.5	1640	29.2
560	19.8	1660	29.4
580	20.6	1680	29.6
600	21.3	1700	29.8
620	21.5	1720	30.3
640	21.2	1740	30.8
660	21.4	1760	31.1
680	21.9	1780	31.0
700	22.2	1800	30.9
720	22.2	1820	30.7
740	22.1	1840	30.6
760	22.3	1860	30.6
780	22.6	1880	30.6
800	22.7	1900	30.6
820	22.9	1920	30.7
840	23.1	1940	30.9
860	23.4	1960	31.2
880	23.8	1980	31.6
900	24.1	2000	32.0
920	24.1		

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



Antenna factor
Double-ridged wave guide horn antenna
Model 3115, S/N 9911-5964, HL1984

Frequency, MHz	Antenna factor, dB(1/m)
1000.0	24.7
1500.0	25.7
2000.0	27.6
2500.0	28.9
3000.0	31.2
3500.0	32.0
4000.0	32.5
4500.0	32.7
5000.0	33.6
5500.0	35.1
6000.0	35.4
6500.0	34.9
7000.0	36.1
7500.0	37.8
8000.0	38.0
8500.0	38.1
9000.0	39.1
9500.0	38.3
10000.0	38.6
10500.0	38.2
11000.0	38.7
11500.0	39.5
12000.0	40.0
12500.0	40.4
13000.0	40.5
13500.0	41.1
14000.0	41.6
14500.0	41.7
15000.0	38.7
15500.0	38.2
16000.0	38.8
16500.0	40.5
17000.0	42.5
17500.0	45.9
18000.0	49.4

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



Antenna factor
Double-ridged guide horn antenna
Model 3115, serial number: 00027177, HL2432

Frequency, MHz	Antenna factor. dB(1/m)
1000.0	24.7
1500.0	25.7
2000.0	27.8
2500.0	28.9
3000.0	30.7
3500.0	31.8
4000.0	33.0
4500.0	32.8
5000.0	34.2
5500.0	34.9
6000.0	35.2
6500.0	35.4
7000.0	36.3
7500.0	37.3
8000.0	37.5
8500.0	38.0
9000.0	38.3
9500.0	38.3
10000.0	38.7
10500.0	38.7
11000.0	38.9
11500.0	39.5
12000.0	39.5
12500.0	39.4
13000.0	40.5
13500.0	40.8
14000.0	41.5
14500.0	41.3
15000.0	40.2
15500.0	38.7
16000.0	38.5
16500.0	39.8
17000.0	41.9
17500.0	45.8
18000.0	49.1

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).



Cable loss
Cable Coaxial, GORE A2P01POL118, 2.3 m, model:GORE-3, HL 0589
+ Cable Coaxial, ANDREW PSWJ4, 6m, model: ANDREW-6, HL 1004

No.	Frequency, MHz	Cable loss, dB	Tolerance (Specification), dB	Measurement uncertainty, dB
1	30	0.33	≤ 6.5	±0.12
2	50	0.40		
3	100	0.57		
4	300	0.97		
5	500	1.25		
6	800	1.59		
7	1000	1.81		
8	1200	1.97		
9	1400	2.15		
10	1600	2.28		
11	1800	2.43		
12	2000	2.61		
13	2200	2.75		
14	2400	2.89		
15	2600	2.97		
16	2800	3.21	≤ 6.5	±0.12
17	3000	3.32		
18	3300	3.47		
19	3600	3.62		
20	3900	3.84		
21	4200	3.92		
22	4500	4.07		
23	4800	4.36		
24	5100	4.62		
25	5400	4.78		
26	5700	5.16		
27	6000	5.67		
28	6500	5.99		±0.17



Cable loss
Cable coaxial, M17/164, model: C17164-10, s/n 161, HL 1003

No.	Frequency, MHz	Cable loss, dB	Tolerance, dB	Measurement uncertainty, dB
1	30	0.41	≤ 12.5	±0.12
2	50	0.52		
3	100	0.75		
4	300	1.45		
5	500	2.01		
6	800	2.71		
7	1000	3.14		
8	1200	3.56		
9	1400	3.93		
10	1600	4.31		
11	1800	4.63		
12	2000	4.97		
13	2200	5.32		
14	2400	5.65		
15	2600	6.01	≤ 12.5	±0.12
16	2800	6.42		
17	3000	6.76		
18	3300	7.12		
19	3600	7.53		
20	3900	7.95		
21	4200	8.32		
22	4500	8.72		
23	4800	9.14		
24	5100	9.59		
25	5400	10.00		
26	5700	10.49		
27	6000	11.07		
28	6500	11.80		
				±0.17



Cable loss
Cable coaxial, 6 m, model: M17/167 MIL-C-17, HL 1503

Frequency, MHz	Cable loss, dB
0.1	0.02
1	0.07
3	0.15
5	0.17
10	0.26
30	0.43
50	0.57
80	0.72
100	0.81
300	1.48
500	2.00
800	2.70
1000	3.09



Cable loss
Cable 18 GHz, 4 m, blue, model: SPS-1803A-4000-NPS, S/N T4658, HL 1942

Frequency, GHz	Cable loss, dB
0.03	0.21
0.05	0.26
0.10	0.36
0.20	0.50
0.30	0.61
0.40	0.70
0.50	0.78
0.60	0.85
0.70	0.93
0.80	0.99
0.90	1.04
1.00	1.10
1.10	1.16
1.20	1.22
1.30	1.26
1.40	1.31
1.50	1.35
1.60	1.41
1.70	1.45
1.80	1.49
1.90	1.53
2.00	1.57
2.10	1.61
2.20	1.65
2.30	1.69
2.40	1.72
2.50	1.76
2.60	1.79
2.70	1.83
2.80	1.87
2.90	1.90
3.10	1.97
3.30	2.04
3.50	2.11
3.70	2.18
3.90	2.24
4.10	2.31
4.30	2.38
4.50	2.43
4.70	2.53
4.90	2.53
5.10	2.63
5.30	2.65
5.90	2.79

Frequency, GHz	Cable loss, dB
6.10	2.88
6.30	2.90
6.50	2.97
6.70	3.02
6.90	3.04
7.10	3.07
7.30	3.12
7.50	3.13
7.70	3.19
7.90	3.24
8.10	3.30
8.30	3.36
8.50	3.45
8.70	3.41
8.90	3.45
9.10	3.42
9.30	3.55
9.50	3.48
9.70	3.58
9.90	3.61
10.10	3.66
10.30	3.68
10.50	3.70
10.70	3.70
10.90	3.75
11.10	3.78
11.30	3.86
11.50	3.98
11.70	4.10
11.90	4.12
12.10	4.09
12.40	4.13
13.00	4.23
13.50	4.35
14.00	4.40
14.50	4.44
15.00	4.57
15.50	4.66
16.00	4.64
16.50	4.66
17.00	4.75
17.50	4.85
18.00	4.93



Cable loss
Cable 18 GHz, 6.5 m, blue, model: NPS-1803A-6500-NPS, S/N T4974, HL 1947

Frequency, GHz	Cable loss, dB
0.03	0.30
0.05	0.38
0.10	0.53
0.20	0.74
0.30	0.91
0.40	1.05
0.50	1.18
0.60	1.29
0.70	1.40
0.80	1.50
0.90	1.59
1.00	1.68
1.10	1.77
1.20	1.86
1.30	1.94
1.40	2.01
1.50	2.08
1.60	2.16
1.70	2.22
1.80	2.29
1.90	2.36
2.00	2.42
2.10	2.48
2.20	2.54
2.30	2.60
2.40	2.66
2.50	2.71
2.60	2.77
2.70	2.83
2.80	2.89
2.90	2.95
3.10	3.06
3.30	3.17
3.50	3.28
3.70	3.39
3.90	3.51
4.10	3.62
4.30	3.76
4.50	3.87
4.70	4.01
4.90	4.10
5.10	4.21
5.30	4.31
5.50	4.43
5.70	4.56
5.90	4.71

Frequency, GHz	Cable loss, dB
6.10	4.87
6.30	4.95
6.50	4.94
6.70	4.88
6.90	4.87
7.10	4.83
7.30	4.85
7.50	4.86
7.70	4.91
7.90	4.96
8.10	5.03
8.30	5.08
8.50	5.13
8.70	5.21
8.90	5.22
9.10	5.34
9.30	5.35
9.50	5.52
9.70	5.51
9.90	5.66
10.10	5.70
10.30	5.78
10.50	5.79
10.70	5.82
10.90	5.86
11.10	5.94
11.30	6.06
11.50	6.21
11.70	6.44
11.90	6.61
12.10	6.76
12.40	6.68
13.00	6.66
13.50	6.81
14.00	6.90
14.50	6.90
15.00	6.97
15.50	7.17
16.00	7.28
16.50	7.27
17.00	7.38
17.50	7.68
18.00	7.92



Cable loss
RF cable 8 m, model RG-214, HL 2009

No.	Frequency, MHz	Cable loss, dB	Tolerance (Specification), dB	Measurement uncertainty, dB
1	1	0.10	NA	±0.12
2	10	0.14		
3	30	0.25		
4	50	0.34		
5	100	0.53		
6	300	0.99		
7	500	1.31		
8	800	1.73		
9	1000	1.98		
10	1100	2.11		
11	1200	2.21		
12	1300	2.35		
13	1400	2.46		
14	1500	2.55		
15	1600	2.68		
16	1700	2.78		
17	1800	2.88		
18	1900	2.98		
19	2000	3.09		



Cable loss
Cable 40 GHz, 0.8 m, blue, model: KPS-1503A-800-KPS, serial number W4907, HL 2254

Frequency, GHz	Cable loss, dB	Frequency, GHz	Cable loss, dB	Frequency, GHz	Cable loss, dB
0.03	0.04	5.10	0.80	15.00	1.49
0.05	0.07	5.30	0.83	15.50	1.49
0.10	0.09	5.50	0.83	16.00	1.46
0.20	0.15	5.70	0.84	16.50	1.47
0.30	0.19	5.90	0.87	17.00	1.50
0.40	0.25	6.10	0.86	17.50	1.57
0.50	0.29	6.30	0.89	18.00	1.63
0.60	0.33	6.50	0.90	18.50	1.57
0.70	0.37	6.70	0.89	19.00	1.63
0.80	0.41	6.90	0.93	19.50	1.65
0.90	0.44	7.10	0.92	20.00	1.64
1.00	0.45	7.30	0.95	20.50	1.75
1.10	0.48	7.50	0.96	21.00	1.72
1.20	0.51	7.70	0.97	21.50	1.78
1.30	0.53	7.90	1.01	22.00	1.76
1.40	0.54	8.10	1.00	22.50	1.72
1.50	0.57	8.30	1.05	23.00	1.83
1.60	0.59	8.50	1.04	23.50	1.80
1.70	0.04	8.70	1.07	24.00	1.90
1.80	0.07	8.90	1.11	24.50	1.81
1.90	0.09	9.10	1.09	25.00	1.98
2.00	0.15	9.30	1.14	25.50	1.91
2.10	0.19	9.50	1.12	26.00	2.02
2.20	0.25	9.70	1.15	26.50	1.92
2.30	0.29	9.90	1.16	27.00	1.97
2.40	0.33	10.10	1.16	28.00	2.02
2.50	0.37	10.30	1.19	29.00	1.95
2.60	0.41	10.50	1.14	30.00	1.94
2.70	0.44	10.70	1.19	31.00	2.11
2.80	0.45	10.90	1.17	32.00	2.17
2.90	0.48	11.10	1.13	33.00	2.27
3.10	0.61	11.30	1.20	34.00	2.27
3.30	0.64	11.50	1.13	35.00	2.29
3.50	0.65	11.70	1.20	36.00	2.35
3.70	0.68	11.90	1.18	37.00	2.37
3.90	0.69	12.10	1.14	38.00	2.40
4.10	0.71	12.40	1.19	39.00	2.57
4.30	0.73	13.00	1.34	40.00	2.36
4.50	0.75	13.50	1.33		
4.70	0.77	14.00	1.48		
4.90	0.79	14.50	1.45		



Cable loss
Cable coaxial, 40GHz, 1.5 m, Blue, Rhophase Microwave Limited, model: KPS-1503A-1500-KPS, HL 2399

Frequency, GHz	Cable loss, dB	Frequency, GHz	Cable loss, dB	Frequency, GHz	Cable loss, dB
0.03	0.07	6.5	1.57	15.50	2.50
0.05	0.10	6.7	1.60	16.00	2.51
0.1	0.16	6.9	1.55	16.50	2.58
0.2	0.26	7.1	1.65	17.00	2.65
0.3	0.33	7.3	1.65	17.50	2.73
0.5	0.38	7.5	1.70	18.00	2.74
0.7	0.41	7.7	1.71	18.50	2.67
0.9	0.58	7.9	1.73	19.00	2.67
1.1	0.64	8.1	1.79	19.50	2.74
1.3	0.70	8.3	1.81	20.00	2.69
1.5	0.75	8.5	1.84	20.50	2.80
1.7	0.79	8.7	1.85	21.00	2.82
1.9	0.83	8.9	1.90	21.50	2.87
2.1	0.88	9.1	1.95	22.00	2.87
2.3	0.93	9.3	1.93	22.50	2.92
2.5	0.97	9.5	1.98	23.50	3.04
2.7	1.01	9.7	1.96	24.00	3.05
2.9	1.04	9.9	2.03	24.50	3.03
3.1	1.08	10.1	1.99	25.00	3.11
3.3	1.14	10.30	2.02	25.50	3.10
3.5	1.17	10.50	2.02	26.00	3.17
3.7	1.21	10.70	2.02	26.50	3.11
3.9	1.24	10.90	2.08	27.00	3.16
4.1	1.26	11.10	2.02	28.00	3.19
4.3	1.26	11.30	2.09	29.00	3.19
4.5	1.29	11.50	2.05	30.00	3.30
4.7	1.34	11.70	2.11	31.00	3.31
4.9	1.34	11.90	2.11	32.00	3.35
5.1	1.40	12.10	2.12	33.00	3.46
5.3	1.43	12.40	2.17	34.00	3.45
5.5	1.45	13.00	2.29	35.00	3.49
5.7	1.47	13.50	2.31	36.00	3.54
5.9	1.40	14.00	2.43	37.00	3.62
6.1	1.53	14.50	2.43	39.00	3.69
6.3	1.55	15.00	2.46	40.00	3.75



Appendix D General information

Test facility description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility. Hermon Laboratories is listed by the Federal Communications Commission (USA) for all parts of Code of Federal Regulations 47 (CFR 47) and by Industry Canada for electromagnetic emissions (file numbers IC 2186-1 for OATS and IC 2186-2 for anechoic chamber), certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, C-845 for conducted emissions site), assessed by TNO Certification EP&S (Netherlands) for a number of EMC, telecommunications, environmental, safety standards, and by AMTAC (UK) for safety of medical devices. The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01).

Address: PO Box 23, Binyamina 30500, Israel.

Telephone: +972 4628 8001

Fax: +972 4628 8277

e-mail: mail@hermonlabs.com

website: www.hermonlabs.com

Person for contact: Mr. Alex Usoskin, QA manager.

Abbreviations and acronyms

The following abbreviations and acronyms are applicable to this test report:

AC	alternating current
dB	decibel
dBm	decibel referred to one milliwatt
dB(μ V)	decibel referred to one microvolt
dB(μ V/m)	decibel referred to one microvolt per meter
DSS	Part 15 spread spectrum transmitter
EMC	electromagnetic compatibility
EUT	equipment under test
GHz	gigahertz
H	height
Hz	hertz
IF	intermediate frequency
kHz	kilohertz
kV	kilovolt
L	length
LISN	line impedance stabilization network
LO	local oscillator
m	meter
MHz	megahertz
NA	not applicable
QP	quasi-peak
RF	radio frequency
RE	radiated emission
rms	root mean square
s	second
V	volt
W	width

Specification references

47CFR part 15: 2003	Radio Frequency Devices
ANSI C63.2: 1996	American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications.
ANSI C63.4: 2001	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.