



AIRUNITY 3550-3700 MHz

Indoor Antenna

Data Sheet

Model Number: AN1018-1

Document Part Number: DPS01159

Document Revision: 1.0 Published: Jan 2023 © Copyright by Airspan Networks Ltd., 2023. All rights reserved worldwide.

Legal Notices

The information contained within this document is proprietary, privileged and intended only for the recipient. As such, the information is subject to all relevant copyright, patent and other laws protecting intellectual property, as well as any specific agreements protecting Airspan Networks Ltd. rights in the aforesaid information. Neither this document nor the information contained herein may be published, reproduced, transmitted or disclosed to third parties, in whole or in part, without the express, prior, written permission of Airspan Networks Ltd. In addition, any use of this document or the information contained herein for the purposes other than those for which it is disclosed is strictly forbidden.

Airspan Networks Ltd. reserves the right, without prior notice or liability, to make changes in equipment design or specifications.

Information supplied by Airspan Networks Ltd. is believed in good faith to be accurate and reliable, while every care has been taken in preparing these documents. However, Airspan Networks Ltd. does not make any representations and gives no warranties of whatever nature in respect of these documents, including without limitation, the accuracy or completeness of any information, facts and/or opinions contained therein. No responsibility is assumed by Airspan Networks Ltd. for the use of the documents nor for the rights of third parties which may be effected in any way by the use thereof. The provision of these documents (and the documents themselves) does not constitute professional advice of any kind. Any representation(s) in these documents concerning performance of Airspan Networks Ltd. product(s) are for informational purposes only and are not warranties of future performance, either expressed or implied. Airspan Networks Ltd., its affiliates, directors, employees and agents shall not be held liable for any damages or losses, of any nature whatsoever, arising from any use of and/or reliance on the documents.

These documents may contain flaws, omissions or typesetting errors; no warranty is granted nor liability assumed in relation thereto unless specifically undertaken in Airspan Networks Ltd. sales contract or order confirmation. Information contained herein is periodically updated and changes will be incorporated into subsequent editions. If you have encountered an error, please notify Airspan Networks Ltd.

P/N: DPS01159

Product performance figures quoted within this document are indicative and for information purposes only.

Document Information

Revision History

| Revision | Date | Summary of Changes | Created by |
|----------|--------------|--------------------|------------|
| Rev1.0 | January 2023 | First Release | Moti S |

1. Specifications

Manufactured by: Airspan Model Number: AN1018-1

| Frequency range | 3550 – 3700 MHz | |
|---|-------------------------------------|--|
| Gain Max | 10dBi | |
| Azimuth HPBW | 60° ± 10° | |
| Elevation HPBW @ Boresight | 40° ± 10° | |
| Polarization discrimination at 0° | > 18 dB | |
| Front to back ratio ((Typical) | ≥ 15 dB | |
| Polarization | Dual Slant ±45° | |
| Electrical Down-tilt | 0° | |
| Impedance | 50 ohms | |
| VSWR | <1.5:1 | |
| First side-lob level | <12dB | |
| Isolation between RF Ports | ≥ 22 dB | |
| Average transmission power per polarization | 26 dBm | |
| Peak transmission power per polarization | 36 dBm | |
| Connector type | 2 x U.FL RA | |
| Cable | RG 178 with FEP jacket | |
| Cable length /Connector orientation | 170 &170 mm/N | |
| DC Grounding | All Antenna ports to be DC grounded | |