



Operational description

# WiMAX 3.7 GHz

MicroMAX 3.7GHz

Connecting the World with Wireless Access Solutions

Revision Record: WiMAX. 3.7GHz		
Pub/ Rev	Date	Update Description
01	Decembert-31	Airspan. Author: InterDoc
Publication No. 28080512-01		

© Copyright by **Airspan Networks LTD.**, 2003. All rights reserved worldwide.

The information contained in this document is proprietary and is subject to all relevant copyright, patent and other laws protecting intellectual property, as well as any specific agreement protecting **Airspan Networks LTD.** rights in the aforesaid information. Neither this document nor the information contained herein may be published, reproduced or disclosed to third parties, in whole or in part, without the express, prior, written permission of **Airspan Networks LTD.** In addition, any use of this document or the information contained herein for any purposes other than those for which it was disclosed is strictly forbidden.

**Airspan Networks LTD.** reserves the right, without prior notice or liability, to make changes in equipment design or specifications.

Information supplied by **Airspan Networks LTD.** is believed to be accurate and reliable. However, no responsibility is assumed by **Airspan Networks LTD.** for the use thereof nor for the rights of third parties which may be effected in any way by the use thereof.

Any representation(s) in this document concerning performance of **Airspan Networks LTD.** product(s) are for informational purposes only and are not warranties of future performance, either express or implied. **Airspan Networks LTD.** standard limited warranty, stated in its sales contract or order confirmation form, is the only warranty offered by **Airspan Networks LTD.** in relation thereto.

This document may contain flaws, omissions or typesetting errors; no warranty is granted nor liability assumed in relation thereto unless specifically undertaken in **Airspan Networks LTD.** sales contract or order confirmation. Information contained herein is periodically updated and changes will be incorporated into subsequent editions. If you have encountered an error, please notify **Airspan Networks LTD.** All specifications are subject to change without prior notice.

## 1. Scope

This document provides a description of the WiMAX 3.7GHz product.

## 2. MicroMAX(Base Station)

A Base station radio, MicroMAX 3.7GHz TDD Int., is part of a WiMAX broadband fixed cellular wireless access system. The system provides a radio link between an end-user (a subscriber) and a network to give high-speed data access. The MicroMAX's transceiver/receiver (Up to 64 QAM modulation, data rate up to 18Mbps) uses OFDM and operating in TDD duplexing mode, equipped with a 14 dBi internal antenna. The maximum RF output power (not including antenna gain) is 27.43 dBm and it can be reduced by software.

The MicroMAX is installed outdoors and typically is mounted on a pole. The ProST transmits and receives traffic to and from the base station respectively. The transceiver provides subscribers with "always-on" Internet, high speed data only, or data and voice (VoIP) services and is configured with a unique base station reference number, preventing the ProST from relocating to another subscriber premises without authorization.

### 2.1. EUT (MicroMAX) test configuration

The EUT ports and lines description is given in the table below.

Port type	Port description	Connector type	Quantity	Cable type	Cable length (m)	Indoor /outdoor	Connected to
Data + DC	48 VDC + Ethernet	15-pin D-type	1	Cat. 5 – 4x2 twisted pair	100	Outdoor	SDA

### 3.3 - 3.8 GHz Integrated Antenna Sector 60°

#### MA-WC36-AS14

#### Specifications

Electrical	
Frequency range	3.3 - 3.8 GHz
GAIN.	3.4-3.8 GHz @14 dBi min. 3.3-3.4 GHz @13.7 dBi min
VSWR, max.	1.5: 1
3dB Beam Width - Azimuth, Typical	60°
3dB Beam Width - Elevation, Typical	16.5° ± 2°
Polarization	Linear, Vertical
Side-lobes Level H-Plane	ETSI EN-302 085 V1.2.1 (2003-03) class CS3
Cross Polarization, min	-18 dB
Front to Back Ratio	ETSI EN-302 085 V1.2.1 (2003-03) class CS2
Power Handling	5 Watt
Input Impedance	50 Ohm
Mechanical and Environmental	
Dimensions (L x W x H)	135 x 265 x 0.8 mm
Connector	MCX, Male
Radume	Airspan Enclosure
Flammability	UL 94V-0
Operating Temperature	-40° to +85°
Lightning Protection	DC Grounded