

# Analysis Report

The Equipment Under Test (EUT) is a portable 2.4GHz Pure Transmitter operating at 2408-2472MHz for RC Car. The EUT is powered by 2 X 1.5V AA batteries. After switch on the EUT and paired with RC Car, the RC Car can be controlled to move forward, backward, turning left/ right direction by the controller.

Antenna Type: Internal antenna

Antenna Gain: 0Bi

Nominal rated field strength: 94.2dB $\mu$ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 4dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 98.2dB $\mu$ V/m at 3m in frequency 2.4GHz, thus;

The EIRP =  $[(FS * D)^2 * 1000 / 30] = 1.982\text{mw}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 1.982mW.

The SAR Exclusion Threshold Level:

=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in}$

GHz) =  $3.0 * 5 / \text{sqrt}(2.475) \text{ mW}$

= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.