

Analysis Report

The Equipment Under Test (EUT) is a 2.4GHz Car operating from 2408.2-2464.2MHz with 1MHz channel spacing for RC Controller. The EUT is powered by 4*1.5V AA batteries. After switch on the EUT and paired with RC Controller, the EUT can be controlled to move forward, backward, turn left/right by Controller.

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength: 82.3dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 82.9dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS * D)^2 * 1000 / 30] = 0.102\text{mw}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.102mW.

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in}$

GHz) = $3.0 * 5 / \text{sqrt}(2.4642) \text{ mW}$

= 0.102 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.