

Analysis Report

The Equipment Under Test (EUT) is a 2.4GHz Pure Transmitter Controller for RC car operated at 2410.2, 2420.2 and 2460.2MHz only. The EUT is powered by 2 X 1.5V AAA batteries. After switch on the EUT and RC Car, the RC Car can be controlled to move forward, backward, turn right/left by the controller.

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength: 83.2dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 86.2dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS * D)^2 * 1000 / 30] = 0.125mw$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.125mW.

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in}$

GHz) = $3.0 * 5 / \text{sqrt}(2.4602) \text{ mW}$

= 9.56 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.