

| Report N | Vo. : | - | AE019179-001 | Date: | 20 | 04 | · N | Joveml | oer (|)2 |
|----------|-------|---|--------------|-------|----|----|-----|--------|-------|----|
|----------|-------|---|--------------|-------|----|----|-----|--------|-------|----|

Application No.: LE211474(8)

Client : Mattel Asia Pacific Sourcing Ltd.

13/F., South Tower, World Finance Centre,

Harbour City, Tsim Sha Tsui, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be <u>Swamp Blaster Airboat</u> of Model No. <u>H2552</u>

Rating : 9.6V Rechargeable battery

No. of sample(s) : Two (2) piece(s) ***

Date Received : 2004 October 11.

Test Period : 2004 October 11 - 2004 October 25.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – April 2004

ANSI C63.4 – 2001

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC

Part 15 Subpart B.

For and on behalf of CMA Testing and Certification Laboratories

Authorized Signature: Page 1 of 11

Danny Chui

EMC Engineer - EL. Division

FCC ID: PIYH2552-04A4R



Report No. : AE019179-001 Date : 2004 October 21

Table of Contents

| G | eneral Information | 3 |
|-----|--|---|
| 1.1 | General Description | 3 |
| 1.2 | Related Submittal Grants | 3 |
| 1.3 | Location of the test site | 4 |
| 1.4 | List of measuring equipment | 5 |
| D | escription of the radiated emission test | 6 |
| 2.1 | Test Procedure | 6 |
| 2.2 | Test Result | 6 |
| 2.3 | Radiated Emission Measurement Data | 7 |
| D | escription of the Line-conducted Test | 8 |
| 3.1 | Test Procedure | 8 |
| 3.2 | Test Result | 8 |
| 3.3 | Graph and Table of Conducted Emission Measurement Data | 8 |
| Pł | hotograph | 9 |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conduction Emission | 9 |
| 4.2 | Photographs of the External and Internal Configurations of the EUT | 9 |
| Su | pplementary document | 10 |
| 5.1 | Bandwidth | 10 |
| 6 | Appendices | 11 |
| | 1.1 1.2 1.3 1.4 D 2.1 2.2 2.3 D 3.1 3.2 3.3 Pl 4.1 4.2 Su 5.1 | 1.2 Related Submittal Grants 1.3 Location of the test site |



Report No. AE019179-001 Date: 2004 October 21

1 **General Information**

1.1 **General Description**

The equipment under test (EUT) is a super regenerative receiver for Swamp Blaster Airboat. Operating at 49.860 MHz which is controlled by a LRC circuit. The EUT is powered by 9.6V rechargeable battery. When it received Forward, Backward, Turn Left & Turn Right radio signal, it will moving to difference direction.

- The brief circuit description is listed as follows:
 Q1 and associated circuit act as RF demodulcation.
- Q13, Q14, Q17, Q18 and associated circuit act as low voltage protection.
- U1 and associated circuit act as decoder.
- RL1, RL2 & Q9 ~ Q12 and associated circuit act as main motor driver.
- $Q3 \sim Q8$ and associated circuit act as steering motor driver.

1.2 **Related Submittal Grants**

This is a single application for certification of a receiver.



Report No. : AE019179-001 Date : 2004 October 21

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. A double shielded room is located at :

Roof Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AE019179-001 Date : 2004 October 21

1.4 List of measuring equipment

| Equipment | Manufacturer | Model No. | Serial No. | Calibration Certification No. |
|-------------------|--------------|-----------|------------|-------------------------------|
| EMI Test Receiver | R&S | ESCS30 | 100001 | S21141 |
| Broadband Antenna | Schaffner | CBL6113B | 2718 | AC1753 |
| Signal Generator | IFR | 2023B | 202302/938 | Nil |
| LISN | R&S | ESH3-Z5 | 100038 | S21142 |
| Pulse Limiter | R&S | ESH3-Z2 | 100001 | 20-73194 |
| Biconical Antenna | R&S | HK116 | 837414/004 | 4000.7752.02 |



Report No. : AE019179-001 Date : 2004 October 21

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of $1.5 \,\mathrm{m}\,x$ 1m and $0.8 \,\mathrm{m}$ high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (super regenerative receiver) at its operating frequency in order to "cohere" the characteristic broadband emissions from the receiver.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR qusai-peak detector.

It was found that the EUT meet the FCC requirement.



Report No. : AE019179-001 Date : 2004 October 21

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dBµV/m) | Antenna and Cable factor (dB) | Field Strength (dBµV/m) | Limit at 3m (dBµV/m) | Margin (dB) |
|-----------------|-------------------|------------------------|-------------------------------|-------------------------|----------------------|----------------|
| 49.311 | V | 12.9 | 13.2 | 26.1 | 40.0 | -13.9 |
| 50.086 | V | 16.8 | 8.7 | 25.5 | 40.0 | -14.5 |
| 51.166 | V | 15.3 | 8.7 | 24.0 | 40.0 | -16.0 |
| 52.190 | V | 15.4 | 8.7 | 24.1 | 40.0 | -15.9 |
| 52.760 | V | 15.2 | 8.7 | 23.9 | 40.0 | -16.1 |
| 94.156 | Н | 15.1 | 10.0 | 25.1 | 43.5 | -18.4 |
| 95.110 | Н | 14.9 | 10.0 | 24.9 | 43.5 | -18.6 |
| 95.338 | Н | 15.5 | 10.0 | 25.5 | 43.5 | -18.0 |
| 95.599 | Н | 15.9 | 10.0 | 25.9 | 43.5 | -17.6 |
| 140.637 | Н | 12.4 | 12.4 | 24.8 | 43.5 | -18.7 |



Report No. : AE019179-001 Date : 2004 October 21

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2001. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AE019179-001 Date : 2004 October 21

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



Report No. : AE019179-001 Date : 2004 October 21

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document | Filename |
|-------------------------|--------------|
| ID Label/Location | LabelSmp.jpg |
| Block Diagram | BlkDia.pdf |
| Schematic Diagram | Schem.pdf |
| Users Manual | UserMan.pdf |
| Operational Description | OpDes.pdf |

5.1 Bandwidth

NA

5.2 The duty cycle is simply the on-time divided by the period :

NA



Report No. : AE019179-001 Date : 2004 October 21

6 Appendices

| A1. | Photos of the set-up of Radiated Emissions | 1 page |
|-----|--|---------|
| A2. | Photos of External Configurations | 1 page |
| A3. | Photos of Internal Configurations | 1 page |
| A4. | ID Label/Location | 2 pages |
| A5. | Block Diagram | 1 page |
| A6. | Schematics | 1 page |
| A7. | User Manual | 4 pages |
| A8. | Operation Description | 1 page |

***** End of Report *****