

Report No. : AF013230-001 Date : 2005 June 24

Application No.: LF210675(0)

Client : Mattel Asia Pacific Sourcing Ltd.

13/F., South Tower, World Finance Centre,

Harbour City, Tsim Sha Tsui, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be Shell Shocker of Model No. H6927

Rating : 1 x 9V size battery

No. of submitted sample : One (1) piece ***

Date Received : 2005 June 08

Test Period : 2005 June 08 – 2005 June 20

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004

ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart C.

For and on behalf of CMA Testing and Certification Laboratories

Authorized Signature : Page 1 of 11

Damy Chui

EMC Engineer - EL. Division



Report No. : AF013230-001 Date : 2005 June 24

Table of Contents

1	Gen	neral Information	3
	1.1	General Description	3
	1.2	Location of the test site	4
	1.3	List of measuring equipment.	5
2	Des	cription of the radiated emission test	
	2.1	Test Procedure	6
	2.2	Test Result	6
	2.3	Radiated Emission Measurement Data	7
3	Des	cription of the Line-conducted Test	8
	3.1	Test Procedure	8
	3.2	Test Result	8
	3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Pho	tograph	9
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	
	4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supp	olementary document	10
	5.1	Bandwidth	10
	5.2	Duty Cycle	10
6	App	endices	11



Date: 2005 June 24 Report No. AF013230-001

1 **General Information**

General Description 1.1

The equipment under test (EUT) is a transmitter for shell shocker. Operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by 9V battery and it has two control buttons in the EUT. When the control button is pressed once, it will transmit a radio signal to receiver unit.

The brief circuit description is listed as follows:

- U1 and associated circuit act as encoder.
- Y1, Q2 and associated circuit act as oscillator.Q3 and associated circuit act as RF amplify.
- D2 and associated circuit act as voltage adjust.



Report No. : AF013230-001 Date : 2005 June 24

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AF013230-001 Date : 2005 June 24

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001
Loop Antenna	EMCO	6502	00056620	49906



Report No. : AF013230-001 Date : 2005 June 24

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



Report No. : AF013230-001 Date : 2005 June 24

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
27.145	V	75.0	9.0	-7.1	76.9	80.0	-3.1
52.290	V	14.3	8.8	-	23.1	40.0	-16.9
81.435	Н	13.3	7.9	-	21.2	40.0	-18.8
* 108.580	Н	13.7	11.9	-	25.6	43.5	-17.9
* 135.725	Н	10.4	13.4	-	23.8	43.5	-19.7
* 162.870	Н	14.5	11.4	-	25.9	43.5	-17.6
190.015	Н	14.7	10.1	-	24.8	43.5	-18.7
217.160	Н	24.8	10.8	-	35.6	46.0	-10.4
* 244.305	Н	20.2	10.8	-	31.0	46.0	-15.0
* 271.450	Н	12.0	14.3	-	26.3	46.0	-19.7



Report No. : AF013230-001 Date : 2005 June 24

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AF013230-001 Date : 2005 June 24

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



Report No. : AF013230-001 Date : 2005 June 24

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt 2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 Duty Cycle

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 9.72 ms

Effective period of the cycle = $(550 \times 5) \mu s + (260 \times 6) \mu s$

= 4.31 ms

Duty Cycle = 4.31 ms / 9.72 ms

= 0.44

Therefore, the average factor is found by $20 \log_{10} 0.44 = -7.1 \text{ dB}$



Report No. : AF013230-001 Date : 2005 June 24

6 Appendices

A5 Bandwidth Plot 1 p A6 Average Factor 2 p A7 Block Diagram 1 p A8 Schematics 1 p A9 User Manual 4 p	ages age ages age age ages
1	ages

***** End of Report *****