



## TEST REPORT

Report No. : AF011572-001 Date : 2005 June 03  
Application No. : LF209310(4)  
Client : Mattel Asia Pacific Sourcing Ltd.  
13/F., South Tower, World Finance Centre,  
Harbour City, Tsim Sha Tsui, Kowloon, Hong Kong  
Sample Description : One(1) submitted sample stated to be Chrysler 300C of Model No. J4032  
Rating : 4 x 1.5V AA size battery  
7.2V rechargeable battery  
No. of submitted sample : One (1) piece\*\*\*  
Date Received : 2005 May 23  
Test Period : 2005 May 23 – 2005 May 31  
Test Requested : FCC Part 15 Certification  
Test Method : FCC Rules and Regulations Part 15 – July 2004  
ANSI C63.4 – 2003  
Test Result : See attached sheet(s) from page 2 to 11.  
Conclusion : The submitted sample was found to comply with requirement of FCC Part 15  
Subpart B.

*For and on behalf of*  
CMA Testing and Certification Laboratories

Authorized Signature : \_\_\_\_\_

Daimy Chui  
EMC Engineer - EL. Division

Page 1 of 11

FCC ID : PIYJ4032-05A4R



## TEST REPORT

Report No. : AF011572-001

Date : 2005 June 03

### Table of Contents

|     |  |    |
|-----|--|----|
| 1   | General Information .....  | 3  |
| 1.1 | General Description .....  | 3  |
| 1.2 | Location of the test site .....  | 4  |
| 1.3 | List of measuring equipment.....   | 5  |
| 2   | Description of the radiated emission test .....                                  | 6  |
| 2.1 | Test Procedure .....   | 6  |
| 2.2 | Test Result .....  | 6  |
| 2.3 | Radiated Emission Measurement Data .....   | 7  |
| 3   | Description of the Line-conducted Test.....                                      | 8  |
| 3.1 | Test Procedure .....   | 8  |
| 3.2 | Test Result .....  | 8  |
| 3.3 | Graph and Table of Conducted Emission Measurement Data .....                     | 8  |
| 4   | Photograph .....   | 9  |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conduction Emission..... | 9  |
| 4.2 | Photographs of the External and Internal Configurations of the EUT.....          | 9  |
| 5   | Supplementary document.....  | 10 |
| 5.1 | Bandwidth.....   | 10 |
| 5.2 | Duty Cycle .....   | 10 |
| 6   | Appendices.....  | 11 |



## **TEST REPORT**

Report No. : AF011572-001

Date : 2005 June 03

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a superregenerative receiver for Chrysler 300C. Operating at 49.860MHz which is controlled by LRC circuit. The EUT is powered by 7.2V rechargeable battery and 4 x 1.5V "AA" size battery. When it power on, it can receive a radio signal and go difference direction with LED flashing and music.

The brief circuit description is listed as follows :

- Q1 and associated circuit act as RF AMP.
- U1 and associated circuit act as RX decoder.
- U7, U8 and associated circuit act as sound AMP.
- Q24 ~ Q26 and associated circuit act as M1 motor control.
- Q7, Q8, Q10, Q11, Q14, RL1, RL2 and associated circuit act as M2 motor control.
- U3, U4 and associated circuit act as protect circuit.
- Q6 and associated circuit act as voltage regulator.



## **TEST REPORT**

Report No. : AF011572-001

Date : 2005 June 03

### **1.2 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## TEST REPORT

Report No. : AF011572-001

Date : 2005 June 03

### 1.3 List of measuring equipment

| Equipment         | Manufacturer | Model No. | Serial No. | Calibration Certification No. |
|-------------------|--------------|-----------|------------|-------------------------------|
| EMI Test Receiver | R&S          | ESCS30    | 100001     | S43284                        |
| Broadband Antenna | Schaffner    | CBL6112B  | 2692       | CA3025                        |
| Signal Generator  | IFR          | 2023B     | 202302/938 | S43098                        |
| LISN              | R&S          | ESH3-Z5   | 100038     | S43377                        |
| LISN              | R&S          | ESH3-Z5   | 100010     | S43101                        |
| Pulse Limiter     | R&S          | ESH3-Z2   | 100001     | S43325                        |
| Biconical Antenna | R&S          | HK116     | 837414/004 | 2GB05000535-0001              |



## **TEST REPORT**

Report No. : AF011572-001

Date : 2005 June 03

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

#### **2.2 Test Result**

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasipeak detector.

It was found that the EUT meet the FCC requirement.



## TEST REPORT

Report No. : AF011572-001

Date : 2005 June 03

### 2.3 Radiated Emission Measurement Data

**Radiated emission**  
**pursuant to**  
**the requirement of FCC Part 15 subpart B**

| Frequency<br>(MHz) | Polarity<br>(H/V) | Reading at 3m<br>(dB $\mu$ V/m) | Antenna and<br>Cable factor<br>(dB) | Field Strength<br>(dB $\mu$ V/m) | Limit at 3m<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|--------------------|-------------------|---------------------------------|-------------------------------------|----------------------------------|-------------------------------|----------------|
| 49.149             | V                 | 17.3                            | 10.3                                | 27.6                             | 40.0                          | -12.4          |
| 49.505             | V                 | 18.2                            | 10.3                                | 28.5                             | 40.0                          | -11.5          |
| 50.037             | V                 | 21.1                            | 8.1                                 | 29.2                             | 40.0                          | -10.8          |
| 50.215             | V                 | 21.2                            | 8.1                                 | 29.3                             | 40.0                          | -10.7          |
| 52.697             | V                 | 19.1                            | 8.1                                 | 27.2                             | 40.0                          | -12.8          |
| 95.147             | V                 | 13.8                            | 9.2                                 | 23.0                             | 43.5                          | -20.5          |
| 101.797            | V                 | 12.4                            | 11.0                                | 23.4                             | 43.5                          | -20.1          |
| 143.567            | V                 | 17.2                            | 11.9                                | 29.1                             | 43.5                          | -14.4          |
| 143.866            | V                 | 14.0                            | 11.9                                | 25.9                             | 43.5                          | -17.6          |
| 202.303            | V                 | 13.6                            | 9.7                                 | 23.3                             | 43.5                          | -20.2          |



## **TEST REPORT**

Report No. : AF011572-001

Date : 2005 June 03

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable





## **TEST REPORT**

Report No. : AF011572-001

Date : 2005 June 03

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho6.jpg.



## TEST REPORT

Report No. : AF011572-001

Date : 2005 June 03

### 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document                | Filename     |
|-------------------------|--------------|
| ID Label/Location       | LabelSmp.jpg |
| Block Diagram           | BlkDia.pdf   |
| Schematic Diagram       | Schem.pdf    |
| Users Manual            | UserMan.pdf  |
| Operational Description | OpDes.pdf    |

#### 5.1 Bandwidth

N/A

#### 5.2 Duty Cycle

N/A



## **TEST REPORT**

Report No. : AF011572-001

Date : 2005 June 03

### **6 Appendices**

|    |  |         |
|----|--|---------|
| A1 | Photos of the set-up of Radiated Emissions | 1 page  |
| A2 | Photos of External Configurations          | 1 page  |
| A3 | Photos of Internal Configurations          | 3 pages |
| A4 | ID Label/Location                          | 1 page  |
| A5 | Block Diagram                              | 1 page  |
| A6 | Schematics Diagram                         | 1 page  |
| A7 | User Manual                                | 4 pages |
| A8 | Operation Description                      | 1 page  |

\*\*\*\*\* End of Report \*\*\*\*\*