



TEST REPORT

Report No. : AG010058-001 Date : 2006 June 16

Application No. : LG207288(5)

Client : Mattel Asia Pacific Sourcing Limited
13/F., South Tower, World Finance Centre,
Harbour City, Tsim Sha Tsui,
Kowloon, Hong Kong.

Sample Description : One(1) submitted sample(s) stated to be Naruto Ninja Challenge
of Model No. J7838
Rating : 4 x 1.5V AAA size batteries
No. of submitted sample : Two (2) piece(s) ***

Date Received : 2006 April 21

Test Period : 2006 April 26 – 2006 April 28

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Danny Chui
Deputy Manager - EL. Division

FCC ID: PIYJ7838-06A4T

Page 1 of 11



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

Table of Contents

1	General Information.....	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test.....	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph.....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT.....	9
5	Supplementary document.....	10
5.1	Bandwidth.....	10
5.2	Duty cycle.....	10
5.3	Transmission time.....	10
6	Appendices.....	11



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for Naruto Ninja Challenge. It is operate at radio frequency channel 49.860MHz which generated by a crystal. The EUT is powered by 4 x 1.5V AAA size batteries. When it switched on and press the button switch once, it will transmit a radio signal to receiver and the sound will come out.

The brief circuit description is listed as follows:

- U1, Q4, Q3 and associated circuit act as encoder.
- Y1, Q1 and associated circuit act as oscillator
- Q2 and associated circuit act as RF amplify.



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCI	100152
Broadband Antenna	Schaffner	CBL6112B	2692



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasi-peak detector.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

2.3 Radiated Emission Measurement Data

Radiated emission
pursuant to
the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
49.860	V	52.8	10.3	-6.6	56.5	80.0	-23.5
99.728	H	30.6	9.2	-	39.8	43.5	-3.7
149.581	H	10.9	11.9	-	22.8	43.5	-20.7
199.452	H	13.6	9.2	-	22.8	43.5	-20.7
*249.164	H	20.9	9.7	-	30.6	46.0	-15.4
299.269	H	21.3	13.9	-	35.2	46.0	-10.8
349.071	H	15.8	14.9	-	30.7	46.0	-15.3
398.807	H	14.5	14.9	-	29.4	46.0	-16.6
448.742	H	10.5	17.7	-	28.2	46.0	-17.8
498.579	H	11.9	17.7	-	29.6	46.0	-16.4



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26dB below the carrier level. It meets the requirement of Section 15.235(b).

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

$$\begin{aligned} \text{The duration of one cycle} &= 55.6\text{ms} \\ \text{Effective period of the cycle} &= (0.96 \times 12)\text{ms} + (0.48 \times 30)\text{ms} \\ &= 25.92\text{ms} \\ \text{Duty Cycle} &= (25.92 / 55.6)\text{ms} \\ &= 0.466 \end{aligned}$$

Therefore, the average factor is found by $20 \log_{10} 0.466 = -6.6\text{dB}$

5.3 Transmission time

N/A



TEST REPORT

Report No. : AG010058-001

Date : 2006 June 16

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics n	1	page
A9.	User Manual	11	pages
A10.	Operation Description	1	page

***** End of Report *****