



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1) Date : 04 Oct 2011

Application No. : LN030478(0)

Applicant : Mattel Asia Pacific Sourcing Ltd.
1301, South Tower, World Finance Center,
Harbour City, Tsimshatsui, Hong Kong

Sample Description : One(1) item of submitted sample stated to be RC ANNV MONSTER JAM
VEHIC
of Model No. W5697
Radio Frequency : 27.145MHz Transmitter
Rating : 2 x 1.5V AA size batteries
No. of submitted sample : Two (2) piece (s)

Date Received : 05 Sep 2011.

Test Period : 23 Sep 2011 to 30 Sep 2011.

Test Requested : FCC Part 15 Certification.


Test Method : 47 CFR Part 15 (10-1-10 Edition)
ANSI C63.4 – 2009

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Mr. WONG Lap-pong, Andrew
Assistant Manager
Electrical Division

Page 1 of 11

FCC ID: PIYW5697-12A2T



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心 **TEST REPORT**

Report No. : AN0054419(1)

Date : 04 Oct 2011

Table of Contents

| | | |
|-----|---|----|
| 1 | General Information..... | 3 |
| 1.1 | General Description..... | 3 |
| 1.2 | Location of the test site..... | 4 |
| 1.3 | List of measuring equipment..... | 5 |
| 1.4 | Measurement Uncertainty..... | 5 |
| 2 | Description of the radiated emission test..... | 6 |
| 2.1 | Test Procedure..... | 6 |
| 2.2 | Test Result..... | 6 |
| 2.3 | Radiated Emission Measurement Data..... | 7 |
| 3 | Description of the Line-conducted Test..... | 8 |
| 3.1 | Test Procedure..... | 8 |
| 3.2 | Test Result..... | 8 |
| 3.3 | Graph and Table of Conducted Emission Measurement Data..... | 8 |
| 4 | Photograph..... | 9 |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conducted Emission..... | 9 |
| 4.2 | Photographs of the External and Internal Configurations of the EUT..... | 9 |
| 5 | Supplementary document..... | 10 |
| 5.1 | Bandwidth..... | 10 |
| 5.2 | Duty cycle..... | 10 |
| 5.3 | Transmission time..... | 10 |
| 6 | Appendices..... | 11 |



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for RC ANNV MONSTER JAM VEHIC. It operates at 27.145MHz and the oscillation of radio control is generated by a crystal. The EUT is powered by 2 x 1.5V AA size batteries. There are four buttons on the EUT. When the button are pressed, the EUT will transmit radio control signal to the receiver.

The antenna is permanently attached in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

- U1 and its associated circuit act as an encoder.
- Y1 and its associated circuit act as an oscillator
- U2 and its associated circuit act as a sound IC.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2009. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

1.3 List of measuring equipment

| Equipment | Manufacturer | Model No. | Serial No. | Calibration Due Date |
|-------------------|--------------|-----------|------------|----------------------|
| EMI Test Receiver | R&S | ESCI | 100152 | 16 May 2012 |
| Broadband Antenna | Schaffner | CBL6112B | 2718 | 31 Oct 2012 |
| Loop Antenna | EMCO | 6502 | 91072651 | 19 Apr 2012 |
| Coaxial Cable | Schaffner | RG213/U | N/A | 03 Aug 2012 |
| Coaxial Cable | Schaffner | RG213/U | N/A | 03 Aug 2012 |

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

| Frequency | Uncertainty (U_{lab}) |
|------------------------------|---------------------------|
| 30MHz ~ 200MHz (Horizontal) | 4.63dB |
| 30MHz ~ 200MHz (Vertical) | 4.64dB |
| 200MHz ~1000MHz (Horizontal) | 4.65dB |
| 200MHz ~1000MHz (Vertical) | 4.64dB |

Conducted emissions

| Frequency | Uncertainty (U_{lab}) |
|----------------|---------------------------|
| 150kHz ~ 30MHz | 3.04dB |



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

The frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

| Parameter | Recorded value |
|----------------------|----------------|
| Ambient temperature: | 24 °C |
| Relative humidity: | 56 % |

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dBμV) | Antenna Factor and Cable Loss (dB/m) | Average Factor (dB) | Field Strength at 3m (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|-----------------|----------------|----------------------|--------------------------------------|---------------------|-------------------------------|----------------------|-------------|
| 27.145 | V | 72.8 | 8.7 | - 6.7 | 74.8 | 80.0 | - 5.2 |
| 54.291 | V | 9.7 | 10.4 | - | 20.1 | 40.0 | - 19.9 |
| 81.436 | V | 8.7 | 7.9 | - | 16.6 | 40.0 | - 23.4 |
| #108.582 | H | 12.4 | 11.8 | - | 24.2 | 43.5 | - 19.3 |
| #135.728 | H | 9.1 | 13.7 | - | 22.8 | 43.5 | - 20.7 |
| #162.875 | H | 11.3 | 11.6 | - | 22.9 | 43.5 | - 20.6 |
| 190.016 | H | 15.7 | 11.5 | - | 27.2 | 43.5 | - 16.3 |
| 217.161 | H | 22.8 | 11.0 | - | 33.8 | 46.0 | - 12.2 |
| #244.308 | H | 33.0 | 11.0 | - | 44.0 | 46.0 | - 2.0 |
| #271.454 | H | 16.1 | 14.9 | - | 31.0 | 46.0 | - 15.0 |



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2009. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document | Filename |
|-------------------------|--------------|
| ID Label/Location | LabelSmp.jpg |
| Block Diagram | BlkDia.pdf |
| Schematic Diagram | Schem.pdf |
| Users Manual | UserMan.pdf |
| Operational Description | OpDes.pdf |

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

$$\text{The duration of one cycle} = 32.1\text{ms}$$

$$\begin{aligned} \text{Effective period of the cycle} &= (6 \times 940\mu\text{s}) + (20 \times 460\mu\text{s}) \\ &= 14.84\text{ms} \end{aligned}$$

$$\begin{aligned} \text{Duty Cycle} &= 14.84 / 32.1 \\ &= 0.46 \end{aligned}$$

Therefore, the average factor is found by $20 \log_{10} 0.46 = -6.7\text{dB}$

5.3 Transmission time

Not Applicable



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0054419(1)

Date : 04 Oct 2011

6 Appendices

| | | | |
|------|--|---|-------|
| A1. | Photos of the set-up of Radiated Emissions | 1 | page |
| A2. | Photos of External Configurations | 1 | page |
| A3. | Photos of Internal Configurations | 1 | page |
| A4. | ID Label/Location | 1 | page |
| A5. | Bandwidth Plot | 1 | page |
| A6. | Average Factor | 2 | pages |
| A7. | Block Diagram | 1 | page |
| A8. | Schematics Diagram | 1 | page |
| A9. | User Manual | 2 | pages |
| A10. | Operation Description | 1 | page |

***** End of Report *****