



TX:49M

Standard Common part for master

Capacitor
(1st priority)

No:	Part Value	Qty for update SCH
1	10PF chip 50v +80-20% SMD 0603	
2	20pF chip 50v +80-20% SMD 0603	
3	25pF chip 50v +80-20% SMD 0603	
4	1000pF chip 50v +80-20% SMD 0603	
5	0.1uF chip 50V +80-20% Y5V, 50V SMD0603	
6	0.1uF 25V +80-20% Y5V, PKG: Ceramic dia 6mm x 3.5	
7	0.033uF 25V Y5V, PKG: dia 4mm x 3.5	
8	10uF 25V +/-20% AL EL PKG-5x11mm	
9	47uF 25V +/-20% AL EL PKG-5x11mm	
10	100uF 25V +/-20% AL EL PKG-5x11mm	
10	220uF 25V +/-20% AL EL PKG-5x11mm	

Resistor:

1	10 ohm +/-5% 0603
2	100 ohm +/-5% 0603
3	1K ohm +/-5% 0603
4	4.7Kohm +/-5% 0603
5	10k ohm +/-5% 0603
6	47k ohm +/-5% 0603
7	100kohm +/-5% 0603
8	220k ohm +/-5% 0603
9	1M ohm +/-5% 0603
10	2.2M ohm +/-5% 0603

Diode:

1	IN4001PKG: DO-41 50V
2	IN4148 PKG: DO-35 50V

Transistor

1	S8050NPN (1.5A /SOT-23 V: 40; W: 0.3;
2	S8550D PNP(1.5A /SOT-23 V: 40; W: 0.3;
3	S9014D NPN (1.5A /SOT-23 V: 40; W: 0.3;
4	B772 PNP A: 3; V: 40; Max. W: 1.25; PKG: TO-126;
5	D882 NPN A: 3; V: 40; Max. W: 1.25; PKG: TO-126;

Inductor

1	Choke Coil DESC: 5.6uH 10% 1/2W
---	---------------------------------

PTC

1	MF-R400-0-99
---	--------------

Diode:

1	IN5817: DO-41 50V
---	-------------------

Non Standard parts Guide Line (2nd priority)
Using E3 value for resistor, capacitor and inductor
Standard IEC E3 Decade Value = 100, 220 & 470

Non Standard parts Guide Line (3rd priority)
Using E6 value for resistor, capacitor and inductor
Standard IEC E6 Decade value = 100, 150, 220, 330, 470 & 680

MATEL MAPS All rights reserved

TEST MODE:	REMARKS:	IC information:	History
		1.operating voltage:2.2V-5.5V 2.Standby current is 1uA 3.DATA rate is 1.25Kbps	

Size	Number	Project Name	Revision
A3	X7273	RC-CARS 2 EZ DRIVER	R0
Date	1/12/2012	MATER REFRESH	Sheet of
File : C:\Documents and Settings\huhce1\Desktop\X7271 FCC & RSS-310 document\X7271 TX sch 49M SchDoc			