



Raymarine UK Ltd  
Marine House  
Cartwright Drive  
Segensworth  
Fareham  
Hampshire  
PO15 5RJ  
Tel: 01329 246700




Email: [compliance@raymarine.com](mailto:compliance@raymarine.com)

<http://www.raymarine.com>

---

## Test Report for a75WIFI, a77WIFI & a78WIFI Marine Multifunction Displays

### To RSS-210 and 47 CFR Part 15 Subpart C – Spurious Emissions

Model Number	E70166, E70167, E70203		
Product Description	a75 WIFI, a77 WIFI, a78 WIFI		
Report Number	TP/847/1012		
Report Author Mike Thompson EMC Engineer		Date	7 <sup>th</sup> August 2013
Technical Check Paul Pitt EMC Engineer		Date	8 <sup>th</sup> August 2013
Approval Andrew Little Compliance Manager		Date	8 <sup>th</sup> August 2013

Test Date Range	29 <sup>th</sup> July 2013 – 2 <sup>nd</sup> August 2013
-----------------	--

Product Status	PASS
----------------	------

This test report shall not be reproduced except in full, without written approval of Raymarine UK Ltd.

The test data and results contained within this report relate only to the items tested.

# 1 RSS 210 and 47 CFR Part 15 Test Summary


	CFR 47 Part 15	RSS-210	Section	Result
Hopping Sequence	15.247(a)		See TP/808/1066a section 5.4	Pass
Peak Output Power	15.247(b)	A8.4(2)	See TP/808/1066a section 5.3	Pass
Carrier Frequency Separation	15.247(a)	A8.1(b)	See TP/808/1066a section 5.4	Pass
Frequency Band Edges	15.247(d)		See TP/808/1066a section 5.8	Pass
20dB Bandwidth	15.247(a)(1)	A8.1(a)	See TP/808/1066a section 5.7	Pass
Radiated Emissions	15.209(a)	RSS-GEN 7.5.2	6	Pass
Spurious Emissions	15.247(d)	A8.5	7	Pass
Number of Channels	15,247(a)(1)	A8.1(d)	See TP/808/1066a section 5.4	Pass
Directional antenna with >6dBi	15.247(c)		See TP/808/1066a section 5.2 Antenna<6dBi	N/A
Dwell Time	15.247(a)	A8.1(d)	See TP/808/1066a section 5.4	Pass
6dB Bandwidth		A8.2(a)	See TP/808/1066a section 5.9	Pass
Power Spectral Density		A8.2(b)	See TP/808/1066a section 5.10	Pass

## 2 Attestations

This equipment has been tested in accordance with the standards identified in this report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in these reports.

All measuring instruments used to determine the status of the product's compliance to the identified standards are calibrated regularly in accordance with UKAS requirements.

A comprehensive system of traceable calibration in accordance with ISO9001 is maintained.

Name/Position	Signature	Date
Mike Thompson EMC Engineer		6 <sup>th</sup> August 2013

I attest that the necessary measurements were made, under my supervision at:

Raymarine UK Ltd, Marine House, Cartwright Drive, Segensworth, Fareham, Hampshire,  
PO15 5RJ.



Andy Little  
Compliance Manager

**Date 8<sup>th</sup> August 2013**

TABLE OF CONTENTS

1 RSS 210 and 47 CFR Part 15 Test Summary ..... 2

2 Attestations ..... 3

3 Test Information ..... 5

    3.1 Test Facilities ..... 5

    3.2 Overall Test Conditions ..... 5

    3.3 Test Methods ..... 5

4 EUT Information ..... 6

    4.1 Test Rationale ..... 6

    4.2 Description of Equipment under Test (EUT) ..... 6

    4.3 Additional information ..... 7

    4.4 Description of Auxiliary Equipment ..... 7

    4.5 Test setup ..... 8

    4.6 Emissions – Below 2GHz ..... 9

    4.7 Transmitter Spurious Emissions – 2GHz to 26GHz ..... 9

5 Photographs ..... 9

6 Emissions Results ..... 10

    6.1 a77, 30 foot range, Radiated Emissions 9 kHz to 150 kHz ..... 10

    6.2 a77, 400 foot range, Radiated Emissions 9 kHz to 150 kHz ..... 11

    6.3 a77, 30 foot range, Radiated Emissions 150 kHz to 30MHz ..... 12

    6.4 a77, 400 foot range, Radiated Emissions 150 kHz to 30MHz ..... 13

    6.5 a77, 30 foot range, Radiated Emissions 30MHz to 300MHz ..... 14

    6.6 a77, 400 foot range, Radiated Emissions 30MHz to 300MHz ..... 15

    6.7 a77, 30 foot range, Radiated Emissions 300MHz to 1GHz ..... 16

    6.8 a77, 400 foot range, Radiated Emissions 300MHz to 1GHz ..... 17

    6.9 a77, 30 foot range, Radiated Emissions 1GHz to 2GHz ..... 18

    6.10 a77, 400 foot range, Radiated Emissions 1GHz to 2GHz ..... 18

    6.11 FCC Part 15, Chapter 47\_15.247 Spurious Emissions 2GHz to 26GHz ..... 19

7 Receiver Spurious Emissions ..... 29

8 List of Test Equipment ..... 30

### 3 Test Information

#### 3.1 Test Facilities

Site 1	9m x 6m x 5.5m Semi Anechoic Chamber	FCC ID IC Certification	371673 4069B-2
--------	---	----------------------------	-------------------

#### 3.2 Overall Test Conditions

Work Area	Relative Humidity (%)	Air Pressure (mbar)	Ambient Temperature (°C)
Site 1-5	60-65	1003-1005	18.5-19.6
Sites 6-10	59-65	1013-1015	21.2-22.0

#### 3.3 Test Methods

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C paragraph 15.247(d) (Bluetooth and WIFI, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

Number	Standard Number	Document Title
1	47 CFR Part 15 (10-01-09 Edition)	Radio Frequency Devices

##### 3.3.1 Deviations from Test Methods

None

## 4 EUT Information

### 4.1 Test Rationale

Tested to ensure compliance to FCC Chapter 47, part 15: 15.209(a) Radiated Emissions 15.247(d) Spurious Emissions
---

### 4.2 Description of Equipment under Test (EUT)

Date of Receipt:	25 <sup>th</sup> July 2013
Client:	Stephen Grant
Brand Name:	Raymarine
Product Range:	a7
Country of Manufacture:	China
Operational voltage range:	12VDC

#### Unit 1

Model Name or Number:	a78WIFI
Unique Type Identification:	E70203
FCC ID	PJ5-WFBT8
IC ID	4069B-WFBT8
Serial Number:	EMC130725b
CCT Diagram Number(s) & Issue:	CPU 1002601-4 Sonar 1002573-2 Keyboard 1001673-1 GPS 1001653-5 Chart 1001663-1
PCB Assembly Number(s) & Issue:	CPU 1002602-4 Sonar 1002574-2 D-13-0184 v3 Keyboard 1001674-1 GPS 1001654-5 Chart 1001664-1
Software Version:	Boot 7.26-00131 Kernel 3.4.41-rm Application 7.32-00619
Modifications to Unit:	None


#### 4.3 Additional information

This test report is also applicable to the following multifunctional displays :-  
a75 WIFI & a77 WIFI

#### 4.4 Description of Auxiliary Equipment

Product Type	Part Number	Serial Number
E97	E70022	EMC120117A
i70 Instrument	E22172	E221721010302
Transducer	P58	

4.5 Test setup






#### 4.6 Emissions – Below 2GHz

Below 2GHz the unit was setup in a system to ensure the EUT was fully functional. The Bluetooth and WIFI were functional during testing.

#### 4.7 Transmitter Spurious Emissions – 2GHz to 26GHz


2GHz to 26GHz the unit was setup in a system to ensure the EUT was fully functional. Control of the Bluetooth & WiFi was controlled externally to enable the Bluetooth and WiFi Emissions to be measured separately.

### 5 Photographs




## 6 Emissions Results

### 6.1 a78, 30 foot range, Radiated Emissions 9 kHz to 150 kHz




Loop Face On




Loop Side On


6.2 a78, 400 foot range, Radiated Emissions 9 kHz to 150 kHz



6.3 a78, 30 foot range, Radiated Emissions 150 kHz to 30MHz





Loop Face On




Loop Side On

6.4 a78, 400 foot range, Radiated Emissions 150 kHz to 30MHz




6.5 a78 30 foot range, Radiated Emissions 30MHz to 300MHz




Nr	Frequency (MHz)	Peak Value (dBµV/m)	QP Value (dBµV/m)	QP Limit (dBµV/m)	Result	Angle	Height (m)	H/V
1	249.997	43.45	41.89	46	Pass	115 Degree	1.5 m	V
2	199.177	40.49	32.53	43.5	Pass	77 Degree	1.5 m	H
3	85.174	37.87	26.28	40	Pass	231 Degree	1.5 m	V
4	210.005	40.88	36.74	43.5	Pass	231 Degree	1.5 m	H

6.6 a78, 400 foot range, Radiated Emissions 30MHz to 300MHz



Nr	Frequency (MHz)	Peak Value (dBµV/m)	QP Value (dBµV/m)	QP Limit (dBµV/m)	Result	Angle	Height (m)	H/V
1	199.163	42.83	35.29	43.5	Pass	77 Degree	1.5 m	H
2	209.988	42.02	37.49	43.5	Pass	231 Degree	1.5 m	H
3	249.993	41.99	40.04	46	Pass	77 Degree	1.5 m	V
4	187.643	37.18	28.34	43.5	Pass	38 Degree	1.5 m	H
5	67.415	35.95	28.22	40	Pass	154 Degree	1.5 m	V
6	71.19	33.82	26.21	40	Pass	38 Degree	1.5 m	V


6.7 a78, 30 foot range, Radiated Emissions 300MHz to 1GHz



Nr	Frequency (MHz)	Peak Value (dBµV/m)	QP Value (dBµV/m)	QP Limit (dBµV/m)	Result	Angle	Height (m)	H/V
1	555.049	46.28	44.27	46	Pass	0 Degree	1.5 m	V
2	625.003	44.19	42.19	46	Pass	270 Degree	1.5 m	V
3	500	40.63	38.89	46	Pass	0 Degree	1.5 m	V
4	628.972	43.94	41.53	46	Pass	0 Degree	1.5 m	V
5	745.007	40.51	31.94	46	Pass	90 Degree	1.5 m	V




6.8 a78, 400 foot range, Radiated Emissions 300MHz to 1GHz




Nr	Frequency (MHz)	Peak Value (dBµV/m)	QP Value (dBµV/m)	QP Limit (dBµV/m)	Result	Angle	Height (m)	H/V
1	555.023	45.52	43.74	46	Pass	0 Degree	1.5 m	V
2	624.982	44.06	42.32	46	Pass	270 Degree	1.5 m	V
3	629.013	43.57	40.93	46	Pass	0 Degree	1.5 m	V

6.9 a78, 30 foot range, Radiated Emissions 1GHz to 2GHz



6.10 a78, 400 foot range, Radiated Emissions 1GHz to 2GHz



## 6.11 FCC Part 15, Chapter 47\_15.247 Spurious Emissions 2GHz to 26GHz


The following plots illustrate the radiated emissions of the EUT from 2GHz to 26GHz. The limit for emissions in this band is 20dBc for harmonics and 500 $\mu$ V/m. Any emissions more than 10dB of this limit are not recorded, however all emissions were more than 10dB below this limit.

A 100 kHz RBW was used in order to reduce to noise floor in the measuring receiver. The EUT was rotated through 360 degrees and antenna oriented horizontally & vertically during a peak hold sweep. The following graphs are the resultant peak hold results.

Emissions between 2GHz to 18GHz (Excluding specific plot 2GH-3GHz) were carried out using a 2.4GHz band stop filter to prevent the receiver from saturating.




### 6.11.2 54G WIFI Emissions 2GHz to 3GHz




Date: 1.AUG.2013 12:03:11

#### Channel 1



Date: 1.AUG.2013 12:05:49


#### Channel 7



Date: 1.AUG.2013 12:08:23


#### Channel 11

### 6.11.3 Bluetooth Emissions 2GHz to 3GHz




Date: 1.AUG.2013 12:18:52

#### Channel 1



Date: 1.AUG.2013 12:16:21


#### Channel 40



Date: 1.AUG.2013 12:13:31


#### Channel 79

### 6.11.4 11B WIFI Emissions 2GHz to 18GHz (With 2.4GHz Band stop filter)




Date: 1.AUG.2013 12:34:17

#### Channel 1



Date: 1.AUG.2013 12:36:57


#### Channel 7



Date: 1.AUG.2013 12:39:27


#### Channel 11

6.11.5 54G WiFi Emissions 2GHz to 18GHz (With 2.4GHz band stop filter)




Date: 1.AUG.2013 12:41:52

Channel 1



Date: 1.AUG.2013 12:44:25

Channel 7




Date: 1.AUG.2013 12:46:53

Channel 11




### 6.11.6 Bluetooth Emissions 2GHz to 18GHz (2.4GHz Band stop filter fitted)




Date: 1.AUG.2013 13:00:56

#### Channel 1



Date: 1.AUG.2013 13:03:18


#### Channel 40



Date: 1.AUG.2013 13:05:42


#### Channel 79

### 6.11.7 11B WiFi Emissions 18GHz to 26GHz




Date: 1.AUG.2013 13:15:35

#### Channel 1



Date: 1.AUG.2013 13:18:28


#### Channel 7



Date: 1.AUG.2013 13:21:00


#### Channel 11

### 6.11.8 54G WiFi Emissions 18GHz to 26GHz




Date: 1.AUG.2013 13:23:32

#### Channel 1



Date: 1.AUG.2013 13:25:57


#### Channel 7



Date: 1.AUG.2013 13:28:29


#### Channel 11

### 6.11.9 Bluetooth Emissions 18GHz to 26GHz




Date: 1.AUG.2013 13:34:21

#### Channel 1



Date: 1.AUG.2013 13:36:59


#### Channel 40



Date: 1.AUG.2013 13:39:31


#### Channel 79

# 7 Receiver Spurious Emissions



Date: 1.AUG.2013 12:29:42

## Receiver spurious emissions 2GHz to 18GHz



Date: 1.AUG.2013 13:31:06

## Receiver spurious emissions 18GHz to 26GHz

## 8 List of Test Equipment

Test Equipment Type	Manufacturer and Type Number	Serial Number	Cal No.	Cal Due
Digital Multimeter	Fluke 175	97460092	2248	7 <sup>th</sup> Nov 2013
EMI Receiver 20Hz to 26.5GHz	Rohde & Schwarz ESCI	100416	001692	22 <sup>nd</sup> Aug 2013
Active Loop Antenna 9kHz - 30MHz	Chase EMC HLA6120	1122	00442	14 <sup>th</sup> Feb 2014
Loop Antenna PSU/Charger	Chase EMC CBP9721	N/A	02671	N/A
Antenna Horn 1-18GHz	Chase BBHA9120D	9120D-578	01719	2 <sup>nd</sup> Nov 2014
Antenna Horn 18GHz-26GHz	Credowan 20-R-2843-0007	36755	482	16 <sup>th</sup> Nov 2014
Antenna 30MHz-3GHz	Chase CBL6141	22932	01802	23 <sup>rd</sup> Jul 2014
Antenna Mast (Site 1)	Inn-co GmbH MM4000	MM4000/056/13750 806/L	02075	N/A
Turntable (Site 1)	Inn-co GmbH DS1200S	DS1200S/175/1375 0806/L	02076	N/A
Mast/Turntable Controller (Site 1)	Inn-co GmbH Co 2000	CO/2000/359/137/5 0806/L	02077	N/A
EMI Receiver 20Hz to 40GHz	Rohde & Schwarz ESU40	100017	01721	22 <sup>nd</sup> Mar 2014
Power Supply Unit	Palstar PS30M	G290775401	2020	N/A

In accordance with UKAS requirements, all measuring equipment is on a calibration cycle.