

FCC PART 15.247
TEST REPORT

For

Baby's Journey, Inc.

22 Shore Rd, Narragansett, Rhode Island, United States 02882

FCC ID: PJF-2313RX1

Report Type: Original Report	Product Type: 5" Color Flatscreen Video Monitor
Test Engineer: Liewei Liu	<i>Liewei</i>
Report Number: RSZ150917018-00	
Report Date: 2015-10-09	
Reviewed By: RF Engineer	<i>Jimmy xiao</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)4

 OBJECTIVE4

 RELATED SUBMITTAL(S)/GRANT(S).....4

 TEST METHODOLOGY4

 TEST FACILITY5

SYSTEM TEST CONFIGURATION6

 DESCRIPTION OF TEST CONFIGURATION6

 EUT EXERCISE SOFTWARE6

 EQUIPMENT MODIFICATIONS6

 EXTERNAL I/O CABLE.....6

 BLOCK DIAGRAM OF TEST SETUP7

SUMMARY OF TEST RESULTS8

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....9

 APPLICABLE STANDARD9

 RESULT9

FCC §15.203 – ANTENNA REQUIREMENT10

 APPLICABLE STANDARD10

 ANTENNA CONNECTOR CONSTRUCTION10

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS11

 APPLICABLE STANDARD11

 MEASUREMENT UNCERTAINTY11

 EUT SETUP11

 EMI TEST RECEIVER SETUP.....12

 TEST PROCEDURE12

 TEST EQUIPMENT LIST AND DETAILS.....12

 TEST RESULTS SUMMARY13

 TEST DATA13

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....16

 APPLICABLE STANDARD16

 MEASUREMENT UNCERTAINTY16

 EUT SETUP16

 EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP17

 TEST PROCEDURE17

 TEST EQUIPMENT LIST AND DETAILS.....18

 CORRECTED AMPLITUDE & MARGIN CALCULATION18

 TEST RESULTS SUMMARY18

 TEST DATA19

FCC §15.247(a) (1)-CHANNEL SEPARATION22

 APPLICABLE STANDARD22

 TEST PROCEDURE22

 TEST EQUIPMENT LIST AND DETAILS.....22

 TEST DATA22

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....25

 APPLICABLE STANDARD25

TEST PROCEDURE25
 TEST EQUIPMENT LIST AND DETAILS.....25
 TEST DATA25

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL28
 APPLICABLE STANDARD28
 TEST PROCEDURE28
 TEST EQUIPMENT LIST AND DETAILS.....28
 TEST DATA28

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....30
 APPLICABLE STANDARD30
 TEST PROCEDURE30
 TEST EQUIPMENT LIST AND DETAILS.....30
 TEST DATA30

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT33
 APPLICABLE STANDARD33
 TEST PROCEDURE33
 TEST EQUIPMENT LIST AND DETAILS.....33
 TEST DATA33

FCC §15.247(d) - BAND EDGES36
 APPLICABLE STANDARD36
 TEST PROCEDURE36
 TEST EQUIPMENT LIST AND DETAILS.....36
 TEST DATA36

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Baby's Journey, Inc.*'s product, model number: *5F62313A (FCC ID: PJF-2313RX1)* (the "EUT") in this report was a *5" Color Flatscreen Video Monitor*, which was measured approximately: 14.3 cm (L) x 9.8 cm (W) x 1.7 cm (H), rated with input voltage: DC 3.6 V Ni-MH battery or DC 7.5V from adapter.

Adapter Information:

Model: P5 0750500

Input: AC 100~240V, 250mA, 50/60Hz

Output: DC 7.5V, 500mA

** All measurement and test data in this report was gathered from production sample serial number: 1506548 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2015-09-17*

Objective

This report is prepared on behalf of *Baby's Journey, Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode which was selected by manufacturer.

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2409.0	10	2440.6
2	2412.4	11	2445.0
3	2415.8	12	2448.4
4	2419.2	13	2451.8
5	2423.6	14	2455.2
6	2427.0	15	2458.6
7	2430.4	16	2463.0
8	2433.8	17	2466.4
9	2437.2	18	2469.8

EUT was tested with Channel 1, 9 and 18.

EUT Exercise Software

No exercise software was used.

Equipment Modifications


No modification was made to the EUT tested.

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Un-detachable DC Power Cable	1.5	EUT	Adapter

Block Diagram of Test Setup

For Conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b)(1), §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2469.8	0	1	16.22	41.88	20	0.0083	1.0

Note: To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2015-06-03	2016-06-02
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2014-12-01	2015-12-01
Rohde & Schwarz	Transient limitator	ESH3Z2	DE25985	2015-05-14	2016-05-13
Rohde & Schwarz	CE Test software	EMC 32	V8.53	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as bellow:

10.5 dB at 0.392090 MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

in BA CL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Liewei Liu on 2015-09-28.

Test Mode: Transmitting

AC 120 V, 60 Hz, Line:


EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/QP/Ave.)
0.392090	37.7	19.9	58.0	20.3	QP
0.392090	37.5	19.9	48.0	10.5	Ave.
3.130570	37.1	20.0	56.0	18.9	QP
3.130570	28.9	20.0	46.0	17.1	Ave.
3.135410	37.8	20.0	56.0	18.2	QP
3.135410	27.1	20.0	46.0	18.9	Ave.
3.281490	35.9	20.0	56.0	20.1	QP
3.281490	27.1	20.0	46.0	18.9	Ave.
3.379390	37.2	20.0	56.0	18.8	QP
3.379390	27.4	20.0	46.0	18.6	Ave.
3.643070	35.9	20.0	56.0	20.1	QP
3.643070	25.8	20.0	46.0	20.2	Ave.

AC 120V, 60 Hz, Neutral:

EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/QP/Ave.)
3.266270	41.9	20.0	56.0	14.1	QP
3.266270	30.1	20.0	46.0	15.9	Ave.
3.288410	39.3	20.0	56.0	16.7	QP
3.288410	29.5	20.0	46.0	16.5	Ave.
3.686590	37.6	20.0	56.0	18.4	QP
3.686590	25.9	20.0	46.0	20.1	Ave.
4.408450	36.1	20.0	56.0	19.9	QP
4.408450	24.9	20.0	46.0	21.1	Ave.
4.600010	33.8	20.0	56.0	22.2	QP
4.600010	24.0	20.0	46.0	22.0	Ave.
4.927510	35.8	20.0	56.0	20.2	QP
4.927510	26.0	20.0	46.0	20.0	Ave.

Note:

- 1) Corrected Amplitude = Reading + Correction Factor
- 2) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss
- 3) Margin = Limit - Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz. And the uncertainty will not be taken into consideration for the test data recorded in the report

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz to 1GHz and peak and Average detection modes for frequencies above 1GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2015-05-06	2016-05-05
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2014-11-03	2015-11-03
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Mini	Amplifier	ZVA-183-S+	5969001149	2015-04-23	2016-04-22
A.H. System	Horn Antenna	SAS-200/571	135	2015-02-10	2016-02-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2014-12-11	2015-12-11
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
TDK	Chamber	Chamber A	2#	2012-10-15	2015-10-15
TDK	Chamber	Chamber B	1#	2015-07-22	2016-07-22
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2015-08-03	2016-08-03
R&S	Auto test Software	EMC32	V9.10	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, the worst margin reading as bellow:

1.82 dB at 2485.14 MHz in the Horizontal polarization for High channel

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level compliance with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

in BACL., $U_{(L_m)}$ is less than $+ U_{cispr}$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Liewei Liu on 2015-10-26.

30 MHz -25 GHz:

Test Mode: Transmitting

Frequency (MHz)	Receiver		Turn table Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
Low Channel (2409MHz)									
152.00	48.54	PK	129	2.2	V	-13.9	34.64	43.5	8.86
2409.00	102.99	PK	240	1.9	H	4.97	107.96	/	/
2409.00	79.33	Ave.	240	1.9	H	4.97	84.30	/	/
2409.00	100.41	PK	358	2.1	V	4.97	105.38	/	/
2409.00	78.14	Ave.	358	2.1	V	4.97	83.11	/	/
2389.40	65.98	PK	338	1.8	H	4.97	70.95	74	3.05
2389.40	38.02	Ave.	338	1.8	H	4.97	42.99	54	11.01
2486.12	65.74	PK	43	2.3	H	6.29	72.03	74	1.97
2486.12	38.24	Ave.	43	2.3	H	6.29	44.53	54	9.47
2493.15	65.52	PK	243	2.4	H	6.29	71.81	74	2.19
2493.15	38.15	Ave.	243	2.4	H	6.29	44.44	54	9.56
4818.00	45.12	PK	93	2.4	V	16.92	62.04	74	11.96
4818.00	23.52	Ave.	93	2.4	V	16.92	40.44	54	13.56
7227.00	40.89	PK	62	2.4	H	19.08	59.97	74	14.03
7227.00	22.02	Ave.	62	2.4	H	19.08	41.10	54	12.90
9636.00	39.12	PK	120	1.1	H	22.72	61.84	74	12.16
9636.00	20.52	Ave.	120	1.1	H	22.72	43.24	54	10.76
Middle Channel (2437.2MHz)									
152.00	49.72	Ave.	247	2.2	V	-13.9	35.82	43.5	7.68
2437.20	102.59	PK	134	1.1	H	4.97	107.56	/	/
2437.20	80.21	Ave.	134	1.1	H	4.97	85.18	/	/
2437.20	100.02	PK	0	1.4	V	4.97	104.99	/	/
2437.20	78.56	Ave.	0	1.4	V	4.97	83.53	/	/
2386.98	66.23	PK	14	2.3	H	4.97	71.20	74	2.80
2386.98	38.12	Ave.	14	2.3	H	4.97	43.09	54	10.91
2484.11	65.86	PK	126	1.7	H	6.29	72.15	74	1.85
2484.11	38.21	Ave.	126	1.7	H	6.29	44.50	54	9.50
2495.26	65.32	PK	30	1.6	H	6.29	71.61	74	2.39
2495.26	38.01	Ave.	30	1.6	H	6.29	44.30	54	9.70
4874.40	49.44	PK	231	1.1	V	16.91	66.35	74	7.65
4874.40	31.23	Ave.	231	1.1	V	16.91	48.14	54	5.86
7311.60	40.23	PK	272	2.1	H	19.40	59.63	74	14.37
7311.60	21.52	Ave.	272	2.1	H	19.40	40.92	54	13.08
9748.80	39.52	PK	115	1.9	V	22.72	62.24	74	11.76
9748.80	20.89	Ave.	115	1.9	V	22.72	43.61	54	10.39

Frequency (MHz)	Receiver		Turn table Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
High Channel (2469.8 MHz)									
152.00	48.89	PK	146	2.2	V	-13.9	34.99	43.5	8.51
2469.80	100.86	PK	10	2.1	H	6.29	107.15	/	/
2469.80	79.54	Ave.	10	2.1	H	6.29	85.83	/	/
2469.80	100.02	PK	55	2.2	V	6.29	106.31	/	/
2469.80	79.36	Ave.	55	2.2	V	6.29	85.65	/	/
2388.11	66.11	PK	339	1.8	H	4.97	71.08	74	2.92
2388.11	38.04	Ave.	339	1.8	H	4.97	43.01	54	10.99
2485.14	65.89	PK	349	1.8	H	6.29	72.18	74	1.82
2485.14	38.52	Ave.	349	1.8	H	6.29	44.81	54	9.19
2489.84	64.58	PK	40	2.2	H	6.29	70.87	74	3.13
2489.84	37.12	Ave.	40	2.2	H	6.29	43.41	54	10.59
4939.60	45.74	PK	28	2.0	V	16.91	62.65	74	11.35
4939.60	22.26	Ave.	28	2.0	V	16.91	39.17	54	14.83
7409.40	40.02	PK	243	1.2	H	18.34	58.36	74	15.64
7409.40	22.52	Ave.	243	1.2	H	18.34	40.86	54	13.14
9879.20	38.56	PK	236	1.9	V	23.79	62.35	74	11.65
9879.20	21.02	Ave.	236	1.9	V	23.79	44.81	54	9.19

Note:

1. Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor
2. Corrected Amplitude = Corrected Factor + Receiver Reading
3. Margin = Limit- Corrected Amplitude

FCC §15.247(a) (1)-CHANNEL SEPARATION

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in operating mode, RBW was set at 100 kHz, VBW \geq 3RBW maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2015-06-13	2016-06-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Liewei Liu on 2015-09-30

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Channel Separation (MHz)	≥ Limit (MHz)
Low	2409.0	3.381	2.42
Adjacent	2412.4		
Middle	2437.2	3.369	2.41
Adjacent	2440.6		
High	2469.8	3.381	2.41
Adjacent	2466.4		


Note: limit =2/3 of 20 dB bandwidth

Low Channel




Date: 30.SEP.2015 11:34:04

Middle Channel



Date: 30.SEP.2015 11:35:18

High Channel



Date: 30.SEP.2015 11:30:10

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
3. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2015-06-13	2016-06-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Liewei Liu on 2015-09-30


Test Result: Compliance.

Please refer to following table and plots

Test Mode: Transmitting


Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
Low	2409.0	3.632
Middle	2437.2	3.618
High	2469.8	3.618

Low Channel




Date: 30.SEP.2015 13:31:17

Middle Channel



Date: 30.SEP.2015 13:29:44

High Channel



Date: 30.SEP.2015 13:27:43

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2015-06-13	2016-06-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Liewei Liu on 2015-09-30


Test Result: Compliance.

Please refer to following table and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400 ~ 2483.5	18	≥ 15

Number of Hopping Channels



Date: 30.SEP.2015 11:09:44

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; spectrum span was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= Pulse time (ms) * hope rate/ number of hopping channels * hopping No.*0.4 s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2015-06-13	2016-06-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Liewei Liu on 2015-09-30

Test Result: Compliance.


Please refer to following table and plots

Test Mode: Transmitting

Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
Low	0.363	0.0523	0.4	Pass
Middle	0.362	0.0521	0.4	Pass
High	0.364	0.0524	0.4	Pass


Note: Dwell time=Pulse time (ms) × (360/18) × 18*0.4 S
Hopping rate = 360 times per second

Low Channel




Date: 30.SEP.2015 11:12:44

Middle Channel



Date: 30.SEP.2015 11:14:17

High Channel



Date: 30.SEP.2015 11:14:56

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2015-06-13	2016-06-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Liewei Liu on 2015-09-30

Test Result: Compliance.


Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	2409.0	15.76	21
Middle	2437.2	16.09	21
High	2469.8	16.22	21

Low Channel




Middle Channel



Date: 30.SEP.2015 13:32:57

High Channel



Date: 30.SEP.2015 13:33:23

FCC §15.247(d) - BAND EDGES

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
3. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2015-06-13	2016-06-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Liewei Liu on 2015-09-30.

Test Result: Compliance.

Test Mode: Transmitting


Please refer to follow plots:

Band Edge: Left Side



Date: 30.SEP.2015 13:44:46

Band Edge: Right Side



Date: 30.SEP.2015 13:43:34

***** END OF REPORT *****