



**HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.**

PRODUCT COMPLIANCE TEAM  
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA  
TEL : +82 31 639 8518 FAX : +82 31 639 8525

<b>Manufacture;</b> IMAGEQUEST CO., LTD.  SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA  IMAGEQUEST FRN : 0005-8664-39	<b>Date of Issue:</b> JULY 23, 2002  <b>Test Report No.:</b> HCT-F02-0703  Test Site: HYUNDAI CALIBRATION & CERTIFICATION <b>TECHNOLOGIES CO., LTD.</b>  HCT FRN : 0005-8664-21
--	--

**CERTIFICATION (Permissive change class II)**

**FCC Rule Part(s):** Part 15 & 2; ET Docket 95-19  
**Classification:** FCC Class B Peripheral Device (JBP)  
**Standard(s):** FCC Class B: 1998 (CISPR 22)  
**Equipment(EUT) Type:** 17" CRT Monitor  
**Max Resolution:** 1600 X 1200 Non-interlaced (@93.8KHz/ 75Hz)

<b>FCC ID :</b>	<b>PJIC17F06091</b>	<b>Port/ Connector(s)</b>
<b>MODEL / TYPE :</b>		15-pin D-sub VGA connector, 3D Glasses Input

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992.(See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HYUNDAI C-Tech. certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse of 1988,21 U.S.C.853(a).

*Ki Soo Kim*  
Report prepared by : Ki-Soo Kim  
Manager of EMC Tech. Part



# TABLE OF CONTENTS

	<b>PAGE</b>
<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 Product Description.....	3
1.2 Related submittal(s)/Grant(s).....	3
1.3 Tested System Details.....	4
1.4 Test Methodology.....	4
1.5 Test Facility.....	4
<b>2. SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
2.1 Justification.....	5
2.2 EUT Exercise Software.....	5
2.3 Cable Description.....	6
2.4 Noise Suppression Parts on Cable.....	6
2.5 Equipment Modifications.....	7
2.6 Configuration of Tested System.....	8
<b>3. PRELIMINARY TESTS.....</b>	<b>9</b>
3.1 Power line Conducted Emissions Tests.....	9
3.2 Radiated Emissions Tests.....	9
<b>4. FINAL CONDUCTED AND RADIATED EMISSION TESTS SUMMARY.....</b>	<b>9</b>
4.1 Conducted Emission Tests.....	10
4.2 Radiated Emission Tests.....	11
<b>5. FIELD STRENGTH CALCULATION.....</b>	<b>12</b>
<b>6. LIST OF TEST EQUIPMENT .....</b>	<b>13</b>

<b>ATTACHMENT A .....</b>	<b>ID Label / Location Info.</b>
<b>ATTACHMENT B.....</b>	<b>External Photos.</b>
<b>ATTACHMENT C .....</b>	<b>Block Diagram..</b>
<b>ATTACHMENT D .....</b>	<b>Test Setup Photos.</b>
<b>ATTACHMENT E .....</b>	<b>User's Manual.</b>
<b>ATTACHMENT F .....</b>	<b>Internal Photos.</b>

# 1. GENERAL INFORMATION

## 1.1 Product Description

The ImageQuest CO., LTD. Model F790D (referred to as the EUT in this report) is a 17" CRT Monitor with HOR. Freq. 93.8KHz (Max) and Resolution of 1600 X 1200 (Non-Interlaced). Product specification information described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	PLASTIC
LIST OF EACH OSC. OR XTAL. FREQ.(FREQ.≥ 1MHz)	12MHz
POWER REQUIREMENT	100 - 240V AC 2.5A 60/50Hz
NUMBER OF LAYERS	MAIN BOARD 1 LAYER CRT BOARD 1 LAYER 3D BOARD 2 LAYER
MAX. RESOLUTION	1600 X 1200 NON-INTERLACED(@93.8KHz/ 75Hz)
H-SYNC FREQUENCY RANGE	30KHz ~ 97KHz
V-SYNC FREQUENCY RANGE	50Hz ~ 150Hz
CRT TYPE	17" ( CRT Type : M41QCJ761X172)

## 1.2 Related Submittal(s) / Grant(s)

ORIGINAL SUBMITTAL ONLY

### 1.3 Tested System Details

The Model names for all equipment, plus descriptions used in the tested system (including inserted cards) are:

DEVICE TYPE	MANUFACTURER	MODEL NUMBER	FCC ID / DoC	CONNECTED TO
MONITOR (EUT)	IMAGEQUEST CO.,LTD.	F790D	PJIC17F06091	HOST
PC(HOST)	H/P	DTPC-17	DoC	N/A
KEY BOARD	H/P	SK-2501-2D-K	GYUR385K	HOST
PRINTER	H/P	HP895C	DoC	HOST
MODEM	3COM CORPORATION	56K FAX MODEM	DoC	HOST
VIDEO CARD	MATROX	MIL2P/4G	DoC	HOST
MOUSE	H/P	M-S34	DZL211029	HOST
3D GLASS	IMAGEQUEST CO.,LTD.	3D GALSS	-	EUT
3D GLASS	IMAGEQUEST CO.,LTD.	3D GALSS	-	EUT

### 1.4 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4/1992. Radiated testing was performed at an antenna to EUT distance of 10 meters.

### 1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1,MAEKOK-RI,HOBUP-MYUN,ICHON-SI,KYOUNGKI-DO, 467-701,KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 24,2000(Confirmation Number: EA90661)

---

## 2.SYSTEM TEST CONFIGURATION

### 2.1 Justification

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following components and I/O cards inside the E.U.T were used.

DEVICE TYPE	MANUFACTURE	MODEL/PART NUMBER
MAIN BOARD	ImageQuest CO., Ltd.	304010087904
CRT BOARD	ImageQuest CO., Ltd.	304010088002
3D BOARD	ImageQuest CO., Ltd.	304100104701

### 2.2 EUT exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software, contained on a 3-1/2 inch disc, was inserted into drive A and is auto starting on power-up. Once loaded, the program sequentially exercises each system component in turn. The sequence used is :(1) Display test, (2) RS 232 test (3) Key board test,(4) Printer test,(5) FDD test,(6) HDD test. The complete cycle takes about 20 seconds and is repeated continuously. As the keyboard and mouse are strictly input devices, no data is transmitted to them during test. They are however, continuously scanned for data input activity. The video resolution modes setup and change program was used during the radiated and conducted emission testing.

## 2.3 Cable Description

	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
MONITOR(EUT)	N	Y	1.8(P), 1.5(D)
PC(HOST)	N	N/A	1.8(P)
PRINTER	N	Y	2.0(P),1.8(D)
KEY BOARD	N/A	Y	2.0(D)
3D GLASS	N	N	2.2(D)
3D GLASS	N	N	2.2(D)
MODEM	N	Y	2.0(P),0.8(D)
MOUSE	N/A	Y	1.8(D)

The marked "(D)" means the Data Cable and "(P)" means the Power Cable.

## 2.4 Noise Suppression Parts on Cable. (I/O CABLE)

	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
MONITOR(EUT)	Y	PC END	Y	PC END
PRINTER	Y	PC END	Y	BOTH END
KEY BOARD	Y	PC END	Y	PC END
3D GLASS	Y	EUT END	Y	EUT END
3D GLASS	Y	EUT END	Y	EUT END
MODEM	Y	PC END	Y	BOTH END
MOUSE	N	N/A	Y	PC END

## **2.5 Equipment Modifications**


N/A

## 2.6 Configuration of Test system

**Line Conducted Test** : EUT was connected to LISN, all other supporting equipment were connected to another LISN.  
 Preliminary Power line Conducted Emission tests were performed by using the procedure in ANSI C63.4/1992 7.2.3 to determine the worse operating conditions.

**Radiated Emission Test** : Preliminary Radiated Emissions tests were conducted using the procedure in ANSI C63.4/1992 8.3.1.1 to determine the worse operating condition. Final Radiated Emission tests were conducted at 10 meter open area test site.

[Configuration of Tested System]





### 3. PRELIMINARY TESTS

#### 3.1 AC Power line Conducted Emission Tests

During Preliminary Tests, the following operating mode were investigated

Processor Speed (MHz)	Video Resolution (w/max)	The worst operating condition
Pentium 350 MHz	1600 X 1200 Non-Interlaced (93.8KHz/75Hz)	X
	1280 X 1024 Non-Interlaced (80.0KHz/75Hz)	
	1024 x 768 Non-Interlaced (68.7KHz/85Hz)	
	800 x 600 Non-Interlaced (53.7KHz/85Hz)	
	640 x 480 Non-Interlaced (50.6KHz/100Hz)	

#### 4.2 Radiated Emission Tests

During Preliminary Tests, the following operating mode were investigated

Processor Speed (MHz)	Video Resolution (w/max)	The worst operating condition
Pentium 350 MHz	1600 X 1200 Non-Interlaced (93.8KHz/75Hz)	X
	1280 X 1024 Non-Interlaced (80.0KHz/75Hz)	
	1024 x 768 Non-Interlaced (68.7KHz/85Hz)	
	800 x 600 Non-Interlaced (53.7KHz/85Hz)	
	640 x 480 Non-Interlaced (50.6KHz/100Hz)	

Tested by **Kyoung-Houn Seo / Engineer**

Date : **JUNE 25, 2002**






**HYUNDAI C-TECH. CO., LTD.  
EMC TEST LAB.**

EUT: F790D  
 Manufacturer: IMAGEQUEST  
 Operating Condition: 1600 X 1200 75Hz  
 Test Site: Shield Room  
 Operator: KH-SEO  
 Test Specification: CLASS B  
 Comment: N  
 Start of Test:

**SCAN TABLE: "EN 55022 V (PKH) "**

Short Description:		EN 55022 Voltage				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	3.0 kHz	MaxPeak	10.0 ms	9 kHz	old-C/E FACTOR
			Average			
500.0 kHz	5.0 MHz	3.0 kHz	MaxPeak	5.0 ms	9 kHz	old-C/E FACTOR
			Average			



**MEASUREMENT RESULT: "F790D\_fin QP"**

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
10.328000	44.80	0.6	60	15.2	1	---

**MEASUREMENT RESULT: "F790D\_fin AV"**


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
10.136000	41.50	0.6	50	8.5	1	---

**HYUNDAI C-TECH. CO., LTD.  
EMC TEST LAB.**

EUT: F790D  
 Manufacturer: IMAGEQUEST  
 Operating Condition: 1600 X 1200 75Hz  
 Test Site: Shield Room  
 Operator: KH-SEO  
 Test Specification: CLASS B  
 Comment: H  
 Start of Test:

**SCAN TABLE: "EN 55022 V (PKH)"**

Short Description:			EN 55022 Voltage			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	3.0 kHz	MaxPeak	10.0 ms	9 kHz	old-C/E FACTOR
			Average			
500.0 kHz	5.0 MHz	3.0 kHz	MaxPeak	5.0 ms	9 kHz	old-C/E FACTOR
			Average			



**MEASUREMENT RESULT: "F790D\_fin QP"**

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
10.325000	48.40	0.6	60	11.6	1	---

**MEASUREMENT RESULT: "F790D\_fin AV"**

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
9.761000	44.10	0.6	50	5.9	1	---



## 5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dBuV is obtained. The Antenna Factor of 7.4 and a Cable Factor of 1.1 is added. The 30 dBuV/m value was mathematically converted to its corresponding level in uV/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dBuV/m}$$

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(30 \text{ dBuV/m})/20] = 31.6 \text{ uV/m}$$

## 6. LIST OF TEST EQUIPMENT

<u>TYPE</u>	<u>MANUFACTURE</u>	<u>MODEL</u>	<u>CAL. DATE</u>
EMI Test Receiver	Rohde & Schwarz	ESH3	2002.6.29
EMI Test Receiver	Rohde & Schwarz	ESVP	2002.2.14
EMI Test Receiver	Rohde & Schwarz	ESI40	2001.11.5
EMI Test Receiver	Rohde & Schwarz	ESVS30	2002.3.6
Spectrum Monitor	Rohde & Schwarz	EZM	N.A
Graphic Plotter	Rohde & Schwarz	DOP2	N.A
Printer	Rohde & Schwarz	PDN	N.A
Spectrum Analyzer	H.P	8591EM	2001.7.11
LISN	EMCO	3825/2	2002.2.7
LISN	Rohde & Schwarz	ESH2-Z5	2001.8.12
Amplifier	Hewlett-Packard	8447E	2002.3.2
Dipole Antennas	Rohde & Schwarz	VHAP	2002.6.28
Dipole Antennas	Rohde & Schwarz	UHAP	2002.6.28
Biconical Antenna	Rohde & Schwarz	BBA-9106	2002.6.28
Log-Periodic Antenna	Rohde & Schwarz	UHALP-9107	2002.6.26
Antenna Position Tower	EMCO	1051-12	N.A
Turn Table	EMCO	1060-06	N.A
Line Filter	KEENE	ULW 2X30-60	N.A
Power Analyzer	Voltech	PM 3300	2002.2.20
Reference Network Impedance	Voltech	IEC 555	N.A
AC Power Source	PACIFIC	Magnetic Module	N.A
AC Power Source	PACIFIC	360AMX	N.A



