

Electromagnetic Emission
FCC MEASUREMENT REPORT
CERTIFICATION OF COMPLIANCE
FCC Part 15 Certification Measurement

PRODUCT : LCD MONITOR
MODEL/TYPE NO : L24C0F080 / NONE
FCC ID : PJIL24C0F080
APPLICANT : HYUNDAI IT CORP.
San 136-1, Ami-ri, Bubal-eub, Icheon-si, Gyeonggi-do,
467-701, Korea
Attn. : Kim, Kyoung-Ok / Assistant Manager
MANUFACTURER : HYUNDAI IT CORP.
San 136-1, Ami-ri, Bubal-eub, Icheon-si, Gyeonggi-do,
467-701, Korea
FCC CLASSIFICATION : Class B Personal computers and peripherals
RULE PART(S) : FCC Part 15 Subpart B
FCC PROCEDURE : Certification
TEST REPORT No. : ETLE070618.400
DATES OF TEST : June 28, 2007
REPORT ISSUE DATE : July 03, 2007
TEST LABORATORY : ETL Inc. (FCC Registration Number : 95422)

This LCD MONITOR, Model L24C0F080 has been tested in accordance with the measurement procedures specified in ANSI C63.4-2003 at the ETL Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B:

I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



Chon Sik, Kim / Chief Engineer

ETL Inc.
#584, Sangwhal-ri, Ganam-myeon, Yaju-gun, Gyeonggi-do, 469-885, Korea
Tel: 82-2-858-0786 Fax: 82-2-858-0788

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the ETL Inc.

Table of Contents

FCC Measurement Report

1. Introduction
2. Product Information
3. Description of Tests
4. Test Condition
5. Test Results
 - 5.1 Summary of Test Results
 - 5.2 Conducted Emissions Measurement
 - 5.3 Radiated Emissions Measurement
6. Sample Calculation
7. List of test Equipment used for Measurement

Appendix A. FCC ID Label and Location

Appendix B. Test Setup Photographs

Appendix C. External Photographs

Appendix D. Internal Photographs

Appendix E. Block Diagram

FCC MEASUREMENT REPORT

Scope – Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

General Information

Applicant Name	: HYUNDAI IT CORP.
Address	: San 136-1, Ami-ri, Bubal-eub, Icheon-si, Gyeonggi-do, 467-701, Korea
Attention	: Kim, Kyoung-Ok / Assistant Manager

- **EUT Type :** LCD MONITOR
- **Model Number :** L24C0F080
- **S/N :** N/A
- **FCC Rule Part(s) :** FCC Part 15 Subpart B
- **Test Procedure :** ANSI C63.4-2003
- **FCC Classification :** Class B Personal computers and peripherals
- **Dates of Tests :** June 28, 2007
- **Place of Tests :** ETL Inc. Testing Lab.

Radiated Emission test;
#584, Sangwhal-ri, Ganam-myeon, Yoju-gun,
Gyeonggi-do, 469-885, Korea

Conducted Emission test;
ETL Inc. Testing Lab.
371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea
- **Test Report No. :** ETLE070618.400

1. INTRODUCTION

The measurement test for radiated and conducted emission test were conducted at the ETL Inc. The site is constructed in conformance with the requirements of the ANSI C63.4-2003 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 m and 10 m site configurations. Detailed description of test facility was found to be in compliance with FCC Rules according to the ANSI C63.4-2003 and registered to the Federal Communications Commission (FCC Registration Number : 95422).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2003) was used in determining radiated and conducted emissions from the HYUNDAI IT CORP.. Model: L24C0F080

2. PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the Model: L24C0F080.

2.2 General Specification

LCD	24" viewable, Diagonal, Pixel pitch 0.270mm, A-si TFT
Display area	518.4(H) X 324(V), 24" Diagonal
Number of color	16.7 million colors (true 8-bit color)
Input signals	R.G.B Analog, 15pin D-sub / DVI-D / Component / HDMI
Frequency rate	Horizontal : 30.0 to 80.0KHz, Vertical : 56 to 75Hz
Maximum bandwidth	162MHz
Maximum resolution	1920 X 1200 @ 60Hz
Recommanded resolution	1920 X 1200 @ 60Hz
Input voltage	100-240V AC, 2.0A
Power consumption	85W(Typ.)
Power management	VESA DPMS
Plug & Play	VESA DDC 1/2B
OSD menu	BRIGHTNESS, CONTRAST, H/W POSITION, CLOCK, PHASE, AUTO ADJUST AUTO COLOR, SOUND, OSD CONFIGURATION, INPUT SOURCE, DISPLAY CONTROL, GENERAL RECALL, LANGUAGE
Audio system	2ch X 3watts / Ear Phone Jack
VESA FPMPI	75mm X 75mm screw mounting
Ergonomics, Safety and EMC	Energystar CE, CB, TUV/GS, ICE/ EN60950-1, EN55022, EN55024
Operating Temperature	5 ~ 40° C
Weight	9.9Kg unpacked, 7.9Kg packed
Dimensions (W X H X D mm)	579.5 X 455.0 X 240 mm

3. DESCRIPTION OF TESTS

3.1 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with section 11, "Measurement of Information Technology Equipment" of ANSI C63.4-2003. The measurements were performed over the frequency range of 0,15 MHz to 30 MHz using a 50 Ω / 50 μ H LISN as the input transducer to a Spectrum Analyzer or a Test Receiver. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 9 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

The line-conducted emission test is conducted inside a shielded anechoic chamber room with 1 m x 1,5 m x 0,8 m wooden table which is placed 0,4 m away from the vertical wall and 1,5 m away from the side wall of the chamber room. Two LISN are bonded to the shielded room. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1,2 cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN. Non-inductive bundling to a 1 m length shortened all interconnecting cables more than 1 m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the EMI Test Receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0,15 MHz to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

Photographs of the worst-case emission can be seen in photographs of conducted emission test setup in Appendix B.

3.2 Radiated Emission Measurement

Radiated emission measurements were made in accordance with section 11, "Measurement of Information Technology Equipment" of ANSI C63.4-2003. The measurements were performed over the frequency range of 30 MHz to 1 GHz using antenna as the input transducer to a spectrum analyzer or a field intensity meter. The measurements were made with the detector set for "Quasi-peak" within a bandwidth of 120 kHz.

Preliminary measurements were made at 3 m using broadband antennas, and spectrum analyzer to determine the frequency producing the maximum emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 MHz to 1000 MHz using Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site at 3 m. The test equipment was placed on a wooden turn-table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR Quasi-peak mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency of type of signal. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0,8 m high nonmetallic 1m x 1,5 m table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

4. TEST CONDITION

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

4.2 EUT operation

Operating Mode	The worst operating condition
Stand by mode	X
1 920 X 1 200, 60 Hz, Full "H" pattern display and MP3 play mode	O

O: Worst case investigated during the Test


4.3 Support Equipment Used

Description	Model Name	Serial No.	Manufacturer
Keyboard	SEM-DT35	96023777	SAMSUNG
Mouse	M-S48a	4882A011	Logitech
Computer	DHM	G9MB71S	Dell Asia Pacific Sdn.
DVD Player	DVA-4000	NONE	ELLION
Earphone	NONE	NONE	NONE

4.4 Type of Cables Used

Device from	Device to	Type of I/O port	Length(m)	Type of shield
EUT	Computer	RGB IN	1,5	Shielded
EUT	Computer	DVI	1,5	Shielded
EUT	Computer	AUDIO IN	1,5	Shielded
EUT	Earphone	Earphone	1,2	Unshielded
EUT	DVD Player	Component	1,5	Shielded
EUT	DVD Player	Component Audio In	1,5	Shielded
EUT	Termination	HDMI	1,8	Shielded
EUT	Power socket	AC INPUT	1,0	Unshielded
Computer	Keyboard	PS/2	1,2	Shielded
Computer	Mouse	PS/2	1,2	Shielded
Computer	Power socket	AC INPUT	1,2	Unshielded
DVD Player	Power socket	AC INPUT	1,2	Unshielded

4.5 The setup drawing(s)



- : Data Line
- : Power Line
- : Termination

5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

LIMIT	Measurement Required	Result
15.107	Conducted Emission Measurement	Passed by 6,60 dB
15.109(g)	Radiated Emission Measurement	Passed by 3,10 dB

The data collected shows that the **HYUNDAI IT CORP. / LCD MONITOR / L24C0F080** complied with technical requirements of above rules part 15.107 and 15.109(g)

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

5.2 Conducted Emissions Measurement

EUT	LCD MONITOR / L24C0F080
Limit apply to	FCC Part 15. 107 (CISPR Publication 22) Class B
Test Date	June 28, 2007
Operating Condition	Full "H" pattern display mode (1 920*1 200, Vf = 60Hz)
Result	Passed by 6,6 dB

Conducted Emission Test Data


The following table shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth : 9 kHz)

Frequency [MHz]	Result [dB μ V]		Phase (*L/**N)	Limit [dB μ V]		Margin [dB]	
	Quasi-peak	Average		Quasi-peak	Average	Q.Peak	Average
0,167	53,2	46,4	H	65,1	55,1	11,9	8,7
0,234	50,9	45,7	H	62,3	52,3	11,4	6,6
0,293	48,6	42,7	H	60,4	50,4	11,8	7,7
0,531	40,8	35,1	H	56,0	46,0	15,2	10,9
0,877	41,4	36,3	H	56,0	46,0	14,6	9,7
1,586	40,9	34,5	H	56,0	46,0	15,1	11,5
5,310	39,6	29,8	N	60,0	50,0	20,4	20,2
12,018	38,9	35,9	H	60,0	50,0	21,1	14,1
24,052	32,6	26,3	N	60,0	50,0	27,4	23,7


NOTES :

1. * H : HOT Line , **N : Neutral Line
2. Margin value = Limit – Result
3. Measurement were performed at the AC Power Inlet in the frequency band of 150 kHz ~ 30 MHz according to the FCC Part 15



 Test Engineer : **Hyung-min, Choi**

Line: HOT Line

Limit : — Quasi-Peak
— Average



Line: Neutral Line



5.3 Radiated Emissions Measurement

EUT	LCD MONITOR / L24C0F080
Limit apply to	15.109(g)
Test Date	June 28, 2006
Operating Condition	Full "H" pattern display mode (1 920*1 200, Vf = 60Hz)
Result	Passed by 3,10 dB


Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.
 Detector mode: CISPR Quasi – Peak mode (6 dB Bandwidth: 120 kHz)

Frequency [MHz]	Reading [dB μ V]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
53,89	11,57	V	11,83	2,10	25,50	30,0	4,50
68,84	15,12	V	9,59	2,19	26,90	30,0	3,10
115,94	9,52	V	10,76	3,02	23,30	30,0	6,70
132,82	6,65	V	12,06	3,29	22,00	30,0	8,00
166,38	8,42	V	12,22	3,76	24,40	30,0	5,60
205,24	12,13	H	9,04	4,13	25,30	30,0	4,70
233,19	14,56	H	10,21	4,63	29,40	37,0	7,60
297,94	10,75	H	12,37	5,48	28,60	37,0	8,40
537,78	6,35	H	17,44	8,20	32,00	37,0	5,00
690,67	1,92	H	19,73	9,54	31,20	37,0	5,80

NOTES :

- * H : Horizontal polarization , ** V : Vertical polarization
- Result = Reading + Antenna factor + Cable loss
- Margin value = Limit - Result
- The measurement was performed for the frequency range 30 MHz – 1 000 MHz according to CISPR Publication 22. Class B.


 Test Engineer : **Hyung-min, Choi**

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

$$dB(\mu V) = 20 \log_{10} (uV) : \text{Equation}$$

Example : @ 68,84 MHz

Class A Limit	=	30,00 dBuV/m
Reading	=	15,12 dBuV
Antenna Factor + Cable Loss	=	9,59 + 2,19 = 11,78 dBuV/m
Total	=	26,90 dBuV/m
Margin	=	30,00 – 26,90 = 3,10 dB
	=	3,10 dB below Limit

7. List of test equipments used for measurements

	Test Equipment	Model	Mfg.	Serial No.	Cal. Due Date
<input checked="" type="checkbox"/>	Receiver	ESVS 10	R & S	835165/001	08.05.03
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESPI3	R & S	100478	07.10.17
<input checked="" type="checkbox"/>	LISN	3816/2	EMCO	1001	07.10.17
<input checked="" type="checkbox"/>	LISN	3816/2	EMCO	1002	07.10.17
<input checked="" type="checkbox"/>	LogBicon	VULB9160	Schwarz Beck	3082	07.08.11
<input checked="" type="checkbox"/>	Turn-Table	DETT-03	Daeil EMC	-	N/A
<input checked="" type="checkbox"/>	Antenna Master	DEAM-03	Daeil EMC	-	N/A