

**Precautions Precautions** 

Warning: The following information will help you avoid the risk of electric shock, serious injury or death.



Plug the power cord into a properly grounded outlet. There is the risk of electric shock.



If you hear a noise or smell smoke from the computer or adaptor, unplug the power cord immediately, and call the service center. There is the risk of electric shock or fire.



Do not overload an electrical outlet with too many devices. There is the risk of fire.



Do not unplug from the outlet by pulling the power cord or when your hands are wet. There is the risk of electric shock or fire.



Do not bend the power cord excessively nor place heavy objects on it. Keep children and pets away from the power cord as they may damage the power cord. There is the risk of electric shock or fire.



Do not use a damaged power cord or plug. Make sure the plug fits snugly into the outlet. There is the risk of electric shock or fire.



Do not expose the monitor to the direct sun light.



Keep the monitor away from high temperature, humidity, and dust.

- Operating environment =10~40degrees Celsius
- Operating environment =20~80 relative humidity.



Do not block the fan louvers. There is the risk of fire or damage to the monitor.



Do not allow any object or liquid to enter inside the monitor. There is the risk of electric shock, fire or damage to the monitor.



Do not attempt to disassemble, fix or modify the monitor. There is the risk of electric shock or fire.



Caution: The following information will help you avoid the risk of minor or moderate injury or damage to the monitor.



Use a proper voltage/current level indicated



Do not clean the LCD with abrasive chemicals. There is the risk of damage to the LCD.



Do not scratch and damage the LCD with sharp objects.



Keep the monitor away from objects and electrical appliances that may generate electromagnetic fields.




Place the monitor on a flat, stable surface. The monitor may fall and there is the risk of damage or injury.




Unplug the power cord when the monitor is not in use for a long period of time.

The socket - outlet shall be installed near the equipment and shall be easily accessible.


2 3 Items Items






















- \*1: For Audio Model Only.
  \*2: For USB Model Only.
- Please make sure the following items are included with your monitor. If any items are missing, contact your dealer.

Also we'd like to ask you to use our 'D-Sub' cable all the time, otherwise we are not in a position to be responsible for all the matters caused by that.

# Setting up the LCD monitor 1 2 3 4 5 6 7

No.	Name	Cable connections	
1	Power	Power Cord	
2	USB Downstream Port (4) (Option)	To connect another USB Device*1	
3	USB Upstream Port (Option)	USB to PC *1	
4	AUDIO IN	AUDIO Cable *2	_
5	VGA	15-pin D-Sub Signal Cable	_
6	DVI	DVI-D Cable	- - *1 : For USB Model On
7	DISPLAY PORT	DP Cable	*2 : For Audio Model On

# Plug & Play

The adoption of the new VESA Plug and Play solution eliminates complicated and time consuming setup. It allows you to install your monitor in a Plug and Play compatible sys tem without the usual hassles and confusion. Your PC system can easily identify and configure itself for use with your display. This monitor automatically tells the PC system its Extended Display Identification Data (EDID) using Display Data Channel (DDC) pro tocols so the PC system can automatically configure itself to use the flat panel display.

# Warm-up Time

All LCD monitors need time to become thermally stable whenever you turn on the monitor after letting the monitor be turned off for a couple of hours. Therefore, to achieve more accurate adjustments for parameters, allow the LCD monitor to be warmed up for at least 30 minutes before making any screen adjustments.



When the condition of the screen is not good, please press the button " AUTO". (This function may cause some noises on the screen according to VGA Cards)

**Notice** 


# **Buttons & functions**

Button	Function description	Hot key setting
MENU	Opens OSD MENU window. Chooses icons.	
DOWN	Moves down icon choice bar. Decreases value of chosen icon.	Volume
UP	Moves up icon choice bar. Increases value of chosen icon.	
EXIT	Cancels chosen OSD MENU step by step. Closes OSD MENU.	Automatic setting * VGA Only
SCALE	Change Ratio (Wide or Normal)	
SOURCE	Change Input Signal	
<b>О</b> POWER	turns on/off monitors.	
State Lamp	Indicates monitors' state. LCD ON(green) in normal state LCD flicker(green off) in standby mode	

# **Functions**

Hot key is a handy key to execute frequently used functions.

▼ Monitor & OSD screen settings



# OSD screen selection and control procedures.

- 1. Press the "MENU" button to bring up the OSD screen.
- 2. Press the "UP, DOWN" buttons to select the main option.
- 3. Press the "MENU" button after selecting the main option.
- 4. Bring up the sub-menu. Use the "UP, DOWN" buttons to select the desired option.
- 5. Press the "MENU" button after selecting the desired sub-menu option.
- 6. Use the "UP, DOWN" buttons to adjust the set value.
- 7. Pressing the "EXIT" button three times saves and exits the setting mode.

\*Pressing the "EXIT" button moves back to the previous menu.

MAIN MENU ICON	MAIN MENU	SUB MENU	FUNCTION
	PICTURE	BRIGHTNESS	Adjusts screen brightness.
		CONTRAST	Adjusts screen light and darkness.
		H.POSITION	Adjusts screen left or right. *1
		V.POSITION	Adjusts screen upwards or downwards. *1
		PHASE	Removes noise coming out horizontally on screen. *1
		CLOCK	Removes noise coming out vertically on screen. *1
		AUTO ADJUST	Automatically sets optimum screen *1
\$	COLOR	COLOR TEMP	Select the most comfortable color tone to your eyes STANDARD -> REDDISH -> BLUISH -> USER * STANDARD: for general color tone. * REDDISH: for reddish color with warm tone. * BLUISH: for bluish color with cool tone. * USER: for adjusting degree of RGB as user wants
		RED,GREEN,BLUE	For adjusting the each color as user wants.
		AUTO COLOR	Automatically set optimum screen. *1
p.	FUNCTION	INPUT SELECT	To switch current and other input source.
		ASPECT RATIO	Adjusts screen ratio. (4:3, 16:9)
		DCR	Turn on / off DCR Function.
	OSD	RECALL	Recall the saved initial data.
		H.POSITION	Adjusts OSD screen left or right.
		V.POSITION	Adjusts OSD screen upwards or downwards.
		TIMER	Adjusts OSD display time on the screen.
	LANGUGAE		Select OSD language.( 5 langauges )
			*4 · Net evelleble in DV/I and DD aceds

<sup>\*1:</sup> Not available in DVI and DP mode

### English

### Disposal of Used Electrical & Electronic Equipment



The meaning of the symbol on the product, its accessory or packaging indicates that this product shall not be treated as household waste. Please, dispose of this equipment at your applicable collection point for the recycling of electrical & electronic equipments waste. In the European Union and Other European countries which there are separate collection systems for used electrical and electronic product. By ensuring the correct disposal of this product, which could otherwise be caused by unsuitable waste handling of this product. The recycling of materials will help conserve natural resources. Please do not therefore dispose of your old electrical and electronic equipment with your househol waste. For more detailed information about recycling of this product, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

### Dansk



# Handtering af udtjente elektriske og elektroniske produkter (Gaelder for den Europaeiske Union og andre europaeiske lande medseparate indsamlingssystemer)

Dette symbol pa produktet eller emballagen angiver, at produktet ikke ma benandles som husholdningsaffald. Det skal i stedet indleveres pa en deponeringsplads specielt indretter til modtagelse of oparbejdning af elektriske og elektroniske produkter. Ved at sikre at produktet bortskaffes korrekt, forebygges de eventuelle negative miljo-og sundhedsskadelige pavirkninger, som en ukorrekt affaldshandtering af produktet kan forarsage. Genindvinding af materialer vil medvirke til at bevare naturens ressourcer. Yderligere information om genindvindingen af dette produkt kan fas hos myndighederne, det lokale renovationsselskab eller butikken, hvor produktet blev kobt.

### Español





Este simbolo en el producto, sus accesorios o embalaje indica que el producto no debe tratarse como un residuo domestico. Deshagase de este equipamiento en su punto de recogida mas cercano para el reciclaje de residuos electricos y electronicos. En la Union Europea y otros países europeos existen diferentes sistemas de recogida de productos electricos y electronicos usados. Al asegurar la correcta eliminacion de este producto ayudara a evitar riesgos potenciales para el medio ambiente y al salud de las personas que podrian tener lugar si el producto no se eliminara de forma adecua. El reciclaje de materiales ayudara a conservar los recursos naturales. Por consiguiente, no elimine equipamiento electrico y electronico usado junto con residuos domesticos. Para informacion mas detallada acerca del reciclaje de este producto, pongase en contacto con su oficina municipal, el servicio de eliminacion de residuosdomesticos o el establecimiento donde adquirio el producto.

## Português

### Eliminação de Equipaménto Electrico e Electrónico Usado



O simbolo no aparelho, nos seus acessórios ou na embalagem indica que este aparelho nao deve ser tratado como residuos domésticos. Deixe deste aparelho no ponto de recolha de material eléctrico e electrónico para reciclagem mais perto de si. Na União Europeia e noutros países europeus existem sistemas de recolha separada para produtos eléctricos e electronicos usados. Garantindo uma eliminação correcta deste aparelho, ajudara a evitar possiveis danos ambientais e/ou pessoais, que um incorrecto tratamento do aparelho usado poderia provocar. A reciclagem de materiais ajuda a conservar os recursos naturais. Por isso, não deite fora os aparelhos eléctricos e electronicós junto com os seus residuos domesticos. Para informacao detalhada sobre a reciclagem deste aparelho, contacte a sua Camare Municipal, o seu servico de recolha de lixo ou a loja onde comprou o aparelho.

# Display Modes and frequency

Resolution	Horizontal Frequency (kHz)	Vertical Frequency(Hz)		
800 x 600	35.2 kHz	56 Hz		
000 X 000	37.8 kHz	60 Hz		
1024 x 768	48.3 kHz	60 Hz		
1280 x 960	60.0 kHz	60 Hz		
1280 x 1024	63.9 kHz	60 Hz		
1440 x 900	55.9 kHz	60 Hz		
1680 x 1050	64.7 kHz	60 Hz		
1920 x 1080	67.5 kHz	60 Hz		
480p		50/60		
576p		50/60	DVI(HDCP)	
720p		50/60	2	
1080p		50/60		

## **Power Save**

This monitor has a built-in power management system called PowerSave. This system saves energy by switching your monitor into a low-power mode when it has not been used for a certain period of time. The monitor automatically returns to normal operation when you press a key on the keyboard. For energy saving, turn your monitor OFF when it is not used, or when leaving it unattended for a long period.

State	Power consumption	LED Color
ON	Under 28W	Green
OFF	Less then 0.5W	Flickering (Green)

8

**Specifications Troubleshooting** 

Problem	Solution
Abnormal colors appear. It is in black and white.	Reconnect the cable to PC. Insert the PC's video card correctly. Re-boot the PC. Set the video card again after referring to the video card manual.
The displayed screen position suddenly changes or tilts inward.	Use the screen control to adjust the displayed screen shape. Set the resolution and/or frequency on the video card (refer to the supported mode table).  Differences in the signal period of the video card may cause changes in the displayed position from time to time. Use the screen control functions to correct the displayed screen position.
Displays 16 colors only. The color has changed after replacing the video card.	Windows ME/XP/vista: Re-set the color from the Control Panel -> Display -> Setting.Re-install the video card driver.
Power indicator lamp blinks Green.	Monitor is in Sleep Mode
Cannot control the screen with the buttons on the front of the monitor.	Contact technical support
There are colored spots on the screen.	There may be a few colored (red, green, white, black) pixel spots on the screen during use. This is a natural characteristic in LCD panels. It is not a malfunction and does not affect the monitor's performance.
The power indicator lamp is off.	Check if the power cable is intact. Reconnect the power cable correctly if necessary.
The "No Signal" message appears on the screen.	Check if the connection between the PC and monitor is intact. Reconnect the cable correctly if necessary.
The "Out of Range" message appears on the screen.	The output signal from the video card exceeds the monitor's maximum resolution or frequency limit. Set the maximum resolution and frequency to suit the product limits.
The screen appears to be sliding downward.	Check the connection between the PC and monitor. Re-connect if necessary.
The screen is unclear.	Run the auto-adjusting function.
The screen appears unstable or flickers. The screen leaves shadows.	Check if the computer or video card output resolution and frequency is set within the limits. Re-set the screen display by referring to the resolution information and standard supported mode table.
The screen is too bright or dark.	Use the brightness or contrast controls to adjust the display.
The color on the screen is not uniform.	Use the color density control to set the color.
Lines appear on the screen and the screen flickers.	Turn off any cordless phones, hair dryers, electrical drills etc. that are in use.

Caution Use a soft dry cloth to clean the product.

Do not scratch the monitor panel with your fingernails or other sharp objects.

Use a clean cloth with a special screen cleanser.

- Do not use flammable substances such as benzene or paint thinner on the product. Do not use a wet cloth.
- Do not use acetone, benzene or paint thinner on the product.

	Specification	24" Wide
	Visible Screen Area	531.36mm(H) x 298.89mm(V) (24 inch)
	Pixel Pitch	0.276mm(H) x 0.276mm(V)
	Recommended Resolution	1920 x 1080@60Hz
1.00	Maxium Visible Angle	170º/170º(H/V)
LCD	Displayed Color	16.7M
	Brightness	250cd/m²
	Contrast Ratio	1000:1
	Response Time	5 msec
	Horizontal Frequency	30KHz-80KHz
Input	Vertical Frequency	60KHz-75KHz
Signal	Video Signal	Analong RGB, DVI
	Connector	DVI-D, AUDIO 1 DISPLAY PORT USB 2
	Power Consumption	< 28W (Typ.)
Power	Stand by Power	< 0.5W
	Input Power	AC:100V-240V 50/60Hz, 2.0A
Multimedia Speakers		1Wx2*1
Operating Environment		Operation:10 to 40°C, humidity: 20-80%(non-condensing)
		Storage: -10 to 50°C, humidity: 10-90%(non-condensing)

※ The above specifications are subject to change without prior notice to improve performance.

- \*1: For Audio Model Only.
- \*2: For USB Model Only.

10 11

# **FCC** compliance

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- · Reorient or relocate the receiving antenna.
- · Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- · Consult the dealer or an experienced radio/TV technician for help.

Change or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment under FCC rules.