

HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.

Product Compliance Division, EMC Team
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA
TEL : +82 31 639 8518 FAX : +82 31 639 8525

TEST REPORT

Manufacture;
HYUNDAI IMAGEQUEST CO., LTD.

**SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI,
KYOUNKI-DO, 467-701, KOREA**

HYUNDAI IMAGEQUEST FRN : 0005-8664-39

Date of Issue : July 19, 2005

Test Report No.: HCT-F05-0705

**Test Site: HYUNDAI CALIBRATION & CERTIFICATION
TECHNOLOGIES CO., LTD.**

HCT FRN : 0005-8664-21

FCC ID :

PJILT32DW000

MODEL /TYPE:

Q320/LT32DW000

Rule Part(s) : Part 15 & 2

Equipment Class : FCC Class B Peripheral Device (JBP)

Standard(s) : FCC Class B: (CISPR 22)

EUT Type : 32" LCD TV Monitor

**Max. Resolution(s): Analog : 1024x768 (@85Hz)
Digital : 1024x768 (@85Hz)**


Model(s) : Q320

**Port/Connector(s): Poewr,D-Sub,DVI/D-Sub Audio input,Subwoofer,Component 1.2,S-Video,
Composit 1.2,Antenna 1.2,Coaxial Audio out,Optical Audio out,Speaker USB,
Memory card slot**

LCD Panel : Samsung Electronics(LTA320W2-L03)

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Report prepared by : Ki-Soo Kim

Manager of EMC Tech. Part



TABLE OF CONTENTS

	PAGE
REPORT COVER	1
TABLE OF CONTENTS	2
1.1 SCOPE	3
2.1 INTRODUCTION (SITE DESCRIPTION)	4
3.1 PRODUCTION INFORMATION	5-8
4.1 DESCRIPTION OF TESTS (CONDUCTED)	9
4.3 DESCRIPTION OF TESTS (RADIATED)	10
5.1 LIST OF SUPPORT EQUIPMENT	11-12
6.1 TEST DATA (CONDUCTED)	13-21
7.1 TEST DATA (RADIATED)	22-23
8.1 SAMPLE CALCULATIONS	24
9.1 TEST EQUIPMENT	25
10.1 TEST SOFTWARE USED	26
11.1 CONCLUSION	27

ATTACHMENT A :	FCC ID LABEL & LOCATION
ATTACHMENT B :	EXTERNAL PHOTOGRAPHS
ATTACHMENT C :	BLOCK DIAGRAM
ATTACHMENT D :	TEST SETUP PHOTOGRAPHS
ATTACHMENT E :	USER'S MANUAL
ATTACHMENT F :	INTERNAL PHOTOGRAPHS

MEASUREMENT REPORT

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

Applicant Name:	HYUNDAI IMAGEQUEST
Address:	SAN 136-1, AMI-RI , BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701,KOREA

- **FCC ID : PJILT32DW000**
- Equipment Class: FCC Class B Peripheral Device (JBP)
- EUT Type: 32 " LCD TV MONITOR
- Model/Type: Q320/LT32DW000
- LCD Panel: Samsung Electronics(LTA320W2-L03)
- Maximum Resolution(s) : Analog : 1024x768(@85Hz)
Digital : 1024x768(@85Hz)
- Power Supply:AC 100-240V,50/60Hz

Consumption power : Typical 140W

Stand-by power : Typical 2W
- Cable(S) : Poewr,D-Sub,DVI/D-Sub Audio input,Subwoofer,Component 1.2,S-Video,
Composit 1.2,Antenna 1.2,Coaxial Audio out,Optical Audio out,Speaker USB,
Memory card slot
- Power Cord: Unshielded
- Rule Part(s): FCC Part 15 Subpart B
- Test Procedure(s): ANSI C63.4 (2003)
- Dates of Tests: July 05, 2005 ~ July 07, 2005
- Place of Tests: 254-1,MAEKOK-RI,HOBUP-MYUN,ICHON-SI,KYOUNGKI-DO,467-701,KOREA

2.1 INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2001) was used in determining radiated and conducted emissions emanating from **HYUNDAI IMAGEQUEST CO.,LTD. 32-inch LCD TV Monitor FCC ID: PJILT32DW000**

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, MAEKOK-RI,HOBUP-MYUN,ICHON-SI,KYOUNGKI-DO, 467-701,KOREA. The site is constructed in conformance with the requirements of ANSI C63.4and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 23,2003 (Confirmation Number: EA90661)

3.1 PRODUCT INFORMATION

3.2 Equipment Description

Equipment Under Test (EUT) is the **HYUNDAI IMAGEQUEST CO.,Ltd. (Model : Q320) 32-inch LCD TV Monitor**

FCC ID: PJILT32DW000

Maximum Resolution(s) : Analog : 1024x768(@85Hz)
Digital : 1024x768(@85Hz)

Power Supply: AC 100-240V, 50/60Hz

Power Cord : Unshielded AC power cord

Port(s)/Input Connector(s): Poewr,D-Sub,DVI/D-Sub Audio input,Subwoofer,Component 1.2,S-Video, Composit 1.2,Antenna 1.2,Coaxial Audio out,Optical Audio out,Speaker USB, Memory card slot

Cable(s) : Shieled D-Sub(with ferrite on bothends), Shieled DVI(with ferrite on bothends), Shieled S-Video(with ferrite on bothends), Shielded Componet 1.2, Shielded Composite 1.2, Shieleded Antenna 1.2, Shieleded subwoofer, Shieleded Audio in, Shieleded Coxial Audio out, unShieleded speaker.


Dimensions (WxHxD) : 772x230x563mm (WxHxD)

Weight (Net) : 19.3Kg(With stand)


EMI Suppression Devices:

Modifications were made to the device. Please refer to the next page.


1. Attach aluminum tape on the frame and lcd Rear panel.




2. Apply a ferrite core to the interface Cable of MMB Board.




3. Attach fabric tape and a gasket on the frame.




4. Attach a gasket on the tuner and the frame.




5. Attach a gasket on the inside frame.



6. Attach a gasket on the main board case.



7. Apply a ferrite core to the audio speaker cable.



4.1 Description of Tests(Conducted)

4.2 Powerline Conducted RFI (150kHz- 30MHz)

The power line conducted RFI measurements were performed according to CISPR 22.

The EUT was placed on a non-conducting 1.0 by 1.5 meter table which is 0.8 meters in height and 0.40 meters away from the vertical wall of the shielded enclosure. Power to the EUT is provided through a Rohde & Schwarz 50 Ω / 50 uH Line Impedance Stabilization Network (LISN) and the support equipment through a separate Solar 50 Ω / 50 uH Line- Conducted Test Facility LISN. Sufficient time for the EUT, support equipment, and test equipment were allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME. The spectrum was scanned from 150kHz to 30 MHz. Each maximum EME was remeasured using an EMI receiver. The detector function of the receiver was set to CISPR quasi- peak and average mode with the bandwidth set to 9 kHz. Each emission was maximized consistent with the typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum Diagram emission. Excess cable lengths were bundled at the center with 30- 40cm. in length. The worst-case configuration is noted in the test report and the photographs are attached. Each EME reported was calibrated using the Rohde & Schwarz SMX signal generator and are listed on Table 1. RFI Conducted FCC Class B

RFI CONDUCTED	CISPR 22 CLASS B Limits dB(uV/m)	
	CISPR 22 Quasi-Peak	CISPR 22 Average
Freq. Range		
150kHz - 0.5MHz	66-56**	56-46**
0.5MHz - 5MHz	56	46
5MHz - 30MHz	60	50
**Limits decreases linearly with the logarithm of frequency		

Table 1. RFI Conducted Limits

4.3 Description of Tests(Radiated)

Radiated Emissions

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The spectrum was scanned from 30 to 300 MHz using biconical antenna, 300 to 1000 MHz using log- periodic antenna, and above 1 GHz using linearly polarized horn antennas. Final measurements were made outdoors at 10-meter test range using Dipole antennas and EMI receiver. For frequencies above 1 GHz, horn antennas were used. Sufficient time for the EUT, support equipment, and test equipment were allowed in order for them to warm up to their normal operating condition. The EMI receiver detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120 kHz. The EUT, support equipment, and interconnecting cables were arranged to the configuration that produces the maximum EME emission found during preliminary scan. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Horizontal and vertical antenna polarizations were checked. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/ or support equipment, and powering the monitor the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

ITE Radiated Limits			
Frequency (MHz)	FCC Limit @ 3m. Quasi-Peak dB[μV/m]	FCC Limit @ 10m.* Quasi – Peak dB [μV/m]	CISPR Limit @ 10m. Quasi-Peak dB [μV/m]
30-88	40.0	29.5	30.0
88-216	43.5	33.0	30.0
216-230	46.0	35.6	30.0
230-960	46.0	35.6	37.0
960-1000	54.0	43.5	37.0
> 1000	54.0	43.5	No Specified Limit
* Limit extrapolated 20 dB/decade			

Table 2. Radiated Class B limits @ 10-meters

5.1 Support Equipment Used

DEVICE TYPE	MANUFACTURER	MODEL NUMBER	FCC ID / DoC	CONNECTED TO
Monitor (EUT)	HYUNDAI IMAGEQUEST CO., LTD.	HQL322WD, HQL320WDE	PJILT32DW000	P.C
P.C	H/P	HP Pavilion 8921	DoC	EUT
KEY BOARD	H/P	5181	DoC	P.C
MOUSE	Microsoft	IntelliMouse Optical USB and PS/2 Compatible	DoC	P.C
SERIAL MOUSE	Logitech	M-M28	DoC	P.C
PRINTER	H/P	C6410A	DoC	P.C
MPEG Recoder	Tektronix J310478	MTX 100	DoC	EUT
All Channel up Cover	EIDEN EJ96182	4220C-006	DoC	EUT
8VSB Modulator	EIDEN EJ96656	3313B-002	DoC	EUT

Termination	<p>Component port 75</p> <p>S-Video Port 75</p> <p>Video port 75</p> <p>Audio port 30</p>
-------------	---

5.2 Cable Description

		Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
LCD TV Monitor (EUT)	Component 1.2	N	N/A	1.8(D)
	Composite 1.2	N/A	Y	1.8(D)
	S-Video	N/A	Y	1.5(D)
	ANT 1.2	N/A	Y	3.0(D)
	PC Audio in	N/A	Y	1.8(D)
	DVI	N/A	Y	1.8(D)
	D-sub	N/A	Y	1.8(D)
	Power	N/A	Y	1.8(P)
	Woofers	N/A	Y	1.8(D)
5.1 channel out	N/A	Y	1.8(D)	
PC		N	N/A	1.8(P)
Key Board		N/A	Y	1.8(D)
Mouse		N/A	Y	1.8(D)
Serial Mouse		N/A	Y	1.8(D)
Printer		N	Y	1.8(P,D)

The marked "(D)" means the Data Cable and "(P)" means the Power Cable.

5.3 Noise Suppression Parts on Cable. (I/O CABLE)

		Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
LCD TV Monitor (EUT)	Component 1.2	N	N/A	Y	BOTH END
	Composite 1.2	N	N/A	Y	BOTH END
	S-Video	N	N/A	Y	BOTH END
	ANT 1.2	N	N/A	Y	BOTH END
	PC Audio in	N	N/A	Y	BOTH END
	DVI	Y	N/A	Y	BOTH END
	D-sub	Y	BOTH END	Y	BOTH END
	Woofers	N	BOTH END	Y	BOTH END
	5.1 channel out	N	N/A	Y	BOTH END
PC		N	N/A	N/A	N/A
Key Board		N	N/A	Y	PC END
Mouse		N	N/A	Y	PC END
Serial Mouse		N	N/A	Y	PC END
Printer		Y	BOTH END	Y	BOTH END

6.1 LINE-CONDUCTED TEST DATA


HCT

EMC TEST LAB

EUT: Q320 (ATSC)
 Manufacturer: HYUNDAI IMAGEQUEST
 Operating Condition: 1024 X 768 85Hz (A)
 Test Site: SHIELD ROOM
 Operator: GS,KIM
 Test Specification: CISPR 22 CLASS B
 Comment: H

SCAN TABLE: "CISPR 22 Voltage"

Short Description:		CISPR 22 Voltage					
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
Frequency	Frequency	Width					
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "lcd tv_fin QP"

7/6/2005 8:56AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.152600	50.30	10.1	66	15.6	---	---
0.190100	46.30	10.1	64	17.8	---	---
0.362600	42.70	10.1	59	16.0	---	---
0.725000	34.70	10.2	56	21.3	---	---
1.085000	33.90	10.1	56	22.1	---	---
1.450000	34.00	10.2	56	22.0	---	---
11.590000	42.30	10.4	60	17.7	---	---
11.665000	42.50	10.4	60	17.5	---	---
11.740000	41.90	10.4	60	18.1	---	---

MEASUREMENT RESULT: "lcd tv_fin AV"

7/6/2005 8:56AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150100	49.50	10.1	56	6.5	---	---
0.190100	44.20	10.1	54	9.8	---	---
0.362600	40.70	10.1	49	8.0	---	---
0.725000	32.20	10.2	46	13.8	---	---
1.085000	33.00	10.1	46	13.0	---	---
1.450000	30.30	10.2	46	15.7	---	---
11.515000	37.80	10.4	50	12.2	---	---
11.665000	36.90	10.4	50	13.1	---	---
11.740000	37.00	10.4	50	13.0	---	---


HCT

EMC TEST LAB

EUT: Q320 (ATSC)
 Manufacturer: HYUNDAI IMAGEQUEST
 Operating Condition: 1024 X 768 85Hz (A)
 Test Site: SHIELD ROOM
 Operator: GS,KIM
 Test Specification: CISPR 22 CLASS B
 Comment: N

SCAN TABLE: "CISPR 22 Voltage"

Short Description:		CISPR 22 Voltage					Transducer
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.		
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "lcd tv_fin QP"

7/6/2005 8:52AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Line	PE
0.150100	52.70	10.1	66	13.3	---	---
0.160100	39.30	10.1	66	26.2	---	---
0.362600	42.40	10.1	59	16.3	---	---
0.725000	35.00	10.2	56	21.0	---	---
1.085000	34.30	10.1	56	21.7	---	---
1.450000	34.40	10.2	56	21.6	---	---
11.530000	35.40	10.4	60	24.6	---	---
11.680000	34.80	10.4	60	25.2	---	---
11.755000	34.40	10.4	60	25.6	---	---

MEASUREMENT RESULT: "lcd tv_fin AV"

7/6/2005 8:52AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150100	49.40	10.1	56	6.6	---	---
0.190100	42.60	10.1	54	11.5	---	---
0.362600	40.90	10.1	49	7.8	---	---
0.725000	32.60	10.2	46	13.4	---	---
1.085000	33.20	10.1	46	12.8	---	---
1.450000	30.90	10.2	46	15.1	---	---
11.530000	30.50	10.4	50	19.5	---	---
11.680000	29.60	10.4	50	20.4	---	---
11.755000	29.40	10.4	50	20.6	---	---


HCT

EMC TEST LAB

EUT: Q320 (ATSC)
 Manufacturer: HYUNDAI IMAGEQUEST
 Operating Condition: 1024 X 768 85Hz
 Test Site: SHIELD ROOM
 Operator: GS,KIM
 Test Specification: CISPR 22 CLASS B
 Comment: N

SCAN TABLE: "CISPR 22 Voltage"

Short Description:		CISPR 22 Voltage					Transducer
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.		
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "lcd tv_fin QP"

7/6/2005 8:46AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.152600	51.00	10.1	66	14.8	---	---
0.190100	44.80	10.1	64	19.2	---	---
0.362600	42.70	10.1	59	16.0	---	---
0.725000	34.90	10.2	56	21.1	---	---
1.090000	32.90	10.1	56	23.1	---	---
1.450000	34.10	10.2	56	21.9	---	---
11.260000	34.00	10.4	60	26.0	---	---
11.410000	33.70	10.4	60	26.3	---	---
11.635000	32.90	10.4	60	27.1	---	---

MEASUREMENT RESULT: "lcd tv_fin AV"

7/6/2005 8:46AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.152600	47.50	10.1	56	8.4	----	----
0.190100	42.70	10.1	54	11.4	----	----
0.362600	40.80	10.1	49	7.8	----	----
0.725000	32.60	10.2	46	13.4	----	----
1.090000	32.10	10.1	46	13.9	----	----
1.450000	31.00	10.2	46	15.0	----	----
11.185000	28.70	10.4	50	21.3	----	----
11.410000	28.70	10.4	50	21.3	----	----
11.560000	28.90	10.4	50	21.1	----	----


HCT

EMC TEST LAB

EUT: Q320 (ATSC)
 Manufacturer: HYUNDAI IMAGEQUEST
 Operating Condition: 1024 X 768 85Hz
 Test Site: SHIELD ROOM
 Operator: GS,KIM
 Test Specification: CISPR 22 CLASS B
 Comment: H

SCAN TABLE: "CISPR 22 Voltage"

Short Description:		CISPR 22 Voltage					Transducer
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.		
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "lcd tv_fin QP"

7/6/2005 8:42AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.150100	53.40	10.1	66	12.6	---	---
0.187600	46.30	10.1	64	17.9	---	---
0.362600	42.80	10.1	59	15.9	---	---
0.725000	34.90	10.2	56	21.1	---	---
1.090000	33.40	10.1	56	22.6	---	---
1.450000	33.60	10.2	56	22.4	---	---
11.055000	42.60	10.4	60	17.4	---	---
11.205000	42.40	10.4	60	17.6	---	---
11.430000	42.60	10.4	60	17.4	---	---

MEASUREMENT RESULT: "lcd tv_fin AV"

7/6/2005 8:42AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150100	49.70	10.1	56	6.3	---	---
0.190100	44.00	10.1	54	10.1	---	---
0.362600	40.70	10.1	49	8.0	---	---
0.725000	32.30	10.2	46	13.7	---	---
1.090000	32.60	10.1	46	13.4	---	---
1.450000	30.50	10.2	46	15.5	---	---
10.980000	37.10	10.4	50	12.9	---	---
11.055000	37.60	10.4	50	12.4	---	---
11.205000	37.90	10.4	50	12.1	---	---

NOTES:

- 1. All modes of operation were investigated and the worst-case emissions are reported.**
- 2. The CISPR RFI conducted limits are listed on Table 1 (Page 9).**
- 3. Line H = Phase Line N = Neutral Line**
- 4. Operating Condition**
1024 x 768, 85Hz (A) = Analog Mode, 1024 x 768, 85Hz = Digital Mode

** Measurements using CISPR quasi-peak mode.

7.1 RADIATED TEST DATA

D-Sub

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
55.1	8.9	11.8	1.7	V	22.4	30.0	7.6
91.1	13.2	7.8	2.1	V	23.1	30.0	6.9
123.4	10.9	11.7	2.5	V	25.1	30.0	4.9
152.3	8.7	12.9	2.7	V	24.3	30.0	5.7
189.1	5.3	10.5	3.1	V	18.9	30.0	11.1
196.9	6.5	9.9	3.2	V	19.6	30.0	10.4
301.6	13.2	13.1	4.0	H	30.3	37.0	6.7
332.1	15.3	13.6	4.2	V	33.1	37.0	3.9
412.9	6.6	15.5	4.7	H	26.8	37.0	10.2
436.4	10.5	16.4	4.8	H	31.7	37.0	5.3
561.4	8.3	18.5	5.4	H	32.2	37.0	4.8
649.4	6.8	21.0	5.8	V	33.6	37.0	3.4

Radiated Measurements at 10-meters.

1024 X 768 (@85Hz)

DVI

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
66.4	11.5	10.2	1.8	V	23.5	30.0	6.5
90.6	14.3	7.7	2.1	V	24.1	30.0	5.9
127.0	11.2	12.0	2.6	V	25.8	30.0	4.2
156.1	8.4	12.9	2.8	V	24.1	30.0	5.9
185.2	6.1	10.8	3.1	V	20.0	30.0	10.0
196.9	7.6	9.9	3.2	V	20.7	30.0	9.3
301.6	14.8	13.1	4.0	H	31.9	37.0	5.1
335.6	14.5	13.6	4.2	H	32.3	37.0	4.7
359.8	11.8	14.1	4.4	V	30.3	37.0	6.7
371.9	11.0	14.4	4.4	H	29.8	37.0	7.2
536.8	7.9	17.9	5.3	H	31.1	37.0	5.9
653.2	5.8	21.0	5.9	V	32.7	37.0	4.3

Radiated Measurements at 10-meters.

1024 X 768 (@85Hz)

NOTES:

1. All modes of operation were investigated, and the worst-case emissions are reported.
2. The radiated limits are listed on Table 2 (Page 10).

** AFCL = Antenna Factor (Roberts dipole) and Cable Loss .

*** Measurements using CISPR quasi-peak mode. Above 1GHz, peak detector function mode is used using a resolution bandwidth of 1MHz and a video bandwidth of 1MHz. The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.

8.1 Sample Calculations

$$\text{dB } \mu\text{V} = 20 \log_{10} (\text{mV/m})$$

8.2 Example 1:

@ 0.1526 MHz

Class B limit = 66.0 dB μV
Reading = 50.3 dB μV (calibrated level)

Margin = 50.3 – 66.0 = -15.7 dB μV
= **15.7 dB below limit**

8.3 Example 2:

@ 649.4 MHz

Class B limit = 37 dB $\mu\text{V/m}$
Reading = 6.8 dB $\mu\text{V/m}$ (calibrated level)
Antenna Factor + Cable Loss = 26.8 dB
Total = 33.6 dB $\mu\text{V/m}$

Margin = 33.6 - 37.0 = - 3.4
= **3.4 dB below limit**

9.1 Test Equipment

<u>Type</u>	<u>Manufacture</u>	<u>Model Number</u>	<u>CAL Due Date</u>
EMI Test Receiver	Rohde & Schwarz	ESCI40	2005.11.16
EMI Test Receiver	Rohde & Schwarz	ESVS30	2006.07.01
EMI Test Receiver	Rohde & Schwarz	ESCI	2005.09.13
LISN	Rohde & Schwarz	ESH2-Z5	2006.04.26
Attenuator	Rohde & Schwarz	ESH3-Z2	2005.11.16
TRILOG Antenna	Schwarzbeck	9160	2006.03.31
Antenna Position Tower	HD	MA240	N/A
Turn Table	EMCO	1050	N/A
Power Analyzer	Voltech	PM 3300	2006.03.22
Reference Network Impedance	Voltech	IEC 555	N/A
AC Power Source	PACIFIC	Magnetic Module	N/A
AC Power Source	PACIFIC	360-AMX	2005.11.25
Controller	HD GmbH	HD 100	N/A
SlideBar	HD GmbH	KMS 560	N/A
PULSE LIMITER	Rohde & Schwarz	ESH3-Z2	2005.11.16

10.1 Test Software Used

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software, contained on a 3-1/2 inch disc, was inserted into drive A and is auto starting on power-up. Once loaded, the program sequentially exercises each system component in turn. The sequence used is :(1) Display test, (2) RS 232 test (3) Key board test,(4) Printer test,(5) FDD test,(6) HDD test. The complete cycle takes about 20 seconds and is repeated continuously. As the keyboard and mouse are strictly input devices, no data is transmitted to them during test. They are however, continuously scanned for data input activity. The video resolution modes setup and change program was used during the radiated and conducted emission testing.

NOTE: This is a sample of the basic program used during the test. However, during testing, a different software program may be used; whichever determines the worst-case condition. In addition, the program used also depends on the number and type of devices being tested.

Actual program used is the "H" pattern in Notepad under Windows environment. All resolution modes (1024x768, 800x600, 640x480, 832x624, 720x400, 640x350) were investigated and tested

11.1 Conclusion

The data collected shows that the HYUNDAI IMAGEQUEST CO., LTD. 32-inch LCD TV Monitor **FCC ID: PJILT32DW000** complies with §15.107 and §15.109 of the FCC Rules.