



RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

EUT Specification

EUT	ADSL2+ 4-PORT 802.11N WiFi Router
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others _
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5mW/cm^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input checked="" type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	24.59101dBm (287.81mW)
Antenna gain (Max)	1.00dBi (Numeric gain:1.26)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation
Note:	
<ol style="list-style-type: none"> 1. The maximum output power is <u>24.59101dBm (287.81mW)</u> at <u>2437MHz</u> (with <u>1.26</u> numeric antenna gain.) 2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser. 	

TEST RESULT

No non-compliance noted.



Compliance Certification Services Inc.

Report No: C140902Z01-RP1_MPE

FCC ID: PJZ6519W1

Date of Issue: September 9, 2014

Calculation

Given $S = \frac{P \times G}{4\pi d^2}$ ***Equation 1***

Where $d =$ distance in cm

$P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power Density in mW / cm²

Maximum Permissible Exposure

EUT Output Power=24.59101mW

Numeric antenna gain=1.26

Substituting the MPE safe distance using d=20 cm into ***Equation 1***:

Fields

The power density $S = 24.59101 \times 1.26 / (4\pi \times 400) \text{ cm}^2 = 0.006167\text{mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW / cm² even if the calculation indicates that the power density would be larger.)