



FCC 47 CFR PART 15 SUBPART C

for

XDSL(30A) 4 Port WiFi 802.11N Gateway

Model: 6738-XX-YY (The first "X"=A~Z, the second "X"=0~9. Which represents the product version. The "YY"=EU, UK, US, JP, NA, etc. which represents the difference Country or Area, e.g.: EU represents the Europe, UK represents the United Kingdom)

Brand: ZHONE

Test Report Number:

C130609Z04-RP1

Issued Date: July 18, 2013

Issued for

Zhone Technologies, Inc

7195 Oakport Street Oakland, CA 94621 USA

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,

Guan Lan Town, Baoan District, Shenzhen, China

TEL: 86-755-28055000

FAX: 86-755-28055221



TESTING CERT #2861.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	C130609Z04-RP1	Initial Issue	ALL	Vicky Chen



TABLE OF CONTENTS

1 TEST CERTIFICATION 4

2 TEST RESULT SUMMARY 5

3 EUT DESCRIPTION 6

4 TEST METHODOLOGY 7

 4.1. DESCRIPTION OF TEST MODES 7

5 SETUP OF EQUIPMENT UNDER TEST 8

 5.1. DESCRIPTION OF SUPPORT UNITS 8

 5.2. CONFIGURATION OF SYSTEM UNDER TEST 8

6 FACILITIES AND ACCREDITATIONS 9

 6.1. FACILITIES 9

 6.2. ACCREDITATIONS 9

 6.3. MEASUREMENT UNCERTAINTY 9

7 FCC PART 15.247 REQUIREMENTS 10

 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT 10

 7.2. SPURIOUS EMISSIONS MEASUREMENT 17

 7.3. 6dB BANDWIDTH MEASUREMENT 58

 7.4. PEAK OUTPUT POWER 72

 7.5. BAND EDGES MEASUREMENT 75

 7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT 97



1 TEST CERTIFICATION

Product	XDSL(30A) 4 Port WiFi 802.11N Gateway
Model	6738-XX-YY (The first "X"=A~Z, the second "X"=0~9. Which represents the product version. The "YY"=EU, UK, US, JP, NA, etc. which represents the difference Country or Area, e.g.: EU represents the Europe, UK represents the United Kingdom)
Brand	ZHONE
Tested	July 5 ~ 18, 2013
Applicant	Zhone Technologies, Inc 7195 Oakport Street Oakland, CA 94621 USA
Manufacturer	Zhone Technologies, Inc 7195 Oakport Street Oakland, CA 94621 USA

APPLICABLE STANDARDS			
Standard	Test Type	Standard	Test Type
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	<ul style="list-style-type: none"> ● Spurious Emissions ● Conducted Measurement ● Radiated Emissions
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2009** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Tom Gan
Supervisor of EMC Dept.
Compliance Certification Service Inc.

Ruby Zhang
Supervisor of Report Dept.
Compliance Certification Service Inc.



2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	<ul style="list-style-type: none">● Spurious Emissions● Conducted Measurement● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

- Note:
1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
 2. The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	XDSL(30A) 4 Port WiFi 802.11N Gateway
Model Number	6738-XX-YY (The first "X"=A~Z, the second "X"=0~9. Which represents the product version. The "YY"=EU, UK, US, JP, NA, etc. which represents the difference Country or Area, e.g.: EU represents the Europe, UK represents the United Kingdom)
Brand	ZHONE
Model Discrepancy	All models have same circuit diagram, PCB layout and same components used, the only different are label, model name, product version and sales country or area.
Serial Number	C130609Z04-RP1
Received Date	June 9, 2013
Power Supply	DC12V powered by the adapter
Adapter Manufacturer/ Model Name	Adapter 1# : Shenzhen Gongjin Electronics Co., Ltd./S24B12-120A200-Y4 I/P: 100-240Vac, 50/60Hz, Max 0.7A O/P: 12Vdc, 2A DC Output Cable: Unshielded,1.50m Adapter 2# : ShenZhen RuiDe Electronic Industrial Co.,Ltd/ RDA024120020-AC I/P: 100-240Vac, 50/60Hz, 0.6A O/P: 12Vdc, 2A DC Output Cable: Unshielded,1.50m
Transmit Power	IEEE 802.11b mode: 18.09dBm (Antenna 0) IEEE 802.11g mode: 24.22dBm(Antenna 0) IEEE 802.11g mode: 24.30dBm(Antenna 1) IEEE 802.11n HT20 MHz mode: 26.42dBm(Combine with Antenna 0 and Antenna 1) IEEE 802.11n HT40 MHz mode: 25.29dBm(Combine with Antenna 0 and Antenna 1)
Modulation Technique	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
Transmit Data Rate	IEEE 802.11b: 11Mbps(CCK) with fall back rates of 5.5/2/1Mbps IEEE 802.11g: 54Mbps with fall back rates of 48/36/24/18/12/9 /6Mbps IEEE 802.11n HT20:130Mbps with fall back rates of 130/117/104/78/52/39/26/13Mbps IEEE 802.11nHT40:270Mbps with fall back rates of 270/243/216/162/108/81/54/27Mbps
Number of Channels	IEEE 802.11b mode: 11 Channels IEEE 802.11g mode: 11 Channels IEEE 802.11n HT20 MHz mode: 11 Channels IEEE 802.11n HT40 MHz mode:7 Channels
Antenna Specification	PCB Antenna with 5.0dBi gain (Max)
Channels Spacing	IEEE 802.11b/g ,802.11n HT20/HT40 : 5MHz
Temperature Range	0°C ~ +40°C

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: **PJZ6738** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: Normal Link + Adapter 1#	<input checked="" type="checkbox"/>
	Mode 2: Normal Link + Adapter 2#	<input checked="" type="checkbox"/>
Radiated Emission	Mode 1: TX	<input checked="" type="checkbox"/>

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and power line conducted emission below 30MHz, which worst case was in normal link mode.

IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High(2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 MHz mode: Channel Low (2412MHz), Channel Mid(2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT40 MHz mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 27Mbps data rate were chosen for full testing.



5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook#1	B475	WB04591721	N/A	LENOVO	N/A	AC cable: Unshielded 0.80m DC Cable: Unshielded 1.20m
2	Notebook#2	5310m	N/A	N/A	IBM	N/A	AC cable: Unshielded 0.80m DC Cable: Unshielded 1.20m
3	DSL Source	MA-160	14465250	N/A	ZHONE	Unshielded, 6.00m	Unshielded 1.80m
4	3.0HDD1	WDBACY320 5ABK-PESN	WX11EAOY4 182	N/A	WD	Unshielded 0.50m	N/A
5	3.0HDD2	WDBACY500 0ASL-OP	WX81E81YX S60	N/A	WD	Unshielded 0.50m	N/A

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-3478, R-3135, T-652, G-624)
Canada	INDUSTRY CANADA
Taiwan	BSMI
Norway	Nemko

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



7 FCC PART 15.247 REQUIREMENTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
ESCI EMI TEST RECEIVER.ESCI	ROHDE&SCHWARZ	ESCI	100783	03/09/2013	03/08/2014
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	04/20/2013	04/19/2014
LISN	EMCO	3825/2	8901-1459	03/09/2013	03/08/2014
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2013	03/03/2014
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. N.C.R = No Calibration Request.




7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.



7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Frequency (MHz)	LISN Factor (dB)	Cable Loss (dB)	Meter Reading (dBuV)	Measured Level (dBuV)	Limits (dBuV)	Over Limits (dBuV)	Detector	Line (L1/L2)
X.XX	8.93	0.07	25.96	34.96	60.00	-25.04	QP	L1

- Freq. = Emission frequency in MHz
- LISN Factor = Insertion loss of LISN and Pulse Limiter
- Cable Loss = Insertion loss of Cable (LISN to EMI Tester Receiver)
- Meter Reading = Uncorrected Analyzer/Receiver reading
- Measured Level = Read Level + Factor
- Limit = Limit stated in standard
- Over Limit = Reading in reference to limit
- Peak = Peak Reading
- QP = Quasi-peak Reading
- AV = Average Reading

Calculation Formula


1. Measured Level (dBuV) = LISN Factor (dB) + Cable Loss (dB)+ Meter Reading (dBuV)
2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)



7.1.6. TEST RESULTS

Model No.	6738-W1-NA	RBW,VBW	9 kHz
Environmental Conditions	26°C, 60% RH	Test Mode	Mode 1
Tested by	Sun Guo	Line	L1

(The chart below shows the highest readings taken from the final data.)




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1740	50.07	36.66	9.63	59.70	46.29	64.76	54.77	-5.06	-8.48	Pass
0.2300	43.07	29.16	9.69	52.76	38.85	62.45	52.45	-9.69	-13.60	Pass
0.3980	42.18	33.19	9.68	51.86	42.87	57.89	47.90	-6.03	-5.03	Pass
0.4740	42.21	34.20	9.68	51.89	43.88	56.44	46.44	-4.55	-2.56	Pass
0.6620	35.53	25.95	9.77	45.30	35.72	56.00	46.00	-10.70	-10.28	Pass
8.3820	32.47	20.01	9.83	42.30	29.84	60.00	50.00	-17.70	-20.16	Pass

NOTE: L1 = Line One (Live Line)



Model No.	6738-W1-NA	RBW,VBW	9 kHz
Environmental Conditions	26°C, 60% RH	Test Mode	Mode 1
Tested by	Sun Guo	Line	L2

(The chart below shows the highest readings taken from the final data.)




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1660	50.88	38.30	9.78	60.66	48.08	65.15	55.16	-4.49	-7.08	Pass
0.2180	44.96	32.09	9.78	54.74	41.87	62.89	52.89	-8.15	-11.02	Pass
0.4020	42.70	29.71	9.71	52.41	39.42	57.81	47.81	-5.40	-8.39	Pass
0.4780	42.42	33.35	9.69	52.11	43.04	56.37	46.37	-4.26	-3.33	Pass
0.6620	36.57	24.59	9.69	46.26	34.28	56.00	46.00	-9.74	-11.72	Pass
1.5820	31.59	16.82	9.76	41.35	26.58	56.00	46.00	-14.65	-19.42	Pass

NOTE: L2 = Line Two (Neutral Line).



Model No.	6738-W1-NA	RBW,VBW	9 kHz
Environmental Conditions	26°C, 60% RH	Test Mode	Mode 2
Tested by	Sun Guo	Line	L1

(The chart below shows the highest readings taken from the final data.)




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1620	38.18	18.44	9.60	47.78	28.04	65.36	55.36	-17.58	-27.32	Pass
0.2540	32.90	20.25	9.69	42.59	29.94	61.62	51.63	-19.03	-21.69	Pass
0.3558	31.48	9.44	9.68	41.16	19.12	58.82	48.83	-17.66	-29.71	Pass
1.0220	28.30	15.39	9.71	38.01	25.10	56.00	46.00	-17.99	-20.90	Pass
2.8460	27.49	16.89	9.71	37.20	26.60	56.00	46.00	-18.80	-19.40	Pass
11.2860	40.28	28.57	9.88	50.16	38.45	60.00	50.00	-9.84	-11.55	Pass

NOTE: L1 = Line One (Live Line)



Model No.	6738-W1-NA	RBW,VBW	9 kHz
Environmental Conditions	26°C, 60% RH	Test Mode	Mode 2
Tested by	Sun Guo	Line	L2

(The chart below shows the highest readings taken from the final data.)



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1660	36.66	21.42	9.61	46.27	31.03	65.15	55.16	-18.88	-24.13	Pass
0.5220	25.77	12.82	9.69	35.46	22.51	56.00	46.00	-20.54	-23.49	Pass
1.3380	27.34	16.09	9.72	37.06	25.81	56.00	46.00	-18.94	-20.19	Pass
2.8220	27.65	17.99	9.71	37.36	27.70	56.00	46.00	-18.64	-18.30	Pass
11.1020	40.60	28.18	9.88	50.48	38.06	60.00	50.00	-9.52	-11.94	Pass
29.2340	22.32	13.54	9.98	32.30	23.52	60.00	50.00	-27.70	-26.48	Pass

NOTE: L2 = Line Two (Neutral Line).



7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.2.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

7.2.3. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.




7.2.4. TEST RESULTS

Test Plot


Antenna 0

IEEE 802.11b mode

CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.42GHz)






CH Mid (30MHz ~26.5GHz)




CH High (30MHz ~26.5GHz)






CH High (2.45GHz ~2.5GHz)



Antenna 0


IEEE 802.11g mode

CH Low (30MHz ~26.5GHz)






CH Low (2.31GHz ~2.42GHz)




CH Mid (30MHz ~26.5GHz)






CH High (30MHz ~26.5 GHz)



CH High (2.45GHz ~2.5GHz)







Antenna 1

IEEE 802.11g mode

CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.42GHz)






CH Mid (30MHz ~26.5GHz)




CH High (30MHz ~26.5GHz)






CH High (2.45GHz ~2.5GHz)




Antenna 0 IEEE 802.11n HT20 MHz mode CH Low (30MHz ~26.5GHz)






CH Low (2.31GHz ~2.42GHz)




CH Mid (30MHz ~26.5GHz)






CH High (30MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)







Antenna 1

IEEE 802.11n HT20 MHz mode

CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.42GHz)






CH Mid (30MHz ~26.5GHz)




CH High (30MHz ~26.5GHz)






CH High (2.45GHz ~2.5GHz)



Antenna 0


IEEE 802.11n HT40 MHz mode

CH Low (30MHz ~26.5GHz)






CH Low (2.31GHz ~2.45GHz)




CH Mid (30MHz ~26.5GHz)






CH High (30MHz ~26.5GHz)



CH High (2.43GHz ~2.5GHz)







Antenna 1

IEEE 802.11n HT40 MHz mode

CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.45GHz)






CH Mid (30MHz ~26.5GHz)




CH High (30MHz ~26.5GHz)





CH High (2.43GHz ~2.5GHz)





7.2.4.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

NOTE:(1) The lower limit shall apply at the transition frequencies.
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).



7.2.4.2. TEST INSTRUMENTS

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014
ESCI EMI TEST RECEIVER.ESCI	ROHDE&SCHWARZ	ESCI	100783	03/09/2013	03/08/2014
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2013	03/18/2014
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2013	03/18/2014
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	06/21/2013	06/21/2014
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/02/2013	03/01/2014
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/02/2013	03/01/2014
Loop Antenna	A、R、A	PLA-1030/B	1029	03/23/2013	03/23/2014
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	03/04/2013	03/03/2014
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The FCC Site Registration number is 101879.
 3. N.C.R = No Calibration Required.




7.2.4.3. TEST PROCEDURE (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
 - Below 1GHz:
 - RBW=100kHz / VBW=300kHz / Sweep=AUTO
 - Above 1GHz:
 - (a) PEAK: RBW=1MHz,VBW=3MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.




7.2.4.4. TEST SETUP

Below 30MHz




Below 1 GHz





Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



7.2.4.5. DATA SAMPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	36.37	-12.20	24.17	40.00	-15.83	V	QP

Frequency (MHz) = Emission frequency in MHz
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading
 Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)
 Limit (dBuV/m) = Limit stated in standard
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)
 Q.P. = Quasi-peak Reading

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading
 Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)
 Limit (dBuV/m) = Limit stated in standard
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)
 Peak = Peak Reading
 AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m)
 Result (dBuV/m) = Reading (dBuV) + Correction Factor



7.2.4.6. TEST RESULTS

Below 1 GHz

Test Mode: TX

Test Date: July 5, 2013

Temperature: 22°C

Tested by: Mack Li

Humidity: 58% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
400.5400	44.26	-7.25	37.01	46.00	-8.99	V	QP
500.4500	40.30	-5.92	34.38	46.00	-11.62	V	QP
559.6200	43.38	-4.49	38.89	46.00	-7.11	V	QP
625.5800	43.49	-3.46	40.03	46.00	-5.97	V	QP
875.8400	38.34	1.03	39.37	46.00	-6.63	V	QP
960.2300	45.49	1.16	46.65	54.00	-7.35	V	QP
359.8000	47.82	-8.45	39.37	46.00	-6.63	H	QP
400.5400	50.64	-7.25	43.39	46.00	-2.61	H	QP
559.6200	44.89	-4.49	40.40	46.00	-5.60	H	QP
640.1300	42.25	-2.91	39.34	46.00	-6.66	H	QP
679.9000	38.09	-1.43	36.66	46.00	-9.34	H	QP
875.8400	38.35	1.03	39.38	46.00	-6.62	H	QP

**Remark: No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

- Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
- Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.
- | | |
|------------------------|--|
| Frequency (MHz). | = Emission frequency in MHz |
| Reading (dBuV/m) | = Receiver reading |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBuV/m) | = Limit stated in standard |
| Margin (dB) | = Measured (dBuV/m) – Limits (dBuV/m) |
| Antenna Pol e(H/V) | = Current carrying line of reading |



Above 1 GHz

Antenna 0

Operation Mode: TX / IEEE 802.11b/ CH Low

Test Date: July 5, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3205.0000	50.54	-4.09	46.45	74.00	-27.55	V	Peak
3775.0000	47.39	-2.55	44.84	74.00	-29.16	V	Peak
4825.0000	47.71	0.52	48.23	74.00	-25.77	V	Peak
5260.0000	45.99	1.54	47.53	74.00	-26.47	V	Peak
6160.0000	45.02	3.56	48.58	74.00	-25.42	V	Peak
6910.0000	45.40	5.89	51.29	74.00	-22.71	V	Peak
1210.0000	54.60	-8.69	45.91	74.00	-28.09	H	Peak
1465.0000	50.30	-8.11	42.19	74.00	-31.81	H	Peak
3220.0000	52.72	-4.08	48.64	74.00	-25.36	H	Peak
4825.0000	49.26	0.52	49.78	74.00	-24.22	H	Peak
5170.0000	45.58	1.52	47.10	74.00	-26.90	H	Peak
5770.0000	45.50	2.65	48.15	74.00	-25.85	H	Peak
1210.0000	54.60	-8.69	45.91	74.00	-28.09	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b/ CH Mid
Temperature: 24°C
Humidity: 52% RH

Test Date: July 5, 2013
Tested by: Mack Li
Polarity: Ver. / Hor.

Table with 8 columns: Frequency (MHz), Reading (dBuV), Correction Factor (dB/m), Result (dBuV/m), Limit (dBuV/m), Margin (dB), Antenna Pole (V/H), Remark. It contains two sets of data rows for various frequencies.

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH High

Test Date: July 5, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3280.0000	50.59	-4.05	46.54	74.00	-27.46	V	Peak
4105.0000	45.71	-2.03	43.68	74.00	-30.32	V	Peak
4930.0000	55.51	1.00	56.51	74.00	-17.49	V	Peak
4930.0000	51.88	1.00	52.88	54.00	-1.12	V	AVG
5845.0000	44.39	2.85	47.24	74.00	-26.76	V	Peak
6385.0000	44.90	4.22	49.12	74.00	-24.88	V	Peak
6805.0000	45.16	5.52	50.68	74.00	-23.32	V	Peak
3280.0000	51.69	-4.05	47.64	74.00	-26.36	H	Peak
4930.0000	53.75	1.00	54.75	74.00	-19.25	H	Peak
4930.0000	50.88	1.00	51.88	54.00	-2.12	H	AVG
5500.0000	45.58	1.73	47.31	74.00	-26.69	H	Peak
6100.0000	45.15	3.39	48.54	74.00	-25.46	H	Peak
6565.0000	45.39	4.72	50.11	74.00	-23.89	H	Peak
7390.0000	49.23	7.57	56.80	74.00	-17.20	H	Peak
7390.0000	42.58	7.57	50.15	54.00	-3.85	H	AVG

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Antenna 0

Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: July 6, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3205.0000	50.54	-4.09	46.45	74.00	-27.55	V	Peak
3775.0000	47.39	-2.55	44.84	74.00	-29.16	V	Peak
4825.0000	47.71	0.52	48.23	74.00	-25.77	V	Peak
5260.0000	45.99	1.54	47.53	74.00	-26.47	V	Peak
6160.0000	45.02	3.56	48.58	74.00	-25.42	V	Peak
6910.0000	45.40	5.89	51.29	74.00	-22.71	V	Peak
1210.0000	54.60	-8.69	45.91	74.00	-28.09	H	Peak
1465.0000	50.30	-8.11	42.19	74.00	-31.81	H	Peak
3220.0000	52.72	-4.08	48.64	74.00	-25.36	H	Peak
4825.0000	54.74	0.52	55.26	74.00	-18.74	H	Peak
4825.0000	44.80	0.52	45.32	54.00	-8.68	H	AVG
5170.0000	45.58	1.52	47.10	74.00	-26.90	H	Peak
5770.0000	45.50	2.65	48.15	74.00	-25.85	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: July 6, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3250.0000	50.20	-4.07	46.13	74.00	-27.87	V	Peak
4405.0000	46.30	-0.81	45.49	74.00	-28.51	V	Peak
4870.0000	50.83	0.73	51.56	74.00	-22.44	V	Peak
5590.0000	44.35	1.91	46.26	74.00	-27.74	V	Peak
6175.0000	44.13	3.61	47.74	74.00	-26.26	V	Peak
6925.0000	45.17	5.97	51.14	74.00	-22.86	V	Peak
3250.0000	50.89	-4.07	46.82	74.00	-27.18	H	Peak
4255.0000	45.64	-1.37	44.27	74.00	-29.73	H	Peak
4870.0000	55.68	0.73	56.41	74.00	-17.59	H	Peak
4870.0000	45.45	0.73	46.18	54.00	-7.82	H	AVG
6025.0000	44.81	3.16	47.97	74.00	-26.03	H	Peak
6760.0000	44.33	5.36	49.69	74.00	-24.31	H	Peak
7120.0000	44.09	6.96	51.05	74.00	-22.95	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH High

Test Date: July 6, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1345.0000	51.55	-8.08	43.47	74.00	-30.53	V	Peak
3280.0000	49.59	-4.05	45.54	74.00	-28.46	V	Peak
4105.0000	45.71	-2.03	43.68	74.00	-30.32	V	Peak
4930.0000	52.42	1.00	53.42	74.00	-20.58	V	Peak
4930.0000	42.69	1.00	43.69	54.00	-10.31	V	AVG
5845.0000	44.39	2.85	47.24	74.00	-26.76	V	Peak
6550.0000	44.11	4.68	48.79	74.00	-25.21	V	Peak
1210.0000	53.74	-8.69	45.05	74.00	-28.95	H	Peak
3280.0000	50.69	-4.05	46.64	74.00	-27.36	H	Peak
3835.0000	46.57	-2.50	44.07	74.00	-29.93	H	Peak
4930.0000	54.96	1.00	55.96	74.00	-18.04	H	Peak
4930.0000	44.83	1.00	45.83	54.00	-8.17	H	AVG
5500.0000	45.58	1.73	47.31	74.00	-26.69	H	Peak
6100.0000	44.65	3.39	48.04	74.00	-25.96	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Antenna 1

Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: July 6, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1285.0000	51.09	-8.35	42.74	74.00	-31.26	V	Peak
3205.0000	49.04	-4.09	44.95	74.00	-29.05	V	Peak
3775.0000	46.39	-2.55	43.84	74.00	-30.16	V	Peak
4825.0000	49.71	0.52	50.23	74.00	-23.77	V	Peak
5260.0000	45.49	1.54	47.03	74.00	-26.97	V	Peak
6295.0000	44.91	3.97	48.88	74.00	-25.12	V	Peak
1210.0000	53.60	-8.69	44.91	74.00	-29.09	H	Peak
3220.0000	51.72	-4.08	47.64	74.00	-26.36	H	Peak
4825.0000	50.77	0.52	51.29	74.00	-22.71	H	Peak
5770.0000	45.00	2.65	47.65	74.00	-26.35	H	Peak
6220.0000	45.04	3.74	48.78	74.00	-25.22	H	Peak
6940.0000	44.45	6.04	50.49	74.00	-23.51	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: July 6, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3250.0000	50.20	-4.07	46.13	74.00	-27.87	V	Peak
4405.0000	45.80	-0.81	44.99	74.00	-29.01	V	Peak
4870.0000	50.33	0.73	51.06	74.00	-22.94	V	Peak
5245.0000	45.93	1.54	47.47	74.00	-26.53	V	Peak
6475.0000	44.24	4.47	48.71	74.00	-25.29	V	Peak
6925.0000	45.17	5.97	51.14	74.00	-22.86	V	Peak
2815.0000	47.50	-4.98	42.52	74.00	-31.48	H	Peak
3445.0000	46.23	-3.78	42.45	74.00	-31.55	H	Peak
4375.0000	44.92	-0.91	44.01	74.00	-29.99	H	Peak
4870.0000	49.95	0.73	50.68	74.00	-23.32	H	Peak
5590.0000	44.90	1.91	46.81	74.00	-27.19	H	Peak
6295.0000	44.55	3.97	48.52	74.00	-25.48	H	Peak
2815.0000	47.50	-4.98	42.52	74.00	-31.48	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH High
Temperature: 24°C
Humidity: 52 % RH

Test Date: July 6, 2013
Tested by: Mack Li
Polarity: Ver. / Hor.

Table with 8 columns: Frequency (MHz), Reading (dBuV), Correction Factor (dB/m), Result (dBuV/m), Limit (dBuV/m), Margin (dB), Antenna Pole (V/H), Remark. It contains two sets of data rows for various frequencies.

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Combine with Antenna 0 and Antenna 1

Operation Mode: TX / IEEE 802.11n HT20 MHz/ CH Low **Test Date:** July 6, 2013

Temperature: 24°C

Tested by: Mack Li

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3205.0000	49.04	-4.09	44.95	74.00	-29.05	V	Peak
4300.0000	45.15	-1.20	43.95	74.00	-30.05	V	Peak
4825.0000	48.71	0.52	49.23	74.00	-24.77	V	Peak
5725.0000	44.93	2.46	47.39	74.00	-26.61	V	Peak
6295.0000	44.91	3.97	48.88	74.00	-25.12	V	Peak
7405.0000	43.81	7.58	51.39	74.00	-22.61	V	Peak
3220.0000	51.22	-4.08	47.14	74.00	-26.86	H	Peak
3835.0000	46.95	-2.50	44.45	74.00	-29.55	H	Peak
4825.0000	51.16	0.52	51.68	74.00	-22.32	H	Peak
5770.0000	45.00	2.65	47.65	74.00	-26.35	H	Peak
6250.0000	44.72	3.83	48.55	74.00	-25.45	H	Peak
6940.0000	44.45	6.04	50.49	74.00	-23.51	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11n HT20 MHz/ CH Mid **Test Date:** July 6, 2013
Temperature: 24°C **Tested by:** Mack Li
Humidity: 52% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2875.0000	47.05	-4.74	42.31	74.00	-31.69	V	Peak
3385.0000	48.31	-4.01	44.30	74.00	-29.70	V	Peak
4255.0000	45.68	-1.37	44.31	74.00	-29.69	V	Peak
4870.0000	49.83	0.73	50.56	74.00	-23.44	V	Peak
5845.0000	43.99	2.85	46.84	74.00	-27.16	V	Peak
6685.0000	44.39	5.11	49.50	74.00	-24.50	V	Peak
3250.0000	49.39	-4.07	45.32	74.00	-28.68	H	Peak
3835.0000	46.57	-2.50	44.07	74.00	-29.93	H	Peak
4870.0000	49.95	0.73	50.68	74.00	-23.32	H	Peak
5755.0000	45.87	2.59	48.46	74.00	-25.54	H	Peak
6175.0000	45.28	3.61	48.89	74.00	-25.11	H	Peak
6865.0000	45.32	5.72	51.04	74.00	-22.96	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*



Operation Mode: TX / IEEE 802.11n HT20 MHz/ CH High Test Date: July 6, 2013

Temperature: 24°C Tested by: Mack Li

Humidity: 52% RH Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2560.0000	48.55	-5.98	42.57	74.00	-31.43	V	Peak
3520.0000	47.03	-3.41	43.62	74.00	-30.38	V	Peak
4330.0000	44.86	-1.09	43.77	74.00	-30.23	V	Peak
4930.0000	53.68	1.00	54.68	74.00	-19.32	V	Peak
4930.0000	43.37	1.00	44.37	54.00	-9.63	V	AVG
6085.0000	43.52	3.34	46.86	74.00	-27.14	V	Peak
6895.0000	45.63	5.82	51.45	74.00	-22.55		Peak
3280.0000	50.69	-4.05	46.64	74.00	-27.36	H	Peak
3835.0000	46.57	-2.50	44.07	74.00	-29.93	H	Peak
4390.0000	44.81	-0.86	43.95	74.00	-30.05	H	Peak
4930.0000	50.37	1.00	51.37	74.00	-22.63	H	Peak
5500.0000	45.58	1.73	47.31	74.00	-26.69	H	Peak
6565.0000	45.39	4.72	50.11	74.00	-23.89	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Combine with Antenna 0 and Antenna 1

Operation Mode: TX / IEEE 802.11n HT40 MHz/ CH Low **Test Date:** July 6, 2013

Temperature: 24°C **Tested by:** Mack Li

Humidity: 52% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1285.0000	51.09	-8.35	42.74	74.00	-31.26	V	Peak
3205.0000	49.54	-4.09	45.45	74.00	-28.55	V	Peak
4435.0000	45.01	-0.76	44.25	74.00	-29.75	V	Peak
4845.0000	48.74	0.61	49.35	74.00	-24.65	V	Peak
5725.0000	44.93	2.46	47.39	74.00	-26.61	V	Peak
6535.0000	44.29	4.64	48.93	74.00	-25.07	V	Peak
1210.0000	52.60	-8.69	43.91	74.00	-30.09	H	Peak
3220.0000	50.72	-4.08	46.64	74.00	-27.36	H	Peak
3835.0000	46.95	-2.50	44.45	74.00	-29.55	H	Peak
4845.0000	47.67	0.61	48.28	74.00	-25.72	H	Peak
5770.0000	45.50	2.65	48.15	74.00	-25.85	H	Peak
6220.0000	45.04	3.74	48.78	74.00	-25.22	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).