

RF EXPOSURE

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

MPE Calculations : WLAN2.4GHz(802.11b_2412 MHz)

- Frequency Range : 2412 MHz ~ 2462 MHz
- Measured RF Maximum Output Power(Avg.) : 17.13 dBm
- Target Power & Tolerance 16.50 dBm & \pm 1.00 dB
(Maximum : 17.50 dBm & Minimum : 15.50 dBm)
- Maximum Peak Antenna Gain : 4.99 dBi
- **Maximum Output Power for the Calculation : 17.50 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>17.50</u> dBm + <u>4.99</u> dBi</p> <p>= <u>22.49</u> dBm</p> <p>= <u>177.42</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

Power Density at the specific separation

<p>- S = EIRP / (4 X R²π)</p> <p>= <u>177.42</u> / (4 X 20² X π)</p> <p>= <u>0.035 296</u> mW/cm²</p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p> <p>Limit : 1.00 mW/cm²</p>
---	--

MPE Calculations : WLAN5GHz(802.11ax VHT80 MIMO 5290 MHz)

- Frequency Range : 5180 MHz ~ 5805 MHz

- Measured RF Maximum Output Power(Avg.) : 18.09 dBm

- Target Power & Tolerance 17.50 dBm & \pm 1.00 dB

(Maximum : 18.50 dBm & Minimum : 16.50 dBm)

- Maximum Peak Antenna Gain : 4.78 dBi

- **Maximum Output Power for the Calculation : 18.50 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>18.50</u> dBm + <u>4.78</u> dBi</p> <p>= <u>23.28</u> dBm</p> <p>= <u>212.81</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

Power Density at the specific separation

<p>- S = EIRP / (4 X R²π)</p> <p>= 212.81 / (4 X 20² X π)</p> <p>= <u>0.042 338</u> mW/cm²</p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p> <p>Limit : 1.00 mW/cm²</p>
--	--

MPE Calculations : WLAN2.4GHz+5GHz

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

simultaneous MPE for Wi-Fi and Bluetooth

WLAN2.4GHz+5GHz

<p>- Total (%) =</p> $[2.4\text{GHz Result}(\text{mW}/\text{cm}^2) / \text{Limit}(\text{mW}/\text{cm}^2)] +$ $[5\text{GHz Result}(\text{mW}/\text{cm}^2) / \text{Limit}(\text{mW}/\text{cm}^2)] * 100$ $= [\underline{0.035\ 296} / 1] +$ $[\underline{0.042\ 338} / 1] * 100$ $= \underline{7.763} \%$	<p>- NOTE</p> <p>WLAN2.4GHz + 5GHz</p> <p>WLAN2.4GHz = <u>0.035 296</u> mW/cm²</p> <p>WLAN5GHz = <u>0.042 338</u> mW/cm²</p> <p>Distance to the center of the radiation of the antenna (<u>20</u> cm)</p> <p>Limit : ≤ 100 %</p>
---	--