

TEST REPORT N°: (5210)258-0124

TEST REPORT

To:	MAY CHEONG TOY PRODUCTS FTY. LTD.	To:	-
Attn:	Huang Hai Yu	Attn:	-
Address:	7/F., East Wing, Tsim Sha Tsui Centre, 66 Mody Road, Tsimshatsui East, Kowloon, Hong Kong	Address:	-
Fax:	0769-87753123	Fax:	-
E-mail:	Huanghaiyu.mt@maycheonggroup.com.cn	E-mail:	-
Folder No.:	BVCK10SE144MTHS-B		

Factory name:	--
Location:	--
Product:	1:24 Radio Control Vehicles, Assorted MODEL: 81018



Sample No:	(5210)258-0124
Test date:	September 21, 2010
Test Requested:	FCC Part 15 - 2008
Test Method:	ANSI C63.4 - 2003
FCC ID:	PKG10130RC49

The results given in this report are related to the tested specimen of the described electrical apparatus.

CONCLUSION: The submitted sample was found to COMPLY with requirement of FCC Part 15 Subpart C.

Authorized Signature:

	
Reviewed by: Keith Yeung	Approved by: Steven Tsang
Date: September 29, 2010	Date: September 29, 2010

**BUREAU VERITAS HONG KONG LIMITED –
Kowloon Bay Office
1/F Pacific Trade Centre,
2 Kai Hing Road, Kowloon Bay,
Kowloon, HONG KONG**
Tel: +852 2331 0888
Fax: +852 2331 0889
www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TEST REPORT N^o: (5210)258-0124

Location of the test site

Radiated and Conducted emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. An Open Area Test Site and Full Anechoic Chamber (FCC Listed Site, Registration No. 642151) are set up for investigation and located at :

BUREAU VERITAS HONG KONG LIMITED, EMC CENTRE

No. 2106-2107, 21/F., Westin Centre,
26 Hung To Road,
Kwun Tong, Kowloon,
Hong Kong

List of measuring equipment

Radiated Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATION DUE
EMI TEST RECEIVER	R&S	ESCS 30	830986/030	26-SEP-2010
BILOG ANTENNA	SCHAFFNER	CBL6112D	25229	02-AUG-2011
OPEN AREA TEST SITE	BVCPS	N/A	N/A	05-JULY-2011
ANECHOIC CHAMBER	ALBATROSS	M-CDC	80374004499B	06-JULY-2011
COAXIAL CABLE	SUHNER	N/A	N/A	07-DEC-2010

Remarks:-

N/A : Not Applicable or Not Available

The measurement instrumentation uncertainty would be taking into consideration on each of the test result

TEST REPORT N^o: (5210)258-0124

Equipment Under Test [EUT]

Description of Sample:

Model Name: 1:24 Radio Control Vehicles, Assorted
Model Number: 81018
Additional Model Name: 1:24 CSRC with working headlights Asst./
1:16 Off-Road R/C, Assorted
Additional Model Number: 81056 / 81100 / 10130 / 81051 / 81052 / 81053 / 81054 /
81055 / 81057 / 81058 / 81059 / 81061 / 81062 / 81063 /
81064 / 81065 / 81066 / 81067 / 81068 / 81091
Additional Model information: Declare the Circuit, PCB layout and Electrical parts of the products are identical to the basic model. Except the outlook and colour of shell is different.
Rating: 9Vd.c. ("6F22" size battery x 1)

Description of EUT Operation:

The Equipment Under Test (EUT) is a MAY CHEONG TOY PRODUCTS FTY. LTD. of Radio Control toy. The transmitter is 2 buttons and 1 wheel transmitter and operating at 49.86MHz. The EUT continues to transmit when buttons are being pressed, Modulation by IC, and type is pulse modulation.

The transmitter has different control:

1. Top button – control forward
2. Bottom button – control backward
3. Wheel – control left and right

Antenna Requirement (Section 15.203)

The EUT is use of a permanently antenna. The antenna consists of 17cm metal spring covered with rubber. The antenna is not replaceable or user serviceable. The requirements of S15.203 are met. There are no deviations or exceptions to the specifications.

Photo of Antenna



TEST REPORT N°: (5210)258-0124

Radiated Emissions (Fundamental)

Test Requirement: FCC Part 15 Section 15.235
Test Method: ANSI C63.4
Test Date(s): 2010-09-21
Temperature: 27.0 °C
Humidity: 78.0 %
Atmospheric Pressure: 100.4 kPa
Mode of Operation: Transmission mode
Tested Voltage: 9Vd.c. ("6F22" size battery x 1)

Test Procedure:


Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using new battery. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

Location: The Roof, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Test Setup: Open Area Test Site





TEST REPORT N°: (5210)258-0124

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [$\mu\text{V}/\text{m}$]	Field Strength of Fundamental Emission [Average] [$\mu\text{V}/\text{m}$]
49.82 – 49.90	100,000 (100 dB $\mu\text{V}/\text{m}$)	10,000 (80 dB $\mu\text{V}/\text{m}$)

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V) and degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB $\mu\text{V}/\text{m}$)	Limit at 3m (dB $\mu\text{V}/\text{m}$)	Margin (dB)
49.86	V	9.9	66.8	100	-33.2

Detection mode: # Average

Frequency (MHz)	Polarity (H/V) and degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB $\mu\text{V}/\text{m}$)	Limit at 3m (dB $\mu\text{V}/\text{m}$)	Margin (dB)
49.86	V	9.9	**62.6	80	-17.4

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\text{Log}(0.62) = -4.2\text{dB}$

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 100KHz
VBW = 300KHz



TEST REPORT N°: (5210)258-0124

Radiated Emissions (9kHz – 1GHz)

Test Requirement: FCC Part 15 Section 15.209
 Test Method: ANSI C63.4
 Test Date(s): 2010-09-21
 Temperature: 27.0 °C
 Humidity: 78.0 %
 Atmospheric Pressure: 100.4 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: 9Vd.c. ("6F22" size battery x 1)

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [$\mu\text{V}/\text{m}$]
1.705-30	300
30-88	100
88-216	150
216-960	200
Above960	500

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB $\mu\text{V}/\text{m}$)	Limit at 3m (dB $\mu\text{V}/\text{m}$)	Margin (dB)
99.72	V	10.7	28.8	43.5	-14.7
149.58	V	10.9	20.4	43.5	-23.1
199.44	V	11.6	19.2	43.5	-24.3
249.30	H	13.8	21.4	46.0	-24.6
299.16	H	15.0	23.6	46.0	-22.4
349.02	H	16.8	25.8	46.0	-20.2
398.88	V	18.1	27.0	46.0	-19.0
448.74	V	19.0	27.5	46.0	-18.5
498.60	H	19.9	28.5	46.0	-17.5
548.46	H	21.0	31.6	46.0	-14.4

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 120KHz
 VBW = 120KHz



TEST REPORT N°: (5210)258-0124

26dB Bandwidth of Fundamental Emission

Test Requirement:	FCC 47 CFR 15.235
Test Method:	ANSI C63.4:2003 (Section 13.1.7)
Test Date(s):	2010-09-21
Temperature:	27.0 °C
Humidity:	78.0 %
Atmospheric Pressure:	100.4 kPa
Mode of Operation:	Transmission mode
Tested Voltage:	9Vd.c. ("6F22" size battery x 1)

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Limits for 26dB Bandwidth of Fundamental Emission:

Frequency [MHz]	26dB Bandwidth [KHz]	Limits [MHz]
49.861	24.4	within 49.82-49.90


TEST REPORT N°: (5210)258-0124

Measurement Data :

Test Result of 26dB Bandwidth of Fundamental Emission: PASS



21.Sep 10 14:09 RBW 3 kHz Marker 1 [T1]
 Ref 82 dBµV/m VBW 10 kHz 68.47 dBµV/m
 *Att 10 dB SWT 15 ms 49.861000000 MHz



Date: 21.SEP.2010 14:09:14



TEST REPORT N°: (5210)258-0124

Duty Cycle Correction During 100msec:

Each function key sends a different series of characters, but each packet period (17.1msec) never exceeds a series of 4 long (1.4msec) and 10 short (0.5msec) pulses. Assuming any combination of short or long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered $(4 \times 1.4\text{msec}) + (10 \times 0.5\text{msec})$ per 17.1msec = 62.0% duty cycle. Figure A through C show the characteristics of the pulse train for one of these functions.


Remarks:

Duty Cycle Correction = $20\text{Log}(0.62) = -4.2\text{dB}$

The following figures [Figure A to Figure C] show the characteristics of the pulse train for one of these functions.


TEST REPORT N°: (5210)258-0124

Figure A [Pulse Train]



Date: 21.SEP.2010 14:11:36


Figure B [Long Pulse]



Date: 21.SEP.2010 14:11:50

TEST REPORT N°: (5210)258-0124

Figure C [Short Pulse]



Date: 21.SEP.2010 14:12:38

TEST REPORT N°: (5210)258-0124

Photographs of EUT


Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



TEST REPORT N°: (5210)258-0124

Battery compartment



Battery Cover



Internal View of the product



Antenna



TEST REPORT N°: (5210)258-0124

Measurement of Radiated Emission Test Set Up



******* End of Report *******