

INTERTEK TESTING SERVICES

Analysis Report

The equipment under test (EUT) is a portable transmitter for 1:14 Voice Defender R/C operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by two 1.5V AA size batteries. For more detail information, pls. refer to the user manual.

Antenna Type: Integral antenna

Antenna Gain: 0dBi

The nominal conducted output power specified: -26.00dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -28.15dBm (+/- 3dB)

Modulation Type: Pulse modulation

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 68.90dBμV/m at 3m in the frequency 27.145MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -26.33dBm

The ERP = EIRP - 2.15 = -28.48 dBm

which is within the production variation.

The maximum conducted output power specified is -23dBm = 0.005mW

The source-based time-averaging conducted output power

= 0.005 * Duty Cycle mW < 0.1mW

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

= $474 * [1 + \log(100/f(\text{MHz}))]/2$

= 371.2 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 74.60ms

Effective period of the cycle = $160\mu\text{s} \times 9 + 256\mu\text{s} \times 6 + 384\mu\text{s} \times 1 = 3.36\text{ms}$

DC = $3.36\text{ms} / 74.60\text{ms} = 0.0450$ or 4.50%