

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Off Road Attack operating at 2.4G Band. The EUT can be powered by DC3.0V (2 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 2.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 2.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 98.2dB μ V/m at 3m in the frequency 2475MHz

The EIRP = [(FS*D) ² / 30] mW = 2.97dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 95.1dB μ V/m at 3m in the frequency 2442MHz

The EIRP = [(FS*D) ² / 30] mW = -0.13dBm

which is within the production variation.

The maximum conducted output power specified is 5dBm =3.2mW

The source- based time-averaging conducted output power

=3.2* Duty cycle mW <3.2 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.475) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 10.1304ms

Effective period of the cycle = 391.3 μ s x 2 = 782.6 μ s=0.7826ms

DC =0.7826ms / 10.1304ms =0.0773 or 7.73%