

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a 10.5" RC Rock Hopper operating at 2.4G Band. The EUT can be powered by DC 3.2V (1 x 3.2V rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -5.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -5.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 91.0dB μ V/m at 3m in the frequency 2420MHz

The EIRP = [(FS*D) ^2 / 30] mW = -4.23dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 88.3.dB μ V/m at 3m in the frequency 2462MHz

The EIRP = [(FS*D) ^2 / 30] mW = -6.93dBm

which is within the production variation.

The maximum conducted output power specified is -2dBm= 0.631mW

The source- based time-averaging conducted output power =0.631mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.462) mW

= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: PKG81806RC