

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a R/C Work Machines Bobcat T590 Compact Track Loader operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal peak radiated output power (e.i.r.p) is: -6.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is -6.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 89.1 dB μ V/m at 3m in the frequency 2462MHz

The EIRP = [(FS*D) ^2 / 30] mW = -6.13dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 87.9dB μ V/m at 3m in the frequency 2420MHz

The EIRP = [(FS*D) ^2 / 30] mW = -7.33dBm

which is within the production variation.

The maximum conducted output power specified is -3dBm= 0.501mW

The source- based time-averaging conducted output power =0.501* Duty cycle mW <0.501 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.462) mW

= 9.56 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 31.8116ms

Effective period of the cycle = 0.4348ms x 2 = 0.8696ms

DC =0.8696ms / 31.8116ms =0.0273 or 2.73%