

INTERTEK TESTING SERVICES

RF Exposure

The Equipment under Test (EUT) is a Car unit for DESERT REBELS (2.4GHZ + USB RECHARGEABLE VER.), ASST operating at 2.4GHz band. It is powered by 1 x DC 3.2V rechargeable battery. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 2dBm (tolerance: +/- 3dB).

The normal conducted output power is: 2dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 99.8dB μ V/m at 3m in the frequency 2410MHz

The EIRP = [(FS*D) ^2 / 30] mW = 4.57dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 96.6dB μ V/m at 3m in the frequency 2441MHz

The EIRP = [(FS*D) ^2 / 30] mW = 1.37dBm

which is within the production variation.

The maximum conducted output power specified is 5.0dBm = 3.2mW

The source- based time-averaging conducted output power

= 3.2* Duty cycle mW <3.2mW(Duty cycle <100%

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.471) mW

= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 1.2ms

Effective period of the cycle = 0.320ms x 1 = 0.320ms

DC = 0.320ms / 1.200ms = 0.2667 or 26.67%