

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a RC 1:14 (2.4G, 3.2V, 360mAh, USB) asst (1:14 RC (2.4G, 3.2V, 360mAh, USB) Lamborghini Centenario) operating at 2.4G Band. The EUT can be powered by DC 3.2V (1 x 3.2V Rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 98.8dB μ V/m at 3m in the frequency 2420MHz

The EIRP = [(FS*D) ^2 / 30] mW = 3.57dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 96.9dB μ V/m at 3m in the frequency 2462MHz

The EIRP = [(FS*D) ^2 / 30] mW = 1.67dBm

which is within the production variation.

The maximum conducted output power specified is 4dBm= 2.512mW

The source- based time-averaging conducted output power =2.512mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.462) mW

= 9.56 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.