



FCC RADIO TEST REPORT

FCC ID : PKRISGMD2000
Equipment : Wireless Module
Brand Name : Inseego
Model Name : MD2000
Applicant : Inseego Corporation
9710 Scranton Road Suite 200, San Diego, CA 92121
Manufacturer : Inseego Corporation
9710 Scranton Road Suite 200, San Diego, CA 92121
Standard : FCC Part 15 Subpart E §15.407

The product was received on Sep. 11, 2020 and testing was started from Sep. 23, 2020 and completed on Sep. 29, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 26dB & 99% Occupied Bandwidth Measurement	11
3.2 Maximum Conducted Output Power Measurement	14
3.3 Power Spectral Density Measurement	16
3.4 Unwanted Emissions Measurement.....	19
3.5 Automatically Discontinue Transmission	24
3.6 Antenna Requirements.....	25
4 List of Measuring Equipment.....	26
5 Uncertainty of Evaluation	28
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i)	26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 1.17 dB at 5148.200 MHz
-	15.207	AC Conducted Emission	Not Required	-
3.5	15.407(c)	Automatically Discontinue Transmission	Pass	-
3.6	15.203 15.407(a)	Antenna Requirement	Pass	-

Note: Not required means after assessing, test items are not necessary to carry out.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Ruby Zou



1 General Description

1.1 Product Feature of Equipment Under Test

WCDMA/LTE/5G NR, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: Monopole Antenna WLAN: <Ant. 0>: Monopole Antenna <Ant. 1>: Monopole Antenna GPS/Galileo/Glonass/BDS: Monopole Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.



1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH05-HY
Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH15-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned two degrees (0° and 90°). The worst cases (Degree 0) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5150-5250 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42#	5210		

Note:

- 1. The above Frequency and Channel in "*" were 802.11n HT40, 802.11ac VHT40 and 802.11ax HE40
- 2. The above Frequency and Channel in "#n" were 802.11ac VHT80 and 802.11ax HE80.



2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


The CDD mode is chosen as worst case configuration for all test cases due to higher power than SISO mode.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by HE20)	MCS0
802.11n HT40 (Covered by HE40)	MCS0
802.11ac VHT20 (Covered by HE20)	MCS0
802.11ac VHT40 (Covered by HE40)	MCS0
802.11ac VHT80 (Covered by HE80)	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Ch. #		Band I : 5150-5250 MHz			
		802.11a	802.11ax HE20	802.11ax HE40	802.11ax HE80
L	Low	36	36	38	-
M	Middle	44	-	-	42
H	High	48	-	-	-

Remark: For radiation spurious emission, the final modulation and the worst data rate was reference the max RF conducted power.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Power Supply	GW Instek	GPE-2323	N/A	N/A	N/A
2.	Notebook	HP	15-cs3019nr	N/A	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility “QRCT V4.0.00172.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
8. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 26dB & 99% Occupied Bandwidth



Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<For 802.11ax Mode>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For the 5.15–5.25 GHz bands:

- For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For the 5.15–5.25 GHz bands:

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1.0 MHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

Method SA-3

(power averaging (rms) detection with max hold):


- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW \geq 3 MHz
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time \leq (number of points in sweep) \times T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
- Detector = power averaging (rms).
- Trace mode = max hold.
- Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.


The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points; the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



<For 802.11ax Mode>





3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu V/m, \text{ where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.
- (ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.5 Automatically Discontinue Transmission

3.5.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = 10 log(NANT/NSS=1) dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain GANT is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>

	Ant. 1 (dBi)	Ant. 2 (dBi)	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
Band I	2.80	2.80	2.80	5.81	0.00	0.00

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	Sep. 27, 2020~ Sep. 29, 2020	Jan. 08, 2021	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0800N1D01N- 06	41912&05	30MHz to 1GHz	Feb. 09, 2020	Sep. 27, 2020~ Sep. 29, 2020	Feb. 08, 2021	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 27, 2019	Sep. 27, 2020~ Sep. 29, 2020	Dec. 26, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-162 0	1-18GHz	Oct. 28, 2019	Sep. 27, 2020~ Sep. 29, 2020	Oct. 27, 2020	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 10, 2019	Sep. 27, 2020~ Sep. 29, 2020	Dec. 09, 2020	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055006	1GHz~18GHz	May 07, 2020	Sep. 27, 2020~ Sep. 29, 2020	May 06, 2021	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY532701 95	1GHz~26.5GHz	Aug. 21, 2020	Sep. 27, 2020~ Sep. 29, 2020	Aug. 20, 2021	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Sep. 27, 2020~ Sep. 29, 2020	Dec. 12, 2020	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	20MHz~8.4GHz	Nov. 01, 2019	Sep. 27, 2020~ Sep. 29, 2020	Oct. 31, 2020	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	May 04, 2020	Sep. 27, 2020~ Sep. 29, 2020	May 03, 2021	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Sep. 27, 2020~ Sep. 29, 2020	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Sep. 27, 2020~ Sep. 29, 2020	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k 5)	RK-00045 1	N/A	N/A	Sep. 27, 2020~ Sep. 29, 2020	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/ 4	30M-18G	Apr. 14, 2020	Sep. 27, 2020~ Sep. 29, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4 PE	30M-18G	Apr. 14, 2020	Sep. 27, 2020~ Sep. 29, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY37710/ 4	30M-18G	Apr. 17, 2020	Sep. 27, 2020~ Sep. 29, 2020	Apr. 16, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz-40GHz	Feb. 25, 2020	Sep. 27, 2020~ Sep. 29, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz-40GHz	Feb. 25, 2020	Sep. 27, 2020~ Sep. 29, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz~30MHz	Mar. 12, 2020	Sep. 27, 2020~ Sep. 29, 2020	Mar. 11, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN4	1.53G Low Pass	Jul. 03, 2020	Sep. 27, 2020~ Sep. 29, 2020	Jul. 02, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000 -40ST	SN6	6.75GHz High Pass Filter	Jul. 03, 2020	Sep. 27, 2020~ Sep. 29, 2020	Jul. 02, 2021	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Sep. 23, 2020~ Sep. 29, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 23, 2019	Sep. 23, 2020~ Sep. 29, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Dec. 30, 2019	Sep. 23, 2020~ Sep. 29, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Sep. 23, 2020~ Sep. 29, 2020	Mar. 16, 2021	Conducted (TH05-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	23.6~23.7	°C
Test Date:	2020/9/23~2020/9/29	Relative Humidity:	53.5~54.1	%

TEST RESULTS DATA
26dB and 99% OBW

Band I MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		Note
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	2	36	5180	16.45	16.45	21.05	21.15	-	-	22.16	-	
11a	6Mbps	2	44	5220	16.45	16.45	21.00	20.95	-	-	22.16	-	
11a	6Mbps	2	48	5240	16.45	16.40	21.05	21.10	-	-	22.15	-	

TEST RESULTS DATA
Average Power Table

FCC Band I single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	36	5180	13.70	13.50		24.00	24.00	2.80	2.80	Pass
11a	6Mbps	1	44	5220	13.70	13.80		24.00	24.00	2.80	2.80	Pass
11a	6Mbps	1	48	5240	13.60	13.40		24.00	24.00	2.80	2.80	Pass
HT20	MCS0	1	36	5180	13.70	13.70		24.00	24.00	2.80	2.80	Pass
HT20	MCS0	1	44	5220	13.60	13.70		24.00	24.00	2.80	2.80	Pass
HT20	MCS0	1	48	5240	13.40	13.50		24.00	24.00	2.80	2.80	Pass
HT40	MCS0	1	38	5190	13.50	13.50		24.00	24.00	2.80	2.80	Pass
HT40	MCS0	1	46	5230	13.30	13.60		24.00	24.00	2.80	2.80	Pass
VHT20	MCS0	1	36	5180	13.70	13.70		24.00	24.00	2.80	2.80	Pass
VHT20	MCS0	1	44	5220	13.60	13.70		24.00	24.00	2.80	2.80	Pass
VHT20	MCS0	1	48	5240	13.40	13.50		24.00	24.00	2.80	2.80	Pass
VHT40	MCS0	1	38	5190	13.50	13.50		24.00	24.00	2.80	2.80	Pass
VHT40	MCS0	1	46	5230	13.30	13.60		24.00	24.00	2.80	2.80	Pass
VHT80	MCS0	1	42	5210	12.70	13.10		24.00	24.00	2.80	2.80	Pass

FCC Band I MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	2	36	5180	13.80	13.60	16.71	24.00		2.80		Pass
11a	6Mbps	2	44	5220	13.80	13.90	16.86	24.00		2.80		Pass
11a	6Mbps	2	48	5240	13.70	13.50	16.61	24.00		2.80		Pass
HT20	MCS0	2	36	5180	13.80	13.80	16.81	24.00		2.80		Pass
HT20	MCS0	2	44	5220	13.70	13.80	16.76	24.00		2.80		Pass
HT20	MCS0	2	48	5240	13.50	13.60	16.56	24.00		2.80		Pass
HT40	MCS0	2	38	5190	13.70	13.60	16.66	24.00		2.80		Pass
HT40	MCS0	2	46	5230	13.40	13.70	16.56	24.00		2.80		Pass
VHT20	MCS0	2	36	5180	13.80	13.80	16.81	24.00		2.80		Pass
VHT20	MCS0	2	44	5220	13.70	13.80	16.76	24.00		2.80		Pass
VHT20	MCS0	2	48	5240	13.50	13.60	16.56	24.00		2.80		Pass
VHT40	MCS0	2	38	5190	13.70	13.60	16.66	24.00		2.80		Pass
VHT40	MCS0	2	46	5230	13.40	13.70	16.56	24.00		2.80		Pass
VHT80	MCS0	2	42	5210	12.90	13.30	16.11	24.00		2.80		Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	2	36	5180			6.76	11.00	5.81		Pass	
11a	6Mbps	2	44	5220			7.05	11.00	5.81		Pass	
11a	6Mbps	2	48	5240			6.67	11.00	5.81		Pass	

TEST RESULTS DATA
26dB and 99% OBW

Band I MIMO														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		Note
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	2	36	5180	Full	18.95	18.95	22.65	22.50	-	-	22.78	22.78	
HE20	MCS0	2	44	5220	Full	18.95	19.00	22.55	22.50	-	-	22.78	22.78	
HE20	MCS0	2	48	5240	Full	19.00	19.00	22.55	22.45	-	-	22.79	22.79	
HE40	MCS0	2	38	5190	Full	38.00	37.90	41.52	41.76	-	-	23.01	23.01	
HE40	MCS0	2	46	5230	Full	38.00	38.10	41.40	41.40	-	-	23.01	23.01	
HE80	MCS0	2	42	5210	Full	78.24	78.36	82.72	82.72	-	-	23.01	23.01	

TEST RESULTS DATA
Average Power Table

FCC Band I single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	1	36	5180	Full	13.80	13.80		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	36	5180	26/0	4.40	4.60		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	36	5180	52/37	7.40	7.80		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	36	5180	106/53	10.50	10.60		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	44	5220	Full	13.70	13.80		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	44	5220	26/4	5.70	5.80		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	44	5220	52/39	8.00	7.60		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	44	5220	106/53	10.70	10.30		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	48	5240	Full	13.50	13.60		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	48	5240	26/8	4.60	4.90		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	48	5240	52/40	6.90	7.90		24.00	24.00	2.80	2.80	Pass
HE20	MCS0	1	48	5240	106/54	10.10	10.50		24.00	24.00	2.80	2.80	Pass
HE40	MCS0	1	38	5190	Full	13.70	13.60		24.00	24.00	2.80	2.80	Pass
HE40	MCS0	1	38	5190	242/61	9.30	9.70		24.00	24.00	2.80	2.80	Pass
HE40	MCS0	1	46	5230	Full	13.40	13.70		24.00	24.00	2.80	2.80	Pass
HE40	MCS0	1	46	5230	242/62	10.90	11.10		24.00	24.00	2.80	2.80	Pass
HE80	MCS0	1	42	5210	Full	12.80	13.20		24.00	24.00	2.80	2.80	Pass
HE80	MCS0	1	42	5210	484/65	9.90	9.70		24.00	24.00	2.80	2.80	Pass

FCC Band I MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	2	36	5180	Full	13.90	13.90	16.91	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	36	5180	26/0	4.50	4.80	7.66	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	36	5180	52/37	7.50	7.90	10.71	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	36	5180	106/53	10.70	10.80	13.76	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	44	5220	Full	13.80	13.90	16.86	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	44	5220	26/4	5.80	5.90	8.86	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	44	5220	52/39	8.10	7.70	10.91	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	44	5220	106/53	10.80	10.40	13.61	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	48	5240	Full	13.60	13.70	16.66	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	48	5240	52/40	7.00	8.00	10.54	24.00	24.00	2.80	2.80	Pass
HE20	MCS0	2	48	5240	106/54	10.20	10.60	13.41	24.00	24.00	2.80	2.80	Pass
HE40	MCS0	2	38	5190	Full	13.80	13.70	16.76	24.00	24.00	2.80	2.80	Pass
HE40	MCS0	2	38	5190	242/61	9.40	10.00	12.72	24.00	24.00	2.80	2.80	Pass
HE40	MCS0	2	46	5230	Full	13.50	13.80	16.66	24.00	24.00	2.80	2.80	Pass
HE40	MCS0	2	46	5230	242/62	11.00	11.20	14.11	24.00	24.00	2.80	2.80	Pass
HE80	MCS0	2	42	5210	Full	12.90	13.40	16.17	24.00	24.00	2.80	2.80	Pass
HE80	MCS0	2	42	5210	484/65	10.00	9.80	12.91	24.00	24.00	2.80	2.80	Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	2	36	5180	Full			6.71	11.00	5.81		Pass	
HE20	MCS0	2	36	5180	26/0			6.55	11.00	5.81		Pass	
HE20	MCS0	2	36	5180	52/37			6.36	11.00	5.81		Pass	
HE20	MCS0	2	36	5180	106/53			6.35	11.00	5.81		Pass	
HE20	MCS0	2	44	5220	Full			7.09	11.00	5.81		Pass	
HE20	MCS0	2	44	5220	26/4			6.70	11.00	5.81		Pass	
HE20	MCS0	2	44	5220	52/39			6.62	11.00	5.81		Pass	
HE20	MCS0	2	44	5220	106/53			6.59	11.00	5.81		Pass	
HE20	MCS0	2	48	5240	Full			6.67	11.00	5.81		Pass	
HE20	MCS0	2	48	5240	26/8			6.56	11.00	5.81		Pass	
HE20	MCS0	2	48	5240	52/40			6.35	11.00	5.81		Pass	
HE20	MCS0	2	48	5240	106/54			6.30	11.00	5.81		Pass	
HE40	MCS0	2	38	5190	Full			3.81	11.00	5.81		Pass	
HE40	MCS0	2	38	5190	242/61			1.86	11.00	5.81		Pass	
HE40	MCS0	2	46	5230	Full			3.76	11.00	5.81		Pass	
HE40	MCS0	2	46	5230	242/62			3.69	11.00	5.81		Pass	
HE80	MCS0	2	42	5210	Full			0.10	11.00	5.81		Pass	
HE80	MCS0	2	42	5210	484/65			-1.02	11.00	5.81		Pass	



Appendix B. Radiated Spurious Emission

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.3~23.1°C
		Relative Humidity :	48~55%

Band 1 - 5150~5250MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11a CH 36 5180MHz		5150	54.58	-19.42	74	42	32.1	10.49	30.01	100	43	P	H	
		5150	43.74	-10.26	54	31.16	32.1	10.49	30.01	100	43	A	H	
	*	5180	113.71	-	-	101.26	31.92	10.54	30.01	100	43	P	H	
	*	5180	105.75	-	-	93.3	31.92	10.54	30.01	100	43	A	H	
													H	
			5053.56	53.43	-20.57	74	41.19	31.91	10.35	30.02	367	115	P	V
			5149.5	41.83	-12.17	54	29.25	32.1	10.49	30.01	367	115	A	V
	*		5180	107.43	-	-	94.98	31.92	10.54	30.01	367	115	P	V
	*		5180	99.48	-	-	87.03	31.92	10.54	30.01	367	115	A	V
														V
802.11a CH 44 5220MHz		5054.34	53.06	-20.94	74	40.82	31.91	10.35	30.02	100	43	P	H	
		5125.06	42.34	-11.66	54	29.84	32.05	10.46	30.01	100	43	A	H	
	*	5220	113.15	-	-	100.9	31.68	10.58	30.01	100	43	P	H	
	*	5220	105.32	-	-	93.07	31.68	10.58	30.01	100	43	A	H	
			5417.44	52.56	-21.44	74	40.17	31.7	10.68	29.99	100	43	P	H
			5409.04	41.88	-12.12	54	29.51	31.7	10.67	30	100	43	A	H
			5108.68	52.82	-21.18	74	40.38	32.02	10.43	30.01	243	264	P	V
			5103.48	41.55	-12.45	54	29.12	32.01	10.43	30.01	243	264	A	V
	*		5220	106.84	-	-	94.59	31.68	10.58	30.01	243	264	P	V
	*		5220	99.07	-	-	86.82	31.68	10.58	30.01	243	264	A	V
			5422.48	52.24	-21.76	74	39.84	31.7	10.69	29.99	243	264	P	V
			5397	41.45	-12.55	54	29.11	31.68	10.66	30	243	264	A	V



802.11a CH 48 5240MHz		5101.14	53.29	-20.71	74	40.88	32	10.42	30.01	100	41	P	H
		5150	42.4	-11.6	54	29.82	32.1	10.49	30.01	100	41	A	H
	*	5240	112.72	-	-	100.58	31.56	10.59	30.01	100	41	P	H
	*	5240	104.99	-	-	92.85	31.56	10.59	30.01	100	41	A	H
		5454.96	52.58	-21.42	74	40.11	31.73	10.73	29.99	100	41	P	H
		5428.64	41.93	-12.07	54	29.53	31.7	10.69	29.99	100	41	A	H
		5054.6	53	-21	74	40.76	31.91	10.35	30.02	238	265	P	V
		5106.6	41.6	-12.4	54	29.17	32.01	10.43	30.01	238	265	A	V
	*	5240	106.99	-	-	94.85	31.56	10.59	30.01	238	265	P	V
	*	5240	99.24	-	-	87.1	31.56	10.59	30.01	238	265	A	V
		5367.6	52.29	-21.71	74	40.13	31.51	10.65	30	238	265	P	V
		5459.72	41.43	-12.57	54	28.93	31.76	10.73	29.99	238	265	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		10360	48.42	-19.78	68.2	55.01	39.9	14.41	60.9	100	0	P	H
		15540	47.04	-26.96	74	54.47	38	17.28	62.71	100	0	P	H
													H
													H
		10360	48.03	-20.17	68.2	54.62	39.9	14.41	60.9	100	0	P	V
		15540	47.44	-26.56	74	54.87	38	17.28	62.71	100	0	P	V
													V
													V
802.11a CH 44 5220MHz		10440	48.67	-19.53	68.2	55.18	40.1	14.41	61.02	100	0	P	H
		15660	46.68	-27.32	74	53.89	37.58	17.34	62.13	100	0	P	H
													H
													H
		10440	48.08	-20.12	68.2	54.59	40.1	14.41	61.02	100	0	P	V
		15660	46.88	-27.12	74	54.09	37.58	17.34	62.13	100	0	P	V
													V
													V
802.11a CH 48 5240MHz		10480	47.83	-20.37	68.2	54.39	40.1	14.41	61.07	100	0	P	H
		15720	46.37	-27.63	74	53.38	37.46	17.37	61.84	100	0	P	H
													H
													H
		10480	47.7	-20.5	68.2	54.26	40.1	14.41	61.07	100	0	P	V
		15720	46.57	-27.43	74	53.58	37.46	17.37	61.84	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11ax HE20 Full (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 36 5180MHz		5149.76	55.09	-18.91	74	42.51	32.1	10.49	30.01	100	44	P	H	
		5150	44.9	-9.1	54	32.32	32.1	10.49	30.01	100	44	A	H	
	*	5180	114.13	-	-	101.68	31.92	10.54	30.01	100	44	P	H	
	*	5180	103.15	-	-	90.7	31.92	10.54	30.01	100	44	A	H	
													H	
														H
			5108.42	52.86	-21.14	74	40.42	32.02	10.43	30.01	201	261	P	V
			5150	42.14	-11.86	54	29.56	32.1	10.49	30.01	201	261	A	V
	*		5180	108.63	-	-	96.18	31.92	10.54	30.01	201	261	P	V
	*		5180	97.79	-	-	85.34	31.92	10.54	30.01	201	261	A	V
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



**Band 1 5150~5250MHz
WIFI 802.11ax HE20 Partial 106 (Band Edge @ 3m)**

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Partial 106/53 CH 36 5180MHz		5146.38	59.24	-14.76	74	46.67	32.09	10.49	30.01	100	42	P	H	
		5126.88	42.49	-11.51	54	29.99	32.05	10.46	30.01	100	42	A	H	
	*	5180	113.25	-	-	100.8	31.92	10.54	30.01	100	42	P	H	
	*	5180	103.18	-	-	90.73	31.92	10.54	30.01	100	42	A	H	
													H	
													H	
			5076.96	53.69	-20.31	74	41.37	31.95	10.39	30.02	233	267	P	V
			5130.26	42.03	-11.97	54	29.51	32.06	10.47	30.01	233	267	A	V
	*		5180	107.7	-	-	95.25	31.92	10.54	30.01	233	267	P	V
	*		5180	98.39	-	-	85.94	31.92	10.54	30.01	233	267	A	V
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 1 5150~5250MHz
WIFI 802.11ax HE40 Full (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Full CH 38 5190MHz		5148.72	65.83	-8.17	74	53.25	32.1	10.49	30.01	100	41	P	H
		5150	51.94	-2.06	54	39.36	32.1	10.49	30.01	100	41	A	H
	*	5190	111.37	-	-	98.97	31.86	10.55	30.01	100	41	P	H
	*	5190	100.44	-	-	88.04	31.86	10.55	30.01	100	41	A	H
		5370.12	52.72	-21.28	74	40.55	31.52	10.65	30	100	41	P	H
		5400.36	41.78	-12.22	54	29.42	31.7	10.66	30	100	41	A	H
		5150	59.46	-14.54	74	46.88	32.1	10.49	30.01	243	263	P	V
		5150	47	-7	54	34.42	32.1	10.49	30.01	243	263	A	V
	*	5190	106.09	-	-	93.69	31.86	10.55	30.01	243	263	P	V
	*	5190	95.68	-	-	83.28	31.86	10.55	30.01	243	263	A	V
	5435.64	52.34	-21.66	74	39.93	31.7	10.7	29.99	243	263	P	V	
	5399.52	41.38	-12.62	54	29.02	31.7	10.66	30	243	263	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11ax HE40 Partial 242 (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Partial 242/61 CH 38 5190MHz		5150	72.16	-1.84	74	59.58	32.1	10.49	30.01	100	44	P	H
		5149.76	50.46	-3.54	54	37.88	32.1	10.49	30.01	100	44	A	H
	*	5190	107.02	-	-	94.62	31.86	10.55	30.01	100	44	P	H
	*	5190	99.14	-	-	86.74	31.86	10.55	30.01	100	44	A	H
		5420.24	52.66	-21.34	74	40.27	31.7	10.68	29.99	100	44	P	H
		5430.88	42.04	-11.96	54	29.63	31.7	10.7	29.99	100	44	A	H
		5150	64.54	-9.46	74	51.96	32.1	10.49	30.01	243	262	P	V
		5149.76	43.75	-10.25	54	31.17	32.1	10.49	30.01	243	262	A	V
	*	5190	103.49	-	-	91.09	31.86	10.55	30.01	243	262	P	V
	*	5190	93.35	-	-	80.95	31.86	10.55	30.01	243	262	A	V
		5435.64	52.47	-21.53	74	40.06	31.7	10.7	29.99	243	262	P	V
		5459.16	41.75	-12.25	54	29.26	31.75	10.73	29.99	243	262	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11ax HE80 Full (Band Edge @ 3m)

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Full CH 42 5210MHz		5145.86	66.83	-7.17	74	54.26	32.09	10.49	30.01	100	44	P	H
		5148.2	52.49	-1.51	54	39.91	32.1	10.49	30.01	100	44	A	H
	*	5210	109.99	-	-	97.69	31.74	10.57	30.01	100	44	P	H
	*	5210	98.68	-	-	86.38	31.74	10.57	30.01	100	44	A	H
		5405.68	52.26	-21.74	74	39.89	31.7	10.67	30	100	44	P	H
		5404	41.79	-12.21	54	29.42	31.7	10.67	30	100	44	A	H
		5148.72	58.81	-15.19	74	46.23	32.1	10.49	30.01	242	264	P	V
		5149.5	46.32	-7.68	54	33.74	32.1	10.49	30.01	242	264	A	V
	*	5210	102.98	-	-	90.68	31.74	10.57	30.01	242	264	P	V
	*	5210	92.36	-	-	80.06	31.74	10.57	30.01	242	264	A	V
	5416.6	52.86	-21.14	74	40.48	31.7	10.68	30	242	264	P	V	
	5407.08	41.46	-12.54	54	29.09	31.7	10.67	30	242	264	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 1 5150~5250MHz
WIFI 802.11ax HE80 Partial 242 (Band Edge @ 3m)**

WIFI Ant. 0+1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE80 Partial 242/61 CH 42 5210MHz		5148.2	72.83	-1.17	74	60.25	32.1	10.49	30.01	100	43	P	H
		5148.98	51.4	-2.6	54	38.82	32.1	10.49	30.01	100	43	A	H
	*	5210	110.32	-	-	98.02	31.74	10.57	30.01	100	43	P	H
	*	5210	99.29	-	-	86.99	31.74	10.57	30.01	100	43	A	H
		5349.96	55.11	-94.89	150	43.07	31.4	10.64	30	100	43	P	H
		5406.52	42.13	-11.87	54	29.76	31.7	10.67	30	100	43	A	H
		5150.02	63.65	-86.35	150	51.07	32.1	10.49	30.01	257	263	P	V
		5150.02	43.17	-106.83	150	30.59	32.1	10.49	30.01	257	263	A	V
	*	5210	103.1	-	-	90.8	31.74	10.57	30.01	257	263	P	V
	*	5210	92.41	-	-	80.11	31.74	10.57	30.01	257	263	A	V
		5438.72	52.58	-21.42	74	40.16	31.7	10.71	29.99	257	263	P	V
		5455.8	41.82	-12.18	54	29.35	31.73	10.73	29.99	257	263	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11ax HE80 Partial 242 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
0+1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11ax HE80 Partial LF		30	20.38	-19.62	40	29.55	22.45	0.71	32.33	-	-	P	H	
		86.26	21.83	-18.17	40	38.56	14.41	1.26	32.4	-	-	P	H	
		187.14	33.46	-10.04	43.5	48.9	15	1.94	32.38	-	-	P	H	
		217.21	33.5	-12.5	46	48.82	14.97	2.1	32.39	-	-	P	H	
		729.37	32.42	-13.58	46	33.83	27.26	3.77	32.44	-	-	P	H	
		913.67	37	-9	46	35.56	28.83	4.35	31.74	100	0	P	H	
														H
														H
														H
														H
														H
														H
														H
			33.88	20.94	-19.06	40	31.11	21.42	0.74	32.33	-	-	P	V
			85.29	18.56	-21.44	40	35.44	14.28	1.26	32.42	-	-	P	V
			171.62	27.46	-16.04	43.5	42.29	15.74	1.83	32.4	-	-	P	V
			216.24	26.67	-19.33	46	42.05	14.92	2.09	32.39	-	-	P	V
			572.23	27.2	-18.8	46	30.57	25.77	3.31	32.45	-	-	P	V
			910.76	32.64	-13.36	46	31.38	28.71	4.34	31.79	100	0	P	V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.3~23.1°C
		Relative Humidity :	48~55%

Note symbol

-L	Low channel location
-R	High channel location






Band 1 - 5150~5250MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH36 5180MHz	
0+1	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(LINII) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH36 5180MHz	
0+1	Vertical	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank



WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH44 5220MHz - L	
0+1	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH44 5220MHz - R	
0+1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:0.010kHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>



WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH44 5220MHz - L	
0+1	Vertical	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH44 5220MHz - R	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL : RBW:1000.000KHz VBW:0.010KHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>



WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH48 5240MHz - L	
0+1	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH48 5240MHz - R	
0+1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:0.010kHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>






WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH48 5240MHz - L	
0+1	Vertical	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank






WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11a CH48 5240MHz - R	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:0.010kHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>



Band 1 5150~5250MHz
WIFI 802.11ax HE20 Full (Band Edge @ 3m)

WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH36 5180MHz	
0+1	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	Left blank






WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH36 5180MHz	
0+1	Vertical	Fundamental
Peak	 <p>Date: 2020-09-28</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	 <p>Date: 2020-09-28</p> <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	 <p>Date: 2020-09-28</p> <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank



Band 1 5150~5250MHz
WIFI 802.11ax HE20 Partial 106 (Band Edge @ 3m)




WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH36 5180MHz	
0+1	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH36 5180MHz	
0+1	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 9120D_15_1620 VERTICAL Detector : Peak Project : 090125</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 9120D_15_1620 VERTICAL Detector : Peak Project : 090125</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 9120D_15_1620 VERTICAL Detector : Peak Project : 090125</p>	Left blank






Band 1 5150~5250MHz
WIFI 802.11ax HE40 Full (Band Edge @ 3m)

WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH38 5190MHz - L	
0+1	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 090125</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:0.010kHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH38 5190MHz - R	
0+1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:0.010KHz SWF:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>






WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH38 5190MHz - L	
0+1	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH38 5190MHz - R	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125</p>	<p>Left blank</p>






Band 1 5150~5250MHz
WIFI 802.11ax HE40 Partial 242 (Band Edge @ 3m)

WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH38 5190MHz - L	
0+1	Horizontal	Fundamental
Peak	 <p>Level (dBu/m) vs Frequency (MHz) plot showing a peak at 5190 MHz. The y-axis ranges from 10.0 to 140.0 dBu/m, and the x-axis ranges from 5000 to 5260 MHz. A red vertical line marks the peak at 5190 MHz.</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125 Setting : 8.5</p>	 <p>Level (dBu/m) vs Frequency (MHz) plot showing a sharp peak at 5190 MHz. The y-axis ranges from 10.0 to 140.0 dBu/m, and the x-axis ranges from 1000 to 7000 MHz. A red vertical line marks the peak at 5190 MHz.</p> <p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125 Setting : 8.5</p>
Avg.	 <p>Level (dBu/m) vs Frequency (MHz) plot showing the average spectrum. The y-axis ranges from 10.0 to 140.0 dBu/m, and the x-axis ranges from 5000 to 5260 MHz. A red vertical line marks the peak at 5190 MHz.</p> <p>Site : 03CH15-HY Condition : AV6_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125 Setting : 8.5</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH38 5190MHz - R	
0+1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:0.300kHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>	<p>Left blank</p>






WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH38 5190MHz - L	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>	<p>Left blank</p>





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH38 5190MHz - R	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Project : 090125 Setting : 8.5</p>	<p>Left blank</p>



Band 1 5150~5250MHz
WIFI 802.11ax HE80 Full (Band Edge @ 3m)

WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH42 5210MHz - L	
0+1	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125 Setting : 12.5</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125 Setting : 12.5</p>
Avg.	 <p>Site : 03CH15-HY Condition : AV6_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125 Setting : 12.5</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH42 5210MHz - R	
0+1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125 Setting : 12.5</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:0.010kHz SWF:Auto Detector : Peak Project : 090125 Setting : 12.5</p>	<p>Left blank</p>






WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH42 5210MHz - L	
0+1	Vertical	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125 Setting : 12.5</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125 Setting : 12.5</p>
Avg.	<p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125 Setting : 12.5</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH42 5210MHz - R	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 9120d_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 090125 Setting : 12.5</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 9120d_15_1620 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 090125 Setting : 12.5</p>	<p>Left blank</p>






Band 1 5150~5250MHz
WIFI 802.11ax HE80 Partial 484 (Band Edge @ 3m)

WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH42 5210MHz - L	
0+1	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL : RBW1000.000kHz VBW3000.000kHz SWT:Auto Detector : Peak Project : 090125 Setting : 9</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL : RBW1000.000kHz VBW3000.000kHz SWT:Auto Detector : Peak Project : 090125 Setting : 9</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL : RBW1000.000kHz VBW0.300kHz SWT:Auto Detector : Peak Project : 090125 Setting : 9</p>	Left blank





WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH42 5210MHz - R	
0+1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 9120D_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125 Setting : 9</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 9120D_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125 Setting : 9</p>	<p>Left blank</p>



WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH42 5210MHz - L	
0+1	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 090125 Setting : 9.5</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 090125 Setting : 9.5</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 090125 Setting : 9.5</p>	Left blank



WIFI	Band 1 5150~5250MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH42 5210MHz - R	
0+1	Vertical	Fundamental
<p>Peak</p>	 <p>Date: 2020-09-28</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 9120D_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 090125 Setting : 9.5</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Date: 2020-09-28</p> <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 9120D_15_1620 VERTICAL RBW:1000.000kHz VBW:3.000kHz SWF:Auto Detector : Peak Project : 090125 Setting : 9.5</p>	<p>Left blank</p>





Band 1 - 5150~5250MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 1 5150~5250MHz Harmonic @ 3m	
ANT	802.11a CH36 5180MHz	
0+1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH15-FY Condition : PEAK(UNII) 3m 9120D_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	<p>Site : 03CH15-FY Condition : PEAK(UNII) 3m 9120D_15_1620 VERTICAL Detector : Peak Project : 090125</p>



WIFI	Band 1 5150~5250MHz Harmonic @ 3m	
ANT	802.11a CH44 5220MHz	
0+1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 090125</p>



WIFI	Band 1 5150~5250MHz Harmonic @ 3m	
ANT	802.11a CH48 5240MHz	
0+1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNID) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 090125</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNID) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 090125</p>



Emission below 1GHz
5GHz WIFI 802.11ax HE80 Partial 242 (LF)

WIFI	5GHz WIFI	
ANT	802.11ax HE80 Partial 242 LF	
0+1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH15-FY Condition : QP 3m BTL0G_15_41912 HORIZONTAL Detector : Peak Project : 090125</p>	<p>Site : 03CH15-FY Condition : QP 3m BTL0G_15_41912 VERTICAL Detector : Peak Project : 090125</p>







Appendix D. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
0+1	802.11a for Ant 0	98.76	-	-	10Hz	0.05
0+1	802.11a for Ant 1	99.00	-	-	10Hz	0.04
0+1	5GHz 802.11ax HE20 Full RU for Ant 0	98.64	-	-	10Hz	0.06
0+1	5GHz 802.11ax HE20 Full RU for Ant 1	98.73	-	-	10Hz	0.06
0+1	5GHz 802.11ax HE20 106 RU for Ant 0	96.42	4710	0.21	300Hz	0.16
0+1	5GHz 802.11ax HE20 106 RU for Ant 1	95.52	4690	0.21	300Hz	0.20
0+1	5GHz 802.11ax HE40 Full RU for Ant 0	98.19	-	-	10Hz	0.08
0+1	5GHz 802.11ax HE40 Full RU for Ant 1	98.36	-	-	10Hz	0.07
0+1	5GHz 802.11ax HE40 242 RU for Ant 0	93.64	4565	0.22	300Hz	0.29
0+1	5GHz 802.11ax HE40 242 RU for Ant 1	96.64	4605	0.22	300Hz	0.15
0+1	5GHz 802.11ax HE80 Full RU for Ant 0	98.90	-	-	10Hz	0.05
0+1	5GHz 802.11ax HE80 Full RU for Ant 1	98.73	-	-	10Hz	0.06
0+1	5GHz 802.11ax HE80 484 RU for Ant 0	97.99	4630	0.22	300Hz	0.09
0+1	5GHz 802.11ax HE80 484 RU for Ant 1	95.83	4595	0.22	300Hz	0.18





MIMO <Ant. 0>








MIMO <Ant. 1>






802.11ax HE40 242 RU




Date: 24.SEP.2020 11:23:53

802.11ax HE80 Full RU



Date: 24.SEP.2020 10:57:01

802.11ax HE80 484 RU



Date: 24.SEP.2020 11:31:57