



# FCC RADIO TEST REPORT

**FCC ID** : PKRISGFX31001  
**Equipment** : Indoor Router  
**Brand Name** : Inseego  
**Model Name** : FX3100-1  
**Marketing Name** : FX3100  
**Applicant** : Inseego Corp.  
9710 Scranton Road Suite 200, San Diego,, CA 92121  
**Manufacturer** : Inseego Corp.  
9710 Scranton Road Suite 200, San Diego,, CA 92121  
**Standard** : FCC 47 CFR Part 2, and 90(S)

The product was received on Mar. 03, 2023 and testing was performed from Mar. 06, 2023 to Apr. 01, 2023. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

**Sporton International Inc. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Site.....	5
1.4 Applied Standards .....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System .....	8
2.3 Support Unit used in test configuration and system.....	8
2.4 Frequency List of Low/Middle/High Channels.....	9
<b>3 Conducted Test Items.....</b>	<b>10</b>
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power Measurement and ERP Measurement .....	11
3.3 Field Strength of Spurious Radiation Measurement .....	12
<b>4 List of Measuring Equipment.....</b>	<b>15</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>16</b>
<b>Appendix A. Test Results of Conducted Test</b>	
<b>Appendix B. Test Results of Radiated Test</b>	
<b>Appendix C. Test Setup Photographs</b>	





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046 §90.635	Conducted Output Power and Effective Radiated Power	Pass	-
-	-	Peak-to-Average Ratio	-	See Note
-	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	-	See Note
-	§2.1051 §90.691	Emission masks – In-band emissions	-	See Note
-	§2.1051 §90.691	Emission masks – Out of band emissions	-	See Note
-	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	-	See Note
3.3	§2.1053 §90.691	Field Strength of Spurious Radiation	Pass	28.48 dB under the limit at 2448.000 MHz

**Note:** The RF circuit and output power level are the same in WWAN function across all two FCC ID PKRISGM3000B and PKRISGFX31001, since the change, only verify RF output power and radiated spurious emission test data the worst mode was reported in this report.

<p><b>Conformity Assessment Condition:</b></p> <ol style="list-style-type: none"> <li>The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.</li> <li>Please refer to the section “Uncertainty of Evaluation” for measurement uncertainty.</li> </ol> <p><b>Disclaimer:</b></p> <p>The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.</p>
--

**Reviewed by: Lewis Ho**  
**Report Producer: Michelle Chen**

# 1 General Description

## 1.1 Feature of Equipment Under Test

Product Feature	
<b>General Specs</b> 4G-LTE, 5G-FR1, Wi-Fi 2.4GHz 802.11 b/g/n/ax, Wi-Fi 5GHz 802.11 a/n/ac/ax, and GNSS.	
<b>Antenna Type</b> WWAN: Fixed Internal Antenna WLAN: Fixed Internal Antenna GPS / Glonass / BDS / Galileo: Fixed Internal Antenna	
<b>Antenna Gain</b>	LTE Band 26: 0.8 dBi

**Remark:** The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

## 1.2 Modification of EUT

No modifications made to the EUT during the testing.

## 1.3 Testing Site

<b>Test Site</b>	Sporton International Inc. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH03-HY	03CH07-HY
<b>Test Engineer</b>	Cotty Hsu	Jesse Wang, Stan Hsieh and Ken Wu
<b>Temperature (°C)</b>	22.2~23.1	21.0~25.6
<b>Relative Humidity (%)</b>	51.0~56.0	54.7~66.2

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190



## 1.4 Applied Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 90
- ♦ ANSI / TIA-603-E
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

**Remark:**

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and only the worst case emissions were reported in this report..

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel			
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H	
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v
E.R.P.	26	v	v	v	v	v	-	v	v	v	v	Max. Power						
Radiated Spurious Emission	26			v			-	v				v				v	v	v
Remark	<ol style="list-style-type: none"> <li>The mark "v " means that this configuration is chosen for testing</li> <li>The mark "- " means that this bandwidth is not supported.</li> <li>LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies.</li> </ol>																	

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m





### 2.4 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	-	cross-rule channels	-
15	Channel	-	26790	-
	Frequency	-	824	-
10	Channel	-	26790	-
	Frequency	-	824	-
5	Channel	-	26790	-
	Frequency	-	824	-
3	Channel	-	26790	-
	Frequency	-	824	-
1.4	Channel	-	26790	-
	Frequency	-	824	-


### 3 Conducted Test Items

#### 3.1 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.1 Test Setup

##### 3.1.2 Conducted Output Power



##### 3.1.3 Test Result of Conducted Test

Please refer to Appendix A.



## 3.2 Conducted Output Power Measurement and ERP Measurement

### 3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The output power of mobile transmitters must not exceed 100 Watts for LTE Band 26.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

### 3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



### 3.3 Field Strength of Spurious Radiation Measurement

#### 3.3.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43+10\log_{10}(P[\text{Watts}])$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 3.3.2 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
1. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
2. The table was rotated 360 degrees to determine the position of the highest spurious emission.
3. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
4. For testing below 1GHz, make the measurement with the spectrum analyzer's RBW = 100 kHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
5. For testing above 1GHz, make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11.  $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)

### 3.3.3 Test Setup


For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



### 3.3.4 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

**Note:**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Radio Communication Analyzer	Anritsu	MT8821C	6262025353	LTE FDD/TDD LTE-2CC DLCA/ULCA	Oct. 13, 2022	Mar. 06, 2023~ Mar. 22, 2023	Oct. 12, 2023	Conducted (TH03-HY)
Thermal Chamber	ESPEC	SH-641	92013720	-40°C ~90°C	Sep. 07, 2022	Mar. 06, 2023~ Mar. 22, 2023	Sep. 06, 2023	Conducted (TH03-HY)
DC Power Supply	GW Instek	GPP-2323	GES906037	0V~64V ; 0A~6A	Dec. 29, 2022	Mar. 06, 2023~ Mar. 22, 2023	Dec. 28, 2023	Conducted (TH03-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#B	1-18GHz	Jan. 06, 2023	Mar. 06, 2023~ Mar. 22, 2023	Jan. 05, 2024	Conducted (TH03-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	35419 & 03	30MHz~1GHz	Apr. 24, 2022	Mar. 24, 2023~ Apr. 01, 2023	Apr. 23, 2023	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 01, 2022	Mar. 24, 2023~ Apr. 01, 2023	Nov. 30, 2023	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	Mar. 24, 2023~ Apr. 01, 2023	Sep. 19, 2023	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590075	1GHz~18GHz	Apr. 21, 2022	Mar. 24, 2023~ Apr. 01, 2023	Apr. 20, 2023	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 03, 2022	Mar. 24, 2023~ Apr. 01, 2023	Oct. 02, 2023	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Mar. 24, 2023	Mar. 24, 2023~ Apr. 01, 2023	Mar. 23, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15682/4	30MHz to 18GHz	Feb. 22, 2023	Mar. 24, 2023~ Apr. 01, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4	9kHz to 18GHz	Feb. 22, 2023	Mar. 24, 2023~ Apr. 01, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4	9kHz to 18GHz	Feb. 22, 2023	Mar. 24, 2023~ Apr. 01, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126	532078/126E	30MHz~18GHz	Sep. 16, 2022	Mar. 24, 2023~ Apr. 01, 2023	Sep. 15, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 22, 2023	Mar. 24, 2023~ Apr. 01, 2023	Feb. 21, 2024	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 14, 2022	Mar. 24, 2023~ Apr. 01, 2023	Apr. 13, 2023	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Mar. 24, 2023~ Apr. 01, 2023	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Mar. 24, 2023~ Apr. 01, 2023	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Mar. 24, 2023~ Apr. 01, 2023	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Mar. 24, 2023~ Apr. 01, 2023	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Mar. 24, 2023~ Apr. 01, 2023	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Mar. 14, 2023	Mar. 24, 2023~ Apr. 01, 2023	Mar. 13, 2024	Radiation (03CH07-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241058	10Hz~44GHz	Jul. 07, 2022	Mar. 29, 2023~ Mar. 30, 2023	Jul. 06, 2023	Radiation (03CH07-HY)
Double Ridge Horn Antenna	EMCO	3117	00227856	1 - 18 GHz	Sep. 27, 2022	Mar. 24, 2023~ Apr. 01, 2023	Sep. 26, 2023	Radiation (03CH07-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	Jan. 11, 2023	Mar. 24, 2023~ Apr. 01, 2023	Jan. 10, 2024	Radiation (03CH07-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.25 dB
---	---------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.50 dB
---	---------





## Appendix A. Test Results of Conducted Test

### Conducted Output Power (Average power) & ERP)

LTE Band 26 Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
15	1	0	QPSK	24.28	-	-	22.93	0.1963
15	1	37		24.06	-	-		
15	1	74		24.01	-	-		
15	36	0		23.12	-	-		
15	36	20		23.17	-	-		
15	36	39		23.16	-	-		
15	75	0		23.16	-	-		
15	1	0	16-QAM	23.35	-	-	22.03	0.1596
15	1	37		23.38	-	-		
15	1	74		23.26	-	-		
15	36	0		22.13	-	-		
15	36	20		22.19	-	-		
15	36	39		22.18	-	-		
15	75	0		22.19	-	-		
15	1	0	64-QAM	22.24	-	-	20.93	0.1239
15	1	37		22.28	-	-		
15	1	74		22.19	-	-		
15	36	0		21.13	-	-		
15	36	20		21.19	-	-		
15	36	39		21.15	-	-		
15	75	0		21.17	-	-		
15	1	0	256-QAM	19.23	-	-	17.88	0.0614
15	1	37		19.20	-	-		
15	1	74		19.21	-	-		
15	36	0		19.14	-	-		
15	36	20		19.03	-	-		
15	36	39		19.13	-	-		
15	75	0		19.15	-	-		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK	-	23.92	-	22.66	0.1845
10	1	25		-	24.01	-		
10	1	49		-	23.88	-		
10	25	0		-	23.02	-		
10	25	12		-	23.04	-		
10	25	25		-	23.04	-		
10	50	0		-	23.02	-		
10	1	0	16-QAM	-	23.29	-	21.94	0.1563
10	1	25		-	23.29	-		
10	1	49		-	23.16	-		
10	25	0		-	22.07	-		
10	25	12		-	22.09	-		
10	25	25		-	22.13	-		
10	50	0		-	22.05	-		
10	1	0	64-QAM	-	22.16	-	20.95	0.1245
10	1	25		-	22.30	-		
10	1	49		-	22.15	-		
10	25	0		-	21.02	-		
10	25	12		-	21.03	-		
10	25	25		-	21.04	-		
10	50	0		-	21.05	-		
10	1	0	256-QAM	-	19.21	-	17.86	0.0611
10	1	25		-	19.19	-		
10	1	49		-	19.17	-		
10	25	0		-	19.18	-		
10	25	12		-	19.00	-		
10	25	25		-	19.08	-		
10	50	0		-	19.08	-		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	23.93	23.92	23.92	22.67	0.1849
5	1	12		23.97	23.87	23.94		
5	1	24		23.95	24.00	24.02		
5	12	0		23.07	22.97	23.14		
5	12	7		23.10	23.12	23.09		
5	12	13		23.11	23.09	23.14		
5	25	0		23.09	23.07	23.06		
5	1	0	16-QAM	23.32	23.25	23.35	22.00	0.1585
5	1	12		23.30	23.34	23.23		
5	1	24		23.23	23.33	23.26		
5	12	0		22.08	22.10	22.01		
5	12	7		22.12	22.13	22.17		
5	12	13		22.13	22.10	22.16		
5	25	0		22.18	22.18	22.16		
5	1	0	64-QAM	22.16	22.18	22.09	20.92	0.1236
5	1	12		22.21	22.11	22.27		
5	1	24		22.15	22.06	22.25		
5	12	0		21.03	20.97	20.97		
5	12	7		21.18	21.25	21.25		
5	12	13		21.11	21.13	21.13		
5	25	0		21.09	21.02	21.10		
5	1	0	256-QAM	19.22	19.19	19.20	17.87	0.0612
5	1	12		19.11	19.20	19.13		
5	1	24		19.14	19.05	19.14		
5	12	0		19.04	19.02	19.13		
5	12	7		18.96	18.88	18.98		
5	12	13		19.12	19.02	19.22		
5	25	0		19.08	19.05	19.12		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
3	1	0	QPSK	24.00	24.01	23.95	22.73	0.1875
3	1	8		24.03	24.08	24.04		
3	1	14		23.95	23.92	24.01		
3	8	0		23.02	23.04	23.05		
3	8	4		23.17	23.23	23.15		
3	8	7		23.13	23.12	23.03		
3	15	0		23.06	23.16	23.12		
3	1	0	16-QAM	23.34	23.39	23.33	22.09	0.1618
3	1	8		23.38	23.44	23.34		
3	1	14		23.22	23.23	23.24		
3	8	0		22.08	22.14	22.12		
3	8	4		22.15	22.14	22.05		
3	8	7		22.11	22.04	22.04		
3	15	0		22.12	22.09	22.14		
3	1	0	64-QAM	22.21	22.15	22.18	20.94	0.1242
3	1	8		22.21	22.15	22.29		
3	1	14		22.12	22.19	22.03		
3	8	0		21.11	21.09	21.01		
3	8	4		21.18	21.23	21.19		
3	8	7		21.07	21.08	21.08		
3	15	0		21.14	21.17	21.19		
3	1	0	256-QAM	19.13	19.20	19.18	17.88	0.0614
3	1	8		19.15	19.11	19.08		
3	1	14		19.16	19.08	19.23		
3	8	0		19.11	19.12	19.17		
3	8	4		19.03	18.99	19.04		
3	8	7		19.10	19.01	19.11		
3	15	0		19.12	19.08	19.13		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
1.4	1	0	QPSK	24.23	24.23	24.32	23.00	0.1995
1.4	1	3		24.26	24.31	24.32		
1.4	1	5		24.23	24.29	24.14		
1.4	3	0		24.27	24.34	24.27		
1.4	3	1		24.26	24.33	24.33		
1.4	3	3		24.26	24.21	24.35		
1.4	6	0		23.27	23.31	23.19		
1.4	1	0	16-QAM	23.44	23.45	23.41	22.18	0.1652
1.4	1	3		23.43	23.53	23.48		
1.4	1	5		23.41	23.36	23.42		
1.4	3	0		23.38	23.47	23.40		
1.4	3	1		23.41	23.42	23.47		
1.4	3	3		23.40	23.33	23.50		
1.4	6	0		22.31	22.29	22.40		
1.4	1	0	64-QAM	22.43	22.36	22.48	21.14	0.1300
1.4	1	3		22.43	22.42	22.44		
1.4	1	5		22.44	22.48	22.43		
1.4	3	0		22.39	22.49	22.48		
1.4	3	1		22.40	22.31	22.33		
1.4	3	3		22.38	22.30	22.36		
1.4	6	0		21.33	21.30	21.31		
1.4	1	0	256-QAM	19.36	19.44	19.38	18.14	0.0652
1.4	1	3		19.41	19.46	19.35		
1.4	1	5		19.35	19.36	19.41		
1.4	3	0		19.33	19.35	19.37		
1.4	3	1		19.39	19.38	19.49		
1.4	3	3		19.30	19.28	19.33		
1.4	6	0		19.36	19.37	19.29		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
15	1	0	QPSK	-	24.00	-	22.73	0.1875
15	1	37		-	24.08	-		
15	1	74		-	24.00	-		
15	36	0		-	23.12	-		
15	36	20		-	23.20	-		
15	36	39		-	23.20	-		
15	75	0		-	23.20	-		
15	1	0	16-QAM	-	23.34	-	22.10	0.1622
15	1	37		-	23.45	-		
15	1	74		-	23.33	-		
15	36	0		-	22.17	-		
15	36	20		-	22.21	-		
15	36	39		-	22.21	-		
15	75	0		-	22.21	-		
15	1	0	64-QAM	-	22.27	-	20.96	0.1247
15	1	37		-	22.31	-		
15	1	74		-	22.29	-		
15	36	0		-	21.17	-		
15	36	20		-	21.22	-		
15	36	39		-	21.21	-		
15	75	0		-	21.20	-		
15	1	0	256-QAM	-	19.20	-	18.01	0.0632
15	1	37		-	19.36	-		
15	1	74		-	19.35	-		
15	36	0		-	19.24	-		
15	36	20		-	19.35	-		
15	36	39		-	19.26	-		
15	75	0		-	19.31	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK	-	24.29	-	22.94	0.1968
10	1	25		-	24.28	-		
10	1	49		-	24.18	-		
10	25	0		-	23.28	-		
10	25	12		-	23.37	-		
10	25	25		-	23.32	-		
10	50	0		-	23.31	-		
10	1	0	16-QAM	-	23.40	-	22.05	0.1603
10	1	25		-	23.35	-		
10	1	49		-	23.37	-		
10	25	0		-	22.28	-		
10	25	12		-	22.38	-		
10	25	25		-	22.33	-		
10	50	0		-	22.34	-		
10	1	0	64-QAM	-	22.50	-	21.15	0.1303
10	1	25		-	22.41	-		
10	1	49		-	22.45	-		
10	25	0		-	21.28	-		
10	25	12		-	21.37	-		
10	25	25		-	21.34	-		
10	50	0		-	21.34	-		
10	1	0	256-QAM	-	19.41	-	18.12	0.0649
10	1	25		-	19.47	-		
10	1	49		-	19.37	-		
10	25	0		-	19.32	-		
10	25	12		-	19.39	-		
10	25	25		-	19.36	-		
10	50	0		-	19.35	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	-	24.26	-	22.98	0.1986
5	1	12		-	24.33	-		
5	1	24		-	24.23	-		
5	12	0		-	23.26	-		
5	12	7		-	23.36	-		
5	12	13		-	23.31	-		
5	25	0		-	23.31	-		
5	1	0	16-QAM	-	23.47	-	22.15	0.1641
5	1	12		-	23.50	-		
5	1	24		-	23.43	-		
5	12	0		-	22.29	-		
5	12	7		-	22.40	-		
5	12	13		-	22.36	-		
5	25	0		-	22.34	-		
5	1	0	64-QAM	-	22.42	-	21.12	0.1294
5	1	12		-	22.47	-		
5	1	24		-	22.43	-		
5	12	0		-	21.28	-		
5	12	7		-	21.37	-		
5	12	13		-	21.33	-		
5	25	0		-	21.34	-		
5	1	0	256-QAM	-	19.39	-	18.12	0.0649
5	1	12		-	19.47	-		
5	1	24		-	19.36	-		
5	12	0		-	19.27	-		
5	12	7		-	19.39	-		
5	12	13		-	19.35	-		
5	25	0		-	19.33	-		
Limit	Reporting only			Result			N/A	





LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
3	1	0	QPSK	-	24.10	-	22.85	0.1928
3	1	8		-	24.20	-		
3	1	14		-	24.12	-		
3	8	0		-	23.15	-		
3	8	4		-	23.24	-		
3	8	7		-	23.22	-		
3	15	0		-	23.19	-		
3	1	0	16-QAM	-	23.48	-	22.14	0.1637
3	1	8		-	23.43	-		
3	1	14		-	23.49	-		
3	8	0		-	22.25	-		
3	8	4		-	22.34	-		
3	8	7		-	22.32	-		
3	15	0		-	22.24	-		
3	1	0	64-QAM	-	22.38	-	21.06	0.1276
3	1	8		-	22.41	-		
3	1	14		-	22.37	-		
3	8	0		-	21.20	-		
3	8	4		-	21.32	-		
3	8	7		-	21.27	-		
3	15	0		-	21.25	-		
3	1	0	256-QAM	-	19.32	-	18.07	0.0641
3	1	8		-	19.42	-		
3	1	14		-	19.39	-		
3	8	0		-	19.25	-		
3	8	4		-	19.41	-		
3	8	7		-	19.36	-		
3	15	0		-	19.35	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = 0.8 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
1.4	1	0	QPSK	-	24.07	-	22.85	0.1928
1.4	1	3		-	24.20	-		
1.4	1	5		-	24.17	-		
1.4	3	0		-	24.20	-		
1.4	3	1		-	24.20	-		
1.4	3	3		-	24.19	-		
1.4	6	0		-	23.18	-		
1.4	1	0	16-QAM	-	23.39	-	22.13	0.1633
1.4	1	3		-	23.43	-		
1.4	1	5		-	23.48	-		
1.4	3	0		-	23.31	-		
1.4	3	1		-	23.32	-		
1.4	3	3		-	23.34	-		
1.4	6	0		-	22.25	-		
1.4	1	0	64-QAM	-	22.29	-	21.01	0.1262
1.4	1	3		-	22.36	-		
1.4	1	5		-	22.36	-		
1.4	3	0		-	22.33	-		
1.4	3	1		-	22.31	-		
1.4	3	3		-	22.29	-		
1.4	6	0		-	21.25	-		
1.4	1	0	256-QAM	-	19.30	-	18.06	0.0640
1.4	1	3		-	19.41	-		
1.4	1	5		-	19.28	-		
1.4	3	0		-	19.33	-		
1.4	3	1		-	19.37	-		
1.4	3	3		-	19.34	-		
1.4	6	0		-	19.32	-		
Limit	Reporting only			Result			N/A	



## Appendix B. Test Results of Radiated Test

### LTE Band 26

LTE Band 26 / 5MHz / QPSK										
Channel	Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Margin ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	
Lowest	1628	-50.98	-13	-37.98	-62.47	-52.8	0.97	4.94	H	
	2440	-41.70	-13	-28.70	-58.94	-43.5	1.27	5.22	H	
	3256	-57.25	-13	-44.25	-76.63	-60.5	1.53	6.93	H	
	4072	-55.24	-13	-42.24	-76.97	-59.9	1.80	8.61	H	
										H
										H
										H
	1628	-50.58	-13	-37.58	-62.47	-52.4	0.97	4.94	V	
	2440	-44.50	-13	-31.50	-62.11	-46.3	1.27	5.22	V	
	3256	-57.55	-13	-44.55	-77.17	-60.8	1.53	6.93	V	
	4072	-53.44	-13	-40.44	-75.04	-58.1	1.80	8.61	V	
										V
										V
										V
Middle	1632	-50.69	-13	-37.69	-62.26	-52.5	0.97	4.93	H	
	2448	-41.48	-13	-28.48	-58.86	-43.3	1.27	5.24	H	
	3266	-57.91	-13	-44.91	-77.44	-61.2	1.53	6.97	H	
	4088	-57.44	-13	-44.44	-79.06	-62.1	1.81	8.62	H	
										H
										H
										H
										V
	1632	-52.29	-13	-39.29	-64.19	-54.1	0.97	4.93	V	
	2448	-46.88	-13	-33.88	-64.74	-48.7	1.27	5.24	V	
	3266	-57.41	-13	-44.41	-77.18	-60.7	1.53	6.97	V	
	4088	-56.54	-13	-43.54	-78.39	-61.2	1.81	8.62	V	
										V
										V



LTE Band 26 / 5MHz / QPSK									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Margin ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	1640	-50.42	-13	-37.42	-62	-52.2	0.97	4.91	H
	2456	-46.66	-13	-33.66	-63.66	-48.5	1.28	5.27	H
	3276	-58.17	-13	-45.17	-77.57	-61.5	1.53	7.01	H
									H
									H
									H
									H
	1640	-50.12	-13	-37.12	-62.12	-51.9	0.97	4.91	V
	2456	-47.26	-13	-34.26	-64.93	-49.1	1.28	5.27	V
	3276	-57.47	-13	-44.47	-77.43	-60.8	1.53	7.01	V
									V
									V
									V
									V


Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

## Appendix C. Setup Photographs

<Radiated Emission>

Y Plane

LF



HF



————THE END————