



FCC RADIO TEST REPORT

FCC ID : PKRISGM2100
Equipment : Wireless Hotspot Modem
Brand Name : Inseego
Model Name : M2100
Marketing Name : M2100
Applicant : Inseego Corporation
9710 Scranton Road Suite 200, San Diego,
CA 92121
Manufacturer : Inseego Corporation
9710 Scranton Road Suite 200, San Diego,
CA 92121
Standard : FCC 47 CFR Part 2, 22(H), 24(E), 27

The product was received on May 15, 2020 and testing was started from Jul. 02, 2020 and completed on Jul. 21, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System.....	8
2.3 Measurement Results Explanation Example.....	8
2.4 Frequency List of Low/Middle/High Channels	9
3 Conducted Test Items.....	10
3.1 Measuring Instruments	10
3.2 Conducted Output Power and ERP/EIRP	11
3.3 Peak-to-Average Ratio	12
3.4 Occupied Bandwidth.....	13
3.5 Conducted Band Edge	14
3.6 Conducted Spurious Emission	15
3.7 Frequency Stability	16
4 Radiated Test Items	17
4.1 Measuring Instruments	17
4.2 Radiated Spurious Emission Measurement	19
5 List of Measuring Equipment.....	20
6 Uncertainty of Evaluation.....	22
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of ERP/EIRP and Radiated Test	
Appendix C. Test Setup Photographs	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
	§22.913 (a)(2)	Effective Radiated Power (n5)	Pass	
	§24.232 (c)	Equivalent Isotropic Radiated Power (n2)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (n66)		
3.3	§24.232 (d) §27.50 (d)(5)	Peak-to-Average Ratio	Pass	-
3.4	§2.1049	Occupied Bandwidth	Reporting only	-
3.5	§2.1051 §22.917 (a) §24.238 (a) §27.53 (h)	Conducted Band Edge Measurement (n2) (n5) (n66)	Pass	-
3.6	§2.1051 §22.917 (a) §24.238 (a) §27.53 (h)	Conducted Spurious Emission (n2) (n5) (n66)	Pass	-
3.7	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	Pass	-
4.2	§2.1053 §22.917 (a) §24.238 (a) §27.53 (h)	Radiated Spurious Emission (n2) (n5) (n66)	Pass	Under limit 6.88 dB at 3742.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Vivian Hsu



1 General Description

1.1 Product Feature of Equipment Under Test

WCDMA/LTE/5G NR, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: Fixed Internal Antenna WLAN: <Ant. 1>: Fixed Internal Antenna <Ant. 2>: Fixed Internal Antenna GPS: Fixed Internal Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH05-HY
Test Engineer	Steve Chen and Thomas Chen
Temperature	25~26°C
Relative Humidity	45~50%

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature	24.3~26.4°C
Relative Humidity	58~66%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 22(H), 24(E), 27
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y Plane for EN-DC 13A_n2A / EN-DC 66A_n2A / EN-DC 2A_n5A / EN-DC 2A_n66A / EN-DC 5A_n66A / EN-DC 13A_n66A / EN-DC 48A_n66A and Z Plane for EN-DC 5A_n2A / EN-DC 48A_n5A / EN-DC 66A_n5A) were recorded in this report.

Test Items	NR Band	Bandwidth (MHz)					Modulation					RB #		Test Channel			
		5	10	15	20	40	50	PI/2 BPSK	QPSK	16QAM	64QAM	256QAM	1	Full	L	M	H
Peak-to-Average Ratio	n2				v	-	-	v	v	v	v	v	v	v	v	v	v
	n5				v	-	-	v	v	v	v	v	v	v	v	v	v
	n66				v	-	-	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	n2	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
Conducted Band Edge	n2	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
Conducted Spurious Emission	n2	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
Frequency Stability	n2				v	-	-		v							v	
	n5				v	-	-		v				v			v	
	n66				v	-	-		v				v			v	
E.R.P / E.I.R.P	n2	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	n2	Worst Case												v	v	v	
	n5	Worst Case												v	v	v	
	n66	Worst Case												v	v	v	
Remark	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. Test combination is EN-DC 5A-n2A, EN-DC 13A-n2A, EN-DC 66A-n2A, EN-DC 2A-n5A, EN-DC 48A-n5A, EN-DC 66A-n5A, EN-DC 2A-n66A, EN-DC 5A-n66A, EN-DC 13A-n66A, EN-DC 48A-n66A. For radiated measurement, pre-scanned in two modes, DFT-s OFDM and CP OFDM. The worst cases (DFT-s OFDM) were recorded in this report, and the worst modes of FR1 and LTE for simultaneous transmission were verified and compliant. The NR radio operation is controlled via software tool QRCT FTM mode (SW: Version 4.0.00156.0) under 100% duty cycle transmission, expect that the frequency stability is tested by system simulator. The reported ERP/EIRP are the worst power across different bandwidths, modulations, resource blocks. 																

2.2 Connection Diagram of Test System



2.3 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$



2.4 Frequency List of Low/Middle/High Channels

5G NR Band n2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	372000	376000	380000
	Frequency	1860	1880	1900
15	Channel	371500	376000	380500
	Frequency	1857.5	1880	1902.5
10	Channel	371000	376000	381000
	Frequency	1855	1880	1905
5	Channel	370500	376000	381500
	Frequency	1852.5	1880	1907.5

5G NR Band n5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	166800	167300	167800
	Frequency	834	836.5	839
15	Channel	166300	167300	168300
	Frequency	831.5	836.5	841.5
10	Channel	165800	167300	168800
	Frequency	829	836.5	844
5	Channel	165300	167300	169300
	Frequency	826.5	836.5	846.5

5G NR Band n66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	344000	349000	354000
	Frequency	1720	1745	1770
15	Channel	343500	349000	354500
	Frequency	1717.5	1745	1772.5
10	Channel	343000	349000	355000
	Frequency	1715	1745	1775
5	Channel	342500	349000	355500
	Frequency	1712.5	1745	1777.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power Measurement and ERP/EIRP

Measurement

The EUT is set to be transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for 5G NR n5

The EIRP of mobile transmitters must not exceed 2 Watts for 5G NR n2

The EIRP of mobile transmitters must not exceed 1 Watts for 5G NR n66

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

The test follows the ANSI C63.26, clause 5.2.4.2

1. The transmitter output port was connected to the power meter.
2. Set EUT at maximum power
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level
5. Follows the EIRP/ERP formula and gets the results.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum analyzer and set at maximum power.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.



3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB BW) and Section 5.4.4 (99%OB BW)

1. The EUT was connected to spectrum analyzer and and set at maximum power.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, 1755-1780 MHz, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and set at maximum power.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.

The limit line is derived from $43 + 10\log(P)\text{dB}$ below the transmitter power $P(\text{Watts})$



3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and set at maximum power.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

22.355

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

24.235 & 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.1.1 Test Setup


For radiated emissions below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.2 Radiated Spurious Emission Measurement

4.2.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz~30GHz	Jan. 10, 2020	Jul. 02, 2020~ Jul. 21, 2020	Jan. 09, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SN O11	10MHz~6GHz	Dec. 30, 2019	Jul. 02, 2020~ Jul. 21, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40°C~90°C	Sep. 02, 2019	Jul. 02, 2020~ Jul. 21, 2020	Sep. 01, 2020	Conducted (TH05-HY)
DC Power Supply	Agilent	E3610A	MY40010395	0-15V, 2A 0-8V, 3A	Aug. 22, 2019	Jul. 02, 2020~ Jul. 21, 2020	Aug. 21, 2020	Conducted (TH05-HY)
Switch Control Manframe	E-IUSTRUMENT	ETF-1405-0	EC1900067	N/A	Aug. 15, 2019	Jul. 02, 2020~ Jul. 21, 2020	Aug. 14, 2020	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	GPP-2323	GES906037	0V~64V ; 0A~6A	Dec. 13, 2019	Jul. 02, 2020~ Jul. 21, 2020	Dec. 12, 2020	Conducted (TH05-HY)
UXM 5G Wireless Test Platform	Keysight	E7515B	MY59321826	FR1 + FR2 (24.25GHz-29.5 GHz)	Feb. 14, 2020	Jul. 02, 2020~ Jul. 21, 2020	Feb. 13, 2021	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jul. 02, 2020~ Jul. 19, 2020	Dec. 25, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	37059 & 01	30MHz~1GHz	Oct. 12, 2019	Jul. 02, 2020~ Jul. 19, 2020	Oct. 11, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Nov. 14, 2019	Jul. 02, 2020~ Jul. 19, 2020	Nov. 13, 2020	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91705 84	18GHz~40GHz	Dec. 10, 2019	Jul. 02, 2020~ Jul. 19, 2020	Dec. 09, 2020	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2020	Jul. 02, 2020~ Jul. 19, 2020	Mar. 24, 2021	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	Mar. 26, 2020	Jul. 02, 2020~ Jul. 19, 2020	Mar. 25, 2021	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-30 3K	1710001800 054002	1GHz~18GHz	Aug. 06, 2019	Jul. 02, 2020~ Jul. 19, 2020	Aug. 05, 2020	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 13, 2019	Jul. 02, 2020~ Jul. 19, 2020	Dec. 12, 2020	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Mar. 12, 2020	Jul. 02, 2020~ Jul. 19, 2020	Mar. 11, 2021	Radiation (03CH12-HY)
Base Station	Anritsu	MT8821C	6201432816	GSM / GPRS /WCDMA / LTE FDD/TDD with 44) /LTE-3CC DLCA,2CC ULCA	May 05, 2020	Jul. 02, 2020~ Jul. 19, 2020	May 04, 2021	Radiation (03CH12-HY)
5G Wireless Test Platform	Anritsu	MT8000A	6262012917	FR1 (+MT8821C SN:6261849015)	Jan. 20, 2020	Jul. 02, 2020~ Jul. 19, 2020	Jan. 19, 2021	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMB100A	101107	100kHz~40GHz	Aug. 27, 2019	Jul. 02, 2020~ Jul. 19, 2020	Aug. 26, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 12, 2019	Jul. 02, 2020~ Jul. 19, 2020	Dec. 11, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 25, 2020	Jul. 02, 2020~ Jul. 19, 2020	Feb. 24, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 25, 2020	Jul. 02, 2020~ Jul. 19, 2020	Feb. 24, 2021	Radiation (03CH12-HY)
Hygrometer	TECEPEL	DTM-303B	TP140349	N/A	Oct. 25, 2019	Jul. 02, 2020~ Jul. 19, 2020	Oct. 24, 2020	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 02, 2020~ Jul. 19, 2020	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jul. 02, 2020~ Jul. 19, 2020	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jul. 02, 2020~ Jul. 19, 2020	N/A	Radiation (03CH12-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Jul. 02, 2020~ Jul. 19, 2020	N/A	Radiation (03CH12-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.24
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.62
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.06
---	------



Appendix A. Test Results Of Conducted Test

FR1 n2

Peak-to-Average Ratio

Mode	FR1 n2 / 20MHz / DFT-S OFDM				
Mod.	PI/2 BPSK	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Lowest CH	3.65	4.43	5.54	6.00	PASS
Middle CH	3.77	4.41	5.57	6.00	
Highest CH	3.74	4.55	5.62	6.03	
Mode	FR1 n2 / 20MHz / DFT-S OFDM				
Mod.	256QAM				Limit: 13dB
RB Size	Full RB				Result
Lowest CH	6.70				PASS
Middle CH	6.75				
Highest CH	6.81				





FR1 n2 / 20MHz / DFT-S OFDM

PI/2 BPSK

QPSK

Lowest Channel / Full RB

Lowest Channel / Full RB





Date: 7_JUL_2020 14:13:43

Date: 7_JUL_2020 14:14:12

Middle Channel / Full RB

Middle Channel / Full RB





Date: 7_JUL_2020 14:13:57

Date: 7_JUL_2020 14:13:16

Highest Channel / Full RB

Highest Channel / Full RB



Date: 7_JUL_2020 14:15:20

Date: 7_JUL_2020 14:15:44





FR1 n2 / 20MHz / DFT-S OFDM

16QAM

64QAM

Lowest Channel / Full RB

Lowest Channel / Full RB





Date: 7_JUL.2020 14:11:39

Date: 7_JUL.2020 14:15:09

Middle Channel / Full RB

Middle Channel / Full RB





Date: 7_JUL.2020 14:12:53

Date: 7_JUL.2020 14:33:16

Highest Channel / Full RB

Highest Channel / Full RB



Date: 7_JUL.2020 14:55:13


Date: 7_JUL.2020 14:55:35




FR1 n2 / 20MHz / DFT-S OFDM

256QAM


Lowest Channel / Full RB



Middle Channel / Full RB



Highest Channel / Full RB





26dB Bandwidth

Mode	FR1 n2 : 26dB BW(MHz) / DFT-S OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	PI/2 BPSK		PI/2 BPSK		PI/2 BPSK		PI/2 BPSK	
Lowest CH	5.08		9.65		14.12		18.82	
Middle CH	4.91		9.53		14.33		18.74	
Highest CH	5.04		9.59		14.48		18.94	

Mode	FR1 n2 : 26dB BW(MHz) / CP OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	5.13	5.04	9.89	9.87	14.87	14.89	19.82	19.82
Middle CH	5.12	4.93	9.93	9.95	14.80	14.93	19.90	19.82
Highest CH	5.17	5.17	9.97	9.93	15.04	14.98	19.78	19.82

Mode	FR1 n2 : 26dB BW(MHz) / CP OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Lowest CH	5.05	5.04	9.75	9.87	14.89	14.87	19.90	19.86
Middle CH	5.28	5.04	9.95	10.03	14.89	14.84	19.82	19.78
Highest CH	5.13	5.03	9.89	9.85	14.89	14.84	19.90	19.74


Note: The CP-OFDM (worst case) is more wider bandwidth than the DFT-S OFDM's.



FR1 n2 / 5MHz / DFT-S OFDM


PI/2 BPSK

Lowest Channel




Date: 6.JUL.2020 09:11:46

Middle Channel



Date: 6.JUL.2020 09:48:45

Highest Channel



Date: 6.JUL.2020 10:18:36





FR1 n2 / 5MHz / CP OFDM

QPSK

16QAM

Lowest Channel

Lowest Channel





Date: 4.JUL.2020 15:24:43

Date: 4.JUL.2020 15:27:21

Middle Channel

Middle Channel





Date: 6.JUL.2020 09:45:12

Date: 6.JUL.2020 09:46:11

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:14:55

Date: 6.JUL.2020 10:15:47





FR1 n2 / 5MHz / CP OFDM

64QAM

256QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:07:137

Date: 6.JUL.2020 09:09:131

Middle Channel

Middle Channel





Date: 6.JUL.2020 09:14:102

Date: 6.JUL.2020 09:14:146

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:11:636


Date: 6.JUL.2020 10:11:736



FR1 n2 / 10MHz / DFT-S OFDM


PI/2 BPSK

Lowest Channel




Date: 6.JUL.2020 09:119:46

Middle Channel



Date: 6.JUL.2020 09:16:52

Highest Channel



Date: 6.JUL.2020 10:24:18





FR1 n2 / 10MHz / CP OFDM

QPSK

16QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:11:47

Date: 6.JUL.2020 09:16:14

Middle Channel

Middle Channel





Date: 6.JUL.2020 09:53:41

Date: 6.JUL.2020 09:54:26

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:20:23

Date: 6.JUL.2020 10:21:07





FR1 n2 / 10MHz / CP OFDM

64QAM

256QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:11:12

Date: 6.JUL.2020 09:18:23

Middle Channel

Middle Channel





Date: 6.JUL.2020 09:55:08

Date: 6.JUL.2020 09:55:51

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:21:55


Date: 6.JUL.2020 10:22:49




FR1 n2 / 15MHz / DFT-S OFDM

PI/2 BPSK


Lowest Channel



Middle Channel



Highest Channel







FR1 n2 / 15MHz / CP OFDM

QPSK

16QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:24:01

Date: 6.JUL.2020 09:25:12

Middle Channel

Middle Channel





Date: 6.JUL.2020 09:58:35

Date: 6.JUL.2020 09:59:22

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:27:25

Date: 6.JUL.2020 10:28:32





FR1 n2 / 15MHz / CP OFDM

64QAM

256QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:26:03

Date: 6.JUL.2020 09:27:03

Middle Channel

Middle Channel





Date: 6.JUL.2020 10:00:32

Date: 6.JUL.2020 10:01:17

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:29:18


Date: 6.JUL.2020 10:30:08



FR1 n2 / 20MHz / DFT-S OFDM


PI/2 BPSK

Lowest Channel




Date: 6.JUL.2020 09:41:04

Middle Channel



Date: 6.JUL.2020 10:09:55

Highest Channel



Date: 6.JUL.2020 11:07:01





FR1 n2 / 20MHz / CP OFDM

QPSK

16QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:30:57

Date: 6.JUL.2020 09:33:41

Middle Channel

Middle Channel





Date: 6.JUL.2020 10:05:12

Date: 6.JUL.2020 10:05:59

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:36:20

Date: 6.JUL.2020 10:40:22





FR1 n2 / 20MHz / CP OFDM

64QAM

256QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:39:33

Date: 6.JUL.2020 09:35:33

Middle Channel

Middle Channel





Date: 6.JUL.2020 10:06:52

Date: 6.JUL.2020 10:07:34

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:41:03

Date: 6.JUL.2020 10:42:04



Occupied Bandwidth

Mode	FR1 n2 : 99%OBW(MHz) / DFT-S OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	PI/2 BPSK		PI/2 BPSK		PI/2 BPSK		PI/2 BPSK	
Lowest CH	4.51		8.91		13.49		17.86	
Middle CH	4.52		8.91		13.46		17.90	
Highest CH	4.49		8.93		13.55		17.90	

Mode	FR1 n2 : 99%OBW (MHz) / CP OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	4.51	4.51	9.27	9.27	14.15	14.09	18.86	18.78
Middle CH	4.50	4.49	9.29	9.25	14.12	14.15	18.90	18.90
Highest CH	4.49	4.49	9.29	9.29	14.12	14.15	18.90	18.90

Mode	FR1 n2 : 99%OBW (MHz) / CP OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Lowest CH	4.47	4.49	9.27	9.29	14.15	14.15	18.98	18.86
Middle CH	4.51	4.49	9.29	9.29	14.15	14.15	18.90	18.98
Highest CH	4.49	4.47	9.27	9.27	14.12	14.18	18.94	18.86


Note: The CP-OFDM (worst case) is more wider bandwidth than the DFT-S OFDM'



FR1 n2 / 5MHz / DFT-S OFDM


PI/2 BPSK

Lowest Channel




Date: 6 JUL 2020 09:11:22

Middle Channel



Date: 6 JUL 2020 09:14:21

Highest Channel



Date: 6 JUL 2020 10:18:09





FR1 n2 / 5MHz / CP OFDM

QPSK

16QAM

Lowest Channel

Lowest Channel





Date: 4 JUL 2020 15:24:00

Date: 4 JUL 2020 15:26:40

Middle Channel

Middle Channel





Date: 6 JUL 2020 09:14:40

Date: 6 JUL 2020 09:45:52

Highest Channel

Highest Channel



Date: 6 JUL 2020 10:14:35

Date: 6 JUL 2020 10:15:28





FR1 n2 / 5MHz / CP OFDM

64QAM

256QAM



Lowest Channel

Lowest Channel





Middle Channel

Middle Channel



Highest Channel

Highest Channel






FR1 n2 / 10MHz / DFT-S OFDM


PI/2 BPSK

Lowest Channel




Date: 6.JUL.2020 09:11:27

Middle Channel



Date: 6.JUL.2020 09:15:32

Highest Channel



Date: 6.JUL.2020 10:23:54





FR1 n2 / 10MHz / CP OFDM

QPSK

16QAM

Lowest Channel

Lowest Channel





Date: 6 JUL 2020 09:13:54

Date: 6 JUL 2020 09:15:49

Middle Channel

Middle Channel





Date: 6 JUL 2020 09:15:25

Date: 6 JUL 2020 09:15:07

Highest Channel

Highest Channel



Date: 6 JUL 2020 10:20:07

Date: 6 JUL 2020 10:20:48





FR1 n2 / 10MHz / CP OFDM

64QAM

256QAM

Lowest Channel

Lowest Channel





Date: 6.JUL.2020 09:16:44

Date: 6.JUL.2020 09:17:53

Middle Channel

Middle Channel





Date: 6.JUL.2020 09:15:53

Date: 6.JUL.2020 09:55:36

Highest Channel

Highest Channel



Date: 6.JUL.2020 10:21:39


Date: 6.JUL.2020 10:22:32



FR1 n2 / 15MHz / DFT-S OFDM


PI/2 BPSK

Lowest Channel




Date: 6 JUL 2020 09:28:01

Middle Channel



Date: 6 JUL 2020 10:03:25

Highest Channel



Date: 6 JUL 2020 10:30:53