



FCC RADIO TEST REPORT

FCC ID : PKRISGM3000A
Equipment : M3000A
Brand Name : Inseego
Model Name : M3000A
Marketing Name : M3000
Applicant : Inseego Corp.
9710 Scranton Road Suite 200, San Diego, CA 92121
Manufacturer : Inseego Corp.
9710 Scranton Road Suite 200, San Diego, CA 92121
Standard : FCC 47 CFR Part 2, 96

The product was received on Mar. 29, 2022 and testing was performed from Apr. 20, 2022 to Jun. 28, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applied Standards	5
2 Test Configuration of Equipment Under Test	6
2.1 Test Mode.....	6
2.2 Measurement Results Explanation Example	7
2.3 Frequency List of Low/Middle/High Channels.....	8
3 Conducted Test Items.....	10
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power	11
3.3 Peak-to-Average Ratio	12
3.4 EIRP	13
3.5 Occupied Bandwidth	14
3.6 Conducted Band Edge	15
3.7 Conducted Spurious Emission	16
3.8 Frequency Stability.....	17
4 List of Measuring Equipment.....	18
Appendix A. Test Results of Conducted Test	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
3.3	§96.41	Peak-to-Average Ratio	Pass	
3.4	§96.41	Effective Isotropic Radiated Power	Pass	-
3.5	§2.1049 §96.41	Occupied Bandwidth	Reporting only	-
3.6	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	-
3.7	§2.1051 §96.41	Conducted Spurious Emission	Pass	
3.8	§2.1055	Frequency Stability for Temperature & Voltage	Pass	-

Declaration of Conformity:

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen
Report Producer: Vivian Hsu



1 General Description

1.1 Product Feature of Equipment Under Test

3G-WCDMA, 4G-LTE, 5G-FR1 & FR2, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax and GNSS.

Product Feature	
Test Antenna Type	WWAN: Fixed Internal Antenna
Test Antenna Gain	LTE Band 48: 1.5 dBi

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY
Test Engineer	Jacky Wang
Temperature (°C)	23.2~25.8
Relative Humidity (%)	55.6~58.2

FCC Designation No.: TW1190

1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 96
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Test Items	Band	Bandwidth (MHz)				Modulation				RB #			Test Channel		
		5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	48	v	v	v	v	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	48	v	v	v	v	v	v	v	v			v		v	
Conducted Band Edge	48	v	v	v	v	v	v	v	v	v		v	v	v	v
Peak-to-Average Ratio	48				v	v	v	v	v			v		v	
Conducted Spurious Emission	48	v	v	v	v	v				v			v	v	v
E.I.R.P	48	v	v	v	v	v	v	v	v	Max. Power					
Frequency Stability	48		v			v				v				v	
Remark	<ol style="list-style-type: none"> The mark "v " means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. One representative bandwidth is selected to perform PAR and frequency stability. 														



Test Items	Band	Bandwidth (MHz)										Modulation				RB #			Test Channel		
		20+20	20+15	15+20	20+10	10+20	20+5	5+20	15+15	15+10	10+15	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	48_CA	v	v	v	v	v	v	v	-	-	-	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	48_CA	v	v	v	v	v	v	v	-	-	-	v	v	v	v			v		v	
Conducted Band Edge	48_CA	v	v	v	v	v	v	v	-	-	-	v	v	v	v	v		v	v	v	v
Conducted Spurious Emission	48_CA	v	v	v	v	v	v	v	-	-	-	v	v	v	v	v		v	v	v	v
E.I.R.P.	48_CA	v	v	v	v	v	v	v	-	-	-	v	v	v	v	Max. Power					
Remark	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																				

2.2 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



2.3 Frequency List of Low/Middle/High Channels

LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560.0	3625.0	3690.0
15	Channel	55315	55990	56665
	Frequency	3557.5	3625.0	3692.5
10	Channel	55290	55990	56690
	Frequency	3555.0	3625.0	3695.0
5	Channel	55265	55990	56715
	Frequency	3552.5	3625.0	3697.5



LTE Band 48C Channel and Frequency List_CA					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
20 + 20	PCC	Channel	55340	55891	56442
		Frequency	3560.0	3565.1	3570.2
	SCC	Channel	55538	56089	56640
		Frequency	3579.8	3634.9	3690
20 + 15	PCC	Channel	55340	55916	56491
		Frequency	3560.0	3617.6	3675.1
	SCC	Channel	55511	56087	56662
		Frequency	3577.1	3634.7	3692.2
15 + 20	PCC	Channel	55318	55893	56469
		Frequency	3557.8	3615.3	3672.9
	SCC	Channel	55489	56064	56640
		Frequency	3574.9	3632.4	3690
20 + 10	PCC	Channel	55340	55941	56541
		Frequency	3560	3620.1	3680.1
	SCC	Channel	55484	56085	56685
		Frequency	3574.4	3634.5	3694.5
10 + 20	PCC	Channel	55295	55896	56496
		Frequency	3555.5	3615.6	3675.6
	SCC	Channel	55439	56040	56640
		Frequency	3569.9	3630	3690
20 + 5	PCC	Channel	55340	55965	56590
		Frequency	3560	3622.5	3685
	SCC	Channel	55457	56082	56707
		Frequency	3571.7	3634.2	3696.7
5 + 20	PCC	Channel	55273	55898	56523
		Frequency	3553.3	3615.8	3678.3
	SCC	Channel	55390	56015	56640
		Frequency	3565	3627.5	3690


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power

3.2.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio



3.4 EIRP

3.4.1 Description of the EIRP Measurement

The EIRP of mobile transmitters must not exceed 23 dBm /10 megahertz for LTE Band 48.

The testing follows ANSI C63.26-2015 Section 5.2.5.5

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - LC$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

Device	Maximum EIRP (dBm/10 MHz)	Maximum PSD (dBm/MHz)
End User Device	23	n/a

Remark: Total channel power is complied with EIRP limit 23dBm/10MHz.

3.4.2 Test Procedures

The testing follows procedure in Section 5.2 of ANSI C63.26-2015 and KDB 940660 D01 Part 96 CBRS Eqpt v03 Section 3.2(b)(2)

Determine the EIRP by adding the effective antenna gain to the measured average conducted power level.



3.5 Occupied Bandwidth

3.5.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.5.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.6 Conducted Band Edge

3.6.1 Description of Conducted Band Edge Measurement

The conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted power of any End User Device emission shall not exceed -25 dBm/MHz. Notwithstanding the emission limits in this paragraph, the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Adjacent Channel Leakage Ratio (ACLR) measurement,

1. The Adjacent Channel Leakage Ratio (ACLR) is the ratio of the average power in the assigned aggregated channel bandwidth to the average power over the equivalent adjacent channel bandwidth.
2. The option ACLR of spectrum analyzer is used and measures the ACLR ratio by setting equivalent channel bandwidth.
3. The measured ACLR ratio shall be at least 30 dB.



3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

96.41 (e)(2)

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is -40dBm/MHz.



3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Radio Communication Analyzer	Anritsu	MT8821C	6201664755	2/3/4G/LTE FDD/TDD with44)/LTE-3C C DLCA/2CC ULCA, CatM1/NB1/NB2	Jul. 21, 2021	Apr. 20, 2022~ Jun. 28, 2022	Jul. 20, 2022	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101908	10Hz~40GHz	Oct. 01, 2021	Apr. 20, 2022~ Jun. 28, 2022	Sep. 30, 2022	Conducted (TH03-HY)
Thermal Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 09, 2021	Apr. 20, 2022~ Jun. 28, 2022	Sep. 08, 2022	Conducted (TH03-HY)
DC Power Supply	GW Instek	GPP-2323	GES906037	0V~64V : 0A~6A	Jan. 06, 2022	Apr. 20, 2022~ Jun. 28, 2022	Jan. 05, 2023	Conducted (TH03-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#B	1-18GHz	Jan. 07, 2022	Apr. 20, 2022~ Jun. 28, 2022	Jan. 06, 2023	Conducted (TH03-HY)



Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power & EIRP)

LTE Band 48 Maximum Average Power [dBm] (GT - LC = 1.5 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
20	1	0	QPSK	20.81	20.97	20.63	22.47	0.1766
20	1	49		20.78	20.81	20.50		
20	1	99		20.69	20.64	20.29		
20	50	0		19.85	19.87	19.65		
20	50	24		19.89	19.85	19.63		
20	50	50		19.85	19.80	19.55		
20	100	0		19.89	19.82	19.60		
20	1	0	16-QAM	19.81	19.97	19.61	21.47	0.1403
20	1	49		19.86	19.85	19.57		
20	1	99		19.69	19.65	19.27		
20	50	0		18.84	18.90	18.68		
20	50	24		18.89	18.83	18.65		
20	50	50		18.86	18.79	18.53		
20	100	0		18.88	18.81	18.61		
20	1	0	64-QAM	18.77	18.84	18.62	20.36	0.1086
20	1	49		18.80	18.86	18.47		
20	1	99		18.62	18.62	18.29		
20	50	0		17.83	17.88	17.66		
20	50	24		17.90	17.84	17.62		
20	50	50		17.85	17.79	17.54		
20	100	0		17.85	17.83	17.59		
20	1	0	256-QAM	15.80	15.75	15.64	17.53	0.0566
20	1	49		15.87	15.74	15.57		
20	1	99		15.95	15.68	15.58		
20	50	0		15.88	15.81	15.74		
20	50	24		16.00	15.83	15.74		
20	50	50		16.03	15.81	15.73		
20	100	0		15.90	15.79	15.73		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48 Maximum Average Power [dBm] (GT - LC = 1.5 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
15	1	0	QPSK	20.87	20.88	20.56	22.38	0.1730
15	1	37		20.84	20.85	20.50		
15	1	74		20.67	20.71	20.32		
15	36	0		19.86	19.87	19.62		
15	36	20		19.82	19.85	19.59		
15	36	39		19.80	19.81	19.54		
15	75	0		19.83	19.85	19.58		
15	1	0	16-QAM	19.89	19.89	19.61	21.39	0.1377
15	1	37		19.87	19.85	19.53		
15	1	74		19.72	19.71	19.34		
15	36	0		18.89	18.88	18.63		
15	36	20		18.84	18.85	18.59		
15	36	39		18.79	18.82	18.54		
15	75	0		18.83	18.84	18.58		
15	1	0	64-QAM	18.86	18.84	18.52	20.36	0.1086
15	1	37		18.81	18.78	18.46		
15	1	74		18.66	18.64	18.26		
15	36	0		17.86	17.87	17.62		
15	36	20		17.83	17.83	17.58		
15	36	39		17.79	17.79	17.52		
15	75	0		17.84	17.83	17.57		
15	1	0	256-QAM	15.78	15.65	15.60	17.49	0.0561
15	1	37		15.77	15.72	15.51		
15	1	74		15.86	15.67	15.50		
15	36	0		15.78	15.75	15.72		
15	36	20		15.93	15.75	15.71		
15	36	39		15.99	15.77	15.67		
15	75	0		15.84	15.79	15.65		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48 Maximum Average Power [dBm] (GT - LC = 1.5 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
10	1	0	QPSK	20.93	20.95	20.72	22.45	0.1758
10	1	25		20.91	20.94	20.66		
10	1	49		20.86	20.93	20.52		
10	25	0		19.99	19.97	19.70		
10	25	12		20.00	19.98	19.69		
10	25	25		19.96	20.02	19.65		
10	50	0		19.98	19.96	19.69		
10	1	0	16-QAM	20.02	20.06	19.77	21.57	0.1435
10	1	25		19.97	20.07	19.69		
10	1	49		19.93	19.96	19.59		
10	25	0		19.03	18.98	18.70		
10	25	12		19.02	19.00	18.71		
10	25	25		18.99	19.01	18.66		
10	50	0		18.98	18.96	18.67		
10	1	0	64-QAM	18.85	18.94	18.65	20.44	0.1107
10	1	25		18.91	18.94	18.61		
10	1	49		18.81	18.87	18.52		
10	25	0		18.01	17.97	17.72		
10	25	12		18.01	17.96	17.69		
10	25	25		17.94	18.00	17.65		
10	50	0		17.99	17.96	17.67		
10	1	0	256-QAM	15.77	15.72	15.54	17.46	0.0557
10	1	25		15.84	15.68	15.48		
10	1	49		15.91	15.59	15.52		
10	25	0		15.80	15.80	15.67		
10	25	12		15.95	15.80	15.74		
10	25	25		15.96	15.80	15.63		
10	50	0		15.87	15.71	15.72		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48 Maximum Average Power [dBm] (GT - LC = 1.5 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
5	1	0	QPSK	20.91	20.96	20.60	22.46	0.1762
5	1	12		20.94	20.95	20.69		
5	1	24		20.94	20.91	20.60		
5	12	0		19.98	19.95	19.70		
5	12	7		19.99	20.04	19.70		
5	12	13		19.96	20.00	19.60		
5	25	0		19.97	19.93	19.67		
5	1	0	16-QAM	19.96	19.92	19.62	21.57	0.1435
5	1	12		20.03	20.07	19.71		
5	1	24		19.98	19.98	19.64		
5	12	0		19.01	18.93	18.69		
5	12	7		18.97	19.02	18.67		
5	12	13		18.89	18.99	18.55		
5	25	0		18.95	18.93	18.64		
5	1	0	64-QAM	18.88	18.92	18.60	20.50	0.1122
5	1	12		18.92	19.00	18.64		
5	1	24		18.86	18.92	18.53		
5	12	0		17.98	17.91	17.72		
5	12	7		17.99	18.15	17.73		
5	12	13		17.98	18.01	17.61		
5	25	0		17.97	17.94	17.67		
5	1	0	256-QAM	15.79	15.69	15.64	17.50	0.0562
5	1	12		15.86	15.66	15.56		
5	1	24		15.93	15.68	15.55		
5	12	0		15.81	15.72	15.66		
5	12	7		15.94	15.79	15.66		
5	12	13		16.00	15.75	15.69		
5	25	0		15.88	15.78	15.66		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 1.5 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
20+20	100	0	100	0	QPSK	14.89	15.02	14.85	18.19	0.0659
20+20	1	0	1	99		0.71	0.71	0.61		
20+20	1	99	1	0		16.69	16.69	16.52		
20+20	100	0	100	0	16-QAM	13.90	14.03	13.78	17.79	0.0601
20+20	1	0	1	99		1.36	1.46	1.24		
20+20	1	99	1	0		16.29	16.12	16.12		
20+20	100	0	100	0	64-QAM	13.81	13.84	13.71	16.68	0.0466
20+20	1	0	1	99		1.27	1.18	1.14		
20+20	1	99	1	0		15.11	15.18	14.87		
20+20	100	0	100	0	256-QAM	11.70	11.99	11.78	13.54	0.0226
20+20	1	0	1	99		0.90	0.97	0.93		
20+20	1	99	1	0		11.90	12.04	11.82		
20+15	100	0	75	0	QPSK	14.89	15.02	14.90	18.16	0.0655
20+15	1	0	1	74		0.73	0.79	0.71		
20+15	1	74	1	0		16.66	16.65	16.58		
20+15	100	0	75	0	16-QAM	13.92	14.02	13.92	17.77	0.0598
20+15	1	0	1	74		1.32	1.39	1.26		
20+15	1	74	1	0		16.24	16.27	16.19		
20+15	100	0	75	0	64-QAM	13.79	13.90	13.84	16.57	0.0454
20+15	1	0	1	74		1.25	1.20	0.87		
20+15	1	74	1	0		15.04	15.07	14.95		
20+15	100	0	75	0	256-QAM	11.73	11.99	11.73	13.49	0.0223
20+15	1	0	1	74		0.83	1.08	0.81		
20+15	1	74	1	0		11.86	11.89	11.80		
15+20	75	0	100	0	QPSK	14.83	15.00	14.93	18.22	0.0664
15+20	1	0	1	99		0.65	0.77	0.70		
15+20	1	74	1	0		16.67	16.72	16.66		
15+20	75	0	100	0	16-QAM	13.85	13.97	13.90	17.82	0.0605
15+20	1	0	1	99		1.24	1.34	1.38		
15+20	1	74	1	0		16.25	16.32	16.22		
15+20	75	0	100	0	64-QAM	13.70	13.85	13.76	16.74	0.0472
15+20	1	0	1	99		1.14	1.09	1.22		
15+20	1	74	1	0		15.21	15.16	15.24		
15+20	75	0	100	0	256-QAM	11.68	11.98	11.73	13.48	0.0223
15+20	1	0	1	99		0.78	0.91	0.80		
15+20	1	74	1	0		11.87	11.97	11.73		
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 1.5 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
20+10	100	0	50	0	QPSK	14.84	15.00	14.90	18.19	0.0659
20+10	1	0	1	49		0.71	0.82	0.73		
20+10	1	99	1	0		16.62	16.69	16.62		
20+10	100	0	50	0	16-QAM	13.85	14.01	13.84	17.79	0.0601
20+10	1	0	1	49		1.43	1.44	1.41		
20+10	1	99	1	0		16.01	16.29	16.29		
20+10	100	0	50	0	64-QAM	13.72	13.83	13.79	16.64	0.0461
20+10	1	0	1	49		1.26	1.27	1.29		
20+10	1	99	1	0		15.04	15.14	14.97		
20+10	100	0	50	0	256-QAM	11.67	11.99	11.72	13.49	0.0223
20+10	1	0	1	49		0.88	1.06	0.91		
20+10	1	99	1	0		11.90	11.91	11.75		
10+20	50	0	100	0	QPSK	14.65	14.98	14.84	18.18	0.0658
10+20	1	0	1	99		0.57	0.76	0.72		
10+20	1	49	1	0		16.52	16.68	16.61		
10+20	50	0	100	0	16-QAM	13.72	14.02	13.86	17.88	0.0614
10+20	1	0	1	99		1.16	1.38	1.32		
10+20	1	49	1	0		16.05	16.38	16.13		
10+20	50	0	100	0	64-QAM	13.61	13.86	13.75	16.60	0.0457
10+20	1	0	1	99		0.96	1.20	0.88		
10+20	1	49	1	0		14.93	15.04	15.10		
10+20	50	0	100	0	256-QAM	11.71	11.99	11.74	13.54	0.0226
10+20	1	0	1	99		0.88	1.06	0.90		
10+20	1	49	1	0		11.81	11.93	12.04		
20+5	100	0	25	0	QPSK	14.77	14.93	14.68	18.12	0.0649
20+5	1	0	1	24		0.66	0.72	0.52		
20+5	1	99	1	0		16.62	16.61	16.43		
20+5	100	0	25	0	16-QAM	13.80	13.97	13.71	17.74	0.0594
20+5	1	0	1	24		1.20	1.45	1.12		
20+5	1	99	1	0		16.24	16.14	15.96		
20+5	100	0	25	0	64-QAM	13.69	13.86	13.60	16.57	0.0454
20+5	1	0	1	24		1.04	1.19	0.92		
20+5	1	99	1	0		15.07	14.95	14.93		
20+5	100	0	25	0	256-QAM	11.64	11.94	11.69	13.44	0.0221
20+5	1	0	1	24		0.82	1.03	0.85		
20+5	1	99	1	0		11.71	11.88	11.79		
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 1.5 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
5+20	25	0	100	0	QPSK	14.73	14.94	14.79	18.14	0.0652
5+20	1	0	1	99		0.56	0.69	0.63		
5+20	1	24	1	0		16.50	16.64	16.56		
5+20	25	0	100	0	16-QAM	13.75	13.96	13.83	17.74	0.0594
5+20	1	0	1	99		1.19	1.21	1.30		
5+20	1	24	1	0		16.02	16.24	16.12		
5+20	25	0	100	0	64-QAM	13.61	13.83	13.70	16.67	0.0465
5+20	1	0	1	99		0.99	1.20	1.13		
5+20	1	24	1	0		15.00	15.17	14.91		
5+20	25	0	100	0	256-QAM	11.72	11.94	11.75	13.55	0.0226
5+20	1	0	1	99		0.80	0.97	0.87		
5+20	1	24	1	0		11.96	12.03	12.05		
Limit	EIRP < 23dBm/10MHz					Result			Pass	


Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48

Peak-to-Average Ratio

Mode	LTE Band 48 / 20MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	5.45	6.38	6.41	6.72	PASS






26dB Bandwidth

Mode	LTE Band 48 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	-	-	-	-	5.02	4.99	9.65	9.67	11.53	14.09	19.10	18.66
Mode	LTE Band 48 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM
Middle CH	-	-	-	-	4.86	4.79	9.65	9.75	14.21	14.39	18.66	19.30




LTE Band 48

Middle Channel / 5MHz / QPSK




Date: 17.MAY.2022 14:02:14

Middle Channel / 5MHz / 16QAM




Date: 17.MAY.2022 14:03:07

Middle Channel / 10MHz / QPSK




Date: 17.MAY.2022 14:05:06

Middle Channel / 10MHz / 16QAM




Date: 17.MAY.2022 14:05:29

Middle Channel / 15MHz / QPSK



Date: 17.MAY.2022 14:07:33

Middle Channel / 15MHz / 16QAM




Date: 17.MAY.2022 14:07:57




LTE Band 48


Middle Channel / 20MHz / QPSK




Middle Channel / 20MHz / 16QAM




Middle Channel / 5MHz / 64QAM




Middle Channel / 10MHz / 64QAM



Middle Channel / 15MHz / 64QAM




Middle Channel / 20MHz / 64QAM






LTE Band 48

Middle Channel / 5MHz / 256QAM




Date: 17.MAY.2022 12:36:44

Middle Channel / 10MHz / 256QAM




Date: 17.MAY.2022 13:01:35

Middle Channel / 15MHz / 256QAM



Date: 17.MAY.2022 13:36:03

Middle Channel / 20MHz / 256QAM



Date: 17.MAY.2022 13:52:12




Occupied Bandwidth

Mode	LTE Band 48 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	-	-	-	-	4.53	4.50	9.03	9.05	13.46	13.40	17.82	17.78
Mode	LTE Band 48 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM
Middle CH	-	-	-	-	4.48	4.50	8.99	8.97	13.49	13.46	17.86	17.86




LTE Band 48

Middle Channel / 5MHz / QPSK




Date: 17.MAY.2022 14:01:57

Middle Channel / 5MHz / 16QAM




Date: 17.MAY.2022 14:02:20

Middle Channel / 10MHz / QPSK




Date: 17.MAY.2022 14:04:19

Middle Channel / 10MHz / 16QAM




Date: 17.MAY.2022 14:04:42

Middle Channel / 15MHz / QPSK



Date: 17.MAY.2022 14:06:41

Middle Channel / 15MHz / 16QAM




Date: 17.MAY.2022 14:07:06




LTE Band 48

Middle Channel / 20MHz / QPSK




Date: 17.MAY.2022 14:09:08

Middle Channel / 20MHz / 16QAM




Date: 17.MAY.2022 14:09:32

Middle Channel / 5MHz / 64QAM




Date: 17.MAY.2022 14:03:01

Middle Channel / 10MHz / 64QAM




Date: 17.MAY.2022 14:05:53

Middle Channel / 15MHz / 64QAM



Date: 17.MAY.2022 14:08:20

Middle Channel / 20MHz / 64QAM




Date: 17.MAY.2022 14:10:42




LTE Band 48

Middle Channel / 5MHz / 256QAM




Date: 17.MAY.2022 12:36:32

Middle Channel / 10MHz / 256QAM




Date: 17.MAY.2022 12:57:02

Middle Channel / 15MHz / 256QAM



Date: 17.MAY.2022 13:35:53


Middle Channel / 20MHz / 256QAM





Date: 17.MAY.2022 13:51:45



ACLR











LTE Band 48 / 10MHz

QPSK

Lowest Channel / 1RB0

Lowest Channel / 1RBmax




Date: 17.MAY.2022 10:12:42


Date: 17.MAY.2022 10:25:24


Lowest Channel / FullIRB


N/A





Date: 17.MAY.2022 10:19:04





















LTE Band 48 / 20MHz

QPSK

Highest Channel / 1RB0

Highest Channel / 1RBmax




Date: 17.MAY.2022 11:05:11


Date: 17.MAY.2022 11:11:21

Highest Channel / FullIRB

N/A



Date: 17.MAY.2022 10:59:01







LTE Band 48 / 5MHz

16QAM

Middle Channel / 1RB0

Middle Channel / 1RBmax




Date: 17.MAY.2022 09:52:44

Date: 17.MAY.2022 10:05:23

Middle Channel / FullIRB

N/A



Date: 17.MAY.2022 09:59:03





LTE Band 48 / 5MHz

16QAM

Highest Channel / 1RB0

Highest Channel / 1RBmax




Date: 17.MAY.2022 09:54:51

Date: 17.MAY.2022 10:07:30

Highest Channel / FullIRB

N/A



Date: 17.MAY.2022 10:01:10

