



## RF Exposure Report

CC760

|              |   |
|--------------|---|
| Equipment:   | CC760 USB Modem   |
| Trade Name:  | MERLIN CC760  |
| Model No:    | CC760   |
| FCC ID:      | PKRNVWCC760   |
| Filing Type: | Original Filing   |
| Applicant:   | Novatel Wireless Inc.<br>9645 Scranton Road<br>San Diego, California<br>92121 |

# Table of Contents

|                                    |   |
|------------------------------------|---|
| 1.0 Introduction.....              | 4 |
| 1.1. FCC Definitions.....          | 4 |
| 1.2. MPE Calculation Formula ..... | 5 |
| 1.3. EUT Information.....          | 5 |
| 1.4. Operational Summary .....     | 6 |
| 1.5 .MPE Figures .....             | 6 |
| 2.0 Conclusion .....               | 6 |

## USER RESPONSIBILITY

**It is the document user's responsibility to ensure that this document is current and complete if using a printed copy. Any hardcopy may be out of date. Consult the on-line version of the document, or the on-line Master List to verify current revision level, or contact Document Control.**

## REVISION HISTORY

| <b>Rev.</b> | <b>Date</b> | <b>Brief Description of Change</b> | <b>Originator</b> | <b>Approved by</b> |
|-------------|-------------|------------------------------------|-------------------|--------------------|
| 1           | 13-03-09    | Initial Revision                   | JT                | PCTEST Inc.        |
|             |             |                                    |                   |                    |
|             |             |                                    |                   |                    |
|             |             |                                    |                   |                    |

## 1.0 Introduction

This report has been issued to show compliance of the Novatel Wireless CC760 to the FCC Maximum Permissible Exposure limits as specified in CFR 47 §2.1091 when using the external antenna port and defined as Mobile equipment . The CC760 is a Cellular/PCS EV-DO modem that can be used as either PC Card or Express Card.

The CC760 is defined as a Mobile configuration as per the FCC Rules, and the user documentation that is available to consumers indicates that the modem must not be used closer than 20 cm to the head or body to ensure safe operation of the device. Also, the maximum gain of an external antenna connected to the antenna port has been defined in the user documentation as 6 dBi in both the Cellular and PCS Bands.

### Model Names:

The CC760 is the designated Model name of the Novatel “generic” model. There are two other models included in this family of product:

- a) C777 – Sprint Specific
- b) PC760 – Verizon Specific

### 1.1. FCC Definitions

As per OET Bulletin 65, three (3) categories of transmitters are defined, these are:

- a) **Fixed Installation** – Defined as a fixed location for the transmitter and it’s antenna that is physically secured at a permanent location and cannot easily be moved. Typical user distance to the transmitting antenna is  $\geq 2$  meters.
- b) **Mobile Installation** –A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter’s radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.
- c) **Portable Installation** - A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

The FCC categorizes the use of any device based upon the users awareness and ability to exercise control over exposure. The definitions of exposure categories are as follows:

a) **Occupational/Controlled Exposure** – Applicable to situations where the end users are exposed to RF energy during routine daily workplace conditions and are fully aware of said exposure.

b) **General Population/Uncontrolled Exposure** – Applicable to situations where the end users are do not a have an awareness of the potential exposure to RF energy or have no control of said exposure.

For purposes of this investigation, the MC990D is evaluated using the exposure limits for General Population/Uncontrolled Exposure.

## **1.2. MPE Calculation Formula**

Per FCC §1.1310, the Power Density limit for General Population/Uncontrolled Exposure is:

- For the Cellular Band – 0.558 mW/cm<sup>2</sup>
- For the PCS Band – 1.000 mW/cm<sup>2</sup>

The calculation is made using the Friis transmission equation:

$$S = \text{EIRP}/4\pi R^2$$

Where:

S = Power Density

EIRP – Effective Isotropic Radiated Power

R = 20 cm distance

## **1.3. EUT Information**

Equipment Under Test: Novatel Merlin CC760

Hardware Revision: 3

Firmware/Software Revision: 1225

Serial Number: N/A (Production Grade Sample)

## 1.4. Operational Summary

The CC760 is capable of transmitting in the Cellular/PCS frequency bands and features EV-DO modulation schemes for WWAN. For purposes of this report, MPE figures for each band is presented operating in the worst case (highest power) mode.

All measurements taken are worst case per band investigated, detailed results can be seen in Report No: 092230325.PKR

## 1.5 .MPE Figures

Maximum Antenna Gain = 6 dBi (as specified in Quick Start guide)

### Case One: 850 MHz

a) Maximum Conducted RF Power Cellular Band:

$$24.74 \text{ dBm} + 6 \text{ dBi (antenna)} = 30.74 \text{ dBm}$$

$$30.74 \text{ dBm} = 1185.7687 \text{ mW}$$

| Maximum EIRP<br>(mw) | Calculated RF Exposure<br>D = 20 cm | Limit<br>(mW/cm <sup>2</sup> ) |
|----------------------|-------------------------------------|--------------------------------|
| 1185.768             | 0.236 mW/cm <sup>2</sup>            | 0.558                          |

### Case Two: PCS 1900

a) Maximum Conducted RF Power PCS Band:

$$24.11 \text{ dBm} + 6 \text{ dBi (antenna)} = 30.11 \text{ dBm}$$

$$30.11 \text{ dBm} = 1025.652 \text{ mW}$$

| Maximum EIRP<br>(mw) | Calculated RF Exposure<br>D = 20 cm | Limit<br>(mW/cm <sup>2</sup> ) |
|----------------------|-------------------------------------|--------------------------------|
| 1025.652             | 0.204 mW/cm <sup>2</sup>            | 1.000                          |

## 2.0 Conclusion

As presented in the previous section, the CC760 complies with all requirements for Maximum Permissible Exposure per CFR 47 §2.1091, defined as Mobile equipment with a minimum separation distance between the end user and the antenna(s) of 20cm.