



**FCC Part 1 Subpart I
FCC Part 2 Subpart J
INDUSTRY CANADA RSS 102 ISSUE 3**

RF EXPOSURE REPORT

FOR

850/1900 GSM/GPRS/EDGE/WCDMA/CDMA/EVDO AND 700MHz LTE MODULE

FCC ID: PKRNVWE362

MODEL NUMBER: E362

REPORT NUMBER: 11I14114-1, REVISION B

ISSUE DATE: NOVEMBER 14, 2011

Prepared for
**NOVATEL WIRELESS INC
6715-8TH STREET NE, SUITE 200
CALGARY
T2E, 7H7, CANADA**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES (UL CCS)
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	11/09/11	Initial Issue	T. Chan
A	11/11/11	Added WLAN and LTE Modes	T. Chan
B	11/14/11	Corrected corrupted table	A. Zaffar

TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS.....	4
2.	METHODOLOGY	5
3.	REFERENCES	5
4.	FACILITIES AND ACCREDITATION.....	5
5.	EUT DESCRIPTION	5
6.	REQUIREMENTS - LIMITATION OF EXPOSURE	6
6.1.	<i>LIMITS</i>	6
6.1.1.	FCC RULES	6
6.1.2.	IC RULES.....	7
6.1.3.	LIMITS APPLICABLE TO THE EUT	7
6.2.	<i>EQUATIONS</i>	8
6.3.	<i>RESULTS</i>	9

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: NOVATEL WIRELESS INC
 6715-8TH STREET NE, SUITE 200
 CALGARY, T2E 7H7, CANADA

EUT DESCRIPTION: 850/1900 GSM/GPRS/EDGE/WCDMA/CDMA/EVDO AND
 700MHz LTE MODULE

MODEL: E362

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass
INDUSTRY CANADA RSS 102 ISSUE 3	Pass

Compliance Certification Services (UL CCS) calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation, as described by the referenced documents. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:

Calculated By:




THU CHAN
 ENGINEERING MANAGER
 UL CCS

TOM CHEN
 EMC ENGINEER
 UL CCS

2. METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01 and IC Safety Code 6.

3. REFERENCES

All measurements were made as documented in PCTEST ENGINEERING LABORATORY, INC. test report serial number: 0Y100913539.PKRL, 0Y100913540.PKR for operation in the 800 and 1900 MHz bands, Elliott Document FCC ID: PD962230ANH for operation in the 2.4 GHz band and in the 5 GHz bands.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Output power, Duty cycle and Antenna gain data is excerpted from product documentation provided by the applicant.

Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from product documentation provided by the applicant.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

5. EUT DESCRIPTION

The EUT is an 850/1900 GSM/GPRS/EDGE/WCDMA/CDMA/EVDO AND 700MHz LTE module transceiver.

Other details regarding the EUT are documented in the applicable test reports and product documentation.

6. REQUIREMENTS - LIMITATION OF EXPOSURE

6.1. LIMITS

6.1.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

6.1.2. IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 5
Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m ²)	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/ <i>f</i>	2.19/ <i>f</i>		6
10–30	28	2.19/ <i>f</i>		6
30–300	28	0.073	2*	6
300–1 500	1.585 <i>f</i> ^{0.5}	0.0042 <i>f</i> ^{0.5}	<i>f</i> /150	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	616 000 / <i>f</i> ^{1.2}
150 000–300 000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616 000 / <i>f</i> ^{1.2}

* Power density limit is applicable at frequencies greater than 100 MHz.

- Notes:**
1. Frequency, *f*, is in MHz.
 2. A power density of 10 W/m² is equivalent to 1 mW/cm².
 3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

6.1.3. LIMITS APPLICABLE TO THE EUT

For mobile radio equipment operating in the cellular phone band, the lowest power density limit is calculated using the lowest frequency, as 824 MHz / 1500 = 0.55 mW/cm² (FCC) and 824 MHz / 150 = 5.5 W/m² (IC).

For operation in the PCS band, the 2.4 GHz band and the 5 GHz bands, from FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm² and from IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m².

6.2. EQUATIONS

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * \text{D}^2)$$

where

S = Power density in W/m²

EIRP = Equivalent Isotropic Radiated Power in W

D = Separation distance in m

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

where

D = Separation distance in m

EIRP = Equivalent Isotropic Radiated Power in W

S = Power density in W/m²

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in W

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the Power * Gain product (in linear units) of each transmitter.

$$\text{Total EIRP} = (\text{P1} * \text{G1}) + (\text{P2} * \text{G2}) + \dots + (\text{Pn} * \text{Gn})$$

where

P_x = Power of transmitter x

G_x = Numeric gain of antenna x

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply, either the lowest limit applicable to the co-located transmitters can be applied or a fraction of the exposure limit is established for each band, such that the sum of the fractions is less than or equal to one.

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

6.3. RESULTS

Separation Distance	(m)	0.2				
Band		850 MHz	1900 MHz	2.4 GHz	2.4 GHz	5 GHz
Mode		GSM	GSM	Bluetooth	WLAN	WLAN
IC Single Tx Limit	(W/m ²)	5.5	10	10	10	10
FCC Single Tx Limit	(mW/cm ²)	0.55	1	1	1	1
Fractional Allocation of Limit	(%)	55	30	1	5	9
Fractional Total	(%)	100.0				
IC Power Density Limit	(W/m ²)	3.025	3	0.1	0.5	0.9
FCC Power Density Limit	(mW/cm ²)	0.3025	0.3	0.01	0.05	0.09
Output Power	(dBm)	31.21	28.21	6.02	16.9	23.91
Antenna Gain	(dBi)	0.6	1.3	0.22	0.22	2.01
EIRP	(dBm)	31.81	29.51	6.24	17.12	25.92
EIRP	(W)	1.52	0.89	0.00	0.05	0.39
Duty Cycle	(%)	100	100	100	100	100
Time-Average EIRP	(W)	1.52	0.89	0.00	0.05	0.39
IC Power Density	(W/m ²)	3.02	1.78	0.01	0.10	0.78
FCC Power Density	(mW/cm ²)	0.302	0.178	0.001	0.010	0.078
Fractional Limit / Actual Red indicates over the limit	(dB)	0.02	4.54	21.54	13.76	1.27

Separation Distance	(m)	0.2			
Band		700 MHz	2.4 GHz	2.4 GHz	5 GHz
Mode		LTE	Bluetooth	WLAN	WLAN
IC Single Tx Limit	(W/m²)	5	10	10	10
FCC Single Tx Limit	(mW/cm²)	0.5	1	1	1
Fractional Allocation of Limit	(%)	40	1	25	34
Fractional Total	(%)	100.0			
IC Power Density Limit	(W/m²)	2	0.1	2.5	3.4
FCC Power Density Limit	(mW/cm²)	0.2	0.01	0.25	0.34
Output Power	(dBm)	23.67	6.02	16.9	23.91
Antenna Gain	(dBi)	1.3	0.22	0.22	2.01
EIRP	(dBm)	24.97	6.24	17.12	25.92
EIRP	(W)	0.31	0.00	0.05	0.39
Duty Cycle	(%)	100	100	100	100
Time-Average EIRP	(W)	0.31	0.00	0.05	0.39
IC Power Density	(W/m²)	0.63	0.01	0.10	0.78
FCC Power Density	(mW/cm²)	0.063	0.001	0.010	0.078
Fractional Limit / Actual	 [(dB)] 	10.10	21.54	27.74	12.81

END OF REPORT