

FCC TEST REPORT

Test report No.: EMC- FCC- R0116

FCC ID: PKRNVWE362

Type of equipment: IP Network Camera

Model Name: 6100 LTE VZW

Variant Model: IPN100LTE-VZW

Applicant: Novatel Wireless Inc

Max.RF Output Power: 233.35mW (23.68dBm) (QPSK - 5MHz BW)
231.74mW (23.65dBm) (16-QAM - 5MHz BW)
232.27mW (23.66dBm) (QPSK - 10MHz BW)
230.67mW (23.63dBm) (16-QAM - 10MHz BW)

FCC Rule Part(s): §2; §27

Frequency Range: 779.5MHz-784.5MHz(5MHz BW LTE – Band 13)
782MHz (10MHz BW LTE - Band 13)


Test result: Complied


The above equipment was tested by EMC compliance Testing Laboratory for compliance with the requirements of FCC Rules and Regulations.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of test: July 1, 2013 ~ July 05, 2013

Issued date: July 08, 2013


Tested by: _____
SON, MIN GI


Approved by: _____
YU, SANG HOON

[Contents]

1. Client information.....	3
2. Laboratory information	4
3. Description of E.U.T.....	5
3.1 Basic description.....	5
3.2 General description	5
3.3 Test frequency.....	6
3.4 Test Voltage	6
4. Summary of test results.....	7
4.1 Standards & results	7
4.2 Uncertainty	7
5. Test results	8
5.1 Occupied Bandwidth	8
5.2 Band Edge / Conducted Spurious Emissions	9
5.3 Transmitter Conducted Output Power	11
5.4 Frequency Stability	12
5.5 Undesirable Out-of-Band Emissions	13
5.6 Undesirable Emissions in the 1559 – 1610MHz band	15
5.7 RF Exposure	16
6. Test equipment used for test	18
Appendix 1 Test setup photos	
Appendix 2 External photos of EUT	
Appendix 3 Internal photos of EUT	
Appendix 4 Block diagram	
Appendix 5 Schematics	
Appendix 6 User manual	
Appendix 7 Part list	
Appendix 8 Layout diagram	
Appendix 9 Antenna Specification	

1. Client information

Applicant: Novatel Wireless Inc
Address: 6715-8th Street NE Suite 200 Calgary, T2E 7H7 Canada
Telephone number: +82-2-2093-3070
Facsimile number : +82-2-2605-1489
Contact person: Eun Sung, Yang / Harold.yang@udptechnology.com

Manufacturer : LG Innotek Co., Ltd
Address: 26, Hanamsandan 5beon-ro, Gwangsan-gu, Gwangju, 506-731, Korea

2. Laboratory information

Address

EMC Compliance Ltd.
480-5 Shin-dong, Yeongtong-gu, Suwon-city, Gyunggi-do, 443-390, Korea
Telephone Number: 82 31 336 9919 Facsimile Number: 82 31 336 4767

Certificate

CBTL Testing Laboratory, KOLAS NO.: 231
FCC Filing No.: 508785
VCCI Registration No.: C-1713, R-1606, T-258
IC Recognition No.:8035A-2

SITE MAP



3. Description of E.U.T.

3.1 Basic description

Applicant :	Novatel Wireless Inc
Address of Applicant:	6715-8th Street NE Suite 200 Calgary, T2E 7H7 Canada
Manufacturer:	LG Innotek Co., Ltd
Address of Manufacturer:	26, Hanamsandan 5beon-ro, Gwangsan-gu, Gwangju, 506-731, Korea
Type of equipment:	IP Network Camera
Basic Model:	6100 LTE VZW
Serial number:	Proto Type

3.2 General description

Communication	5MHz BW LTE - Band 13, 10MHz BW LTE - Band 13
Frequency Range	779.5MHz - 784.5MHz (5MHz BW LTE - Band 13) 782MHz (10MHz BW LTE - Band 13)
Power supply	DC 12 V
Operating temperature	-20 ~ 50 °C
Dimension	75 mm x 90 mm x 140 mm (W x D x H)
Antenna Model	KRS-GANYMEDE-MA
Antenna Type	Intenna(Omni directional single antenna)
Antenna Gain	777 ~ 787 MHz : 2.5 dBi
Antenna characteristic	Vertical Polarization, Omni Directional

3.3 Test frequency

5MHz BW LTE - Band 13

	Frequency
Low frequency	779.50 MHz
High frequency	784.50 MHz

10MHz BW LTE - Band 13

	Frequency
Middle frequency	782.00 MHz

3.4 Test Voltage

mode	Voltage
Norminal voltage	DC 12 V

4. Summary of test results

4.1 Standards & results

Rule Reference	Parameter	Report Section	Test Result
2.1049	Occupied Bandwidth	5.1	NA
2.1051, 27.53(c)(2)	Band Edge / Conducted Spurious Emissions	5.2	NA
2.1046	Transmitter Conducted Output Power Measurements	5.3	NA
2.1055, 27.54	Frequency Stability	5.4	NA
2.1053, 27.53(c)(2) 27.53(c)(4)	Undesirable Out-of-Band Emissions	5.5	C
2.1053, 27.53(f)	Undesirable Emissions in the 1559 – 1610MHz band	5.6	NA
Note: C = complies NC = Not complies NT = Not tested NA = Not Applicable			

4.2 Uncertainty

Measurement Item	Combined Standard Uncertainty U _c	Expanded Uncertainty U = KU _c (K = 2)
Conducted RF power	± 0.29 dB	± 0.58 dB
Radiated disturbance	30 MHz ~ 300 MHz : + 2.43 dB, - 2.44 dB 300 MHz ~ 1 000 MHz : + 2.49dB, - 2.50 dB 1 GHz ~ 6 GHz : + 3.10 dB, - 3.10 dB 6 GHz ~ 18 GHz : + 3.21 dB, - 3.27 dB	30 MHz ~ 300 MHz : + 4.86 dB, - 4.88 dB 300 MHz ~ 1 000 MHz + 4.98 dB, - 4.99 dB 1 GHz ~ 6 GHz : + 6.19 dB, - 6.20 dB 6 GHz ~ 18 GHz : + 6.41 dB, - 6.53 dB

5. Test results

5.1 Occupied Bandwidth

5.1.1 Regulation

According to §2.1049, §27.53(1)(6), The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

5.1.2 Result

- Refer to Module test report

5.2 Band Edge / Conducted Spurious Emissions

5.2.1 Regulation

According to §2.1051, §27.53(c)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

5.2.2 Result

- Refer to Module test report

5.3 Transmitter Conducted Output Power Measurements

- N/A

5.3 Transmitter Conducted Output Power

5.3.1 Regulation

According to §2.1046, The following average conducted output power measurements for the Novatel 850/1900 GSM/GPRS/EDGE/WCDMA/CDMA/EvDO and 700MHz LTE Module FCC ID: PKRNVWE362 were measured using a R&S CMU200 base station simulator for GSM/GPRS/EDGE and WCDMA/HSPA modes and an Agilent 8960 base station simulator for CDMA/EvDO modes.

5.3.2 Test Result

- Refer to Module test report

5.4 Frequency Stability

5.4.1 Regulation

According to §2.1055, §27.54 The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter.

Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

5.4.2 Test Result

- Refer to Module test report

5.5 Undesirable Out-of-Band Emissions

5.5.1 Test Result

-Complied

5 MHz Bandwidth

OPERATING FREQUENCY: 779.50 MHz

Frequency (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)
362.999	48.7	-6.7	42.0	82.2	40.2
1560.00	58.0	-11.5	46.5	82.2	35.7
1843.33	47.0	-9.9	37.1	82.2	45.1
2213.33	46.9	-8.5	38.4	82.2	43.8
2463.33	50.6	-7.0	43.6	82.2	38.6

OPERATING FREQUENCY: 784.50 MHz

Frequency (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)
363.003	48.7	-6.7	42.0	82.2	40.2
1566.67	59.9	-11.5	48.4	82.2	33.8
1800.00	47.3	-10.2	37.1	82.2	45.1
2213.33	47.5	-8.5	39.0	82.2	43.2
2463.33	50.7	-7.0	43.7	82.2	38.5

10 MHz Bandwidth

OPERATING FREQUENCY: 782.00 MHz

Frequency (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)
362.953	46.8	-6.7	40.1	82.2	42.1
1564.13	45.9	-11.5	34.4	82.2	47.8
1843.33	33.2	-9.9	23.3	82.2	58.9
2213.33	44.0	-8.5	35.5	82.2	46.7

5.6 Undesirable Emissions in the 1559 – 1610MHz band

5.6.1 Regulation

The average receive power meter reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the power meter. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm $- (-24.80)$.

5.6.2 Test Result

- Refer to Module test report

5.7 RF Exposure

5.7.1 Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, *=*plane-wave equivalent power density*

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

EUT: Maximum peak output power = 256.448 [mW] (24.09 dBm)

Antenna gain = 0.728 (-1.5 [dBi])

100 mW, at 20 cm from an antenna 6 [dBi]	$S = PG/4\pi R^2 = 100 \times 6 / (4 \times \pi \times 400) = 0.7918 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$
233.35 mW, at 20 cm from an antenna 2.5 [dBi]	$S = PG/4\pi R^2 = 0.08255 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$

5.6.2 RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

5.6.3 Calculation Result of RF Exposure

5MHz bandwidth

Channel	Frequency [MHz]	Ant Gain [mW]	power [dBm]	power [mW]	Power Density at 20 cm [mW/cm ²]
Lowest	779.5	1.778	23.66	232.27	0.082 17
Highest	784.5	1.778	23.68	233.35	0.082 55

10MHz bandwidth

Channel	Frequency [MHz]	Ant Gain [mW]	power [dBm]	power [mW]	Power Density at 20 cm [mW/cm ²]
Middle	782.0	1.778	23.66	232.27	0.082 17

6. Test equipment used for test

	Description	Manufacture	Model No.	Serial No.	Next Cal Date.
<input type="checkbox"/>	Temp & humidity chamber	Taekwang	TK-04	TK001	13.12.07
<input type="checkbox"/>	Temp & humidity chamber	Taekwang	TK-500	TK002	13.09.03
<input type="checkbox"/>	Frequency Counter	HP	53150A	US39250565	13.09.04
<input checked="" type="checkbox"/>	Spectrum Analyzer	Agilent	E4440A	MY46186407	14.06.27
<input type="checkbox"/>	Spectrum Analyzer	R & S	FSG13	100051	13.10.23
<input checked="" type="checkbox"/>	Signal Generator	R & S	SMR40	100007	14.06.27
<input type="checkbox"/>	Vector Signal Generator	R & S	SMBV100A	257566	14.01.07
<input type="checkbox"/>	Wideband Power Sensor	R & S	NRP-Z81	100677	14.05.06
<input type="checkbox"/>	Modulation Analyzer	HP	8901B	3538A05527	13.10.25
<input type="checkbox"/>	Audio Analyzer	HP	8903B	3729A19213	13.10.23
<input type="checkbox"/>	AC Power Supply	Kikusui	PCR2000W	GB001619	13.10.23
<input checked="" type="checkbox"/>	DC Power Supply	Tektronix	PS2520G	TW50517	14.03.12
<input type="checkbox"/>	DC Power Supply	Tektronix	PS2521G	TW53135	13.10.23
<input type="checkbox"/>	Attenuator	HP	8494A	2631A09825	13.10.24
<input type="checkbox"/>	Attenuator	HP	8496A	3308A16640	13.10.24
<input type="checkbox"/>	Attenuator	BIRD	50-A-MFN-20	0403002	13.10.24
<input type="checkbox"/>	Power Divider	Weinschel	1580-1	NX375	13.10.23
<input type="checkbox"/>	Power Divider	Weinschel	1580-1	NX380	13.09.09
<input type="checkbox"/>	Power Divider	Weinschel	1594	671	13.09.10
<input type="checkbox"/>	Power Divider	Krytar	7005265	143244	13.09.03
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESCI	100710	13.11.06
<input checked="" type="checkbox"/>	LOOP Antenna	EMCO	EMCO6502	9205-2745	14.05.23
<input checked="" type="checkbox"/>	BILOG Antenna	Schwarzbeck	VULB 9168	9168-440	13.09.21
<input checked="" type="checkbox"/>	HORN Antenna	ETS	3115	00086706	13.11.21
<input type="checkbox"/>	HORN Antenna	ETS	3116	00086632	13.11.15
<input checked="" type="checkbox"/>	Amplifier	Sonoma	310N	293004	13.11.06
<input checked="" type="checkbox"/>	Amplifier	Agilent	8449B	3008A01802	14.05.06
<input type="checkbox"/>	Attenuator	HP	8491A	27444	13.11.06
<input checked="" type="checkbox"/>	Antenna Mast	Innco Systems	MA4000-EP	303	-
<input checked="" type="checkbox"/>	Turn Table	Innco Systems	DT2000S-1t	079	-
<input type="checkbox"/>	Highpass Filter	Wainwright	WHK2.5/ 18G-10SS	61	14.04.12
<input type="checkbox"/>	Highpass Filter	Wainwright	WHKX6.5/ 18G-8SS	2	14.06.05
<input type="checkbox"/>	Test Receiver	R & S	843276/003	ESHS10	14.06.15
<input type="checkbox"/>	LISN	R & S	100267	ESH3-Z5	13.07.05
<input type="checkbox"/>	LISN	Schwarzbeck	8121-472	NNLK8121	13.07.13