



# Partial FCC RF Test Report

**APPLICANT** : Novatel Wireless  
**EQUIPMENT** : Mini-PCle wireless WAN card  
**BRAND NAME** : Novatel Wireless  
**MODEL NAME** : E396  
**FCC ID** : PKRNVWE396-D  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)  
**Tx/Rx FREQUENCY RANGE** : GSM850 : 824.2 ~ 848.8 MHz /  
869.2 ~ 893.8 MHz  
GSM1900 : 1850.2 ~ 1909.8 MHz /  
1930.2 ~ 1989.8 MHz  
WCDMA Band V : 826.4 ~ 846.6 MHz /  
871.4 ~ 891.6 MHz  
WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz  
2112.4 MHz ~ 2152.6 MHz  
WCDMA Band II : 1852.4 ~ 1907.6 MHz /  
1932.4 ~ 1987.6 MHz  
CDMA2000 BC0 : 824.70 ~ 848.31 MHz /  
869.70 ~ 893.31 MHz  
CDMA2000 BC1 : 1851.25 ~ 1908.75 MHz /  
1931.25 ~ 1988.75 MHz  
**MAX. ERP/EIRP POWER** : GSM850 ( GPRS 8 ) : 1.29 W  
GSM850 ( EDGE 8 ) : 0.28 W  
GSM1900 ( GPRS 8 ) : 1.34 W  
GSM1900 ( EDGE 8 ) : 0.52 W  
WCDMA Band V (RMC 12.2Kbps) : 0.14 W  
WCDMA Band IV ( RMC 12.2Kbps) : 0.40 W  
WCDMA Band II ( RMC 12.2Kbps) : 0.35 W  
CDMA2000 BC0 : 0.14 W  
CDMA2000 BC1 : 0.30 W



This is a partial report which is only valid combined with the integrated the WWAN Module (Brand Name: QUALCOMM / Model Name: Gobi3000, FCC ID: J9CGOBI3000) during the test.

This is a partial report which is included the Radiated Emission. The product was received on Sep. 08, 2011 and completely tested on Oct. 15, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**

**SPORTON INTERNATIONAL INC.**

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : PKRNVWE396-D

Page Number : 2 of 41

Report Issued Date : Nov. 01, 2011

Report Version : Rev. 01



## TABLE OF CONTENTS

REVISION HISTORY ..... 4

SUMMARY OF TEST RESULT ..... 5

1 GENERAL DESCRIPTION ..... 6

    1.1 Applicant ..... 6

    1.2 Manufacturer ..... 6

    1.3 Feature of Equipment Under Test ..... 7

    1.4 Emission Designator and Maximum ERP/EIRP Power ..... 8

    1.5 Testing Site ..... 8

    1.6 Applied Standards ..... 9

    1.7 Ancillary Equipment List ..... 9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 10

    2.1 Test Mode ..... 10

    2.2 Connection Diagram of Test System ..... 12

3 TEST RESULT ..... 13

    3.1 Effective Radiated Power and Effective Isotropic Radiated Power Measurement ..... 13

    3.2 Field Strength of Spurious Radiation Measurement ..... 20

4 LIST OF MEASURING EQUIPMENTS ..... 40

5 UNCERTAINTY OF EVALUATION ..... 41

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.1	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.1	§27.50(d)(2)	RSS-139 (6.4) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.2	§2.1053 §22.917(a) §24.238(a) §27.53(g)	RSS-132 (4.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 12.11 dB at 2509 MHz



# **1 General Description**

## **1.1 Applicant**

**Novatel Wireless**

6715 8th Street N.E. Suite 200, Calgary, Alberta, Canada T2E 7H7

## **1.2 Manufacturer**

**Novatel Wireless**

6715 8th Street N.E. Suite 200, Calgary, Alberta, Canada T2E 7H7

### 1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Mini-PCle wireless WAN card
Brand Name	Novatel Wireless
Model Name	E396
FCC ID	PKRNVWE396-D
Host Tablet PC	Brand Name: Dell Model Name: T02G
Integrated Module	Brand Name : Novatel Wireless Model Name : Novatel Wireless E396 HW Version : P4 SW Version : 1580
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band IV : 1710 MHz ~ 1755 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz CDMA2000 BC0 : 824 MHz ~ 849 MHz CDMA2000 BC1 : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band IV : 2110 MHz ~ 2155 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz CDMA2000 BC0 : 869 MHz ~ 894 MHz CDMA2000 BC1 : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 32.99 dBm GSM1900 : 30.65 dBm WCDMA Band V : 24.32 dBm WCDMA Band IV : 20.57 dBm WCDMA Band II : 22.60 dBm CDMA2000 BC0 : 24.39 dBm CDMA2000 BC1 : 23.61 dBm
Antenna Type	Fixed Internal Antenna
HW Version	10317-SB
SW Version	x14
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) CDMA2000 : QPSK
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Emission Designator and Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP
Part 22	GSM850 GPRS 8	GMSK	1.29 W
Part 22	GSM850 EDGE 8	GMSK / 8PSK	0.28 W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK (Uplink)	0.14 W
Part 22	CDMA2000 BC0 1xEV-DO Rev. A	QPSK	0.14 W
Part 24	GSM1900 GPRS 8	GMSK	1.34 W
Part 24	GSM1900 EDGE 8	GMSK / 8PSK	0.52 W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK (Uplink)	0.35 W
Part 24	CDMA2000 BC1 1xEV-DO Rev. A	QPSK	0.30 W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK (Uplink)	0.40 W

## 1.5 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC/IC Registration No.</b>
	03CH06-HY	722060/4086B-1





### 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-C-2004
- IC RSS-132 Issue 2
- IC RSS-133 Issue 5
- IC RSS-139 Issue 2

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

### 1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850, WCDMA Band V and CDMA2000 BC0.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900, WCDMA Band II and CDMA2000 BC1.

Test Modes	
Band	Radiated TCs
GSM 850	<ul style="list-style-type: none"> <li>■ GPRS 8 Link</li> <li>■ EDGE 8 Link</li> </ul>
GSM 1900	<ul style="list-style-type: none"> <li>■ GPRS 8 Link</li> <li>■ EDGE 8 Link</li> </ul>
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band IV	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
CDMA2000 BC0	<ul style="list-style-type: none"> <li>■ 1xEV-DO Rev. A Link Mode</li> </ul>
CDMA2000 BC1	<ul style="list-style-type: none"> <li>■ 1xEV-DO Rev. A Link Mode</li> </ul>

**Note:**

1. The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, RMC 12.2Kbps WCDMA band IV, and WCDMA band II, 1xEV-DO Rev. A mode for CDMA2000 BC0 and CDMA2000 BC1 on QPSK Link; only these modes were used for all tests.
2. Only the radiated emission, ERP, and EIRP of the WWAN module were performed in this report, and the conducted test cases can be referred to QUALCOMM module report (FCC ID: J9CGOBI3000).




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GPRS 8	32.94	32.91	32.99	30.65	30.48	30.52
GPRS 10	32.87	32.84	32.96	30.60	30.42	30.44
EGPRS 8	27.18	27.16	27.13	26.44	26.39	26.35
EGPRS 10	27.09	27.08	27.10	26.32	26.27	26.25

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Tx Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Rx Channel	4357	4408	4458	9662	9800	9938	1537	1638	1738
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	24.32	24.23	24.19	22.47	22.60	22.41	20.48	20.47	20.57
HSDPA Subtest-1	23.77	23.72	23.74	22.06	22.14	22.02	20.09	20.07	20.10
HSDPA Subtest-2	23.80	23.68	23.75	22.06	22.14	22.02	20.02	20.01	20.07
HSDPA Subtest-3	23.34	23.35	23.28	21.71	21.73	21.49	19.54	19.60	19.72
HSDPA Subtest-4	23.38	23.27	23.29	21.59	21.69	21.45	19.60	19.58	19.64
HSUPA Subtest-1	22.77	22.99	23.01	21.09	21.31	21.36	19.39	19.53	19.99
HSUPA Subtest-2	21.68	21.67	21.76	20.00	20.14	20.26	18.40	18.31	18.55
HSUPA Subtest-3	22.25	22.00	22.11	20.23	20.38	20.39	18.66	18.51	18.99
HSUPA Subtest-4	22.00	22.20	22.21	20.35	20.46	20.54	19.17	18.74	19.00
HSUPA Subtest-5	22.71	22.94	23.06	21.13	21.31	21.42	19.27	19.61	20.04

Conducted Power (*Unit: dBm)						
Band	CDMA2000 BC0			CDMA2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1+SO55	24.32	24.37	24.22	23.55	23.44	23.42
1xRTT RC3+SO55	24.13	24.25	24.14	23.65	23.43	23.41
1xRTT RC3+SO32 (+F-SCH)	24.11	24.14	24.02	23.48	23.36	23.34
1xRTT RC3+SO32 (+SCH)	24.12	24.16	24.15	23.50	23.37	23.35
1xEVDO RTAP 153.6	24.31	24.39	24.38	23.61	23.53	23.40
1xEVDO RETAP 4096	24.27	24.35	24.32	23.59	23.49	23.37

## 2.2 Connection Diagram of Test System



### 3 Test Result

#### 3.1 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

##### 3.1.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts. The EIRP of mobile transmitters are limited to 2 Watts for 1850~1910 MHz and 1 watt for 1710~1755 MHz.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$   
Ps (dBm) : Input power to substitution antenna.  
Gs (dBi or dBd) : Substitution antenna Gain.  
 $E_t = R_t + AF$   
 $E_s = R_s + AF$   
AF (dB/m) : Receive antenna factor  
Rt : The highest received signal in spectrum analyzer for EUT.  
Rs : The highest received signal in spectrum analyzer for substitution antenna.

### 3.1.4 Test Setup





3.1.5 Test Result of ERP

GSM850 ( GPRS 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.28	-48.12	0.00	-1.08	28.76	0.75
836.40	-17.83	-48.28	0.00	-0.93	29.52	0.90
848.80	-16.50	-48.35	0.00	-0.76	31.09	1.29
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-16.66	-47.97	0.00	-1.08	30.23	1.05
836.40	-16.81	-48.01	0.00	-0.93	30.27	1.06
848.80	-16.52	-48.05	0.00	-0.76	30.77	1.19

GSM850 ( EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.63	-48.12	0.00	-1.08	23.41	0.22
836.40	-23.61	-48.28	0.00	-0.93	23.74	0.24
848.80	-23.63	-48.35	0.00	-0.76	23.96	0.25
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-22.49	-47.97	0.00	-1.08	24.40	0.28
836.40	-23.01	-48.01	0.00	-0.93	24.07	0.26
848.80	-23.38	-48.05	0.00	-0.76	23.91	0.25



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-26.73	-48.12	0.00	-1.08	20.31	0.11
836.40	-25.98	-48.28	0.00	-0.93	21.37	0.14
846.60	-26.79	-48.35	0.00	-0.76	20.80	0.12
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-25.47	-47.97	0.00	-1.08	21.42	0.14
836.40	-25.54	-48.01	0.00	-0.93	21.54	0.14
846.60	-26.56	-48.05	0.00	-0.76	20.73	0.12

CDMA2000 BC0 1xEV-DO Rev. A Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.70	-26.69	-48.12	0.00	-1.08	20.35	0.11
836.52	-26.53	-48.28	0.00	-0.93	20.82	0.12
848.31	-26.40	-48.35	0.00	-0.76	21.19	0.13
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.70	-25.76	-47.97	0.00	-1.08	21.13	0.13
836.52	-26.09	-48.01	0.00	-0.93	20.99	0.13
848.31	-25.94	-48.05	0.00	-0.76	21.35	0.14





3.1.6 Test Result of EIRP

GSM1900 ( GPRS 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-23.41	-51.88	0.00	1.96	30.43	1.10
1880.00	-25.42	-52.99	0.00	2.00	29.57	0.91
1909.80	-26.44	-54.28	0.00	1.98	29.82	0.96
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-22.83	-52.13	0.00	1.96	31.26	1.34
1880.00	-24.14	-53.17	0.00	2.00	31.03	1.27
1909.80	-25.16	-54.13	0.00	1.98	30.95	1.24

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-28.33	-51.88	0.00	1.96	25.51	0.36
1880.00	-29.99	-52.99	0.00	2.00	25.00	0.32
1909.80	-31.43	-54.28	0.00	1.98	24.83	0.30
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.94	-52.13	0.00	1.96	27.15	0.52
1880.00	-28.34	-53.17	0.00	2.00	26.83	0.48
1909.80	-29.19	-54.13	0.00	1.98	26.92	0.49



WCDMA Band IV ( RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.4	-30.38	-51.88	0.00	1.96	23.46	0.22
1732.6	-30.91	-52.99	0.00	2.00	24.08	0.26
1752.6	-31.92	-54.28	0.00	1.98	24.34	0.27
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.4	-28.13	-52.13	0.00	1.96	25.96	0.39
1732.6	-29.15	-53.17	0.00	2.00	26.02	0.40
1752.6	-30.70	-54.13	0.00	1.98	25.41	0.35

WCDMA Band II ( RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.41	-51.88	0.00	1.96	24.43	0.28
1880.00	-31.66	-52.99	0.00	2.00	23.33	0.22
1907.60	-33.09	-54.28	0.00	1.98	23.17	0.21
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-28.70	-52.13	0.00	1.96	25.39	0.35
1880.00	-29.74	-53.17	0.00	2.00	25.43	0.35
1907.60	-30.67	-54.13	0.00	1.98	25.44	0.35



CDMA2000 BC1 1xEV-DO Rev. A Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1851.25	-30.13	-51.88	0.00	1.96	23.71	0.23
1880.00	-32.16	-52.99	0.00	2.00	22.83	0.19
1908.75	-33.84	-54.28	0.00	1.98	22.42	0.17
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1851.25	-29.37	-52.13	0.00	1.96	24.72	0.30
1880.00	-30.38	-53.17	0.00	2.00	24.79	0.30
1908.75	-31.76	-54.13	0.00	1.98	24.35	0.27



## **3.2 Field Strength of Spurious Radiation Measurement**

### **3.2.1 Description of Field Strength of Spurious Radiated Measurement**

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


### **3.2.2 Measuring Instruments**

See list of measuring instruments of this test report.

### **3.2.3 Test Procedures**

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$


### 3.2.4 Test Setup





3.2.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	23~24°C
Test Mode :	GPRS 8 Link	Relative Humidity :	46~48%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : D3CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-42.16	-13	-29.16	-52.83	-43.62	1.88	5.49	H	Pass
2509	-25.11	-13	-12.11	-37.67	-26.74	2.44	6.22	H	Pass
3345	-45.83	-13	-32.83	-61.77	-49.28	2.47	8.07	H	Pass
4182	-43.13	-13	-30.13	-62.25	-47.84	2.35	9.21	H	Pass




<b>Band :</b>	GSM850	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	GPRS 8 Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-45.06	-13	-32.06	-55.78	-46.52	1.88	5.49	V	Pass
2509	-26.62	-13	-13.62	-39.37	-28.25	2.44	6.22	V	Pass
4182	-42.94	-13	-29.94	-62.01	-47.65	2.35	9.21	V	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	46~48%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-47.26	-13	-34.26	-57.92	-48.72	1.88	5.49	H	Pass
2509	-38.03	-13	-25.03	-50.70	-39.66	2.44	6.22	H	Pass





<b>Band :</b>	GSM850	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.91	-13	-35.91	-59.57	-50.37	1.88	5.49	V	Pass
2509	-41.32	-13	-28.32	-53.82	-42.95	2.44	6.22	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	GPRS 8 Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-39.09	-13	-26.09	-56.81	-45.34	2.56	8.81	H	Pass
5636	-40.89	-13	-27.89	-63.73	-48.63	2.96	10.70	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	GPRS 8 Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 VERTICAL  
 Project : FG 190847

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-39.80	-13	-26.80	-57.20	-46.05	2.56	8.81	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-43.13	-13	-30.13	-60.87	-49.38	2.56	8.81	H	Pass




<b>Band :</b>	GSM1900	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-43.86	-13	-30.86	-61.25	-50.11	2.56	8.81	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-49.16	-13	-36.16	-59.87	-50.62	1.88	5.49	H	Pass
2509	-43.76	-13	-30.76	-56.25	-45.39	2.44	6.22	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 VERTICAL  
 Project : FG 190847

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-49.97	-13	-36.97	-60.63	-51.43	1.88	5.49	V	Pass
2509	-47.24	-13	-34.24	-59.89	-48.87	2.44	6.22	V	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465	-40.55	-13	-27.55	-57.13	-44.38	4.48	8.31	H	Pass
5197	-41.57	-13	-28.57	-63.15	-46.21	5.332	9.98	H	Pass





<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 VERTICAL  
 Project : FG 190847

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465	-43.80	-13	-30.80	-60.31	-47.63	4.48	8.31	V	Pass
5197	-41.71	-13	-28.71	-63.06	-46.35	5.332	9.98	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-37.98	-13	-24.98	-55.63	-44.23	2.56	8.81	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 VERTICAL  
 Project : FG 190847

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-41.73	-13	-28.73	-59.23	-47.98	2.56	8.81	V	Pass



<b>Band :</b>	CDMA2000 BC0	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	1xEV-DO Rev. A	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : D3CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-45.32	-13	-32.32	-56.01	-46.78	1.88	5.49	H	Pass
2509	-36.81	-13	-23.81	-49.44	-38.44	2.44	6.22	H	Pass



<b>Band :</b>	CDMA2000 BC0	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	1xEV-DO Rev. A	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.73	-13	-35.73	-59.45	-50.19	1.88	5.49	V	Pass
2509	-43.99	-13	-30.99	-56.58	-45.62	2.44	6.22	V	Pass
3345	-44.57	-13	-31.57	-60.74	-48.02	2.47	8.07	V	Pass



<b>Band :</b>	CDMA2000 BC1	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	1xEV-DO Rev. A	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)  
 Site : 03CH06-HY  
 Condition : FCC PART22/24 ETRP\_100524 HORIZONTAL  
 Project : FG 190847

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-34.53	-13	-21.53	-52.25	-40.78	2.56	8.81	H	Pass



<b>Band :</b>	CDMA2000 BC1	<b>Temperature :</b>	23~24°C
<b>Test Mode :</b>	1xEV-DO Rev. A	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Kai Wang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-36.61	-13	-23.61	-54.29	-42.86	2.56	8.81	V	Pass



### 4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Jul. 28, 2011	Jul. 27, 2012	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 13, 2011	Jun. 12, 2012	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100057	9KHz-40GHz	Oct. 25, 2010	Oct. 24, 2011	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESVS10	834468/003	20MHz-1000MHz	May 10, 2011	May 09, 2012	Radiation (03CH06-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH06-HY)
Double Ridge Horn Antenna	EMCO	3117	00066583	1GHz~18GHz	Aug. 01, 2011	Jul. 31, 2012	Radiation (03CH06-HY)
Double Ridge Horn Antenna	Training Research	AH-0801	95119	8GHz~18GHz	Oct. 20, 2010	Oct. 19, 2011	Radiation (03CH06-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH06-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1GHz- 26.5GHz	Apr. 14, 2011	Apr. 13, 2012	Radiation (03CH06-HY)
Amplifier	Agilent	310N	186713	9KHz~1GHz	Apr. 14, 2011	Apr. 13, 2012	Radiation (03CH06-HY)
System Simulator	R&S	CMU200	112403	N/A	Feb. 22, 2011	Feb. 21, 2012	Radiation (03CH06-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.27</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.54</b>		

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$	$C_i$	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	$\pm 0.10$	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	$\pm 1.70$	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	$\pm 0.50$	Normal (k=2)	0.25	1	0.25
Receiver Correction	$\pm 2.00$	Rectangular	1.15	1	1.15
Antenna Factor Directional	$\pm 1.50$	Rectangular	0.87	1	0.87
Site Imperfection	$\pm 2.80$	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>2.36</b>				
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>4.72</b>				



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP190847 as below.