



# PARTIAL FCC TEST REPORT (PART 22)

**REPORT NO.:** RF130513C11  
**MODEL NO.:** CB2U  
**Host FCC ID:** HFS-Y  
**Module FCC ID:** PKRNVWE396  
**RECEIVED:** May 13, 2013  
**TESTED:** May 21, 2013 ~ May 22, 2013  
**ISSUED:** Jun. 03, 2013

**APPLICANT:** Quanta Computer Inc.

**ADDRESS:** No. 188, Wen Hwa 2nd RD., Kuei Shan Hsiang,  
Tao Yuan Shien, Taiwan

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New  
Taipei City, Taiwan ( R.O.C. )

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1 CERTIFICATION .....	4
2 SUMMARY OF TEST RESULTS .....	5
2.1 MEASUREMENT UNCERTAINTY .....	5
2.2 TEST SITE AND INSTRUMENTS .....	6
3 GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 CONFIGURATION OF SYSTEM UNDER TEST .....	8
3.3 DESCRIPTION OF SUPPORT UNITS .....	8
3.4 TEST ITEM AND TEST CONFIGURATION .....	9
3.5 EUT OPERATING CONDITIONS .....	10
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	10
4 TEST TYPES AND RESULTS.....	11
4.1 OUTPUT POWER MEASUREMENT .....	11
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT .....	11
4.1.2 TEST PROCEDURES .....	11
4.1.3 TEST SETUP .....	12
4.1.4 TEST RESULTS .....	13
4.2 RADIATED EMISSION MEASUREMENT .....	15
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	15
4.2.2 TEST PROCEDURES .....	15
4.2.3 DEVIATION FROM TEST STANDARD .....	15
4.2.4 TEST SETUP .....	16
4.2.5 TEST RESULTS .....	17
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	23
6 INFORMATION ON THE TESTING LABORATORIES .....	24
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	25



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130513C11	Original release	Jun. 03, 2013



# 1 CERTIFICATION

**PRODUCT:** Laptop

**MODEL:** CB2U

**APPLICANT:** Quanta Computer Inc.

**TESTED:** May 21, 2013 ~ May 22, 2013

**TEST SAMPLE:** Production Unit

**STANDARDS:** FCC PART 22, Subpart H

The above equipment (model: CB2U) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Vera Huang , **DATE** : Jun. 03, 2013  
Vera Huang / Specialist

**APPROVED BY** : Sam chen , **DATE** : Jun. 03, 2013  
Sam Chen / Assistant Manager

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 22.913 (a)	Effective radiated power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	N/A	Refer to NOTE below.
2.1049	Occupied Bandwidth	N/A	Refer to NOTE below.
22.917	Band Edge Measurements	N/A	Refer to NOTE below.
2.1051 22.917	Conducted Spurious Emissions	N/A	Refer to NOTE below.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -26.34dB at 32.43MHz.

**NOTE:** Test items for radiated emission test and effective radiated power were performed for this report. Other testing data please refer to module (Brand: QUALCOMM, Model: Gobi3000, FCC ID: J9CGOBI3000) Report No.: 80-N2162-203 Rev B

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Aug. 21, 2012	Aug. 20, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2012	Dec. 16, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Mar. 25, 2013	Mar. 24, 2014
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Jan. 07, 2013	Jan. 06, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 25, 2012	Dec. 24, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 184045	980116	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 330H	980112	Dec. 28, 2012	Dec. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable Worken	RG-213	NA	Dec. 29, 2012	Dec. 28, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. The test was performed in HwaYa Chamber 10.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The FCC Site Registration No. is 690701.
  6. The IC Site Registration No. is IC 7450F-10.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Laptop	
<b>MODEL NO.</b>	CB2U	
<b>POWER SUPPLY</b>	5.25Vdc (adapter) 11.1Vdc (battery)	
<b>MODULATION TYPE</b>	<b>GPRS</b>	GMSK
	<b>EDGE</b>	8PSK
	<b>WCDMA</b>	BPSK
<b>FREQUENCY RANGE</b>	<b>GPRS/EDGE</b>	824.2MHz ~ 848.8MHz
	<b>WCDMA</b>	826.4MHz ~ 846.6MHz
<b>MAX. ERP POWER</b>	<b>GPRS</b>	977.24mW
	<b>EDGE</b>	238.23mW
	<b>WCDMA</b>	148.94mW
<b>MULTI-SLOTS CLASS</b>	10	
<b>WCDMA RELEASE VERSION</b>	6	
<b>ANTENNA TYPE</b>	PIFA Antenna	
<b>I/O PORTS</b>	Refer to users' manual	
<b>DATA CABLE</b>	Refer to NOTE as below	
<b>ACCESSORY DEVICES</b>	Refer to NOTE as below	


**NOTE:**

1. The EUT has following accessories.

ITEM	BRAND	MODEL	DESCRIPTION
AC Adapter	LEI	MU15-N1052-A00S	I/P: 100-240Vac, 0.5A, 50-60Hz O/P: 5.25Vdc, 3A
Li-ion Battery	SMP	SQU-1208	Rating: 11.1Vdc, 2700mAh
WWAN Module	NOVATEL	E396U	--
WLAN+Bluetooth	AZUREWAVE	AW-AH397	--
Camera	Lite-on	12P2SF004	--
11.6" LCD Panel	LG	LP116WH6	--
Battery Pack	SMP	SQU-1208	--
CPU	Samsung	Exynos 5250	--
Memory Capacity	N/A	N/A	2GB

2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 CONFIGURATION OF SYSTEM UNDER TEST



### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.



### 3.4 TEST ITEM AND TEST CONFIGURATION

Following channel(s) was (were) selected for the final test as listed below:

#### GSM MODE

TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
ERP	128 to 251	128, 189, 251	GPRS, EDGE
RADIATED EMISSION	128 to 251	189	GPRS, EDGE

#### WCDMA MODE

TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
ERP	4132 to 4233	4132, 4182, 4233	WCDMA
RADIATED EMISSION	4132 to 4233	4233	WCDMA

#### TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	25deg. C, 65%RH	11.1Vdc	Howard Kao
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	David Huang



A D T

### **3.5 EUT OPERATING CONDITIONS**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### **3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 22**

**ANSI/TIA/EIA-603-C 2004**

**NOTE:** All test items have been performed and recorded as per the above standards.

## 4 TEST TYPES AND RESULTS

### 4.1 OUTPUT POWER MEASUREMENT

#### 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

#### 4.1.2 TEST PROCEDURES

##### **EIRP / ERP MEASUREMENT:**


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE, 5MHz for WCDMA and CDMA mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$   
E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dBi.}$

##### **CONDUCTED POWER MEASUREMENT:**

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA & CDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


### 4.1.3 TEST SETUP

#### EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.4 TEST RESULTS

##### CONDUCTED OUTPUT POWER (dBm)

Band	GPRS850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GPRS 8 (GMSK, 1 slot)	32.08	31.89	32.17
GPRS 10 (GMSK, 2 slot)	32.02	31.83	32.11
EDGE 8 (GMSK, 1 Uplink)	31.94	31.75	32.07
EDGE 10 (GMSK, 2 Uplink)	31.84	31.65	32.05
EDGE 8 (8PSK, 1 Uplink)	26.65	26.46	26.68
EDGE 10 (8PSK, 2 Uplink)	26.59	26.40	26.62

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	24.11	23.98	23.96
HSDPA Subtest-1	23.56	23.43	23.41
HSDPA Subtest-2	23.62	23.49	23.47
HSDPA Subtest-3	23.13	23.00	22.98
HSDPA Subtest-4	23.09	22.96	22.94
HSUPA Subtest-1	23.52	23.39	23.37
HSUPA Subtest-2	22.34	22.21	22.19
HSUPA Subtest-3	22.07	21.94	21.92
HSUPA Subtest-4	22.64	22.51	22.49
HSUPA Subtest-5	23.59	23.46	23.44



A D T

## ERP POWER (dBm)

### GSM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
128	824.2	-4.63	32.62	25.84	383.71	H
189	836.4	-4.56	32.52	25.81	381.07	H
251	848.8	-4.71	32.65	25.79	379.31	H
128	824.2	-0.71	32.76	29.90	977.24	V
189	836.4	-0.62	32.39	29.62	916.22	V
251	848.8	-1.02	32.54	29.37	864.97	V

### EDGE

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
128	824.2	-10.82	32.62	19.65	92.26	H
189	836.4	-10.43	32.52	19.94	98.63	H
251	848.8	-10.52	32.65	19.98	99.54	H
128	824.2	-6.84	32.76	23.77	238.23	V
189	836.4	-6.86	32.39	23.38	217.77	V
251	848.8	-7.11	32.54	23.28	212.81	V

### WCDMA (RMC 12.2K)

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
4132	826.4	-12.56	32.62	17.91	61.80	H
4182	836.52	-12.44	32.52	17.93	62.09	H
4233	846.6	-13.47	32.65	17.03	50.47	H
4132	826.4	-9.28	32.76	21.33	135.83	V
4182	836.4	-8.51	32.39	21.73	148.94	V
4233	846.6	-9.38	32.54	21.01	126.18	V

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

### 4.2.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ .
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  
 $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$ .

**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

### 4.2.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).



### 4.2.5 TEST RESULTS


**GPRS:**



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5  
 Condition : PART22/24 3m HORIZONTAL  
 Brand/Model: OC1  
 Remark : GPRS850 Link  
 Tested by : David Huang  
 Temperature : 25°C  
 Humidity : 65%

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	69.96	-54.04	-44.70	-13.00	-41.04	-9.34	Peak
2 pp	211.71	-45.63	-38.20	-13.00	-32.63	-7.43	Peak
3	280.83	-53.04	-46.92	-13.00	-40.04	-6.12	Peak
4	318.20	-59.08	-52.84	-13.00	-46.08	-6.24	Peak
5	478.50	-54.36	-50.71	-13.00	-41.36	-3.65	Peak
6	700.40	-61.02	-62.47	-13.00	-48.02	1.45	Peak
7	1672.80	-55.16	-42.34	-13.00	-42.16	-12.82	Peak
8	2509.20	-46.65	-37.48	-13.00	-33.65	-9.17	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 Chamber 5  
 Condition : PART22/24 3m VERTICAL  
 Brand/Model: OC1  
 Remark : GPRS850 Link  
 Tested by : David Huang  
 Temperature : 25°C  
 Humidity : 65%

	Freq	Level	Read	Limit	Over		
	MHz	dBm/m	Level	Line	Limit	Factor	Remark
			dBm	dBm/m	dB	dB/m	
1 pp	32.43	-39.34	-38.23	-13.00	-26.34	-1.11	Peak
2	167.43	-56.94	-50.28	-13.00	-43.94	-6.66	Peak
3	210.63	-48.93	-41.46	-13.00	-35.93	-7.47	Peak
4	317.50	-65.61	-59.36	-13.00	-52.61	-6.25	Peak
5	480.60	-55.40	-51.82	-13.00	-42.40	-3.58	Peak
6	700.40	-62.23	-63.68	-13.00	-49.23	1.45	Peak
7	1672.80	-54.46	-41.64	-13.00	-41.46	-12.82	Peak
8	2509.20	-48.48	-39.31	-13.00	-35.48	-9.17	Peak


**EDGE:**



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
 Condition : PART22/24 3m HORIZONTAL  
 Brand/Model: OC1  
 Remark : EDGE850 Link  
 Tested by : David Huang  
 Temperature : 25°C  
 Humidity : 65%


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-57.35	-44.53	-13.00	-44.35	-12.82	Peak
2 pp	2509.20	-48.98	-39.81	-13.00	-35.98	-9.17	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5  
 Condition : PART22/24 3m VERTICAL  
 Brand/Model: OC1  
 Remark : EDGE850 Link  
 Tested by : David Huang  
 Temperature : 25°C  
 Humidity : 65%

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.70	-54.67	-41.85	-13.00	-41.67	-12.82	Peak
2 pp	2509.20	-50.01	-40.84	-13.00	-37.01	-9.17	Peak


WCDMA:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5




Site : 966 Chamber 5  
 Condition : PART22/24 3m HORIZONTAL  
 Brand/Model: OC1  
 Remark : Band V Link  
 Tested by : David Huang  
 Temperature : 25°C  
 Humidity : 65%

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-58.02	-45.20	-13.00	-45.02	-12.82	Peak
2 pp	2509.20	-53.35	-44.18	-13.00	-40.35	-9.17	Peak



A D T

Data: 6



Site : 966 Chamber 5  
 Condition : PART22/24 3m VERTICAL  
 Brand/Model: OC1  
 Remark : Band V Link  
 Tested by : David Huang  
 Temperature : 25°C  
 Humidity : 65%

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-58.15	-45.33	-13.00	-45.15	-12.82	Peak
2 pp	2509.20	-49.88	-40.71	-13.00	-36.88	-9.17	Peak



A D T

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



## **7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

---END---