



Product Integrity Laboratory

5151-47th Street, NE
Calgary, Alberta T3J 3R2
Tel: (403) 568-6605
Fax : (403) 568-6970

Novatel Wireless Inc Collocated MPE Report

For

FCC ID # PKRNVWE760D

IC #: 3229B-E760

Project Code CG-1276

(Report CG-1276-RA-1-1)

Revision: 1

August 28, 2009

Prepared for: Novatel Wireless Inc

Author: Glen Moore
Wireless/EMC Manager

Approved by: Nick Kobrosly
Lab Manager

Confidentiality Statement: This report and the information contained herein represent the results of testing articles/products identified and selected by the client. The tests were performed to specifications and/or procedures approved by the client. National Technical Systems ("NTS") makes no representations expressed or implied that such testing fully demonstrates efficiency, performance, reliability, or any other characteristic of the articles being tested, or similar products. This report should not be relied upon as an endorsement or certification by NTS of the equipment tested, nor does it represent any statement whatsoever as to its merchantability or fitness of the test article or similar products for a particular purpose. This document shall not be reproduced except in full without written approval from National Technical Systems ("NTS") and the customer.

Test Facility:	National Technical Systems, Canada Product Integrity Laboratory 5151-47 th Street, N.E. Calgary Alberta T3J 3R2
Accreditation Numbers:	FCC 101386 IC 3978A-1 Accredited by Standards Council of Canada Accredited Laboratory No. 440 Conforms with requirements of CAN-P-4D (ISO/IEC 17025) CLIENTS SERVED: All interested parties FIELDS OF TESTING: Electrical/Electronic, Mechanical/Physical ACCREDITATION DATE:: 2008-06-17 VALID TO: 2013-03-20
Applicant:	Novatel Wireless Inc. 9645 Scranton Rd, Suite 205 San Diego, CA 92121
Customer Representative:	Mr. Todd Gallagher Manager – Regulatory Engineering Office: (403) 295 4891 Cell: (403) 681 8483 Fax: (403) 295 4801 Email: tgallagher@nvtl.com

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

Register of revisions

Revision	Date	Description of Revisions
1	August 28, 2009	Initial release

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970

INTRODUCTION

1.1 PURPOSE

This Maximum Permissible Exposure report demonstrates compliance with FCC CFR 47 1.1310 and 2.1091 for collocated transmitters used in simultaneous conditions with the Model UNDP-1D PCI Wireless WAN Card (FCC ID: PKRNVWE760D, IC: 3229B-E760) installed in a host platform categorized as “mobile”. The mobile classification applies when 20 cm or greater separation distance is maintained between the end user and all transmission antennas. The host platform in this application is the Dell Model P02E-P02E001 laptop computer, marketed under the name: Studio 1745).

2.0 DESCRIPTION OF COLLOCATED DEVICES

2.1 COLLOCATION CONFIGURATIONS

The following devices will be collocated with the Model UNDP-1D PCI Wireless WAN Card (FCC ID: PKRNVWE760D, IC: 3229B-E760) within the Host system. The host platform in this application is the Dell Model P02E-P02E001 laptop computer, marketed under the name: Studio 1745).

Host Platform	Collocated Transmitter(s) Name/Model	Description	FCC ID	IC ID
Dell Model P02E-P02E001	WiFi 5100	802.11 a, g, n	E2K512ANHMW	1514B-512ANH
	WiFi 5300	802.11 a, g, n	E2K533ANH	1514B-533ANH
	WiMax/WiFi Link 5150	Wimax/802.11 a, g, n	PD9512ANXHD	NA
	WLan PCI-E Minicard	802.11 a, b, g draft n	QDS-BRCM1030	4324A-BRCM1030
	WLan PCI-E Minicard	802.11 a, b, g draft n	QDS-BRCM1031	4324A-BRCM1031

2.2 ANTENNA SPECIFICATIONS

The Model UNDP-1D PCI Wireless WAN Card (FCC ID: PKRNVWE760D, IC: 3229B-E760) within the host platform Dell Model P02E-P02E001 laptop computer, marketed under the name: Studio 1745), includes the following antenna types for consideration in this class II permissive change application.

Manufacturer	Model Number	Designation	Frequency Range (MHz)	Maximum Antenna Gain (dBi)
Smart Approach Co., Ltd	PE-110040	WWAN Main	824-960	-0.12
			1710-2170	2.33
Smart Approach Co., Ltd	PE-080130	WWAN Aux	824-960	-2.11
			1710-2170	-1.42
Acon	APP6P-700285	WWAN Main	824-960	0.44
			1710-2170	1.43
Acon	APP8P-700083	WWAN Aux	824-960	-1.95
			1710-2170	0.68

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

3.0 RF EXPOSURE LIMITS AND EQUATIONS

In compliance with FCC CFR 47 1.1310, the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1303 (b).

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mw/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures (f=frequency)				
30-300	61.4	0.163	1	6
300-1500	f/300	6
1500-100,000	5.0	6
(B) Limits for General Population/Uncontrolled Exposure (f=frequency)				
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

Friis Transmission Formula

Friis transmission formula:

$$P_d = (P_{out} * G) / (4\pi R^2)$$

Where,

P_d = power density (mW/cm²)

P_{out} = output power to antenna (mW)

G = gain of antenna in linear scale

R = distance between observation point and center of the radiator (cm)

The resulted power density at a distance of 20cm can be calculated as follows:

$$\text{Power Density} = (\text{EIRP} * \text{DutyCycle}) / (4\pi R^2)$$

The MPE limit for General Population/Uncontrolled Exposure is shown in the table above and can be derived as follows:

$$\text{MPE limit} = 824/1500 = 0.55\text{mW/cm}^2$$

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

4.0 STANDALONE TRANSMITTER MPE CALCULATIONS

The table below summarizes the collocation calculations for the various combinations of transmitters and antenna gains as provided by the applicant.

FCC ID	Technology	Antenna Path /TX Path Description	Operating Frequency/Band	Conducted Power (dBm)	Conducted Power (W)	Antenna Gain dBi	Duty Cycle	EIRP (dBm)	EIRP (W)	Power Density @ 20cm (mW/cm ²)	FCC MPE Limit (mW/cm ²)	Pd as % of Limit
PKRNVWE760D	CDMA1X-EVDO	Smart Approach	Cell	29.43	0.877	-0.12	1	29.31	0.853	0.170	0.549	30.9
PKRNVWE760D	CDMA1X-EVDO	Acon	Cell	29.43	0.877	0.44	1	29.87	0.971	0.193	0.549	35.2
PKRNVWE760D	CDMA1X-EVDO	Smart Approach	PCS	27.98	0.628	2.33	1	30.31	1.074	0.214	1	21.4
PKRNVWE760D	CDMA1X-EVDO	Acon	PCS	27.98	0.628	1.43	1	29.41	0.873	0.174	1	17.4
QDS-BRCM1030	WLAN	Original Grant	2.4 GHz	22.28	0.169	3.9	1	26.18	0.415	0.083	1	8.3
QDS-BRCM1031	WLAN	802.11 a Legacy	5 GHz	14.7	0.030	5.6	1	20.3	0.107	0.021	1	2.1
QDS-BRCM1031	WLAN	802.11 a Legacy	5 GHz	18	0.063	5.6	1	23.6	0.229	0.046	1	4.6
QDS-BRCM1031	WLAN	802.11 a Legacy	5 GHz	18.2	0.066	4.2	1	22.4	0.174	0.035	1	3.5
QDS-BRCM1031	WLAN	802.11n 20 MHz	5 GHz	12.9	0.019	8.6	1	21.5	0.141	0.028	1	2.8
QDS-BRCM1031	WLAN	802.11n 20 MHz	5 GHz	18.7	0.074	8.6	1	27.3	0.537	0.107	1	10.7
QDS-BRCM1031	WLAN	802.11 n 20 MHz	5 GHz	19.6	0.091	7.2	1	26.8	0.479	0.095	1	9.5
QDS-BRCM1031	WLAN	802.11 n 40 MHz	5 GHz	12.9	0.019	8.6	1	21.5	0.141	0.028	1	2.8
QDS-BRCM1031	WLAN	802.11 n 40 MHz	5 GHz	18.7	0.074	8.6	1	27.3	0.537	0.107	1	10.7
QDS-BRCM1031	WLAN	802.11 n 40 MHz	5 GHz	19.6	0.091	7.2	1	26.8	0.479	0.095	1	9.5
E2K512ANHMW	WLAN	Original Grant	2.4 GHz	18.6	0.072	3.2	1	21.8	0.151	0.030	1	3
E2K512ANHMW	WLAN	Original Grant	5 GHz	16.6	0.046	5	1	21.6	0.145	0.029	1	2.9
E2K512ANHMW	WLAN	Original Grant	5 GHz	18.5	0.071	5	1	23.5	0.224	0.045	1	4.5
E2K512ANHMW	WLAN	Original Grant	5 GHz	17.9	0.062	5	1	22.9	0.195	0.039	1	3.9
E2K533ANH	WLAN	Ethertronics Chain B	2.4 GHz	23.84	0.242	3	1	26.84	0.483	0.096	1	9.6
E2K533ANH	WLAN	Ethertronics Chain B	5 GHz	24.03	0.253	5	1	29.03	0.800	0.159	1	15.9
E2K533ANH	WLAN	Ethertronics Chain B	5 GHz	23.84	0.242	3	1	26.84	0.483	0.096	1	9.6

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

E2K533ANH	WLAN	Ethertronics Chain B	5 GHz	24.64	0.291	5	1	29.64	0.920	0.183	1	18.3
E2K533ANH	WLAN	Ethertronics Chain C	2.4 GHz	24.04	0.254	3	1	27.04	0.506	0.101	1	10.1
E2K533ANH	WLAN	Ethertronics Chain C	5 GHz	24.54	0.284	5	1	29.54	0.899	0.179	1	17.9
E2K533ANH	WLAN	Wistron Chain A	2.4 GHz	23.84	0.242	4.95	1	28.79	0.757	0.151	1	15.1
E2K533ANH	WLAN	Wistron Chain A	5 GHz	24.04	0.254	4.87	1	28.91	0.778	0.155	1	15.5
E2K533ANH	WLAN	Wistron Chain B	2.4 GHz	23.84	0.242	4.95	1	28.79	0.757	0.151	1	15.1
E2K533ANH	WLAN	Wistron Chain B	5 GHz	24.64	0.291	4.87	1	29.51	0.893	0.178	1	17.8
E2K533ANH	WLAN	Wistron Chain B	2.4 GHz	24.04	0.254	4.95	1	28.99	0.793	0.158	1	15.8
E2K533ANH	WLAN	Wistron Chain B	5 GHz	24.54	0.284	4.87	1	29.41	0.873	0.174	1	17.4
PD9512ANXHD	WiFi	Original Grant	2.4 GHz	27.67	0.585	3.24	1	30.91	1.233	0.245	1	24.5
PD9512ANXHD	WiFi	Original Grant	5 GHz	25.79	0.379	4.96	1	30.75	1.189	0.236	1	23.6
PD9512ANXHD	WiMax	Original Grant	2.4 Ghz	24.05	0.254	3.45	1	27.5	0.562	0.112	1	11.2

5.0 TRANSMITTER CO-LOCATION COMPLIANCE

Based on the compliance calculations above the combined power density of the PKRNVWE760D modular transmitter and any one combination of the other co-located transmitters does not exceed 100% of the MPE Limits

The test results contained in this report refer exclusively to the product(s) presented for testing. The test results do not cover models or products not referred herein. This test report should not be published or duplicated in whole or part without permission from the testing body and the customer.

NTS Product Integrity Laboratory, 5151-47th Street N.E. Tel: 403-568-6605, Fax: 403-568-6970