

“Novatel Wireless “ logo

NOVATEL WIRELESS™

MiFi®  
4082

Barcode 128-B “YYYYYYYYYYYYYYY”  
Text: “MEID-HEX: YYYYYYYYYYYYYY “  
YYYYYYYYYYYYYYY is modem’s 14 digit MEID-HEX  
Calibri – 6pt bold

Barcode 128-B “XXXXXXXXXXXXXXXXXX”  
Text: “MEID-DEC: XXXXXXXXXXXXXXXXXXXX “  
XXXXXXXXXXXXXXXXXX is modem’s 18 digit Decimal MEID  
Calibri – 6pt bold

Barcode 128-B “XXXXXXXXXXXXXXXXXX”  
Text: “WIMAX MAC: XX:XX:XX:XX:XX:XX “  
XXXXXXXXXXXXXXXXXX is modem’s WIMAX MAC ID  
Calibri – 6pt bold

Text:  
MODEL: MIFI4082  
FCC ID: PKRNVWMIFI4082  
IC: 3229B-MIFI4082  
Arial Black - 4pt

Text \*QUALCOMM 3G CDMA\*  
Arial Narrow – 5pt


Text \*Patents:www.nvtl.com/patents\*  
Verdana – 5pt Bold

Text \*YMMDD\*  
Date Code  
“YY” – Last 2 digits of year  
“MM” – Month  
“DD” - Day  
Arial Black – 5pt **BOLD**

“MiFi 4082” Logo

Barcode 128-B  
“XXXXXXXXXXXXXXXXXX”  
Text:  
“MEID-DEC: XXXXXXXXXXXXXXXXXXXX “  
XXXXXXXXXXXXXXXXXX is modem’s  
18 digit Decimal MEID  
Calibri – 6pt bold

Symbols for “FCC”, “CSA”,  
and “Recycling” to be displayed  
here.



## PKRNVWMIFI4081 - Label Location

The label will be located inside the battery well. When the device is packaged the battery will be located outside of the device.

