

Unit 7 Greenways Business Park Bellinger Close Chippenham Wiltshire SN15 1BN

Telephone: 01249 800100 Facsimile: 01249 800101

21<sup>st</sup> August 2008

RFI Global Services Ltd Pavillion A Ashwood Business Park Basingstoke Hampshire RG23 8BG

## RE: 2.5GHz PCI Express Mini Module FCC ID: PKTPEMAAU MPE Calculation

To Whom It May Concern,

The IPWireless PCI Express Min Module is considered to be mobile equipment and intended for operation with a minimum separation gap of 20cm between the user and the equipment, therefore the RF Exposure performance can be assessed by a Maximum Permissible Exposure (MPE) calculation.

The IPWireless PCI Express Mini module uses time division duplex (TDD) technology in normal operation with a maximum duty cycle of 33%, therefore source based averaging can be applied in the MPE calculation.

MPE Distance Calculation	5.5MHz Channel		11MHz Channel	
Antenna Gain	7	dBi	7	dBi
Line Loss	0	dB	0	dB
Antenna Gain Ratio	5.011872336		5.011872	
PCIe Mini Module Model AAU Tx Power	24	dBm	24	dBm
Output Power mW	251.19	mW	251.19	mW
Maximum EIRP (per Channel)	1258.93	mW	1258.93	mW
MPE Limit from 1.1310	1	mw/cm <sup>2</sup>	1	mw/cm <sup>2</sup>
Un-controlled/General Public Limit				
Minimum Distance to meet MPE Limit	10.01	cm	10.01	cm
(100% Duty Cycle)	3.94	inches	3.94	inches

**Table 1: 100% Duty Cycle Calculation** 

IPWireless U.K. Ltd Registered Office as above Reg. No: 4218312 VAT No: 771 3836 15



Sourced Based Duty Cycle Adjustment	5.5MHz Channel		11MHz Channel	
Total Timeslots in Frame	15		15	
Timeslots for Transmit	5		5	
Timeslots for Receive	10		10	
Percentage time transmitting in Tx timeslot	100	%	100	%
Power Control Attenuation	0	dB	0	dB
Duty Cycle Correction Factor	33.33	%	33.33	%
Minimum Distance to meet MPE Limit	5.78	cm	5.78	cm
(33.33% Duty Cycle)	2.27	inches	2.27	inches

**Table 2: Source Based Averaging Calculation** 

The calculations above show the 2.5GHz PCI Express Mini Module complies with the un-controlled /General Public limit of 1mW/cm2 at a minimum distance of 5.8cm for operation using either 5.5MHz or 11MHz channels.

Yours Faithfully

P Warburg Technical Associate IPWireless UK Ltd