



# FCC TEST REPORT

**REPORT NO.:** RF910208R02E

**MODEL NO.:** NWU11B

**TESTED:** May 3 ~ May 9, 2002

**APPLICANT:** The Linksys Group, Inc.

**ADDRESS:** 17401 Armstrong Ave., Irvine, CA 92614

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 49 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



Lab Code: 200102-0



## Table of Contents

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
4	TEST TYPES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2	TEST INSTRUMENTS .....	9
4.1.3	TEST PROCEDURES .....	10
4.1.4	TEST SETUP .....	11
4.1.5	EUT OPERATING CONDITIONS .....	12
4.1.6	TEST RESULTS .....	13
4.2	RADIATED EMISSION MEASUREMENT .....	19
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	19
4.2.2	TEST INSTRUMENTS .....	20
4.2.3	TEST PROCEDURES .....	21
4.2.4	TEST SETUP .....	22
4.2.5	EUT OPERATING CONDITIONS .....	22
4.2.6	TEST RESULTS .....	23
4.3	6dB BANDWIDTH MEASUREMENT .....	28
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	28
4.3.2	TEST INSTRUMENTS .....	28
4.3.3	TEST PROCEDURE .....	29
4.3.4	TEST SETUP .....	29
4.3.5	EUT OPERATING CONDITIONS .....	29
4.3.6	TEST RESULTS .....	30
4.4	MAXIMUM PEAK OUTPUT POWER .....	34
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	34
4.4.2	INSTRUMENTS .....	34
4.4.3	TEST PROCEDURES .....	35
4.4.4	TEST SETUP .....	35
4.4.5	EUT OPERATING CONDITIONS .....	35
4.4.6	TEST RESULTS .....	36
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	37
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	37
4.5.2	TEST INSTRUMENTS .....	37
4.5.3	TEST PROCEDURE .....	38
4.5.4	TEST SETUP .....	38
4.5.5	EUT OPERATING CONDITION .....	38
4.5.6	TEST RESULTS .....	39



4.6	BAND EDGES MEASUREMENT .....	43
4.6.1	LIMITS OF BAND EDGES MEASUREMENT .....	43
4.6.2	TEST INSTRUMENTS .....	43
4.6.3	TEST PROCEDURE .....	43
4.6.4	EUT OPERATING CONDITION.....	44
4.6.5	TEST RESULTS.....	44
4.7	ANTENNA REQUIREMENT .....	47
4.7.1	STANDARD APPLICABLE .....	47
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	47
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	48
6	INFORMATION ON THE TESTING LABORATORIES.....	50



# 1 CERTIFICATION

**PRODUCT :** Wireless USB Network Adapter  
**BRAND NAME :** Linksys  
**MODEL NO. :** NWU11B  
**APPLICANT :** The Linksys Group, Inc.  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from May 3 to May 9, 2002. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

**CHECKED BY:** Kelsey Chang **DATE:** Nov. 12, 2002  
Kelsey Chang  
**APPROVED BY:** Alan Lane **DATE:** Nov. 12, 2002  
Dr. Alan Lane  
Manager

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -11.96dBuV at 0.170MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.5dBuV at 2038.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Wireless USB Network Adapter
<b>MODEL NO.</b>	NWU11B
<b>POWER SUPPLY</b>	5VDC from Notebook
<b>MODULATION TYPE</b>	DSSS
<b>TRANSFER RATE</b>	1/2/5.5/11Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	15.86dBm
<b>ANTENNA TYPE</b>	Dipole Antenna
<b>DATA CABLE</b>	1.8m (Shielded)
<b>I/O PORTS</b>	USB port
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

- NOTE:** 1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.  
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an Wireless USB Network Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR 47 Part 15, Subpart C. (15.247)**  
**ANSI C63.4 : 1992**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP01L	TW-09C748-12800-190-B220	FCC DoC APPROVED
2	MODEM	ACEEX	1414	980020503	IFAXDM1414
3	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
3	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core

**NOTE:** All power cords of the above support units are non shielded (1.8m).





## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	847793/022	Mar. 12, 2003
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	Jul. 23, 2003
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 30, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 02, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 02, 2002
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	Jul. 23, 2003
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	Jul. 23, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 20, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 20, 2003
Shielded Room	Site 5	ADT-C05	NA
VCCI Site Registration No.	Site 5	C-1093	NA


#### NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2 "\*\*\*\*": These equipment are used for conducted telecom port test only (if tested).
- 3 The test was performed in ADT Open Site No. 5.

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

## 4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.5 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.




4.1.6 TEST RESULTS

<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	52.14	-	52.24	-	64.98	54.98	-12.74	-
2	0.228	0.10	45.98	-	46.08	-	62.52	52.52	-16.44	-
3	0.283	0.10	38.90	-	39.00	-	60.73	50.73	-21.73	-
4	0.341	0.10	37.10	-	37.20	-	59.17	49.17	-21.97	-
5	0.591	0.13	19.92	-	20.05	-	56.00	46.00	-35.95	-
6	0.935	0.19	12.49	-	12.68	-	56.00	46.00	-43.32	-

**NOTE:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	52.92	-	53.02	-	64.98	54.98	-11.96	-
2	0.227	0.10	45.80	-	45.90	-	62.57	52.57	-16.67	-
3	0.283	0.10	40.27	-	40.37	-	60.73	50.73	-20.36	-
4	0.338	0.10	35.84	-	35.94	-	59.26	49.26	-23.32	-
5	0.552	0.13	21.79	-	21.92	-	56.00	46.00	-34.08	-
6	0.626	0.14	21.80	-	21.94	-	56.00	46.00	-34.06	-

**NOTE:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	51.16	-	51.26	-	64.98	54.98	-13.72	-
2	0.228	0.10	45.34	-	45.44	-	62.52	52.52	-17.08	-
3	0.287	0.10	37.41	-	37.51	-	60.62	50.62	-23.11	-
4	0.341	0.10	36.69	-	36.79	-	59.17	49.17	-22.38	-
5	0.568	0.13	27.19	-	27.32	-	56.00	46.00	-28.68	-
6	0.666	0.14	16.11	-	16.25	-	56.00	46.00	-39.75	-

**NOTE:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	49.05	-	49.15	-	64.98	54.98	-15.83	-
2	0.228	0.10	43.56	-	43.66	-	62.52	52.52	-18.86	-
3	0.287	0.10	37.03	-	37.13	-	60.62	50.62	-23.49	-
4	0.341	0.10	35.19	-	35.29	-	59.17	49.17	-23.88	-
5	0.455	0.11	29.21	-	29.32	-	56.79	46.79	-27.47	-
6	0.685	0.15	25.43	-	25.58	-	56.00	46.00	-30.42	-

**NOTE:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.








<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.99	-	49.09	-	64.98	54.98	-15.89	-
2	0.228	0.10	43.50	-	43.60	-	62.52	52.52	-18.92	-
3	0.283	0.10	36.09	-	36.19	-	60.73	50.73	-24.54	-
4	0.341	0.10	33.52	-	33.62	-	59.17	49.17	-25.55	-
5	0.399	0.10	33.57	-	33.67	-	57.88	47.88	-24.21	-
6	0.515	0.12	27.60	-	27.72	-	56.00	46.00	-28.28	-

**NOTE:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	47.82	-	47.92	-	64.98	54.98	-17.06	-
2	0.228	0.10	42.54	-	42.64	-	62.52	52.52	-19.88	-
3	0.287	0.10	35.34	-	35.44	-	60.62	50.62	-25.18	-
4	0.341	0.10	32.21	-	32.31	-	59.17	49.17	-26.86	-
5	0.521	0.12	16.46	-	16.58	-	56.00	46.00	-39.42	-
6	0.664	0.14	15.79	-	15.93	-	56.00	46.00	-40.07	-

**NOTE:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Apr. 29, 2003
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
ANTENNA (Large Biconical)	VHBA9123	449	Dec. 10, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 02, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jul. 03, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 09, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 12, 2003
Open Field Test Site	Site 5	ADT-R05	Jul. 19, 2003
VCCI Site Registration No.	Site 5	R-1039	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.
  2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  3. "\*" = These equipment are used for the final measurement.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The test was performed in ADT Open Site No. 5.




#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5.



## 4.2.6 TEST RESULTS

<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>												
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)	
1	48.00	28.7 QP	40.00	-11.30	3.22H	7	45.46	9.44	0.79	27.00	16.76	
2	60.00	20.1 QP	40.00	-19.90	3.22H	7	40.43	5.76	0.92	27.00	20.33	
3	132.00	26.9 QP	43.50	-16.60	1.86H	140	41.50	11.16	1.24	27.00	14.60	
4	176.00	26.0 QP	43.50	-17.50	1.57H	151	42.55	9.08	1.37	27.00	16.55	
5	208.00	21.9 QP	43.50	-21.60	1.40H	282	38.06	9.40	1.45	27.00	16.16	
6	220.00	29.1 QP	46.00	-16.90	1.57H	56	44.46	10.12	1.53	27.00	15.36	
7	240.00	28.4 QP	46.00	-17.60	1.52H	3	42.32	11.41	1.67	27.00	13.92	
8	264.00	23.5 QP	46.00	-22.50	1.56H	60	35.88	12.89	1.73	27.00	12.38	
9	288.00	20.8 QP	46.00	-25.20	3.02H	7	33.08	12.88	1.83	27.00	12.29	
10	440.00	25.6 QP	46.00	-20.40	1.98H	53	33.98	16.32	2.31	27.00	8.39	
11	484.00	23.1 QP	46.00	-22.90	2.03H	9	30.70	16.96	2.44	27.00	7.61	
12	528.00	27.6 QP	46.00	-18.40	2.42H	161	34.36	17.62	2.62	27.00	6.76	
13	572.00	24.7 QP	46.00	-21.30	2.42H	310	30.66	18.25	2.79	27.00	5.96	
14	616.00	23.8 QP	46.00	-22.20	2.09H	4	29.07	18.82	2.91	27.00	5.27	
15	748.00	34.8 QP	46.00	-11.20	2.54H	254	38.32	20.14	3.34	27.00	3.52	

**NOTE:**

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.



<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	48.00	28.9 QP	40.00	-11.10	1.63V	297	45.66	9.44	0.79	27.00	16.76
2	60.00	30.7 QP	40.00	-9.30	1.63V	216	51.03	5.76	0.92	27.00	20.34
3	132.00	27.5 QP	43.50	-16.00	1.01V	3	42.10	11.16	1.24	27.00	14.60
4	144.00	26.9 QP	43.50	-16.60	1.63V	8	42.04	10.58	1.28	27.00	15.15
5	176.00	24.8 QP	43.50	-18.70	1.09V	213	41.35	9.08	1.37	27.00	16.55
6	220.00	26.3 QP	46.00	-19.70	1.04V	68	41.66	10.12	1.53	27.00	15.36
7	240.00	31.1 QP	46.00	-14.90	1.63V	8	45.02	11.41	1.67	27.00	13.93
8	440.00	20.9 QP	46.00	-25.10	1.43V	269	29.28	16.32	2.31	27.00	8.38
9	484.00	27.3 QP	46.00	-18.70	1.71V	55	34.90	16.96	2.44	27.00	7.61
10	528.00	32.8 QP	46.00	-13.20	1.17V	181	39.56	17.62	2.62	27.00	6.76
11	572.00	22.0 QP	46.00	-24.00	1.23V	254	27.96	18.25	2.79	27.00	5.96
12	616.00	27.3 QP	46.00	-18.70	1.72V	133	32.57	18.82	2.91	27.00	5.27
13	748.00	28.9 QP	46.00	-17.10	1.75V	95	32.42	20.14	3.34	27.00	3.53

#### NOTE:

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.





<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	48.3 AV	54.00	-5.70	1.23H	348	53.13	25.20	4.86	34.90	4.84
2	2038.00	50.4 PK	74.00	-23.60	1.23H	2	55.19	25.20	4.86	34.90	4.84
3	*2412.00	98.7 PK	-	-	1.77H	2	66.50	27.11	5.10	0.00	-32.21
4	*2412.00	95.3 AV	-	-	1.77H	2	63.10	27.11	5.10	0.00	-32.21
5	2580.00	47.5 AV	54.00	-6.50	1.23H	2	49.50	27.75	5.14	34.91	2.03
6	2580.00	50.4 PK	74.00	-23.60	1.13H	5	52.40	27.75	5.14	34.91	2.03
7	4076.00	44.6 PK	74.00	-29.40	1.13H	15	42.20	30.13	6.78	34.52	-2.39

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	52.6 PK	74.00	-21.4	1.75V	6	57.44	25.20	4.86	34.90	4.84
2	2038.00	51.5 AV	54.00	-2.5	1.75V	6	56.34	25.20	4.86	34.90	4.84
3	*2412.00	100.3 PK	-	-	1.75V	6	68.09	27.11	5.10	0.00	-32.21
4	*2412.00	95.0 AV	-	-	1.75V	6	62.79	27.11	5.10	0.00	-32.21
5	2580.00	45.0 PK	74.00	-29.0	1.75V	6	47.03	27.75	5.14	34.91	2.03
6	4076.00	38.2 PK	74.00	-35.8	1.75V	6	35.81	30.13	6.78	34.52	-2.39

**NOTE:**

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.
6. “ \* “ = Fundamental frequency



<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	50.5 PK	74.00	-23.50	1.18H	256	55.00	25.41	4.96	34.90	4.53
2	*2437.00	102.6 PK	-	-	1.48H	259	70.20	27.33	5.08	0.00	-32.40
3	*2437.00	95.1 AV	-	-	1.48H	211	62.70	27.33	5.08	0.00	-32.40
4	2630.00	48.0 PK	74.00	-26.00	1.00H	133	49.90	27.83	5.17	34.92	1.93
5	4126.00	42.8 PK	74.00	-31.20	1.06H	136	40.30	30.32	6.70	34.56	-2.46

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	51.7 PK	74.00	-22.30	1.00V	1	56.28	25.41	4.96	34.90	4.53
2	*2437.00	94.1 PK	-	-	1.82V	89	61.70	27.33	5.08	0.00	-32.40
3	*2437.00	85.3 AV	-	-	1.82V	149	52.90	27.33	5.08	0.00	-32.40
4	2630.00	38.4 PK	74.00	-35.60	1.04V	3	40.30	27.83	5.17	34.92	1.93
5	4126.00	44.8 PK	74.00	-29.20	1.02V	3	42.38	30.32	6.70	34.56	-2.46

#### NOTE:

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.
6. “ \* “ = Fundamental frequency



<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Bunny Yao	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	52.1 PK	74.00	-21.90	1.00H	13	56.40	25.62	5.02	34.90	4.26
2	2088.00	50.0 AV	54.00	-4.00	1.00H	6	54.30	25.62	5.02	34.90	4.27
3	*2462.00	96.3 PK	-	-	1.00H	3	63.90	27.33	5.08	0.00	-32.40
4	*2462.00	89.7 AV	-	-	1.00H	213	57.30	27.33	5.08	0.00	-32.40
5	4176.00	41.5 PK	74.00	-32.50	2.22H	240	39.00	30.41	6.68	34.58	-2.51

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	49.7 PK	74.00	-24.30	1.00V	64	54.00	25.62	5.02	34.90	4.26
2	*2462.00	99.2 PK	-	-	1.19V	132	66.80	27.33	5.08	0.00	-32.40
3	*2462.00	92.7 AV	-	-	1.19V	54	60.30	27.33	5.08	0.00	-32.40
4	2680.00	44.3 PK	74.00	-29.70	1.00V	217	46.10	28.00	5.15	34.94	1.79
5	4176.00	43.2 PK	74.00	-30.80	1.56V	138	40.70	30.41	6.68	34.58	-2.51

#### NOTE:

- Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
- Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
- Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- “ \* ” = Fundamental frequency



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 25, 2003


Notes:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 TEST SETUP



#### 4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.3.6 TEST RESULTS

<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 65%RH, 1005 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	9.78	0.5	PASS
6	2437	9.90	0.5	PASS
11	2462	10.10	0.5	PASS




CH1






CH6







CH11





#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
Peak Power Sensor	NRV-Z32	100013	Feb. 21, 2003
Power Meter	NRVS	100026	Feb. 21, 2003


- NOTE:** 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



#### 4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the peak power meter.

#### 4.4.4 TEST SETUP



#### 4.4.5 EUT OPERATING CONDITIONS

Same as Item 3.4.5



## 4.4.6 TEST RESULTS

<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 65%RH, 1005 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	15.86	30	PASS
6	2437	15.82	30	PASS
11	2462	15.10	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 25, 2003


- NOTE:**1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 TEST SETUP



#### 4.5.5 EUT OPERATING CONDITION

Same as Item 3.4.5




## 4.5.6 TEST RESULTS

<b>EUT</b>	Wireless USB Network Adapter	<b>MODEL</b>	NWU11B
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 65%RH, 1005 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-7.35	8	PASS
6	2437	-7.38	8	PASS
11	2462	-7.65	8	PASS




CH1








CH6





CH11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 25, 2003

#### NOTE:

- 1.The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




#### 4.6.4 EUT OPERATING CONDITION


Same as Item 3.4.5

#### 4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:** The band edge emission plot on the following 2 pages shows 47.03dB delta between carrier maximum power and local maximum emission in restrict band (2.5201GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.6 (Page 26) is 92.7dBuV/m, so the maximum field strength in restrict band is  $92.7 - 47.03 = 45.67$  dBuV/m which is under 54 dBuV/m limit.







## **4.7 ANTENNA REQUIREMENT**

### **4.7.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.7.2 ANTENNA CONNECTED CONSTRUCTION**


The antenna used in this product is Dipole Antenna. There is no antenna connector. The maximum Gain of the antenna is 2.14 dBi only.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST





### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.