



FCC TEST REPORT

REPORT NO.: RF910208R02G

MODEL NO.: WUSB11 ver. 2.6

RECEIVED: Mar. 5, 2003

TESTED: Mar. 6, 2003

APPLICANT: THE LINKSYS GROUP, INC.

ADDRESS: 17401 Armstrong Ave. Irvine, CA 92614

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 32 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION.....	3
2	SUMMARY OF TEST RESULTS	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF EUT	5
3.2	DESCRIPTION OF TEST MODES	6
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	6
3.4	DESCRIPTION OF SUPPORT UNITS.....	7
4	TEST TYPES AND RESULTS	8
4.1	CONDUCTED EMISSION MEASUREMENT.....	8
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
4.1.2	TEST INSTRUMENTS.....	8
4.1.3	TEST PROCEDURES	9
4.1.4	TEST SETUP.....	9
4.1.5	EUT OPERATING CONDITIONS	10
4.1.6	TEST RESULTS	11
4.2	RADIATED EMISSION MEASUREMENT.....	17
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	17
4.2.2	TEST INSTRUMENTS.....	18
4.2.3	TEST PROCEDURES	19
4.2.4	TEST SETUP.....	20
4.2.5	EUT OPERATING CONDITIONS	20
4.2.6	TEST RESULTS	21
4.3	BAND EDGES MEASUREMENT.....	26
4.3.1	LIMITS OF BAND EDGES MEASUREMENT.....	26
4.3.2	TEST INSTRUMENTS.....	26
4.3.3	TEST PROCEDURE.....	26
4.3.4	EUT OPERATING CONDITION.....	27
4.3.5	TEST RESULTS	27
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	30
6	INFORMATION ON THE TESTING LABORATORIES.....	32



1 CERTIFICATION

PRODUCT : 11Mbps Wireless LAN USB Adapter
BRAND NAME : Linksys
MODEL NO. : WUSB11 ver. 2.6
APPLICANT : THE LINKSYS GROUP, INC.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility on Mar. 6, 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY: Rennie Wang, **DATE:** March 7, 2003
Rennie Wang

APPROVED BY: Dr. Alan Lane for, **DATE:** March 7, 2003
Dr. Alan Lane
Manager



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is -13.78dBuV at 0.17MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	NA	NA
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	NA	NA
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -3.60dBuV at 2038.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	NA	NA
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	11Mbps Wireless LAN USB Adapter
MODEL NO.	WUSB11 ver. 2.6
POWER SUPPLY	5VDC from Notebook
MODULATION TYPE	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	NA
ANTENNA TYPE	Monopole Antenna
DATA CABLE	1.8m (Shielded)
I/O PORTS	USB port
ASSOCIATED DEVICES	NA

NOTE:

1. This report is prepared for FCC class II permissive change. The differences compared with the original one are:
 - a. Remove the ferrite cores from USB and antenna cable.
 - b. Remove the copper foil from the PCB board and cover.
2. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

- NOTE:** 1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an 11Mbps Wireless LAN USB Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR 47 Part 15, Subpart C. (15.247)

ANSI C63.4-1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP01L	TW-09C748-12800-190-B220	FCC DoC APPROVED
2	PRINTER	HP	2225C+	3123S97230	DSI6XU2225
3	MODEM	ACEEX	1414	980020510	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core.
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESHS30	828109/007	July 03, 2003
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	839135/006	July 02, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Nov. 29, 2003
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Nov. 29, 2003
EMCO-L.I.S.N. (for peripheral)	3825/2	9204-1964	July 02, 2003
Software	Cond-V2M1	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C02.01	July 5, 2003
HP Terminator (For EMCO LISN)	11593A	E1-01-298	Feb. 23, 2004
HP Terminator (For EMCO LISN)	11593A	E1-01-299	Feb. 23, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. "*": These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Shielded Room No. 2.
 4. The VCCI Site Registration No. is C-240.

4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

4.1.4 TEST SETUP



- Note:**
- 1. Support units were connected to second LISN.
 - 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.




4.1.6 TEST RESULTS

EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	20 deg. C, 82%RH, 1005 hPa	TESTED BY: Steven Lu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	50.91	-	51.01	-	64.79	54.79	-13.78	-
2	0.228	0.10	44.31	-	44.41	-	62.52	52.52	-18.11	-
3	0.287	0.10	38.92	-	39.02	-	60.62	50.62	-21.60	-
4	3.555	0.36	28.26	-	28.62	-	56.00	46.00	-27.38	-
5	20.516	1.11	31.09	-	32.20	-	60.00	50.00	-27.80	-
6	27.133	1.16	29.67	-	30.83	-	60.00	50.00	-29.17	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	20 deg. C, 82%RH, 1005 hPa	TESTED BY: Steven Lu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	49.56	-	49.66	-	64.79	54.79	-15.13	-
2	0.228	0.10	42.53	-	42.63	-	62.52	52.52	-19.89	-
3	0.287	0.10	37.43	-	37.53	-	60.62	50.62	-23.09	-
4	3.382	0.27	31.66	-	31.93	-	56.00	46.00	-24.07	-
5	20.461	0.79	31.18	-	31.97	-	60.00	50.00	-28.03	-
6	26.863	0.66	28.34	-	29.00	-	60.00	50.00	-31.00	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	20 deg. C, 82%RH, 1005 hPa	TESTED BY: Steven Lu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	50.45	-	50.55	-	64.79	54.79	-14.24	-
2	0.460	0.11	32.01	-	32.12	-	56.69	46.69	-24.57	-
3	0.804	0.17	23.67	-	23.84	-	56.00	46.00	-32.16	-
4	3.559	0.36	27.56	-	27.92	-	56.00	46.00	-28.08	-
5	20.566	1.11	30.81	-	31.92	-	60.00	50.00	-28.08	-
6	29.313	1.11	28.25	-	29.36	-	60.00	50.00	-30.64	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	20 deg. C, 82%RH, 1005 hPa	TESTED BY: Steven Lu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	48.18	-	48.28	-	64.79	54.79	-16.51	-
2	0.232	0.10	40.51	-	40.61	-	62.38	52.38	-21.77	-
3	0.688	0.15	25.03	-	25.18	-	56.00	46.00	-30.82	-
4	4.023	0.30	29.01	-	29.31	-	56.00	46.00	-26.69	-
5	13.348	0.47	30.77	-	31.24	-	60.00	50.00	-28.76	-
6	20.578	0.79	29.19	-	29.98	-	60.00	50.00	-30.02	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	20 deg. C, 82%RH, 1005 hPa	TESTED BY: Steven Lu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	49.18	-	49.28	-	64.79	54.79	-15.51	-
2	0.232	0.10	42.75	-	42.85	-	62.38	52.38	-19.53	-
3	0.287	0.10	37.25	-	37.35	-	60.62	50.62	-23.27	-
4	3.109	0.31	28.53	-	28.84	-	56.00	46.00	-27.16	-
5	13.301	0.73	30.56	-	31.29	-	60.00	50.00	-28.71	-
6	21.648	1.13	29.29	-	30.42	-	60.00	50.00	-29.58	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	20 deg. C, 82%RH, 1005 hPa	TESTED BY: Steven Lu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	47.96	-	48.06	-	64.79	54.79	-16.73	-
2	0.232	0.10	40.45	-	40.55	-	62.38	52.38	-21.83	-
3	0.287	0.10	35.73	-	35.83	-	60.62	50.62	-24.79	-
4	4.203	0.30	30.38	-	30.68	-	56.00	46.00	-25.32	-
5	13.527	0.47	30.72	-	31.19	-	60.00	50.00	-28.81	-
6	20.387	0.79	29.76	-	30.55	-	60.00	50.00	-29.45	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Apr. 29, 2003
* HP Preamplifier	8449B	3008A01201	Dec. 01, 2003
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
*Spectrum Analyzer	8593E	3926A04191	Mar. 28, 2003
*Test Receiver	ES17	838496/016	Feb. 23, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Nov. 22, 2003
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 02, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 03, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 09, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	ADT_Radiate d_V5.09	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jul. 11. 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 11. 2003

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

2. "*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 5.
5. The VCCI Site Registration No. is R-1039.




4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5



4.2.6 TEST RESULTS

EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.00	28.5 QP	43.50	-15.00	1.02 H	62	15.80	12.70
2	144.00	29.3 QP	43.50	-14.20	1.26 H	102	17.40	11.90
3	219.99	34.9 QP	46.00	-11.10	1.38 H	87	22.10	12.80
4	240.02	31.1 QP	46.00	-14.90	1.34 H	43	16.40	14.70
5	307.99	30.2 QP	46.00	-15.80	1.25 H	173	13.30	16.90
6	483.99	28.1 QP	46.00	-17.90	1.06 H	82	7.30	20.70
7	528.38	28.3 QP	46.00	-17.70	1.11 H	170	7.20	21.10
8	747.99	35.7 QP	46.00	-10.30	1.32 H	14	11.60	24.10
9	835.99	30.8 QP	46.00	-15.20	1.43 H	266	5.70	25.00

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	120.02	33.0 QP	43.50	-10.50	1.28 V	179	19.50	13.50
2	132.03	37.0 QP	43.50	-6.50	1.21 V	194	24.30	12.70
3	144.02	31.0 QP	43.50	-12.50	1.25 V	157	19.10	11.90
4	220.03	26.9 QP	46.00	-19.10	1.29 V	3	14.10	12.80
5	240.02	33.1 QP	46.00	-12.90	1.24 V	173	18.40	14.70
6	308.00	28.6 QP	46.00	-17.40	1.15 V	90	11.70	16.90
7	528.07	27.7 QP	46.00	-18.30	1.53 V	145	6.50	21.10
8	615.97	27.9 QP	46.00	-18.10	1.29 V	153	5.10	22.70
9	747.97	33.9 QP	46.00	-12.10	1.08 V	341	9.80	24.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2038.00	50.9 PK	74.00	-23.10	1.53 H	73	19.00	31.90
1	2038.00	48.6 AV	54.00	-5.40	1.53 H	73	16.70	31.90
2	*2412.00	103.0 PK			1.09 H	143	70.30	32.80
2	*2412.00	98.5 AV			1.09 H	143	65.80	32.80
3	4076.00	46.6 PK	74.00	-27.40	1.30 H	326	11.30	35.20
4	4824.00	55.1 PK	74.00	-18.90	1.43 H	52	18.10	36.90
4	4824.00	44.9 AV	54.00	-9.10	1.43 H	52	7.90	35.20
5	6114.00	49.2 PK	74.00	-24.80	1.18 H	301	10.70	38.50
6	7236.00	54.3 PK	74.00	-19.70	1.52 H	34	12.80	41.40
6	7236.00	45.4 AV	54.00	-8.60	1.52 H	34	4.00	36.90
7	9647.00	57.2 PK	74.00	-16.80	1.36 H	27	13.80	43.40
7	9647.00	46.3 AV	54.00	-7.70	1.36 H	27	2.90	38.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2038.00	54.2 PK	74.00	-19.80	1.01 V	24	22.30	31.90
1	2038.00	50.4 AV	54.00	-3.60	1.01 V	24	18.50	31.90
2	*2412.00	108.4 PK			1.02 V	45	75.70	32.80
2	*2412.00	104.0 AV			1.02 V	45	71.30	32.80
3	4076.00	46.6 PK	74.00	-27.40	1.46 V	94	11.30	35.20
4	4824.00	47.8 PK	74.00	-26.20	1.02 V	46	10.80	36.90
5	6114.00	48.7 PK	74.00	-25.30	1.33 V	54	10.20	38.50
6	7236.00	56.7 PK	74.00	-17.30	1.41 V	15	15.20	41.40
6	7236.00	46.5 AV	54.00	-7.50	1.41 V	15	5.10	41.40
7	9648.00	58.1 PK	74.00	-15.90	1.02V	45	14.70	43.40
7	9648.00	45.8 AV	54.00	-8.20	1.02 V	45	2.40	43.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2063.00	51.3 PK	74.00	-22.70	1.45 H	64	19.40	32.00
1	2063.00	40.1 AV	54.00	-13.90	1.45 H	64	8.10	32.00
2	*2437.00	103.1 PK			1.11 H	231	70.30	32.80
2	*2437.00	98.6 AV			1.11 H	231	65.80	32.80
3	4126.00	46.1 PK	74.00	-27.90	1.02 H	54	10.80	35.30
4	4874.00	47.9 PK	74.00	-26.10	1.01 H	35	10.70	37.10
5	6188.00	48.5 PK	74.00	-25.50	1.31 H	80	9.80	38.70
6	7310.00	52.0 PK	74.00	-22.00	1.48 H	325	10.40	41.50
6	7310.00	42.4 AV	54.00	-11.60	1.48 H	325	0.90	35.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2063.00	50.9 PK	74.00	-23.10	1.01 V	24	18.90	32.00
1	2063.00	40.3 AV	54.00	-13.70	1.01 V	24	8.30	32.00
2	*2437.00	109.1 PK			1.00 V	207	76.30	32.80
2	*2437.00	104.1 AV			1.00 V	207	71.30	32.80
3	4126.00	45.7 PK	74.00	-28.30	1.25 V	74	10.40	35.30
4	4874.00	48.2 PK	74.00	-25.80	1.64 V	327	11.00	37.10
5	6189.00	48.9 PK	74.00	-25.10	1.37 V	351	10.20	38.70
6	7310.00	52.4 PK	74.00	-21.60	1.36 V	13	10.90	41.50
6	7310.00	43.4 AV	54.00	-10.60	1.36 V	13	1.90	35.30
7	9748.00	57.1 PK	74.00	-16.90	1.08 V	156	13.80	43.30
7	9748.00	47.8 AV	54.00	-6.20	1.08 V	156	4.50	37.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps Wireless LAN USB Adapter	MODEL	WUSB11 ver. 2.6
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2088.00	47.3 PK	74.00	-26.70	1.85 H	39	15.30	32.00
2	*2462.00	104.7 PK			1.06 H	47	71.80	32.90
2	*2462.00	90.2 AV			1.06 H	47	57.30	32.00
3	4176.00	45.8 PK	74.00	-28.20	1.09 H	142	10.40	35.30
4	4924.00	47.9 PK	74.00	-26.10	1.40 H	31	10.50	37.30
5	6263.00	47.9 PK	74.00	-26.10	1.16 H	304	9.00	38.90
6	7386.00	52.3 PK	74.00	-21.70	1.14 H	81	10.60	41.70
6	7386.00	42.5 AV	54.00	-11.50	1.14 H	81	0.80	32.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2088.00	51.1 PK	74.00	-22.90	1.02 V	65	19.10	32.00
1	2088.00	48.8 AV	54.00	-5.20	1.02 V	65	16.80	32.00
2	*2462.00	111.5 PK			1.16 V	32	78.60	32.90
2	*2462.00	100.4 AV			1.16 V	32	67.60	32.90
3	4176.00	45.9 PK	74.00	-28.10	1.01 V	74	10.60	35.30
4	4924.00	50.3 PK	74.00	-23.70	1.32 V	352	12.90	37.30
5	6263.00	49.0 PK	74.00	-25.00	1.19 V	152	10.10	38.90
6	7387.00	52.6 PK	74.00	-21.40	1.15 V	7	10.90	41.70
6	7387.00	42.5 AV	54.00	-11.50	1.15 V	7	0.80	37.30
7	9858.00	56.7 PK	74.00	-17.30	1.26 V	35	13.50	43.20
7	9858.00	48.5 AV	54.00	-5.50	1.26 V	35	5.30	38.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



4.3 BAND EDGES MEASUREMENT

4.3.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 24, 2003

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




4.3.4 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 48.63dB delta between carrier maximum power and local maximum emission in restrict band (2.48389GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.6 (Page 25) is 100.4dBuV/m, so the maximum field strength in restrict band is $100.4 - 48.63 = 51.77$ dBuV/m which is under 54 dBuV/m limit.






5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.