

TABLE OF CONTENTS

APPLICANT: TRAINERS WAREHOUSE

FCC ID: PKXWT2000

TEST REPORT CONTAINING:

PAGE 1	TEST EQUIPMENT LIST & TEST PROCEDURE
PAGE 2	TEST PROCEDURE CONTD.
PAGE 3	RADIATION INTERFERENCE TEST DATA
PAGE 4	OCCUPIED BANDWIDTH TEST DATA
PAGE 5	OCCUPIED BANDWIDTH PLOT

EXHIBIT ATTACHMENTS:

EXHIBIT 1	BLOCK DIAGRAM
EXHIBIT 2	SCHEMATIC
EXHIBIT 3A-3E	INSTRUCTION MANUAL
EXHIBIT 4	FCC ID LABEL SAMPLE
EXHIBIT 5	SKETCH OF FCC ID LABEL LOCATION
EXHIBIT 6	TOP VIEW EXTERNAL PHOTO
EXHIBIT 7	BOTTOM VIEW EXTERNAL PHOTO
EXHIBIT 8	COMPONENT SIDE INTERNAL PHOTO
EXHIBIT 9	COPPER SIDE INTERNAL PHOTO
EXHIBIT 10	CIRCUIT DESCRIPTION
EXHIBIT 11	TEST SET UP PHOTO

APPLICANT: TRAINERS WAREHOUSE

FCC ID: PKXWT2000

REPORT #: T\TRAINERS\155ZU1\155ZU1RPT.doc

PAGE: TABLE OF CONTENTS LIST

APPLICANT: TRAINERS WAREHOUSE
FCC ID: PKXWT2000

TEST EQUIPMENT LIST

1. Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 10/17/99
2. Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3. Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
4. Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
5. Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
6. Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319
7. 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
8. Horn 40-60GHz: ATM Part #19-443-6R
9. Line Impedance Stabilization Network: Electro-Metrics Model
ANS-25/2, S/N 2604 Cal. 2/9/00
10. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
11. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
12. Peak Power Meter: HP Model 8900C, S/N 2131A00545
13. Open Area Test Site #1-3meters Cal. 12/22/99
14. Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
15. Signal Generator: HP 8614A, S/N 2015A07428
16. Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N
9706-1211 Cal. 6/10/00
17. Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153
Cal. 11/24/99
18. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
19. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
20. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
21. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 72°F with a humidity of 21%.

REPORT #: T\TRAINERS\155ZU1\155ZU1RPT.doc
PAGE #: 1

TEST PROCEDURES CONTD.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings were converted to average readings based on the duration of "ON" time.

Measurements were made by TIMCO ENGINEERING INC. at the registered open field test site located at 849 N.W. State Road 45, Newberry, FL 32669.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANTENNA & GROUND:

This unit uses the PCB inductor as the antenna. There is no provision for an external antenna.

APPLICANT: TRAINERS WAREHOUSE
FCC ID: PKXWT2000
REPORT #: T\TRAINERS\155ZU1\155ZU1RPT.doc
PAGE #: 2

APPLICANT: TRAINERS WAREHOUSE
FCC ID: PKXWT2000

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.231

REQUIREMENTS:

Fundamental Frequency MHz	Field Strength of Fundamental dBuV	Field Strength of Harmonics and Spurious Emissions (dBuV/m @ 3m)
40.66 to 40.70	67.04	47.04
70 to 130	61.94	41.94
130 to 174	61.94 to 71.48	41.94 to 51.48
174 to 260	71.48	51.48
260 to 470	71.48 to 81.94	51.48 to 61.94
470 and above	81.94	61.94

THE LIMIT FOR AVERAGE FIELD STRENGTH dBuV/m FOR THE FUNDAMENTAL FREQUENCY= 75.62 dBuV/m. NO FUNDAMENTAL IS ALLOWED IN THE RESTRICTED BANDS.

THE LIMIT FOR AVERAGE FIELD STRENGTH dBuV/m FOR THE HARMONICS AND SPURIOUS FREQUENCIES = 55.62 dBuV/m. SPURIOUS IN THE RESTRICTED BANDS MUST BE LESS THAN 54dBuV/m OR 15.209.

TEST DATA:

EMISSION FREQ. MHz	METER READING @ 3m dBuV	COAX LOSS dB	ACF dB	PEAK FIELD STRNGTH dBuV/m	AVERAGE FIELD STRENGTH dBuV/m	MARGIN dB	ANT.
315.00	57.10	1.40	15.16	73.66	73.66	1.96	H
630.00	24.50	1.60	20.76	46.86	46.86	15.08	H
1260.00	32.40	1.00	25.04	58.44	58.44	3.50	H
1575.00R	12.70	1.00	26.30	40.00	40.00	14.00	H
316.60	56.50	1.40	15.10	73.00	73.00	5.62	H
633.00	21.50	1.60	20.83	43.93	43.93	18.01	H
1267.00	31.70	1.00	25.07	57.77	57.77	4.17	H
1583.00R	11.60	1.00	26.33	38.93	38.93	15.07	H

SAMPLE CALCULATION OF LIMIT @ 303 MHz:

(470 - 260)Mhz = 210 MHz
(12500 - 3750)uV/m = 8750 uV/m
8750uV/m/210MHz = 41.67 uV/m/MHz
(303-260)MHz = 43 MHz
43 MHz * 41.67 uV/m/MHz = 1791.81 uV/m
(1791.81 + 3750)uV/m = 5541.81 uV/m limit @ 303 MHz

The transmitter ceases transmitting when the button is released.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: J. SCOGLIO DATE TESTED: MARCH 26, 2001

REPORT #: T\TRAINERS\155ZU1\155ZU1RPT.doc

PAGE #: 3

APPLICANT: TRAINERS WAREHOUSE

FCC ID: PKXWT2000

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.231(C)

REQUIREMENTS: The bandwidth of the emission shall be no wider than .25% of the center frequency for devices operating between 70 and 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

$$315 * .0025 = 0.7875 \text{ MHz}$$
$$0.7875 \text{ MHz}/2 = +/- 0.3938$$

THE GRAPH ON THE FOLLOWING PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the plot on the following page was generated. The vertical scale is set to 10 dB per division: the horizontal scale is set to 100 kHz per division.

TEST RESULTS: The unit meets the FCC requirements.

PERFORMED BY: J. SCGLIO

DATE: MARCH 26, 2001

APPLICANT: TRAINERS WAREHOUSE
FCC ID: PKXWT2000
REPORT #: T\TRAINERS\155ZU1\155ZU1RPT.doc
PAGE #: 4

