



# MEASUREMENT REPORT

## FCC PART 15.209

---

**FCC ID:** PLE-GA-9660B  
**APPLICANT:** Gigastone Corp  
**Application Type:** Certification  
**Product:** Dual Coil Fast Wireless Charger  
**Model No.:** GA-9660B  
**Serial Model:** GA-9660  
**Brand Name:** Gigastone  
**FCC Classification:** DCD-Part 15 Low Power Transmitter Below 1705 kHz  
**FCC Rule Part(s):** Part 15.209  
**Test Procedure(s):** ANSI C63.10-2013  
**Test Date:** September 10 ~ 28, 2018

Tested By : *Fran Chen*  
( Fran Chen )  
Reviewed By : *Paddy Chen*  
( Paddy Chen )  
Approved By : *Chenz Ker*  
( Chenz Ker )



The test results only relate to the tested sample.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
1809TW0110-U1	1.0	Original Report	2018-09-28	

# CONTENTS

Description	Page
<b>§2.1033 General Information.....</b>	<b>5</b>
<b>1. INTRODUCTION .....</b>	<b>6</b>
1.1. Scope .....	6
1.2. MRT Test Location .....	6
<b>2. PRODUCT INFORMATION.....</b>	<b>7</b>
2.1. Equipment Description .....	7
2.2. Test Mode.....	7
2.3. Test Software .....	8
2.4. Test Configuration .....	8
2.5. EMI Suppression Device(s)/Modifications.....	8
2.6. Labeling Requirements .....	8
<b>3. DESCRIPTION of TEST .....</b>	<b>9</b>
3.1. Evaluation Procedure.....	9
3.2. AC Line Conducted Emissions.....	9
3.3. Radiated Emissions .....	10
<b>4. ANTENNA REQUIREMENTS .....</b>	<b>11</b>
<b>5. TEST EQUIPMENT CALIBRATION DATE .....</b>	<b>12</b>
<b>6. MEASUREMENT UNCERTAINTY .....</b>	<b>13</b>
<b>7. TEST RESULT .....</b>	<b>14</b>
7.1. Summary.....	14
7.2. Radiated Spurious Emissions and Field Strength of Fundamental Emissions Measurement.....	15
7.2.1. Test Limit .....	15
7.2.2. Test Procedure Used.....	15
7.2.3. Test Setup .....	17
7.2.4. Test Result.....	18
7.3. 20dB Bandwidth Measurement .....	26
7.3.1. Test Limit .....	26
7.3.2. Test Procedure Used.....	26
7.3.3. Test Setting.....	26
7.3.4. Test Setup .....	26
7.3.5. Test Result.....	27
7.4. AC Conducted Emissions Measurement .....	28

7.4.1.	Test Limit .....	28
7.4.2.	Test Setup .....	28
7.4.3.	Test Result.....	29
<b>8.</b>	<b>CONCLUSION .....</b>	<b>33</b>

## §2.1033 General Information

<b>Applicant</b>	Gigastone Corp
<b>Applicant Address</b>	12F, No. 480, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C
<b>Manufacturer</b>	Futurepath Technology (Shenzhen) Co., Ltd.
<b>Manufacturer Address</b>	2F, Unit13, Longbi Industrial Park, Jihua Road, Bantian, Longgang District, ShenZhen, China
<b>Test Site</b>	MRT Technology (Taiwan) Co., Ltd
<b>Test Site Address</b>	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
<b>MRT FCC Registration No.</b>	291082
<b>FCC Rule Part(s)</b>	Part 15.209
<b>Model No.</b>	GA-9660B
<b>Test Device Serial No.</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering

### Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Film.
2. MRT facility is an IC registered (MRT Reg. No. 21723-1) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


# 1. INTRODUCTION

## 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	Dual Coil Fast Wireless Charger
Model No.	GA-9660B
Serial Model	GA-9660
Brand Name	Gigastone
Frequency Range	110kHz ~ 205kHz
Modulation	ASK
Antenna Type	Loop
Specification	Input: DC 5V/2A / DC 9V/1.8A Output Power: Max 10W

Model Difference: The different of models only for marketing different, the other was the same.

### 2.2. Test Mode

Test Mode	Mode 1: Transmit by DC 5V
	Mode 2: Transmit by DC 9V

### **2.3. Test Software**

N/A.

### **2.4. Test Configuration**

The **Dual Coil Fast Wireless Charger** , ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

### **2.5. EMI Suppression Device(s)/Modifications**

No EMI suppression device(s) were added and/or no modifications were made during testing.

### **2.6. Labeling Requirements**

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.



### 3. DESCRIPTION of TEST

#### 3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) were used in the measurement of the **Dual Coil Fast Wireless Charger**.

**Deviation from measurement procedure.....None**

#### 3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.4.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

Radiated Emissions test results are shown in Section 7.2.

## 4. ANTENNA REQUIREMENTS

### §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of **Dual Coil Fast Wireless Charger** is **permanently attached**.
- There are no provisions for connection to an external antenna.

### **Conclusion:**

The **Dual Coil Fast Wireless Charger** unit complies with the requirement of §15.203.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2019/3/20
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2019/5/18
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2019/3/19

### Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2019/5/22
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2019/3/19
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2019/4/24
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2019/4/24
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2019/4/23
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2019/4/23
Broadband Preampfier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2019/4/23
Cable	HUBERSUHNER	SF106	MRTTWA00010	1 year	2019/5/18
Cable	Rosnol	K1K50-UP0264- K1K50-4M	MRTTWA00012	1 year	2019/7/30

### Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement – SR2</b>	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ):	
150kHz~30MHz:	2.42dB
<b>Conducted Measurement– SR1</b>	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.3dB	
<b>Radiated Emission Measurement – AC1</b>	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ):	
Horizontal:	9K~30MHz: 4.14dB
	30MHz~1GHz: 4.22dB
	1GHz~40GHz: 4.05dB
Vertical:	9K~30MHz: 4.14dB
	30MHz~1GHz: 3.37dB
	1GHz~40GHz: 4.08dB

## 7. TEST RESULT

### 7.1. Summary

**Product Name:** Dual Coil Fast Wireless Charger

**FCC Classification:** DCD-Part 15 Low Power Transmitter Below 1705 kHz

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.209	Radiated Spurious Emissions and Field Strength of Fundamental Emissions	FCC 15.209 limits	Radiated	Pass	Section 7.2
2.1049	20dB Bandwidth	N/A		Pass	Section 7.3
15.207	AC Conducted Emissions 150kHz - 30MHz	FCC 15.207 limits	Line Conducted	Pass	Section 7.4

#### Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) and Antenna polarization (H,V) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

## 7.2. Radiated Spurious Emissions and Field Strength of Fundamental Emissions Measurement

### 7.2.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.209 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note : The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

### 7.2.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.2.3 (quasi-peak measurements)

ANSI C63.10-2013 - Section 11.12.2.4 (peak power measurements)

ANSI C63.10-2013 - Section 11.12.2.5 (average power measurements)

## Test Setting

### Peak Power Measurement

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3 × RBW
4. Detector = peak
5. Sweep time = auto couple


**Table 1 - RBW as a function of frequency**

Frequency	RBW
9 kHz ~ 150 kHz	200 Hz ~ 300 Hz
0.15 MHz ~ 30 MHz	9 kHz ~ 10 kHz
30 MHz ~ 1000 MHz	100 kHz ~ 120 kHz
> 1000 MHz	1 MHz




### 7.2.3. Test Setup

#### 9kHz ~ 30MHz Test Setup:




#### 30MHz ~ 1GHz Test Setup:



**7.2.4. Test Result**

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	FMZB 1519B (9KHz~30MHz)	Temp. / Humidity	25°C / 57%
Polarity	--	Site / Test Engineer	AC1 / Fran
Test Mode	Mode1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	0.12426	60.39	18.57	78.96	-26.75	105.71	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. According to §15.31, 3m Limit = 300 Limit + 40log(300/3) or 30 Limit + 40log(30/3).

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	FMZB 1519B (9KHz~30MHz)	Temp. / Humidity	25°C / 57%
Polarity	--	Site / Test Engineer	AC1 / Fran
Test Mode	Mode1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	37.49	19.03	56.52	-39.59	96.11	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. According to §15.31, 3m Limit = 300 Limit + 40log(300/3) or 30 Limit + 40log(30/3).

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	FMZB 1519B (9KHz~30MHz)	Temp. / Humidity	25°C / 57%
Polarity	--	Site / Test Engineer	AC1 / Fran
Test Mode	Mode2	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	0.12053	60.9	18.56	79.46	-26.52	105.98	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. According to §15.31, 3m Limit = 300 Limit + 40log(300/3) or 30 Limit + 40log(30/3).

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	FMZB 1519B (9KHz~30MHz)	Temp. / Humidity	25°C / 57%
Polarity	--	Site / Test Engineer	AC1 / Fran
Test Mode	Mode2	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	0.36361	37.78	19.03	56.81	-39.58	96.39	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. According to §15.31, 3m Limit = 300 Limit + 40log(300/3) or 30 Limit + 40log(30/3).

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	25°C / 57%
Polarity	Horizontal	Site / Test Engineer	AC1 / Fran
Test Mode	Mode1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	34.183	7.03	18.74	25.77	-14.23	40	115	140	QP
2	49.855	2.6	21.85	24.45	-15.55	40	125	180	QP
3	100.537	10.56	19.18	29.74	-13.76	43.5	190	400	QP
4	* 209.208	16.13	18.9	35.03	-8.47	43.5	155	180	QP
5	439.279	3.12	24.37	27.49	-18.51	46	130	135	QP
6	729.946	3.09	29.63	32.72	-13.28	46	100	-5	QP

Note:

1. "\*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor)

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	25°C / 57%
Polarity	Vertical	Site / Test Engineer	AC1 / Fran
Test Mode	Mode1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	33.425	17.21	18.56	35.77	-4.23	40	115	375	QP
2		47.854	9.92	21.79	31.71	-8.29	40	150	250	QP
3		117.694	11.51	18.23	29.74	-13.76	43.5	175	390	QP
4		202.478	13	19.09	32.09	-11.41	43.5	155	280	QP
5		470.592	2.67	25.12	27.79	-18.21	46	100	-40	QP
6		728.946	4.04	29.62	33.66	-12.34	46	185	225	QP

Note:

1. "\*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor)

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	25°C / 57%
Polarity	Horizontal	Site / Test Engineer	AC1 / Fran
Test Mode	Mode2	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	53.674	3.91	21.21	25.12	-14.88	40	150	240	QP
2	96.203	15.46	18.35	33.81	-9.69	43.5	115	250	QP
3	136.548	14.11	15.89	30	-13.5	43.5	125	375	QP
4	* 206.449	15.33	18.98	34.31	-9.19	43.5	190	280	QP
5	304.631	9.18	21.58	30.76	-15.24	46	140	150	QP
6	729.249	3.52	29.62	33.14	-12.86	46	195	280	QP

Note:

1. "\*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor)



EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	25°C / 57%
Polarity	Vertical	Site / Test Engineer	AC1 / Fran
Test Mode	Mode2	Test Voltage	AC 120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	34.001	18.22	18.7	36.92	-3.08	40	125	40	QP
2		47.672	11.13	21.78	32.91	-7.09	40	175	180	QP
3		94.414	13.24	17.96	31.2	-12.3	43.5	185	390	QP
4		202.903	11.86	19.07	30.93	-12.57	43.5	115	-5	QP
5		304.571	4.72	21.57	26.29	-19.71	46	200	240	QP
6		729.673	3.61	29.63	33.24	-12.76	46	145	120	QP

Note:

1. "\*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor)

### 7.3. 20dB Bandwidth Measurement

#### 7.3.1. Test Limit

N/A


#### 7.3.2. Test Procedure Used

KDB 789033 D02v01r01 – Section C.1

#### 7.3.3. Test Setting


1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 26$ . The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.

#### 7.3.4. Test Setup



### 7.3.5. Test Result

Test Mode	Frequency (kHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
WPC	128.3	3.403	5.904



## 7.4. AC Conducted Emissions Measurement


### 7.4.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 7.4.2. Test Setup



### 7.4.3. Test Result

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	24°C / 68%
Polarity	Line1	Site / Test Engineer	SR2 / Fran
Test Mode	Mode1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.177	22.28	10.15	32.43	-32.2	64.63	QP
2	0.177	7.01	10.15	17.16	-37.47	54.63	Average
3	0.69445	30.64	10.03	40.67	-15.33	56	QP
4	0.69445	20.8	10.03	30.83	-15.17	46	Average
5	1.176	19.28	9.88	29.16	-26.84	56	QP
6	1.176	6	9.88	15.88	-30.12	46	Average
7	1.698	20.43	9.87	30.3	-25.7	56	QP
8	1.698	8.47	9.87	18.34	-27.66	46	Average
9	7.426	33.2	9.8	43	-17	60	QP
10	7.426	32	9.8	41.8	-8.2	50	Average
11	*	8.402	9.82	46.59	-13.41	60	QP
12	*	8.402	9.82	41.96	-8.04	50	Average

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Factor (dB)+ Cable Loss (dB)
- Measurement (dBuV) = Reading(dBuV)+ C.F (Correction Factor)

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	24°C / 68%
Polarity	Neutral	Site / Test Engineer	SR2 / Fran
Test Mode	Mode1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	*	0.69445	33.98	10.04	44.02	-11.98	56	QP
2	*	0.69445	22.83	10.04	32.87	-13.13	46	Average
3		1.941	20.6	9.86	30.46	-25.54	56	QP
4		1.941	10.14	9.86	20	-26	46	Average
5		2.458	20.22	9.83	30.05	-25.95	56	QP
6		2.458	11.93	9.83	21.76	-24.24	46	Average
7		7.628	44.57	9.8	54.37	-5.63	60	QP
8		7.628	37.94	9.8	47.74	-2.26	50	Average
9		10.215	21.88	9.85	31.73	-28.27	60	QP
10		10.215	13.63	9.85	23.48	-26.52	50	Average
11		15.385	21.58	9.97	31.55	-28.45	60	QP
12		15.385	12.9	9.97	22.87	-27.13	50	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Factor (dB)+ Cable Loss (dB)
3. Measurement (dBuV) = Reading(dBuV)+ C.F (Correction Factor)

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	24°C / 68%
Polarity	Line1	Site / Test Engineer	SR2 / Fran
Test Mode	Mode2	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.159	24.94	10.08	35.02	-30.5	65.52	QP
2	0.159	5.04	10.08	15.12	-40.4	55.52	Average
3	1.126	23.71	9.88	33.59	-22.41	56	QP
4	1.126	18.67	9.88	28.55	-17.45	46	Average
5	2.112	7.41	9.86	17.27	-38.73	56	QP
6	2.112	-2.32	9.86	7.54	-38.46	46	Average
7	* 7.633	41.08	9.81	50.89	-9.11	60	QP
8	* 7.633	37.9	9.81	47.71	-2.29	50	Average
9	9.14	33.31	9.83	43.14	-16.86	60	QP
10	9.14	29.91	9.83	39.74	-10.26	50	Average
11	11.637	25.33	9.88	35.21	-24.79	60	QP
12	11.637	23.1	9.88	32.98	-17.02	50	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Factor (dB)+ Cable Loss (dB)
3. Measurement (dBuV) = Reading(dBuV)+ C.F (Correction Factor)

EUT	Dual Coil Fast Wireless Charger	Date of Test	2018/9/14
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	24°C / 68%
Polarity	Neutral	Site / Test Engineer	SR2 / Fran
Test Mode	Mode2	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.1635	24.41	10.1	34.51	-30.77	65.28	QP
2	0.1635	6.19	10.1	16.29	-38.99	55.28	Average
3	0.87893	24.19	9.95	34.14	-21.86	56	QP
4	0.87893	19.51	9.95	29.46	-16.54	46	Average
5	1.878	25.32	9.86	35.18	-20.82	56	QP
6	1.878	20.92	9.86	30.78	-15.22	46	Average
7	2.629	24.22	9.83	34.05	-21.95	56	QP
8	2.629	20.4	9.83	30.23	-15.77	46	Average
9	* 7.637	44.61	9.8	54.41	-5.59	60	QP
10	* 7.637	37.94	9.8	47.74	-2.26	50	Average
11	9.64	31.42	9.84	41.26	-18.74	60	QP
12	9.64	30	9.84	39.84	-10.16	50	Average

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Factor (dB)+ Cable Loss (dB)
- Measurement (dBuV) = Reading(dBuV)+ C.F (Correction Factor)



## 8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Dual Coil Fast Wireless Charger** is in compliance with Part 15.209 of the FCC Rules.

————— The End —————