



RF Exposure Statement

Equipment Information

Type of equipment: SmartBox
Type / Model: SmartBox A2, SmartBox A2-25B, SmartBox A2-50B
Applicant: Gigastone Corp.
12F, No. 480, Rueiguang Rd., Neihu Dist., Taipei 114, Taiwan

The EUT is SmartBox, and was defined as information technology equipment.

The customer confirmed the models listed as below were series model to model SmartBox A2 (EUT), the difference between main model and series model are listed as below.

Model Number	Difference
SmartBox A2	Lithium-ion Battery Capacity = 2500mAh
SmartBox A2-25B	SmartBox A2 w/ WiFi Bridge function + SDXC Support
SmartBox A2-50B	SmartBox A2 w/WiFi Bridge function + SDXC Support + 5000mAh Li-ion Battery

Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Measurement Result:

The unit is a portable device with the max. average output power 13.5 dBm (22.38mW) lower than the low threshold 60/f GHz mW (24.37 mW).

Therefore, the SAR measurement is not necessary.

Date of issue: Dec. 04, 2012

Jimmy Yang
Engineer
Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan