



18/88 Merrindale Drive Croydon South, Victoria, 3136, Australia
Telephone: +61 3 9761 5888
Facsimile: +61 3 8761 6547
Email: sales@emcbayswater.com.au
ABN: 49 112 221 333

RF Radiation Exposure Evaluation

In accordance with:

CFR47 FCC Part 2, Subpart J, 2.1093

FCC KDB 447498 D01 v06

Adherium (NZ) Limited

NF0106

Hailie for Ellipta

FCC ID: PN2-LPT1

REPORT: E2112-1497-6

DATE: March, 2022



RF Radiation Exposure Evaluation Report

EMC Bayswater Test Report: E2112-1497-6
Issue Date: March, 2022

Product: Hailie for Ellipta
Model No: NF0106
Serial No: B01, B02, B04
FCC ID: PN2-LPT1

Client Details: Mr Iqbal Syre
Adherium (NZ) Limited
Level 11, 16 Kingston Street,
Auckland 1010,
New Zealand
Phone No: +64 9 307 2771
e-mail: IqbalS@adherium.com

Standard(s): CFR47 FCC Part 2, Subpart J, 2.1093
Radiofrequency radiation exposure evaluation: portable devices.
FCC KDB 447498 D01 v06
RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES
FOR MOBILE AND PORTABLE DEVICES

Results Summary: RF Radiation exposure requirements **Complied**

Test Date(s): 9th December 2021

Test House (Issued By) EMC Bayswater Pty Ltd
18/88 Merrindale Drive
Croydon South
Victoria, 3136
Australia

FCC Accredited Test Firm Registration number: 527798
FCC Accredited Test Firm Designation number: AU0004

Phone No: +61 3 9761 5888 Email: sales@emcbayswater.com.au
Fax: +61 3 8761 6547 Web: www.emcbayswater.com.au

The Adherium (NZ) Limited, NF0106, Hailie for Ellipta, measured EIRP is below the SAR exception threshold (5mm distance) and the calculated power density level at a distance of 20cm are below the maximum levels allowed by regulations therefore complied with the requirements of CFR47 FCC Part 2, Subpart J, 2.1093.

This is to certify that the necessary evaluations were made by EMC Bayswater Pty Ltd, and that the Adherium (NZ) Limited, NF0106, Hailie for Ellipta, has been tested in accordance with requirements contained in the appropriate commission regulations.

Prepared by:



Adnan Zaman
(EMC Test Engineer)

Approved by:



Neville Liyanapatabendige
(Manager)

22/03/2022 13:09

Date

RF Radiation Exposure Evaluation *for* Adherium (NZ) Limited

Contents

1. Introduction	4
2. Test Report Revision History.....	4
3. Report Information	4
4. Product Details	5
4.1. Product Sample Details	5
4.2. Product description.....	5
5. SAR and RF Exposure exception evaluation.....	6
5.1. SAR exception evaluation.....	6
5.2. RF Exposure Evaluation (MPE).....	7
6. Conclusion.....	7

1. Introduction

RF Radiation Exposure evaluation was performed on a Adherium (NZ) Limited, NF0106, Hailie for Ellipta in accordance with CFR47 FCC Part 2, Subpart J, 2.1093.

2. Test Report Revision History

None

3. Report Information

EMC Bayswater Pty Ltd reports apply only to the specific samples tested under the stated test conditions. All samples tested were in good operating condition throughout the entire test program unless otherwise stated. EMC Bayswater Pty Ltd does not in any way guarantees the later performance of the product/equipment. It is the manufacturer's responsibility to ensure that additional production units of the tested model are manufactured with identical electrical and mechanical components. EMC Bayswater Pty Ltd shall have no liability for any deductions, inference or generalisations drawn by the clients or others from EMC Bayswater Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Bayswater Pty Ltd. This report shall not be reproduced except in full, without the written approval of EMC Bayswater Pty Ltd. This document may be altered or revised by EMC Bayswater Pty Ltd personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by EMC Bayswater Pty Ltd will nullify the document.

4. Product Details

4.1. Product Sample Details

The device, as supplied by the client, is described as follows:

Product:	Hailie for Ellipta	
Model No:	NF0106	
Serial No:	B01, B02, B04	
Firmware:	8.7.rf2	
Software:	SoftDevice S112 v6.1.1	
Power Specifications	Battery Powered 1 x CR2032 3.0V coin cell	
Dimensions:	75mm x 37mm x 90mm (Length x Width x Height)	
Weight:	30g	
EUT Type:	Portable	
Transmitter details:	Description:	nRF52832-QFAA-R7
	Type:	Bluetooth Low Energy
	Modulation:	GFSK
	Channels:	40 channels with 2 MHz spacing (3 advertising channels/37 data channels).
	Max power:	0 dBm
	Antenna:	Custom PCB trace antenna on flex tail
	Customer declared Antenna Gain:	+1dBm

(Customer supplied product information)

4.2. Product description

The device has been described by the customer as follows:

“The Hailie for Ellipta device is a small hand-held battery-powered electronic module that clips onto a GSK Ellipta Inhaler to remind the user when medication is due and log when medication is taken.

It is powered by a single CR2032 Coin cell battery and can transfer log data via Bluetooth Low Energy (BLE) for later analysis by a health professional. The user operates the device in a home environment.”

(Customer supplied product description information)

5. SAR and RF Exposure exception evaluation

5.1. SAR exception evaluation

As per Appendix A of KDB 447498 D01 General RF Exposure Guidance v06

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

SAR test exclusion threshold for 2402MHz transmitter is 10.16mW for 5mm distance.

- The measured maximum peak conducted power is 0.27mW (-5.7dBm)*
(*The measurement uncertainty was calculated at ±1.4dB. The reported uncertainty is an expanded uncertainty calculated using a coverage factor of approximately k=2 which gives a level of confidence of approximately 95%)
- Customer declared antenna gain is +1dBi
- Therefore the maximum EIRP is 0.34mW (Worst-case, Without Duty Cycle correction factor).

The measured EIRP is below the SAR exception threshold.

Note: The customer declared nominal transmit power is 1dBm (1mw), assumed worst-case output power variation is 0.4dBm therefore nominal power with tune up tolerance is 1.4dBm (1.38mW) and antenna gain is +1dBi. The nominal maximum EIRP will be 2.4dBm (1.74mW) which is below the SAR exception threshold.

5.2. RF Exposure Evaluation (MPE)

As per section 1.1310 of CFR 47 following Maximum Permissible Exposure (MPE) limits are applicable.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields for 2402 to 2480MHz as per Table 1 of Section 15.1310 is 1 mW/cm² (General Population/Un-controlled).

Using equation

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna

Prediction Worst case:

Maximum EIRP: 0.34mW (Worst-case, Without Duty Cycle correction factor)

Distance: 20cm

Calculated Power Density= 0.0000674 mW/cm²

MPE limit for General Population/Un-controlled exposure: 1 mW/cm²

6. Conclusion

The measured EIRP is below the SAR exception threshold (5mm distance) and the calculated power density level at a distance of 20cm are below the maximum levels allowed by regulations.