



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP:// WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

<b>APPLICANT</b>	ADHERIUM (NZ) LTD
	Level 2, 204 Quay Street Auckland 1010 NEW ZEALAND
<b>FCC ID</b>	PN2-STAV1
<b>MODEL NUMBER</b>	NF0080
<b>PRODUCT DESCRIPTION</b>	SMARTTOUCH AV
<b>STANDARD APPLIED</b>	CFR 47 Part 2.1091
<b>PREPARED BY</b>	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

Applicant: ADHERIUM (NZ) LTD  
FCC ID: PN2-STAV1  
Report: V:\A\ADHERIUM\674AUT16\674AUT16RF EXP MPE RPT.DOCX

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**



### Authorized Signatory Name:

Cory Leverett

Engineering Project Manager

**Date: 5/ 26/ 2016**

Applicant: ADHERIUM (NZ) LTD  
FCC ID: PN2-STAV1  
Report: V:\A\ADHERIUM\674AUT16\674AUT16RF EXP MPE RPT.DOCX

# RF Exposure Requirements

## General information

Device type: SMARTTOUCH AV

## Antenna

The EUT uses a integrated antenna

## MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Applicant: ADHERIUM (NZ) LTD

FCC ID: PN2-STAV1

Report: V:\A\ADHERIUM\674AUT16\674AUT16RF EXP MPE RPT.DOCX

**KDB 447498 D01 General RF Exposure Guidance v05r0**

4.3.1. Standalone SAR test exclusion considerations

**0 MHz to 6 GHz at separation distance less than or equal to 50 m**

**SAR Test Exclusion Calculator for Portable Devices**

**Insert values in yellow highlighted boxes to determine SAR Exclusion**

Max Power **1** mW

Min Separ **5** mm

Frequency **2.48** GHz

**When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.**

**Answer 0.3 Must be less than or equal to 3.0 for SAR Exclusion**

**KDB 388624 D02 Permit But Ask List v15, Item II. A. 5.**

**PBA is required if:**

**General Population:** The Answer is equal to or greater than 24 (8x threshold)

**Controlled Use:** The Answer is equal to or greater than 60 (20x threshold)

**and**, when published RF exposure KDB procedures are not established for SAR testing

**Please also note the following: [FCC KDB quote] These test exclusion conditions are based on source-based**